

The Evolution of a Programmer

Junior High School

```
10 PRINT "HELLO WORLD"  
20 END
```

High School

```
program Hello(input, output)  
begin  
  writeln('Hello World')  
end.
```

First year in College

```
#include  
  
main() {  
  printf("Hello, world.\n");  
}
```

Senior year in College

```
(defun hello ()  
  (print  
    (cons 'hello (cons 'world nil))))
```

New professional

```
#include  
void main(void)  
{  
  char *message[] = {"Hello ", "World"};  
  int i;  
  
  for(i = 0; i < 2; ++i)  
    printf("%s", message[i]);  
  printf("\n");  
}
```

Seasoned professional

```
#include
#include

class string
{
private:
    int size;
    char *ptr;
public:
    string() : size(0), ptr(new char('\0')) {}

    string(const string &s) : size(s.size)
    {
        ptr = new char[size + 1];
        strcpy(ptr, s.ptr);
    }

    ~string()
    {
        delete [] ptr;
    }

    friend ostream &operator <<(ostream &, const string &);
    string &operator=(const char *);
};

ostream &operator<<(ostream &stream, const string &s)
{
    return(stream << s.ptr);
}

string &string::operator=(const char *chrs)
{
    if (this != &chrs)
    {
        delete [] ptr;
        size = strlen(chrs);
        ptr = new char[size + 1];
        strcpy(ptr, chrs);
    }
    return(*this);
}

int main()
{
    string str;

    str = "Hello World";
    cout << str << endl;

    return(0);
}
```

}

Master Programmer

```
[
  uuid(2573F8F4-CFEE-101A-9A9F-00AA00342820)
]
library LHello
{
  // bring in the master library
  importlib("actimp.tlb");
  importlib("actexp.tlb");

  // bring in my interfaces
  #include "pshlo.idl"

  [
    uuid(2573F8F5-CFEE-101A-9A9F-00AA00342820)
  ]
  cotype THello
  {
    interface IHello;
    interface IPersistFile;
  };
};

[
  exe,
  uuid(2573F890-CFEE-101A-9A9F-00AA00342820)
]
module CHelloLib
{

  // some code related header files
  importheader();
  importheader();
  importheader();
  importheader("pshlo.h");
  importheader("shlo.hxx");
  importheader("mycls.hxx");

  // needed typelibs
  importlib("actimp.tlb");
  importlib("actexp.tlb");
  importlib("thlo.tlb");

  [
    uuid(2573F891-CFEE-101A-9A9F-00AA00342820),
    aggregatable
  ]
  coclass CHello
  {
```

```
cotype THello;
};
};

#include "ipfix.hxx"

extern HANDLE hEvent;

class CHello : public CHelloBase
{
public:
    IPFIX(CLSID_CHello);

    CHello(IUnknown *pUnk);
    ~CHello();

    HRESULT __stdcall PrintSz(LPWSTR pwszString);

private:
    static int cObjRef;
};

#include
#include
#include
#include
#include "thlo.h"
#include "pshlo.h"
#include "shlo.hxx"
#include "mycls.hxx"

int CHello::cObjRef = 0;

CHello::CHello(IUnknown *pUnk) : CHelloBase(pUnk)
{
    cObjRef++;
    return;
}

HRESULT __stdcall CHello::PrintSz(LPWSTR pwszString)
{
    printf("%ws\n", pwszString);
    return(ResultFromCode(S_OK));
}

CHello::~~CHello(void)
{
    // when the object count goes to zero, stop the server
    cObjRef--;
}
```

```
if( cObjRef == 0 )
    PulseEvent(hEvent);

return;
}

#include
#include
#include "pshlo.h"
#include "shlo.hxx"
#include "mycls.hxx"

HANDLE hEvent;

int _cdecl main(
int argc,
char * argv[]
) {
ULONG ulRef;
DWORD dwRegistration;
CHelloCF *pCF = new CHelloCF();

hEvent = CreateEvent(NULL, FALSE, FALSE, NULL);

// Initialize the OLE libraries
CoInitializeEx(NULL, COINIT_MULTITHREADED);

CoRegisterClassObject(CLSID_CHello, pCF, CLSCTX_LOCAL_SERVER,
    REGCLS_MULTIPLEUSE, &dwRegistration);

// wait on an event to stop
WaitForSingleObject(hEvent, INFINITE);

// revoke and release the class object
CoRevokeClassObject(dwRegistration);
ulRef = pCF->Release();

// Tell OLE we are going away.
CoUninitialize();

return(0);
}

extern CLSID CLSID_CHello;
extern UUID LIBID_CHelloLib;

CLSID CLSID_CHello = { /* 2573F891-CFEE-101A-9A9F-00AA0034282D */
    0x2573F891,
    0xCFEE,
    0x101A,
    { 0x9A, 0x9F, 0x00, 0xAA, 0x00, 0x34, 0x28, 0x20 }
};
```

```
UUID LIBID_CHelloLib = { /* 2573F890-CFEE-101A-9A9F-00AA00342820
*/
    0x2573F890,
    0xCFEE,
    0x101A,
    { 0x9A, 0x9F, 0x00, 0xAA, 0x00, 0x34, 0x28, 0x20 }
};

#include
#include
#include
#include
#include
#include "pshlo.h"
#include "shlo.hxx"
#include "clsid.h"

int _cdecl main(
int argc,
char * argv[]
) {
    HRESULT hRslt;
    IHello *pHello;
    ULONG ulCnt;
    IMoniker * pmk;
    WCHAR wcsT[_MAX_PATH];
    WCHAR wcsPath[2 * _MAX_PATH];

    // get object path
    wcsPath[0] = '\\0';
    wcsT[0] = '\\0';
    if( argc > 1) {
        mbstowcs(wcsPath, argv[1], strlen(argv[1]) + 1);
        wcsupr(wcsPath);
    }
    else {
        fprintf(stderr, "Object path must be specified\n");
        return(1);
    }

    // get print string
    if(argc > 2)
        mbstowcs(wcsT, argv[2], strlen(argv[2]) + 1);
    else
        wcsncpy(wcsT, L"Hello World");

    printf("Linking to object %ws\n", wcsPath);
    printf("Text String %ws\n", wcsT);

    // Initialize the OLE libraries
    hRslt = CoInitializeEx(NULL, COINIT_MULTITHREADED);

    if(SUCCEEDED(hRslt)) {
```

```

    hRslt = CreateFileMoniker(wcsPath, &pmk);
    if(SUCCEEDED(hRslt))
    hRslt = BindMoniker(pm, 0, IID_IHello, (void **)&pHello);

    if(SUCCEEDED(hRslt)) {

// print a string out
pHello->PrintSz(wcsT);

Sleep(2000);
ulCnt = pHello->Release();
}
    else
    printf("Failure to connect, status: %lx", hRslt);

    // Tell OLE we are going away.
    CoUninitialize();
}

return(0);
}

```

Apprentice Hacker

```

#!/usr/local/bin/perl
$msg="Hello, world.\n";
if ($#ARGV >= 0) {
    while(defined($arg=shift(@ARGV))) {
        $outfilename = $arg;
        open(FILE, ">" . $outfilename) || die "Can't write $arg:
$!\n";
        print (FILE $msg);
        close(FILE) || die "Can't close $arg: $!\n";
    }
} else {
    print ($msg);
}
1;

```

Experienced Hacker

```

#include
#define S "Hello, World\n"
main(){exit(printf(S) == strlen(S) ? 0 : 1);}

```

Seasoned Hacker

```
% cc -o a.out ~/src/misc/hw/hw.c
% a.out
```

Guru Hacker

```
% cat
Hello, world.
^D
```

New Manager

```
10 PRINT "HELLO WORLD"
20 END
```

Middle Manager

```
mail -s "Hello, world." bob@b12
Bob, could you please write me a program that prints "Hello,
world."?
I need it by tomorrow.
^D
```

Senior Manager

```
% zmail jim
I need a "Hello, world." program by this afternoon.
```

Chief Executive

```
% letter
letter: Command not found.
% mail
To: ^X ^F ^C
% help mail
help: Command not found.
% damn!
!: Event unrecognized
% logout
```
