Schuldaten.odb : Abfrage1 - LibreOffice Base: Abfrageentwurf 🗸 🗸	$^{\sim}$	📑 🖈 Firebird_3_Functions(2).odb : Dat LibreOffice Base: Abfrageentwurf 🗸 🔨 🛞
<u>D</u> atei <u>B</u> earbeiten <u>A</u> nsicht <u>E</u> infügen E <u>x</u> tras Fen <u>s</u> ter <u>H</u> ilfe		<u>D</u> atei <u>B</u> earbeiten <u>A</u> nsicht <u>E</u> infügen E <u>x</u> tras Fen <u>s</u> ter <u>H</u> ilfe
₽· < < < < < < < < < < < < < < < < < < <		
	∏ »	🖺 🖉 🕺 🖟 🖻 🖹 🔿 🧠 🕲 🖌 🧤 🖓 SQL-Kommando direkt ausführer
ID DATEDIFF('DAY', "StartDate", "EndDate") 1 5		ID DATEDIFF 1 5
Datensatz von 1		Datensatz I von 1
<pre>SELECT "ID", DATEDIFF('DAY', "StartDate", "EndDate") FROM "Tabl</pre>	e3" 🌔	SELECT "ID", DATEDIFF(DAY, "StartDate", "EndDate") FROM "Table3"

On the left: query, executed in HSQLDB.

- SQL-command isn't executed directly
- SQL-code is a little bit different, see the marks round DAY.
- Insert, update and delete is possible, see the added empty row for new data

On the right: query, executed in Firebird

- SQL-command could only be executed directly
- SQL-code is a little bit different, see the marks round DAY.
- Insert, update and delete isn't possible. No row added for insert, line with points round ID=1 (no cursor in field possible).