

[Document History]

- 2019.12.13 Create this Document. (v1.0)
- 2019.03.21 Document update. (v1.1)

[Content]


- Main idea
- Current architecture for collecting sessionHistory changes
- Proposed architecture for collecting sessionHistory changes
- Current architecture for restoring sessionHistory changes
- Proposed architecture for restoring sessionHistory changes
- New added messages
- Follow-up bug after Bug 1507287

[Main idea]

- **Reduce the memory usage of the content process.**
 - When enabling fission, we will have more content processes than before. The memory usage of the content process becomes more and more important.
 - ContentSessionStore.jsm is currently loaded into every tab frame loader. We can reduce memory usage by rewriting the code into C++.
 - [Slides](#) for the current rewriting
 - Rewritings for the modules loaded in ContentSessionStore.jsm:
 - [Bug 1497144](#) - DocShellCapabilities.jsm and ScrollPosition.jsm
 - [Bug 1497146](#) - FormData.jsm
 - [Bug 1497147](#) - Utils.jsm (rewrite mapFrameTree)
 - [Bug 1507286](#) - SessionStorage.jsm
 - Rewritings for the listener in the ContentSessionStore.jsm:
 - [Bug 1474130](#) - ScrollPosition/Privacy/DocCapability listeners
 - [Bug 1544371](#) - FormDataListener
 - [Bug 1549975](#) - SessionStoreListener
- **Make the sessionRestore functionality work when session history living in the parent process.**
 - Fission team is designing the new generation of session history. First idea is to move session history from the child process to the parent process.
 - Now we can enable sessionHistory in the parent process by pref “**fission.sessionHistoryInParent**”.
 - Related bug: [Bug 1438272](#)

[Current architecture for collecting sessionHistory changes]


- There is a sessionHistoryListener which is running in the content process.
 - The listener is implemented in ContentSessionStore.jsm. [[source code](#)]
 - We use the listener to listen for changes of sessionHistory. Whenever the user navigates we will collect everything needed for session history. ContentSessionStore will use “**SessionStore:update**” message to update the data we collect in that listener.
 - How do we collect everything needed for sessionHistory?
 - By [SessionHistoryListener.collect\(\)](#) and use [SessionHistory module](#) to collect the sessionHistory.




[Proposed architecture for collecting sessionHistory changes]

1. Move the original implementation of “sessionHistoryListener” from ContentSessionStore.jsm into a new JSM module([SessionHistoryListener.jsm](#)).
 - [Regression] Bug 1623934 - 1.77 - 2.14% Base Content JS
 - Before the work of sessionHistory is complete, we always load SessionHistoryListener.jsm into the content process. I make sense to inline the listener in order to reduce memory overhead.
2. When the pref “**fission.sessionHistoryInParent**” is false:
 - Load “[SessionHistoryListener.jsm](#)” and new a SessionHistoryListener as before. The behavior keeps the same.
 - Create a SessionHistoryListener as before. The behavior keeps the same.
3. When the pref “**fission.sessionHistoryInParent**” is true:
 - Don’t load “[SessionHistoryListener.jsm](#)” to reduce memory usage.
 - Since ‘sessionHistory’ object should be accessed in the parent process, we divided the listener into 2 places.
 - i. sessionHistoryListener in the parent process is in charge of everything related to sessionHistory object.
 - We collect everything needed for sessionHistory here. In order to use [SessionHistory module](#) to collect the sessionHistory, we will refactor the related function as well.
 - ii. sessionHistoryListener in the child process(SessionStoreListener.cpp) is in charge of the other events we need to listen to in the child process.
 - The sessionStore update flow is also changed. We use the same mechanism as [Bug 1474130](#), [Bug 1544371](#) and [Bug 1549975](#).
 - i. Use the update function in the “SessionStoreFunction.jsm” to update data into SessionStore.jsm directly.

Proposed Architecture (e10s)




If sessionHistory update is needed,



- Use `nsFrameLoader::RequestSHistoryUpdate` to notify `SessionStoreListener` that there is shistory changes.
- In the next sessionStore update, `SessionStore.jsm` will do `SessionHistory.collectFromParent()`.
- Before collecting session history changes, we only need to request once.


[Current architecture for restoring sessionHistory changes]

- When receiving a restore message from sessionStore.jsm, contentSessionStore will use ContentRestore to do the restore.



[Proposed architecture for restoring sessionHistory changes]

- SendMessage to the parent process to do the session history restore.




(Current)

ContentRestore.restoreHistory()

1. Everything before SessionHistory.restore()
2. **Use SessionHistory.jsm to restore sessionHistory.**
3. Everything after SessionHistory.restore()

(Proposed Architecture when pref on)



[New added messages]

From child to parent	
SessionStore:addSHistoryListener	In contentSessionStore constructor, we need to create the listener for session history changes. If pref on, we need to ask sessionStore to create a corresponding listener in the parent process.
SessionStore:removeRestoreListener	When doing restore, we need to add another listener for different purposes in the parent process. Use this message to notify sessionStore when the listener is not needed anymore.
SessionStore:restoreSHistoryInParent	When needing to restore session history with pref on, use this message to ask sessionStore to do the restore.
SessionStore:reloadCurrentEntry	When needing to do the current history entry with pref on, use this message to ask sessionStore to do it.

From parent to child	
SessionStore:finishRestoreHistory	After restoring session history in the parent, use this message to notify ContentSessionStore.
SessionStore:OnHistoryReload	The message is called in the callback of the listener we added when doing the restore.
SessionStore:OnHistoryNewEntry	The message is called in the callback of the listener we added when doing the restore.

[Follow-up Bug after Bug 1507287]

There are some known mochitests failures when enabling sessionHistory in the parent process.

- [Bug 1599105](#) for **browser_500328.js**.
- [bug 1602486](#) for **browser_scrollPositions.js**
- [Bug 1602501](#) for **browser_swapDocShells.js**.
- (found the failure on 2020.03.11) **browser_docshell_uuid_consistency.js**