

No.	Time	Source	Destination	Proto
col	Info			
V	89 0.169476	172.25.135.33	172.25.94.191	YPSER
	V2 FIRST Call (Reply In 90)			

Frame 89 (114 bytes on wire, 114 bytes captured)
 Ethernet II, Src: 00:0a:42:1a:f7:fc, Dst: 00:0e:7f:ef:bf:6f
 Internet Protocol, Src Addr: 172.25.135.33 (172.25.135.33), Dst Addr: 172.25.94.191 (172.25.94.191)
 User Datagram Protocol, Src Port: 32850 (32850), Dst Port: 726 (726)
 Remote Procedure Call, Type:Call XID:0x416c484e
 Yellow Pages Service
 Program Version: 2
 V2 Procedure: FIRST (4)
 Domain: iip.nwi.com
 length: 11
 contents: iip.nwi.com
 fill bytes: opaque data
 Map Name: auto_master
 length: 11
 contents: auto_master
 fill bytes: opaque data

No.	Time	Source	Destination	Proto
col	Info			
V	90 0.169563	172.25.94.191	172.25.135.33	YPSER
	V2 FIRST Reply (Call In 89)			

Frame 90 (78 bytes on wire, 78 bytes captured)
 Ethernet II, Src: 00:0e:7f:ef:bf:6f, Dst: 00:00:0c:07:ac:10
 Internet Protocol, Src Addr: 172.25.94.191 (172.25.94.191), Dst Addr: 172.25.135.33 (172.25.135.33)
 User Datagram Protocol, Src Port: 726 (726), Dst Port: 32850 (32850)
 Remote Procedure Call, Type:Reply XID:0x416c484e
 Yellow Pages Service
 Program Version: 2
 V2 Procedure: FIRST (4)
 Status: YP_NOMAP (-1)
 Value: <EMPTY>
 length: 0
 contents: <EMPTY>
 Key: <EMPTY>
 length: 0
 contents: <EMPTY>

No.	Time	Source	Destination	Proto
col	Info			
V	91 0.170100	172.25.135.33	172.25.94.191	YPSER
	V2 FIRST Call (Reply In 92)			

Frame 91 (114 bytes on wire, 114 bytes captured)
 Ethernet II, Src: 00:0a:42:1a:f7:fc, Dst: 00:0e:7f:ef:bf:6f
 Internet Protocol, Src Addr: 172.25.135.33 (172.25.135.33), Dst Addr: 172.25.94.191 (172.25.94.191)
 User Datagram Protocol, Src Port: 32850 (32850), Dst Port: 726 (726)
 Remote Procedure Call, Type:Call XID:0x416c484f
 Yellow Pages Service
 Program Version: 2
 V2 Procedure: FIRST (4)
 Domain: iip.nwi.com
 length: 11
 contents: iip.nwi.com
 fill bytes: opaque data
 Map Name: auto.master
 length: 11
 contents: auto.master
 fill bytes: opaque data

No.	Time	Source	Destination	Proto
col	Info			

92 0.170136 172.25.94.191 172.25.135.33 YPSER
V V2 FIRST Reply (Call In 91)

Frame 92 (130 bytes on wire, 130 bytes captured)

Ethernet II, Src: 00:0e:7f:ef:bf:6f, Dst: 00:00:0c:07:ac:10

Internet Protocol, Src Addr: 172.25.94.191 (172.25.94.191), Dst Addr:
172.25.135.33 (172.25.135.33)

User Datagram Protocol, Src Port: 726 (726), Dst Port: 32850 (32850)

Remote Procedure Call, Type:Reply XID:0x416c484f

Yellow Pages Service

Program Version: 2

V2 Procedure: FIRST (4)

Status: YP_TRUE (1)

Value: auto.devl -rw,nosuid,wsiz=4096,rsiz=4096

length: 42

contents: auto.devl -rw,nosuid,wsiz=4096,rsiz=4096

fill bytes: opaque data

Key: /devl

length: 5

contents: /devl

fill bytes: opaque data