

Running BIND in a chroot environment

If you have installed the *bind-chroot* package, the BIND service will run in the **/var/named/chroot** environment. In that case, the initialization script will mount the above configuration files using the **mount -b bind** command, so that you can manage the configuration outside this environment.

Bug 922608 - Setting up named-chroot using setup-named-chroot not documented New Text BELOW

12.2.1.1. Installing BIND In A Chroot Environment

To install **BIND** to run in a chroot environment, issue the following commands as root:

```
~]# yum install bind-chroot
```

To enable the **named-chroot** service, first check if the **named** service is running by issuing the following command:

```
~]$ systemctl status named
```

If it is running, it must be disabled.

To disable **named**, issue the following commands as root:

```
~]# systemctl stop named
```

```
~]# systemctl disable named
```

Then, to enable the **named-chroot** service, issue the following commands as root:

```
~]# systemctl enable named-chroot
```

```
~]# systemctl start named-chroot
```

To check the status of the **named-chroot** service, issue the following command as root:

```
~]# systemctl status named-chroot
```

12.2.1.2. Common Statement Types

The following types of statements are commonly used in **/etc/named.conf**:

acl

The **acl** (Access Control List) statement allows you to define groups of hosts, so that they can be permitted or denied access to the nameserver. It takes the following form:

```
acl acl-name {
    match-element;
    ...
};
```

The **acl-name** statement name is the name of the access control list, and the **match-element** option is usually an individual IP address (such as **10.0.1.1**) or a CIDR network notation (for example, **10.0.1.0/24**). For a list of already defined keywords, see [Table 12.2, “Predefined](#)