



SKF Flowline monitor

New dimension of oil circulation flow rate measuring



SKF Flowline monitor – a new dimension

The SKF Flowline Monitor flow rate monitoring system introduces a new dimension for measuring and controlling oil circulation lubrication system flow rates. SKF Flowline flowmeters operate individually, can be programmed and adjusted separately. They can be connected to a centralized control system.

SKF Flowline's user friendly visual design allows operators to see the flow rate status of each individual lubrication point from the SKF Flowline monitor.

SKF Flowline monitor operation


SKF Flowline monitor ensures that the oil supply to the lubrication points is not disturbed or deviated excessively from the set limit values. Alarm limits and nominal flow can be set for each flowmeter individually. The flow rate is calculated by measuring the propeller rotation time by an inductive method and compensating the result by oil viscosity grade and oil temperature.

The user interface

The LED indicators in the flowmeters show a visual indication of oil flow volume. Any deviation from normal can be detected by the different LED indicator colors.

Red indicates that the flow rate is below the low alarm limit value. Yellow indicates that the flow rate is above the high alarm limit value. When the green LED indicators are on, the flow rate is within tolerance – in other words, FLOWLINE! This makes it possible to control the system visually in the production facility during routine control checks without having to use or activate the flowmeters separately.

Flow rates and settings can be observed on the digital display and settings can be made by pushing keys.




SKF Flowline monitor

Control valve and wide adjusting range

A non-linear adjustable valve, together with a sensitive propeller, enables a large operation range in each flow tube and good accuracy also in low flow range.



Flow rates



on of paper machine oil lubrication flow m

Centralized control system

SKF Flowline monitors in the measuring system can be connected together by the CAN-bus to build a centralized control system. There are several alternatives for interfacing with PCs and DCS systems.

The Windows based SKF Flowline Software is the user interface for the centralized control system. The same version of the software is used with all interface alternatives. With SKF Flowline Software, the user can monitor and control the operation of the measuring system, display flow rates and alarms, and modify system settings like flow rate alarm limits of flowmeters. SKF Flowline Software can also be used as an OPC server.

SKF Flowline Software collects continuous flow rate data, oil temperature and alarm trends. The interface with DCS can be built using an OPC interface or SKF Flowline HUB and standard Modbus protocol or using alarm relays in HUB. By OPC or Modbus, the system can be monitored and controlled as with SKF Flowline Software.

For servicing and configuration of a single SKF Flowline monitor, a laptop PC can be temporarily connected by means of a RS232 connector



Flow alarms

A common alarm relay indicates high and low flow situations. The alarm output is a fail-safe type.

More versatile alarms can be obtained by plugging in an extra relay board including the following alternatives

- individual alarms from each lubrication point
- maximum 10 separate low and high level alarms
- zero flow alarm
- pre-alarms.


SKF Flowline monitor features

- Easy to use; practical and visual LED indicator system and clear digital display.
- Wide adjustment range.
- Electronic temperature measurement.
- Temperature compensated measuring results.
- Multimonitoring possibility.
- Modern design.

SKF Flowline monitor technical specifications

	FL15-XX	FL50
Flow rate range*	0,05–15,0 l/min 0,10–30,0 pints/min	10,0–50,0 l/min 20,0–100,0 pints/min
Number of flowmeters	2, 4, 6, 8, 10	1
Connections		
– input	R 1" (NPT 1 in.)	R 1" (NPT 1 in.)
– output	R 1½" (NPT 1½ in.)	R 1" (NPT 1 in.)
Power supply	24 V DC/AC	24 V DC/AC
Power consumption	5 W max	5 W max
Alarm relay	120 V/1 A max, extra relay board available with 11 relays	120 V/1 A max, extra relay board available with 11 relays
Serial bus	CAN	CAN
Maximum operating temperature	70 °C (158 °F)	70 °C (158 °F)
*220 cSt (1000 SUS) max dP = 1,0 bar (14,5 Psi)		


SKF Flowline Software main view



monitoring


Alternative 1

Control by SKF Flowline HUB (RS232 HUB)



Alternative 2

Control by PC without HUB (USB-CAN)




SKF Flowline Hub

Power supply	230 VAC or 115 VAC
Monitor bus interface	
Protocol	CAN
Data transfer distance	1000 m (3 280 ft.)
Max. number of groups	100 pcs
Serial bus interfaces	
	RS485-PC
	RS485-Modbus
	RS232-PC


Alternative 3


Control by multiple PC over ethernet (Ethernet-CAN)



Alternative 4

Local connection to one SKF Flowline monitor







SKF Flowline monitor panels

- Easy and flexible installation with optional legs, wall brackets or hood mounting frame.
- Many standard sizes for up to 60 lubrication points.
- Plexiglass door protects the flowmeters.
- Options: Supply piping assembly, door with hinges, lock and light.

Designation system for SKF Flowline monitor FL15




Designation system for SKF Flowline monitor FL50





SKF Flowline monitor dimensions

FL50



FL15



Designation

L

W

H

mm

in.

mm

in.

mm

in.

FL50

226

8,9

106

4,2

150

5,9

FL15-02

226

8,9

106

4,2

150

5,9

FL15-04

324

12,76

106

4,2

150

5,9

FL15-06

422

16,61

106

4,2

150

5,9

FL15-08

520

20,47

106

4,2

150

5,9

FL15-10

618


24,33

106

4,2

150

5,9



The Power of Knowledge Engineering

Drawing on five areas of competence and application-specific expertise amassed over 100 years, SKF brings innovative solutions to OEMs and production facilities in every major industry worldwide.

These five competence areas include bearings and units, seals, lubrication systems, mechatronics (combining mechanics and electronics into intelligent systems), and a wide range of services, from 3-D computer modelling to advanced condition monitoring and reliability and asset management systems.

A global presence provides SKF customers uniform quality standards and universal product availability.

SKF Lubrication Solutions

e-mail: skf-lube@skf.com

© SKF is a registered trademark of the SKF Group

© SKF Group 2008

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

Publication 6410/I EN • July 2008

Printed in Sweden on environmentally friendly paper.

