

# *Hybrid Wet/Dry Cooling for Power Plants*

Parabolic Trough Technology Workshop  
February 14, 2006

Chuck Kutscher

Aaron Buys

Chris Gladden

**NREL**



## Disclaimer and Government License

This work has been authored by Midwest Research Institute (MRI) under Contract No. DE-AC36-99GO10337 with the U.S. Department of Energy (the “DOE”). The United States Government (the “Government”) retains and the publisher, by accepting the work for publication, acknowledges that the Government retains a non-exclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for Government purposes.

Neither MRI, the DOE, the Government, nor any other agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe any privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not constitute or imply its endorsement, recommendation, or favoring by the Government or any agency thereof. The views and opinions of the authors and/or presenters expressed herein do not necessarily state or reflect those of MRI, the DOE, the Government, or any agency thereof.



# Outline

- Overview of cooling options
- Analysis of evaporative enhancement of air-cooled geothermal power plants
- Field measurements at geothermal plant
- Preliminary analysis of trough plant
- Improvements to air-cooled condensers




# Water-Saving Options

<u>Approach</u>	<u>Pros</u>	<u>Cons</u>
ACC + WCC in Series	<ul style="list-style-type: none"><li>- ACC can handle desuperheating load</li></ul>	<ul style="list-style-type: none"><li>- Cost of dual equipment</li><li>- Condensate temp. very limited</li></ul>
ACC + WCC in Parallel	<ul style="list-style-type: none"><li>- Simple design</li><li>- Improves approach to dry bulb</li></ul>	<ul style="list-style-type: none"><li>- Condensate temp. limited by dry bulb</li></ul>
ACC w/ Evap Media	<ul style="list-style-type: none"><li>- Can achieve good approach to wet bulb on inlet air</li></ul>	<ul style="list-style-type: none"><li>- Cost of media</li><li>- Pressure drop lowers flow rate and LMTD</li></ul>
ACC w/ Spray Nozzles	<ul style="list-style-type: none"><li>- Simple, low cost of nozzles</li><li>- Low pressure drop</li></ul>	<ul style="list-style-type: none"><li>- Overspray and water waste</li><li>- Cost of water treatment or mist eliminator</li><li>- Nozzle maintenance</li><li>- Potential damage to finned tubes</li></ul>
Deluge of ACC	<ul style="list-style-type: none"><li>- Highest enhancement</li></ul>	<ul style="list-style-type: none"><li>- Water treatment or protective coating needed</li></ul>



# Relevance


- Air-cooled geothermal plants especially susceptible to high ambient temperature
- Plant power decreases ~1% of rated power for every 1°F rise in condenser temperature
- Output of air-cooled plant can drop > 50% in summer, when electricity is highly valued






# **Spreadsheet Model of Evaporative Enhancements to Existing Air-Cooled Plants**

# System 1 - Spray Cooling



- Low cost, low air pressure drop
- High water pressure
- Over-spray and carryover or cost of mist eliminator
- Nozzle clogging

# System 2 - Munters Cooling




- High efficiency, minimum carryover
- High air pressure drop (reduces air flow rate and decreases LMTD)
- High cost






# System 3 – Hybrid Cooling



- Inexpensive and simple, used in poultry industry
- Over-spray, carryover, and nozzle cleaning

# System 4 – Deluge Cooling



- Excellent performance
- Danger of scaling and deposition without pure water



**Model Input Dialog Box** [?] [X]

System 3. - Deluge		System 4. - Hybrid		Plant Operation	
Instructions	Model Constants 1	Model Constants 2	System 1. - Spray	System 2. - Munters	

**Ambient Conditions**

Elevation [meters]

Dry Bulb Temperature [F]

Wet Bulb Temperature [F]

RH Ambient [%]

**Economic Parameters**

Plant Live [Years]  Cost\_labor [\$/hour]

Interest rate [%]  Cost Water [\$/kg]

Cost\_condenser [\$]  Electric Price Change [% / year]

**Water Constants**

Density water [kg / m<sup>3</sup>]

pH water

Total Dissolved Solids [mg / L]

Calcium Ion Content [mg / l]

Alkalinity [mg / L]

**System Constants**

Maximum ACHE Dry Air Flow [lbm / hr]  Number of Condensing Units

Efficiency ACHE Fan [%]  Velocity of Air Into Munters Media [m / s]

Single Unit Intake Area [m<sup>2</sup>]  Velocity of Air Into Mist Eliminator [m / s]

Condensing Surface Area [m<sup>2</sup>]  Baseline Pressure Drop Across ACHE [in. H<sub>2</sub>O]

Condenser Height [m]  Fan Blade Diameter [meters]

**Constant Speed Fan Curve**  
(Flow rate (Q) in CFM)


Head Pressure [in. H<sub>2</sub>O] =  \*Q<sup>2</sup> +  \*Q +

Calculate Results      Update Input Values Only      Cancel




# Example Analysis: Net Power Produced





# Example Cost Results



**Note: Value of electricity will be affected by time-of-day rates and capacity payments.**



# Geothermal Analysis Conclusions

- Deluge most attractive if scaling/corrosion issues can be addressed
- Systems 1 to 3 obtain ~40 kWh/kgal of water; deluge can produce an average of ~60 kWh/kgal
- Results very sensitive to water costs, electric rate structure, installation costs


# Coated Fin Test Results



*OMP-coated fin  
unaffected by salt  
spray*

*Plain fin pitted*

# Measurements at Mammoth







# Measurements at Mammoth Binary-Cycle Geothermal Power Plant

Munters system



Hybrid spray/Munters system






# Mammoth Measurement Results: 2001

- Field instrumentation: Type T thermocouples, optical dew point (chilled mirror) hygrometer, handheld anemometer
- Munters had 79% saturation efficiency; hybrid was 50%
- Flow rate with Munters dropped 22-28%
- Munters increased net power 62% (800 kW to 1,300 kW) at 78°F ambient




# Munters Performance at Mammoth






# Mammoth Measurement Results: 2002


- Munters system modified, brine used for cooling water. Munters efficiency dropped from 79% to 66%





# Geothermal Conclusions

- All operators of air-cooled plants interested in evaporative enhancement
- Costs at existing plants are site-specific and negotiable; \$0.50 to \$2.00 per thousand gallons
- Reclaimed water becoming more widely available
- Two-Phase Engineering showed successful use of nozzles with brine
- Can reduce average cost of electricity by about 0.3 ¢/kWh, depending on cost of water
- Capacity payments can be as high as 30 ¢/kWh and lower average cost of electricity by 2–3 ¢/kWh



# Hour-by-Hour Binary-Cycle Simulator

- Settings
- Plant Design
- Cost Data
- Economics

Interpolating Data Points...

24%

Solving Point 2142

Simulation Date:

3/31/2005 5:00:00 AM  
Mar - Winter

Power Plant Type

Recuperator:

Working Fluid: Ammonia

Cooling Fluid: Air

W\_dot\_t\_kW

m\_dot\_wf

epsilon\_2ndLaw

P\_wf[5]

T\_hf[4]

W\_dot\_net\_kW

Number of Runs = 8760

Annual Simulation EES Model Interface V1.6b  
by Chris Gladden, NREL 2005 ©

Test

Pause

Stop

Load Defaults

Full Screen Mode

1280x1024

1024x768

$\dot{m}_{hf} = 2600000$  [lb<sub>m</sub>/hr]     $T_{hf,1} = 330$  [F]

$A_{sh} = 20000$  [ft<sup>2</sup>]

$A_b = 39000$  [ft<sup>2</sup>]

$A_{ph} = 31000$  [ft<sup>2</sup>]



Power Output:  
17.4 MW



Turbine Outlet  
Pressure (psi):  
104.37

Pump Outlet  
Pressure (psi):  
773.71

Plant Capacity: 15 [MW]

Wet Bulb Approach: 10 [F]

Accelerate


$A_c = 129000$  [ft<sup>2</sup>]

Max Cooling Fluid Flowrate:  
110000000 [lb<sub>m</sub>/hr]

Skip Wetbulb  
Calculations



# Parabolic Trough Plant Preliminary Analysis







## Cases Examined

- Air-Cooled
- Water-Cooled
- Air-Cooled with Spray Enhancement



## General Assumptions

- 30 MW<sub>e</sub> SEGS plant, Daggett weather
- \$0.18/kWh electricity (€0.15/kWh)
- Water at \$1.95/kgal (\$515/m<sup>3</sup>, €430/m<sup>3</sup>)
- 15% interest rate
- 30-year life



## Water-Cooled Plant

- Shell-and-tube condenser + cooling tower
- $T_{wb} = 68^{\circ}\text{F}$  ( $20^{\circ}\text{C}$ )
- Approach =  $10^{\circ}\text{F}$  ( $5.6^{\circ}\text{C}$ )
- Range =  $20^{\circ}\text{F}$  ( $11.1^{\circ}\text{C}$ )
- Pinch =  $5^{\circ}\text{F}$  ( $2.8^{\circ}\text{C}$ )
- $U = 400 \text{ Btu/h-ft}^2\text{-}^{\circ}\text{F}$  ( $2270 \text{ W/m}^2\text{-}^{\circ}\text{C}$ )



## Air-Cooled Plant


- Finned tube condenser
- $T_{db} = 104^{\circ}\text{F}$  ( $40^{\circ}\text{C}$ )
- $\text{ITD} = 40^{\circ}\text{F}$  ( $22^{\circ}\text{C}$ )
- $\text{Pinch} = 5^{\circ}\text{F}$  ( $2.8^{\circ}\text{C}$ )
- $U = 150 \text{ Btu/h-ft}^2\text{-}^{\circ}\text{F}$  ( $850 \text{ W/m}^2\text{-}^{\circ}\text{C}$ )




## Evaporative Pre-Cooling


- 300 psig spray nozzles
- 70% evaporation efficiency
- 80% saturation efficiency
- Munters DRIFdek mist eliminator

# Net Electricity Produced Per Year for Different Condenser Types






# Effect of Purchase Price of Electricity on Yearly Revenue (Water Cost = \$2/kgal)






## Effect of Water Price on Yearly Revenue (Electricity Price = \$0.18/kWh)



# Water Use for Different Condenser Types





## Next Steps

- Evaluate potential for water restrictions
- Develop full plant EES model
- Improve cost estimation
- Analyze parallel wet-dry system




# **Brief Review of NREL R&D on Advanced Fins for Air-Cooled Condensers**

# McElroy Enhanced Fins




# Test Section






# Heat Transfer vs. Hydraulic Power

## Different Fin Types (Staggered Array)






# Tabbed Fin Concept



Tabbed Plate Fin



Tabbed Plate Fin Heat Exchanger



# Individual Fins




GEA fins w/spacers




NREL tabbed circular fin





# Detailed CFD Model Isometric Views: Heat Flux and Total Pressure



Surface Heat Flux



Total Pressure



Path Lines Colored by Velocity Magnitude (m/s)

Dec 02, 2004  
FLUENT 6.1 (3d, segregated, lam)



# Recent Tabbed Fin CFD Results

