



List of substances	Limitations
Petroleum alicyclic hydrocarbon resins .....	As defined in § 176.170 of this chapter. Blended with butyl rubber for use as a component of coatings on polyolefin fabric for bulk packaging of raw fruits and vegetables and used at a level not to exceed 30 percent by weight of the total coating solids.
Polyamide resins (CAS Reg. No. 68139-70-8), as the basic resin, derived from: Dimerized vegetable oil or tall oil acids containing not more than 20 percent of monomer acids. Azelaic acid (CAS Reg. No. 123-99-9) in an amount not to exceed 3.7 percent by weight of the polyamide resin. Ethylenediamine (CAS Reg. No. 107-15-3). Piperazine (CAS Reg. No. 110-85-0) in an amount not to exceed 6.4 percent by weight of the polyamide resin.	For use only in coatings for polypropylene films that contact food at temperatures not to exceed room temperature.
Polyamide resins, derived from dimerized vegetable oil acids (containing not more than 20% of monomer acids) and ethylenediamine, as the basic resin.	For use only in coatings for polyolefin films that contact food at temperatures not to exceed room temperature.
Polyamide resins having a maximum acid value of 5 and a maximum amine value of 8.5 derived from dimerized vegetable oil acids (containing not more than 10 percent of monomer acids), ethylenediamine, and 4,4-bis (4-hydroxyphenyl) pentanoic acids (in an amount not to exceed 10 percent by weight of said polyamide resins); as the basic resin.	For use only in coatings that contact food at temperatures not to exceed room temperature provided that the concentration of the polyamide resins in the finished food-contact coating does not exceed 5 milligrams per square inch of food-contact surface.
Polyester resins formed by reaction of one or more of the following polybasic acids and monobasic acids with one or more of the following polyhydric alcohols:	
Polybasic acids: Adipic. Azelaic .....	For use in forming polyester resins intended for use in coatings that contact food only of the type identified in § 176.170(c) of this chapter, table 1, under Category VIII, and under conditions of use E, F, or G, described in table 2 of § 176.170(c) of this chapter.
Dimerized fatty acids derived from: Animal, marine or vegetable fats and oils. Tall oil. Fumaric. Isophthalic. Maleic. o-Phthalic. Sebacic. Terephthalic. Trimellitic.	
Monobasic acids: Fatty acids derived from: Animal, marine, or vegetable fats and oils.	
Gum rosin .....	As defined in § 178.3870 of this chapter. For use in forming polyester resins intended for use in coatings that contact food only of the type identified in § 176.170(c) of this chapter, table 1, under Category VIII, and under conditions of use E, F, or G described in table 2 of § 176.170(c) of this chapter.
Polyhydric alcohols: 1,3-Butylene glycol. Diethylene glycol. 2,2-Dimethyl-1,3-propanediol. Dipropylene glycol. Ethylene glycol. Glycerol. Mannitol. α-Methyl glucoside. Pentaerythritol. Propylene glycol. Sorbitol. Trimethylol ethane. Trimethylol propane.	
Polyethylenimine .....	For use only as a primer subcoat to anchor epoxy surface coatings to the base sheet.
Polystyrene.	
Polyvinyl acetate.	
Polyvinyl chloride .....	

List of substances	Limitations
<p>Siloxanes and silicones: platinum-catalyzed reaction product of vinyl-containing dimethylpolysiloxane (CAS Reg. No. 68083-18-1 and CAS Reg. No. 68083-19-2) with methylhydrogen polysiloxane (CAS Reg. No. 63148-57-2) and dimethylmethylhydrogen polysiloxane (CAS Reg. No. 68037-59-2). The following substances may be used as optional polymerization inhibitors:</p> <p>3,5-Dimethyl-1-hexyne-3-ol (CAS Reg. No. 107-54-0), at a level not to exceed 0.53 weight percent;</p> <p>1-Ethynylcyclohexene (CAS Reg. No. 931-49-7), at a level not to exceed 0.64 weight percent;</p> <p>Bis(methoxymethyl)ethyl maleate (CAS Reg. No. 102054-10-4), at a level not to exceed 1.0 weight percent;</p> <p>Methylvinyl cyclosiloxane (CAS Reg. No. 68082-23-5); and</p> <p>Tetramethyltetravinylcyclotetrasiloxane (CAS Reg. No. 2554-06-5).</p>	<p>Platinum content not to exceed 150 parts per million.</p>
<p>Siloxanes and silicones; platinum-catalyzed reaction product of vinyl-containing dimethylpolysiloxane (CAS Reg. Nos. 68083-19-2 and 68083-18-1), with methyl hydrogen polysiloxane (CAS Reg. No. 63148-57-2). Dimethyl maleate (CAS Reg. No. 624-48-6) and vinyl acetate (CAS Reg. No. 108-05-4) may be used as optional polymerization inhibitors.</p>	<p>Platinum content not to exceed 100 parts per million. For use only as a surface coating under the following conditions:</p> <ol style="list-style-type: none"> <li>1. In coatings for olefin polymers provided the coating contacts food only of the types identified in § 176.170(c) of this chapter, table 1, under Types I, II, VI, and VII-B when used under conditions of use E, F, and G described in table 2 in § 176.170(c) of this chapter.</li> <li>2. In coatings for olefin polymers provided the coating contacts food only of the types identified in § 176.170(c) of this chapter, table 1, under Types III, IV, V, VII-A, VIII, and IX when used under conditions of use A through H described in table 2 in § 176.170(c) of this chapter.</li> </ol>
<p>Siloxanes and silicones; platinum-catalyzed reaction product of vinyl-containing dimethylpolysiloxane (CAS Reg. Nos. 68083-19-2 and 68083-18-1), with methyl hydrogen polysiloxane (CAS Reg. No. 63148-57-2). Dimethyl maleate (CAS Reg. No. 624-48-6), vinyl acetate (CAS Reg. No. 108-05-4), dibutyl maleate (CAS Reg. No. 105-76-0) and diallyl maleate (CAS Reg. No. 999-21-3) may be used as optional polymerization inhibitors. The polymer may also contain C<sub>16</sub>-C<sub>18</sub> olefins (CAS Reg. No. 68855-60-7) as a control release agent.</p> <p>Styrene copolymerized with one or more of the following:</p> <p>Acrylonitrile.</p> <p>α-Methyl styrene.</p> <p>Styrene polymers made by the polymerization of any combination of styrene or alpha methyl styrene with acrylic acid, methacrylic acid, 2-ethyl hexyl acrylate, methyl methacrylate, and butyl acrylate. The styrene and alpha methyl styrene, individually, may constitute from 0 to 80 weight percent of the polymer. The other monomers, individually, may be from 0 to 40 weight percent of the polymer. The polymer number average molecular weight (M<sub>n</sub>) shall be at least 2,000 (as determined by gel permeation chromatography). The acid number of the polymer shall be less than 250. The monomer content shall be less than 0.5 percent.</p> <p>Styrene-isobutylene copolymer.</p> <p>Terpene resins consisting of polymers of α-pinene, β-pinene, and/or dipentene; acid value less than 5, saponification number less than 5, and color less than 4 on the Gardner scale as measured in 50 percent mineral spirits solution.</p> <p>2-Sulfoethyl methacrylate, sodium salt Chemical Abstracts Service No. 1804-87-1].</p>	<p>Platinum content not to exceed 100 parts per million. For use only as a release coating for pressure sensitive adhesives.</p> <p>For use only in contact with foods of Types IV-A, V, and VII in table 1 of § 176.170(c) of this chapter, under use conditions E through G in table 2 of § 176.170(c), and with foods of Types VIII and IX without use temperature restriction.</p> <p>For use only in copolymer coatings under conditions of use E, F, and G described in table 2 of § 176.170(c) of this chapter and limited to use at a level not to exceed 2.0 percent by weight of the dry copolymer coating.</p>
<p>Vinyl chloride-acetate, hydroxyl-modified copolymer or maleic acid-modified copolymer.</p> <p>Vinyl chloride copolymerized with one or more of the following:</p> <p>Acrylonitrile.</p> <p>Vinyl acetate.</p> <p>Vinylidene chloride.</p>	

List of substances	Limitations
<p>Vinylidene chloride copolymerized with one or more of the following:                      Acrylic acid and its methyl, ethyl, propyl, butyl, or octyl esters.                      Acrylonitrile.                      Itaconic acid.                      Methacrylic acid and its methyl, ethyl, propyl, butyl, or octyl esters.                      Methacrylonitrile.                      Vinyl chloride.</p> <p>(ii) Plasticizers:                      Acetyl tributyl citrate.                      Acetyl triethyl citrate.                      Butyl phthalyl butyl glycolate.                      Butyl stearate.                      Dibutyl sebacate.                      Diethyl phthalate.                      2-Ethylhexyl diphenyl phosphate.                      Ethyl phthalyl ethyl glycolate.                      Glycerol monooleate .....                      Glycerol triacetate.                      Triethyl citrate.</p> <p>(iii) Adjuvants (release agents, waxes, and dispersants):                      Acetone.                      Amides (unsubstituted) of fatty acids from vegetable or animal oils.  <i>n</i>-Butyl acetate.  <i>n</i>-Butyl alcohol.                      Candelilla wax.                      Carnauba wax.</p> <p>5-Chloro-2-methyl-4-isothiazolin-3-one (CAS Reg. No. 26172–55–4) and 2-methyl-4-isothiazolin-3-one (CAS Reg. No. 2682–20–4) mixture, at a ratio of 3 parts to 1 part, respectively, manufactured from methyl-3-mercaptopropionate (CAS Reg. No. 2935–90–2) and optionally containing magnesium nitrate (CAS Reg. No. 10377–60–3) at a concentration equivalent to the isothiazolone active ingredients (weight/weight)..                      1,2-Dibromo-2,4-dicyanobutane (CAS Reg. No. 35691–65–7).                      Ethyl acetate.                      Fatty acids from vegetable or animal oils and their aluminum, ammonium, calcium, magnesium, and sodium salts.                      Hexane.                      Methyl ethyl ketone.  <i>N,N</i>-Dioleylethylenediamine (CAS Reg. No. 110–31–6) ..</p> <p>Petroleum waxes conforming to specifications included in a regulation in subchapter B of this chapter.                      Polyvinyl alcohol, minimum viscosity of 4% aqueous solution at 20 °C of 4 centipoises and percent alcoholysis of 87–100.</p> <p>Sodium dioctyl sulfosuccinate.                      Sodium dodecylbenzenesulfonate.                      Sodium lauryl sulfate.                      Sorbitan and sorbitol esters of fatty acids from vegetable or animal oils.                      Spermaceti wax.                      Tetrahydrofuran.                      Toluene.</p> <p>(iv) Preservatives:                      Silver chloride-coated titanium dioxide .....</p>	<p>For use only as an antimicrobial agent in emulsion-based silicone coatings at a level not to exceed 50 milligrams per kilogram (based on isothiazolone active ingredient) in the coating formulation.</p> <p>For use as an antimicrobial agent at levels not to exceed 500 milligrams per kilogram in emulsion-based silicone coating.</p> <p>For use only in ionomeric resins complying with § 177.1330 of this chapter and in ethylene vinyl acetate copolymers complying with § 177.1350 of this chapter at a level not to exceed 0.0085 milligram per square centimeter (0.055 milligram per square inch) in the finished food-contact article.</p> <p>For use only as a dispersing agent at levels not to exceed 6% of total coating weight in coatings for polyolefin films provided the finished polyolefin films contact food only of the types identified in § 176.170(c) of this chapter, table 1, under Types V, VIII, and IX.</p> <p>For use only as a preservative in latex emulsions at a level not to exceed 2.2 parts per million (based on silver ion concentration) in the dry coating.</p>

(c) The coating in the finished form in which it is to contact food, when extracted with the solvent or solvents characterizing the type of food, and under conditions of time and temperature characterizing the conditions of its intended use as determined from tables 1 and 2 of §176.17(c) of this chapter, shall yield net chloroform-soluble extractives not to exceed 0.5 milligram per square inch of coated surface.

(d) Acrylonitrile copolymers identified in this section shall comply with the provisions of §180.22 of this chapter.

[42 FR 14534, Mar. 15, 1977, as amended at 43 FR 7206, Feb. 21, 1978; 45 FR 6541, Jan. 29, 1980; 47 FR 22512, May 25, 1982; 49 FR 36497, Sept. 18, 1984; 50 FR 47209, Nov. 15, 1985; 56 FR 49674, Oct. 1, 1991; 61 FR 14246, Apr. 1, 1996; 63 FR 71017, Dec. 23, 1998; 64 FR 2568, Jan. 15, 1999; 65 FR 6892, Feb. 11, 2000; 65 FR 37041, June 13, 2000]

**§ 175.350 Vinyl acetate/crotonic acid copolymer.**

A copolymer of vinyl acetate and crotonic acid may be safely used as a coating or as a component of a coating which is the food-contact surface of polyolefin films intended for packaging food, subject to the provisions of this section.

(a) The copolymer may contain added optional substances to impart desired properties.

(b) The quantity of any optional substance does not exceed the amount reasonably required to accomplish the intended physical or technical effect nor any limitations further provided.

(c) Any optional substance that is the subject of a regulation in parts 174, 175, 176, 177, 178, and §179.45 of this chapter conforms with any specifications in such regulation.

(d) Optional substances as provided in paragraph (a) of this section include:

(1) Substances generally recognized as safe in food.

(2) Substances subject to prior sanction or approval for uses with a copolymer of vinyl acetate and crotonic acid and used in accordance with such sanction or approval.

(3) Substances identified in this subparagraph and subject to such limitations as are provided:

List of substances	Limitations
Silica. Japan wax.	

(e) Copolymer of vinyl acetate and crotonic acid used as a coating or as a component of a coating conforming with the specifications of paragraph (e)(1) of this section are used as provided in paragraph (e)(2) of this section.

(1) *Specifications.* (i) The chloroform-soluble portion of the water extractives of the coated film obtained with distilled water at 120 °F for 24 hours does not exceed 0.5 milligram per square inch of coated surface.

(ii) The chloroform-soluble portion of the *n*-heptane extractives of the coated film obtained with *n*-heptane at 70 °F for 30 minutes does not exceed 0.5 milligram per square inch of coated surface.

(2) *Conditions of use.* The copolymer of vinyl acetate and crotonic acid is used as a coating or as a component of a coating for polyolefin films for packaging bakery products and confectionery.

**§ 175.360 Vinylidene chloride copolymer coatings for nylon film.**

Vinylidene chloride copolymer coatings identified in this section and applied on nylon film may be safely used as food-contact surfaces, in accordance with the following prescribed conditions:

(a) The coating is applied as a continuous film over one or both sides of a base film produced from nylon resins complying with §177.1500 of this chapter.

(b) The coatings are prepared from vinylidene chloride copolymers produced by copolymerizing vinylidene chloride with one or more of the monomers acrylic acid, acrylonitrile, ethyl acrylate, methacrylic acid, methyl acrylate, methyl methacrylate (CAS Reg. No. 80-62-6; maximum use level 6 weight percent) and 2-sulfoethyl methacrylate (CAS Reg. No. 10595-80-9; maximum use level 1 weight percent). The finished copolymers contain at least 50 weight percent of polymer units derived from vinylidene chloride. The finished coating produced from vinylidene chloride copolymers produced by copolymerizing vinylidene chloride with