

# TF Coil Subassembly


NCSX



Coil Winding +  
Wedge Castings =  
TF Coil Subassembly




- D Shaped Wedging Coil
- SS castings on leading edge
- 3x4 Cross-section
- Solid Copper Conductor
- LN2 Cooled



# Structure Reacts Critical Loads

NCSX


- TF Coils Assembled over Modular Coils
- Centering forces reacted through wedging
- Structure mounted to modular coil winding form reacts out of plane loads



*NCSX Conventional Coils*

# Jack Screw Device Added Pulls Coil Forward

NCSX



Bellville washers  
ensure constant  
4000 lbf load

# Winding Pack Insulation Scheme


NCSX

TF Turn Insulaton				
1/2 Lap Layer Kapton	Kapton	0.002		7.8
	Adhesive	0.0015		
	Kapton	0.002		0
	Adhesive	0.0015		
	Glass	0.007		0.63
	Glass	0.007		0.63
	Glass	0.007		0.63
	Glass	0.007		0.63
	Glass	0.007		0.63
	Glass	0.007		0.63
		<b>0.049</b>	<b>Inches</b>	<b>11.58 KV</b>
Ground Wrap TF				
Twenty One 1/2 Lap Layer	Glass	0.009		0.81
x 21	Glass	0.009		0.81
		<b>0.375</b>	<b>Inches</b>	<b>33.8 KV</b>


- Kapton Tape applied directly to conductor to enhance turn to turn dielectric standoff and allow for decoupling of insulation from conductor during cool down.

- Inner TF leg ground wrap thickness is 1/8"
- Outer leg of TF coil allows for the use of tough 3/8" ground wrap

1/8" Groundwrap on inboard wedging leg





3/8" Groundwrap on outboard leg



# Stress Analysis Insulation - Testing

NCSX

- Analysis showed risk of insulation cracking due to thermal stresses
- Original Plan to resolve thermal stress on winding pack issues
  - Remove Kapton to increase adhesion
  - Test to provide tensile stress allowables
  - Required greater than 10 MPa
- Results from CTD Testing Yielded Poor Results for Tensile strength / adhesion



# PDR Winding Pack Insulation Scheme

NCSX


- Original insulation scheme was re-evaluated and evolved to address thermal stress issue
- 1/2 Lap Layer of Kapton to provide primary dielectric strength
- System to allow loss of adhesion to conductor
- Releasing Kapton layer resolves thermal stress issue.
- Analysis verifies that coil stiffness is adequate after releasing insulation from conductors
- Prototype testing proved out insulation winding pack approach



# Prototype Bar Testing


NCSX

- Prototype bar underwent both thermal and stress cycling
- Proved durability of winding pack design
  - mechanical properties maintained after more than 2x stress at life
  - successful hipot tests
- Proved validity of FEA as measured by:
  - bench mark of mechanical properties to Bar model before and after cycling of prototype
- While the test bar was not identical to the PF geometry cyclical stresses tested were 5x greater than PF cyclical stresses
- Insulation scheme is identical to PF Coils



# Testing Prototype Bar, Thermal / Fatigue/ Electrical

NCSX



Test Equipment

Sealed Insulation box with test bar Inside



Bar Fitted with Probes for Electrical Testing after Cycling

Test Bar in the fixture with insulation box





NCSX Conventional Coils



# Lead Redesign – PDR Design = High Stresses

NCSX

- PDR Lead Design Produced stresses as high as 300MPa
- Lead Area was redesigned and analyzed




NCSX Conventional Coils

# Lead Redesign – Stress Analysis Cu


NCSX

- Redesigned lead area lowers maximum copper stress from 300 MPa to 70 MPa
- This compares to a maximum allowable stress of 270 MPa (1.5Sm)
- The equivalent alternating stress is only 27 MPa which easily meets the fatigue design requirement
- Annealing of Braze area is addressed in specification




# Lead Design – FDR Design

NCSX




- Lead Spur added to distribute stresses
- Lead Blocks transfer load to opposing lead spur




- G11 Pins help carry shear load

# Evolution of Structural Design Calculations (PDR)

NCSX



Smeared Properties




Stress Analysis  
.5 Tesla TF Only




Global Model Deformations

Worst Case Loading

Deformations



Model Modified



NCSX Conventional Coils

# Deflections Produce some non-ideal Flux Islands (as analyzed by A. Brooks)

NCSX

\* Global requirement is that toroidal flux in island regions shall not exceed 10%  
\* Leads and Transitions must have a less than 1% effect on toroidal flux in island regions

- Effects of islands analyzed for original and new insulation scheme
- Island size due to these deflections are within 1% requirement for individual systems chosen to satisfy overall 10% requirement
- Separate analysis shows islands from leads and transitions are well below 1% requirement

Island Size, % Total Flux		Resonance		
ID	Scenario	3/5	6/10	3/6
tfdisp25	TF @ 0.5T	0.02	0.00	0.00
tfdisp26	1.7T Ohmic	0.23	0.10	0.11
tfdisp27	2.0T High Beta	0.10	0.04	0.04
tfdisp29	TF @ 0.5T	0.01	0.00	0.00
tfdisp30	1.7T Ohmic	0.35	0.13	0.15
tfdisp31	2.0T High Beta	0.24	0.08	0.09
tfdisp38	TF @ 0.5T	0.02	0.00	0.00
tfdisp39	1.7T Ohmic	0.40	0.13	0.15
tfdisp40	2.0T High Beta	0.27	0.08	0.09





2x6 Winding  
10/26/04

3x4 Winding  
12/16/04

3x4 Winding  
12/30/04

# Global Model Gives Indication of Relative Stress Level Among Worst Case Time Points

NCSX



**LC1(0.5 T TF): 58 MPa LC2  
(1.7T Ohmic): 31MPa LC3(2T  
High-β): 23 MPa LC4(320kA  
Ohmic): 26 MPa**

# TF Manufacturing Process

NCSX



- Winding
- Induction Brazing
- Wedge Magnetic Permeability
- Vacuum Impregnation
- Coil Geometry Maintained Within Tolerances
- Precise Wedge Cut of front leg
- Electrical Testing Successful
- Final Hi-Pot Testing at Cryogenic Temperature



*NCSX Conventional Coils*

# Fabrication of TF Coil Assemblies

NCSX



First Coil -  
Final Cryogenic  
Electrical  
Testing



Second Coil  
Machine cut of  
Wedge



Third Coil  
ready for  
Vacuum  
Impregnation



Fourth Coil  
Winding

*NCSX Conventional Coils*



# Planarity Geometry Check

NCSX

- Height of center line of coil checked against the center plane of the coil and deviations are recorded.



## Wedge Geometry



- A precisely machined wedge template is used to inspect the wedge angle as well as the location of coil with respect to the intersecting axis formed by the angle




- The remaining coil geometry is located with respect to the axis described by the intersecting wedge planes by referencing back to an inspected point on the fixture
- The true position tolerance with respect to flatness and planarity of the wedge cut is inspected using a probe on the CNC machine



# PF Coils

NCSX




PF4 Upper

PF5 Upper

PF6 Upper

PF6 Lower






NCSX Conventional Coils

# PF Coil Cross Section

NCSX



- PF Coils of conventional design
- Rectangular cross section
- Round Geometry




*NCSX Conventional Coils*

# PF Coils, Conductor

NCSX



- A single copper conductor size is used for all three different types of PF coils to simplify their manufacture and reduce costs.







*NCSX Conventional Coils*



# PF5 Geometry

NCSX

- Turns = 24
- Outer Diameter = 179 inches
- Cross Section = 7.7 x 6.4 inches
- Conductor Length = 1100 ft





NCSX Conventional Coils

# PF6 Geometry

NCSX

- Turns = 14
- Outer Diameter = 216 inches
- Cross Section = 7.3 x 2.0 inches
- Conductor Length = 786 ft







NCSX Conventional Coils



# Lead Blocks

NCSX

- Leads Locked together by G11 Blocks
- Forces on leads very low on the order of 10 lbs excluding exterior fields



*NCSX Conventional Coils*

# Winding Pack Insulation Design

NCSX


PF Turn Insulation				
1/2 Lap Layer Kapton	Kapton	0.002		7.8
	Adhesive	0.0015		
	Kapton	0.002		0
	Adhesive	0.0015		
	Glass	0.007		0.63
	Glass	0.007		0.63
	Glass	0.007		0.63
	Glass	0.007		0.63
	Glass	0.007		0.63
	Glass	0.007		0.63
		<b>0.049</b>	<b>Inches</b>	<b>11.58 KV</b>
Ground Wrap PF				
Twenty One 1/2 Lap Layer	Glass	0.009		0.81
x 21	Glass	0.009		0.81
		<b>0.375</b>	<b>Inches</b>	<b>33.8 KV</b>

Kapton Tape applied directly to conductor to enhance turn to turn dielectric standoff and allow for decoupling of insulation from conductor during cool down.



- Generous 3/8" of ground wrap applied to provide "bullet proof" protection to prevent unforeseen potential damage

3/8" of Ground Wrap Insulation



# Manufacturability - Manufacturing Tolerances


## NCSX

---

- Requirement = In plane and out of plane installed perturbations shall be less than +/- 3mm
- Coil specification will require +/- 1.5mm using half of the allowable installed tolerance budget
- D Shaped NCSX TF Coils have been manufactured to about a +/- 1.5mm tolerance in their free state but a guarantee of that over the larger diameters for the PF Coils is not guaranteed
- Coil as it is removed from the VPI mold will be within +/- 1mm but coil is likely to distort in it's free state
- Support structure must be capable of re-shaping coil as required
- Coils can be positioned during installation to average out of tolerance conditions

# Trim Coil Configuration

NCSX



- 48 Coils
- Only two coil types
- All Coils Planar
- Top bottom symmetric half period patterns




# 48 Coil Trim Coil Configuration Meets Design Objective with Margin

**Design Point  
< 10% Islands  
< 20 kA-T**

NCSX

Trim Coil Configuration	Total Number Coils	Using SVD Solution		Using NLP Solution	
		Total Island Size %Total Flux	Max Current kA-T	Total Island Size %Total Flux	Max Current kA-T
Original 36 coils, 24 circuits	36	4.42	8.34	3.35	10.00
Original with 12 Midplane Coils	48	4.41	7.85	2.55	10.00
All Inner/Outer Coils Only (as Modified)	54	4.30	9.96	2.87	10.00
All Inner/Outer Coils Only (as Modified) (but without Outer AA)	48	4.29	11.36		
		6.95	10.00		
All Inner/Outer & Midplane Coils	66	4.26	9.21	2.17	10.00
All Inner/Outer & Midplane Coils (but without Outer AA)	60	4.25	9.56		
All Inner/Outer Coils (port12 split) (with Outer AA Coils)	60	4.47	10.00	2.89	10.00
		4.21	10.30		
All Inner/Outer Coils (port12 split) (without Outer AA Coils)	54	7.98	10.00	3.00	10.00
		4.18	11.88		
All Inner/Outer Coils (port12 split) (without Outer AA and CC Coils)	48	8.49	10.00	<b>3.12</b>	10.00
		4.06	12.25		
Above Plus Wings Distorted +40 mils (Stellarator Symmetric)		-	-	3.88	10.00
-40 mils		-	-	3.88	10.00
Above Plus Wings Distorted +40 mils (1 HP Only, Non Stellarator Sym)		-	-	3.25	10.00



# Trim Coil Requirements

NCSX


---

- **Meet Requirements when subjected to GRD reference scenarios**
- **Island Suppression 10%**
  - 20 kAmp Turns
  - 48 Coil Configuration
- **Thermal Excursions and Stress within limits**
  - 2 second pulse every 15 minutes
  - 167 amps
- **Withstand Operating Voltages**
  - Max Operating Voltage 1.0kV
  - Design Standoff Voltage to Ground of 6.7 kV
  - Design Standoff Voltage Turn to Turn of 1.0 kV
- **Winding Tolerances**
  - Installed tolerance +/-12mm
  - Fabrication tolerance +/- 6mm
  - Location measured to within 2mm

# Winding Pack Insulation Scheme


NCSX

- Kapton Tape applied directly to conductor to enhance turn to turn dielectric standoff
- One half lap layer of glass to allow for epoxy impregnation
- Additional .006" thk by 1" wide glass between layers to wick epoxy




Trim Ground Wrap				
1/2 Lap Layer Dry Glass	Glass	0.006		0.54
	Glass	0.006		0.54
1/2 Lap Layer Dry Glass	Glass	0.006		0.54
	Glass	0.006		0.54
1/2 Lap Layer Dry Glass	Glass	0.006		0.54
	Glass	0.006		0.54
1/2 Lap Layer Dry Glass	Glass	0.006		0.54
	Glass	0.006		0.54
1/2 Lap Layer Dry Glass	Glass	0.006		0.54
	Glass	0.006		0.54
1/2 Lap Layer Dry Glass	Glass	0.006		0.54
	Glass	0.006		0.54
1/2 Lap Layer Dry Glass	Glass	0.006		0.54
	Glass	0.006		0.54
1/2 Lap Layer Dry Glass	Glass	0.006		0.54
	Glass	0.006		0.54
1/2 Lap Layer Dry Glass	Glass	0.006		0.54
	Glass	0.006		0.54
		<b>0.12</b>	<b>Inches</b>	<b>10.8 KV</b>
Trim Turn to Turn				
1/2 Lap Layer Dry Glass	Glass	0.0012		0.108
	Glass	0.0012		0.108
	Kapton	0.0017		7.7
	Kapton	0.0017		
		<b>0.0058</b>	<b>Inches</b>	<b>7.9 KV</b>



NO.	REVISION	BY	CHK	SEP	APPROVED	DATE



SCALE 0.350



DETAIL B  
SCALE 20



SECTION A-A

- NOTES:
1. DRAWINGS PREPARED IN ACCORDANCE WITH ASME Y14100-2000
  2. INTERPRET DIMENSIONS & TOLERANCES PER ASME Y14.5-1994.
  3. DIMENSIONS ARE IN INCHES.
  4. SEE SPECIFICATION NCSX-CSPEC-133-01 FOR ADDITIONAL INFORMATION AND/OR MATERIAL REQUIREMENTS.
  5. WIRE LEAD STARTS TO PROTRUDE BEYOND OUTSIDE SURFACE AT THIS POINT.
  6. LEAD LENGTH A MINIMUM OF 6 INCHES AND SHIP TEMPORARILY BOUND TO COIL.
  7. SLEEVE LEAD WITH TWO LAYERS OF PTFE HEAT SHRINK TUBING TO A MINIMUM OF 1/2" UNDER THE GROUND WRAP AS SPECIFIED IN NCSX-CSPEC-133-01.

RELEASE LEVEL: WIP  
DWG VERSION NO: 2




COMPUTER GENERATED DRAWING MANUAL CHANGES NOT PERMITTED	GENERAL FILES: UNLESS OTHERWISE SPECIFIED	PRINCETON PLASMA PHYSICS LABORATORY NATIONAL COMPACT STELLARATOR EXPERIMENT
WEIGHT 170.3 lbs	DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED	STEELATOR CORE TRIM COIL B1
MODEL NAME TC133-D31	TOLERANCES UNLESS OTHERWISE SPECIFIED: FRACTIONS DECIMALS AS SHOWN AS SHOWN DECIMALS UNLESS OTHERWISE SPECIFIED	ISSN: B. UPKAYASE DRAWN: W. KALISH CHECKED: SUPP.
NO. OF SHEETS 1	NO. OF SHEETS 1	DRAWING NO: SE133-031
SHEET ASSEMBLY	NO. OF SHEETS 1	SHEET 1 OF 1 REV. 0



# Structural Design

## NCSX

- Coil Assemblies assembled off line and then bolted to TF and PF Coils supports
- Brackets offer 3 degrees of adjustment
- Custom shimming may be required to correct for angle in one plane only
- With all frames accurately machined a representative aluminum template can be used to pre-fab shims if required





*NCSX Conventional Coils*



# R&D Weld Testing Setup

NCSX

- Testing to assure U Channel welding did not exceed 120C at coil surface
- Wooden Block assembled to mockup of Coil Structure
- Ten thermocouples record temperature
- Method and results logged for assembly procedure




# R&D Weld Testing- With Heat Sink

NCSX





TF Coil Weld Test  
4-30-08 w/ Heat Sink







# Structural Design Upper / Lower Coils

NCSX




# Structural Design - Installed

NCSX




*NCSX Conventional Coils*


NO.	REVISION	BY	CHK	SUP	APPROVED	DATE




TOP VIEW




DETAIL A  
SCALE 1



DETAIL B  
SCALE 1



DETAIL C  
SCALE 1



BOTTOM VIEW

PART NO.	DRAWING NO	NOMENCLATURE OR DESCRIPTION	MATERIAL	QTY	REC'D
16	SE133-047-4	TRIM COIL #2 UPPER/LOWER MOUNTING BRACKET LEFT	304L SS/STL	4	
15	SE133-047-1	TRIM COIL #2 UPPER/LOWER MOUNTING BRACKET LEFT	304L SS/STL	4	
14	RU_WASHER	3/8 FLAT WASHER	STN STL	67	
13	RU_TRIM_COIL_1A_WELDMENT	TRIM COILS HALF PERIOD ASSEMBLY	SEE DETAILS	1	
12	RU_NUT	3/8-16 UNC STANDARD HEX NUT	STN STL	32	
11	RU_INSULATOR_WASHER	3/8 FLAT WASHER	STN STL	8	
10	RU_GIO_INSULATOR_A	--	--	4	
9	RU_GIO_CONTACTB	--	--	1	
8	RU_GIO_CONTACT_BOTTOM	--	--	1	
7	RU_BRACE_BLOCK	--	--	2	
6	RU_BRACKET_STOP	--	--	4	
5	RU_BELVILLE	3/8 DISC SPRING 114 LBS (P max)	STN STL	66	
4	RU_12_GAGE_WIRE	--	--	1	
3	RU_12_GAGE_WIRE	--	--	1	
2	92198A633	3/8 - 16 UNC X 1 3/4 LG HEX HD MAWMASTER CARR #92198A630	18-8 STN STL	2	
1	92198A630	3/8 - 16 UNC X 1 3/4 LG HEX HD MAWMASTER CARR #92198A630	18-8 STN STL	2	



PARTS LIST		COMPUTER GENERATED		CENTRAL FILES:		PRINCETON PLASMA PHYSICS LABORATORY	
		DRAWING NO.		UNLESS OTHERWISE SPECIFIED		PROJECT NO. 13	
		13		DIMENSIONS ARE IN INCHES		NATIONAL COMPACT STELLARATOR EXPERIMENT	
		13		MACHINE SURFACES		STELLARATOR CORE	
		13		BRIEF SURF FINISH: 320-320		TRIM COILS	
		13		TOLERANCES: NON-CRITICAL: .005		TRIM COIL PERIOD ASSEMBLY	
		13		CRITICAL: .001		DRAWING NO.:	
		13		DECIMAL: .001		RU_TRIM_COIL_1A	
		13		FRACTIONS: 1/16		SHEET 1 OF 1	
		13		CHG:		REV: 0	
		13		ENGR: KALSH			
		13		SUPP:			

RELEASE LEVEL: WIP  
DWG VERSION NO. 13

# Coil Leads Supports

NCSX

- Leads protrude from a notch in the  $\frac{3}{4}$  inch support plate
- Leads are sleeved with Teflon for improved dielectric standoff
- Leads and Trim Coil cables are brazed into a copper transition block
- G11 blocks strain relieve leads and cable transition






# Conductor Modeled with Equivalent Properties calculated from Flexural Modulus Simulation

NCSX

## Equivalent Flexural Modulus and Stress Scaling for Trim Coils

	E, Mpsi	Sz, psi	E, Mpsi	Sz, psi	Sz/Sz	Sz/Sz_max
Cu Wire	17	18390	<b>5.85</b>	6620	2.78	<b>2.19</b>
Insulation	1.5	2111	<b>5.85</b>	8379	0.25	<b>0.25</b>

- Detailed Model of 120 Turn Coil
- Distinct Elements for Copper and Glass Insulation
- Equivalent properties used for large composite model
- Results from composite model scaled to determine maximum stresses



# Load Cases Investigated for EM Forces


NCSX

- All GRD Load Cases at Multiple (5) time points
  - Additional Flexibility Cases Identified by Physics
    - Iota Scan (2)
    - Shear Scan (2)
  - **Max Running Loads Found**
    - 80 lb/in Inner Coils
    - 60 lb/in Outer Coils
  - Subsequent analysis is run for the worst load case *iota* .19 case
- 2T High Beta
  - 1.7T High beta
  - 1.2T Long Pulse
  - 1.7T Ohmic
  - 320KA Ohmic
  - 0.5 T TF
  - Iota/Shear Scan
    - *iota* -0.10
    - *iota* 0.19 (High TF Field)
    - *iota* +0.20
    - *iota* 0.65

# Conductor Stress Result

NCSX

- EM only= **7.3Ksi**
- EM only allowable=  
 $1.5S_m=$ **10.3ksi**  
(at 77K for local bending)
- Cool Down only= **8ksi**
- CD only allowable  
 $3xS_m=$ **20.7ksi**  
(for secondary thermal stress + primary)
- CD+EM= **10.7ksi**
- Allowable  
 $3xS_m=$ **20.7ksi**  
(for secondary thermal stress + primary)




NCSX Conventional Coils

# 3/4" Support Plate Stress Result

NCSX

- EM only= **11.3ksi**
- EM only allowable= **Sm=20.0ksi**  
(Primary Member Stress)
- Cool Down only= **16.7ksi**
- Allowable 3xSm=**60.0ksi**  
(for secondary thermal stress + primary)
- CD+EM= **23.7ksi**
- Allowable 3xSm=**60.0ksi**  
(for secondary thermal stress + primary)




NCSX Conventional Coils

# U Channel Stress Result

NCSX

- EM only= **16.6 ksi**
- Allowable=  $1.5S_m$ =**35.0ksi**  
(Primary Member Stress)
- Cool Down only= **26.9ksi**
- Allowable  $3xS_m$ =**60.0ksi**  
(for secondary thermal stress + primary)
- CD+EM= **36.7ksi**
- Allowable  $3xS_m$ =**60.0ksi**  
(for secondary thermal stress + primary)
- Element Average Stress is only 30% of Max Stress Result **36.7ksi**→**10.9ksi**



# Coil Cooling Analysis

## Comfortable Design Margins With Convection Cooling

NCSX

- **Requirement**
  - 2 second pulse every 15 minutes
  - 20 Kamp Turns
  - Equivalent average power of 27 watts
- **For 120 Turn Coil With 2mm Conductor (10X20)**
  - Convection cooling adequate
  - Temperature increase per pulse is only approx.= 2.6 C
  - Equilibrium reached with temperature rise approx.= 9.0C
- **Margin Available**
  - Doubling the current to 40 amp turns
  - Equivalent Average Power of 107 watts
  - Temperature increase per pulse is only approx.= 10.3 C
  - Equilibrium reached with temp. rise approx.= 35C

