

**U.S. Department of  
Homeland Security**

**United States  
Coast Guard**



**EIGHTH COAST GUARD DISTRICT  
SPECIAL NOTICE TO MARINERS  
GULF OF MEXICO  
00-2007**

# TABLE OF CONTENTS

<b>Chapter 1.</b>	<b>EIGHTH COAST GUARD DISTRICT UNITS</b>	<b>PAGE</b>
	Eighth Coast Guard District Staff Office	1
	Vessel Traffic Services	2
	Air Stations	2
	Prevention Division	2
	Stations	3
	Loran Stations	4
	Floating Units	4
	Shore Aids to Navigation Units	4

<b>Chapter 2.</b>	<b>EMERGENCY PROCEDURES</b>	<b>PAGE</b>
	International Distress Signals	6
	Distress Procedures	7
	Medical Cases	7
	Other Vessels in Distress	7
	Preparations for Towing	8
	Pump Drop Procedures	8
	Helicopter Hoisting Procedures	8
	Ship Abandonment and Hypothermia	9
	Non-Emergency Cases	10
	False SAR Reports	10
	Urgency and Safety Signals	10
	Automated Mutual Assistance Vessel Response (AMVER)	10
	Emergency Position Indicating Radiobeacon	11

<b>Chapter 3.</b>	<b>COMMUNICATIONS</b>	<b>PAGE</b>
	Channels 13 and 16	13
	Bridge to Bridge Radio Telephone Regulations	13
	Coast Guard Broadcast Notice to Mariners	14
	Eighth Coast Guard District HF Coverage	14
	Scheduled Marine Information Broadcasts	14
	NAVTEX	16
	Coast Guard to Check for FCC License During Boarding	17
	VHF Marine Radio Information	17

<b>Chapter 4.</b>	<b>VESSEL TRAFFIC SAFETY</b>	<b>PAGE</b>
	Berwick Bay Vessel Traffic Service	18
	Traffic Separation Schemes and Areas to be Avoided	18
	Regulated Navigation Areas	20
	Limited Access Areas - Permanent Safety Zones	21
	Anchorage Areas	21
	Inland Waterway Navigation Regulations (Oversize Tows)	22
	Gulf Intracoastal Waterway	22
	High Water Towing Limitations, Morgan City, LA	23
	Vessel Traffic Lights, Algiers Point, New Orleans, LA	23
	Navigation Rules	23
	Alpha Flag Diving Operations	23
	Special Rules - Signal Lights for Navy Ships	25
	Distinctive Lights Authorized for Naval Vessels	26
	Caution - Naval Formations	26
	Improper Use of Searchlights and Floodlights at Sea	26

<b>Chapter 5.</b>	<b>AIDS TO NAVIGATION (ATON)</b>	<b>PAGE</b>
	Caution to be Used in Reliance upon ATON	27
	Reporting ATON Discrepancies	27
	Collision with or Damage to ATON	27
	IALA Maritime Buoyage System	28
	Characteristics of Lights	28
	Isolated Danger Marks	29
	Vandalism of ATON	29
	ATON Maintenance Signals	29
	Private ATON	29
	RACONS Authorized for Private ATON	30
	RACONS	30
	LORAN-C	31
	Global Positioning System	31
	Differential Global Positioning System	31

<b>Chapter 6.</b>	<b>COMMON CAUTIONARY SITUATIONS</b>	<b>PAGE</b>
	Close Approach to Moored Offshore ATON	32
	Oil Well Structures in the Gulf of Mexico	32
	Pipeline Laybarges and Jetbarges	32
	Possible Danger from Unlabeled drums	32
	Seismic Surveys	33
	Danger from Submarine Cables and Pipelines	33
	United States Submarine Cable Act	33
	Submerged Offshore Pipeline	33
	Firing Danger Areas	34
	Explosive Ordnance	34
	Reporting Hazards to Navigation	34
	Mississippi River Gulf Outlet	35
	Inland Hazards to Navigation	35
	Marking of Wrecks	35
	Flood Warnings	35
	Hurricane Season	36
	How Hurricanes are categorized	37
	Storm Surge	37
	Maneuvering to Avoid a Storm Center	37

<b>Chapter 7.</b>	<b>BOATING SAFETY</b>	<b>PAGE</b>
	Alcohol Abuse and Recreational Boating	39
	Boating Safety Hotline	39
	Non-Emergency Assistance	39
	Law Enforcement	40
	Coast Guard Auxiliary	40
	Coast Guard Approved Equipment	41
	Minimum Required Equipment by Length of Boat	42
	Title 33 Code of Federal Regulations – Ventilation	43
	Numbering Requirements	46
	Pollution Placards	47
	Notices to Sponsors of Marine Events	47
	Safe Boating is No Accident	48
	Boating Accident Reports	48
	Make a Float Plan	49
	Marine Sanitation Devices	49

<b>Chapter 8.</b>	<b>WATER POLLUTION</b>	<b>PAGE</b>
	Compliance with Clean Water Act and Refuse Act	51
	Compliance with the Act to Prevent Pollution from Ships	51
	Pollution - Ocean Dumping	52

<b>Chapter 9.</b>	<b>LAW ENFORCEMENT</b>	<b>PAGE</b>
	Law Enforcement	53
	Coast Guard Boarding Policy	53
	Citizenship Requirements	54
	Foreign Fishing Activity off the Coast of the United States	54
	Expansion of the Territorial Sea of the United States	55
	Smuggling	55
	Operation of Vessels While Intoxicated	56
	Mandatory Drug Testing in Marine Workplace	56
	Hijacking Danger	56
	River Watch Program	57

<b>Chapter 10.</b>	<b>CHARTS AND RELATED PUBLICATIONS</b>	<b>PAGE</b>
	Charts and Publications Availability - Purchase and Issue	58
	Local Notice to Mariners	58
	U.S. Coast Pilot	59
	Weekly Notice to Mariners	59
	Light List	59

<b>Chapter 11.</b>	<b>BRIDGES</b>	<b>PAGE</b>
	Bridge Administration	60
	List of Drawbridges with Special Operating Regulations	60

# CHAPTER I

## EIGHTH COAST GUARD DISTRICT OFFICES

<b>OFFICE OF THE DISTRICT COMMANDER</b>	(504) 589-6298
<b>OFFICE OF THE CHIEF OF STAFF</b>	(504) 589-6223
Civil Rights/Equal Employment Opportunity	(504) 671-2011
District Legal Officer	(504) 671-2030
Public Affairs Officer	(504) 671-2019
<b>RESOURCES DIVISION</b>	(504) 671-2174
Deputy for Finance	(504) 671-2200
<b>PREVENTION DIVISION</b>	(504) 671-2105
<b>Waterways Management Branch</b>	
Waterways Federal Projects Section	(504) 671-2112
Waterways Management Private Aids Section	(504) 671-2328
Waterways Management Marine Information Section	(504) 671-2327
Bridge Management Section	(504) 589-2965
<b>Auxiliary Branch</b>	
Coastal Region Auxiliary Affairs Staff, New Orleans, LA	(504) 671-2144 800-524-8835
<b>WESTERN RIVERS DIVISION</b>	
<b>Auxiliary Branch</b>	
Western Rivers Staff, St. Louis, MO	(504) 671-2266
Eastern Region, Louisville, KY	(502) 779-5321 800-217-4420
<b>Marine Investigations Branch</b>	(504) 671-2157
<b>RESPONSE DIVISION</b>	
Enforcement Branch	(504) 671-2243
SAR Controller	(504) 589-6225
Command Center Staff	(504) 589-6225
Hurricane/Emergency Info Line	800-787-8724
<b>Incident Management Branch</b>	(504) 671-2230

## SECTOR OFFICES AND STATIONS

### SECTOR MOBILE

Commander	
U.S. Coast Guard	
Sector Mobile	
BLDG. 101, Brookley Complex	
Mobile, AL 36615	
Commander	(251) 441-5962
Operations	(251) 441-6213
Aids to Navigation Officer	(251) 441-6095
Group Search and Rescue (SAR) Coordinator/OOD	(251) 441-6211

**SECTOR NEW ORLEANS**

Commander  
U. S. Coast Guard  
Sector New Orleans  
201 Hammond Hwy.  
Metairie, LA 70005

Commander	(504) 846-6184
Operations	(504) 846-6160
Search and Rescue (SAR)	(504) 846-6161
Aids to Navigation Officer	(504) 846-6145

**SECTOR HOUSTON-GALVESTON**

Commander  
U.S. Coast Guard  
Sector Houston-Galveston  
P.O. Box 1912  
Galveston, TX 77553-1912

Commander	(409) 766-5613
Operations Officer	(409) 766-5603
Group Search and Rescue (SAR)	(409) 766-5636
Aids to Navigation Officer	(409) 766-5615

**SECTOR CORPUS CHRISTI**

Commander  
U.S. Coast Guard  
Sector Corpus Christi  
Corpus Christi, TX 78419

Commander	(361) 939-6201
Aids to Navigation Officer	(361) 888-3173

**VESSEL TRAFFIC SERVICES**

BERWICK, LA	(504) 380-5300
HOUSTON/GALVESTON, TX	(713) 678-9090

**AIR STATIONS**

MOBILE, AL	(334) 639-6161
NEW ORLEANS, LA	(504) 393-6005
(Aviation Training Center)	
HOUSTON, TX	(281) 482-0025
CORPUS CHRISTI, TX	(361) 939-6200

**PREVENTION DIVISION**

CORPUS CHRISTI, TX	361-888-3162
PORT LAVACA, TX	361-552-7422
BROWNSVILLE, TX	210-546-2786
HOUSTON/GALVESTON, TX	713-671-5199
HUNTINGTON, WV	304-529-5524
LOUISVILLE, KY	502-582-5194
MSD CINCINNATI, OH	513-921-9033/1329
MEMPHIS, TN	901-544-3941
DETACHMENT, GREENVILLE, MS	662-332-0964
DETACHMENT, HELENA, AR	870-338-7524
MOBILE, AL	334-441-5201
DETACHMENT PANAMA CITY, FL	850-233-0366

## PREVENTION DIVISION (Cont.)

MORGAN CITY, LA	504-380-5305
MARINE SAFETY UNIT HOUMA	504-851-1692
MARINE SAFETY FIELD OFFICE GALLIANO	504-632-8676
MARINE SAFETY FIELD OFFICE LAFAYETTE	318-988-9220
NEW ORLEANS, LA	504-589-6196
MARINE SAFETY UNIT BATON ROUGE	225-298-5400
PADUCAH, KY	270-442-1621
DETACHMENT NASHVILLE, TN	615-736-5421
PITTSBURGH, PA	412-644-5808/07/06
PORT ARTHUR, TX	409-723-6513
MSU LAKE CHARLES, LA	337-433-3765
MARINE INSPECTION DETAIL JENNINGS, LA	337-824-6968
ST. LOUIS, MO	314-539-3091
MARINE SAFETY DETACHMENT QUAD CITIES, IL	309-782-0627/28
MARINE SAFETY DETACHMENT ST. PAUL, MN	612-290-3991
DETACHED MARINE INSPECTOR PEORIA, IL	309-694-7779
DETACHED MARINE INSPECTOR LA CRESCENT, MN	507-895-6341

## MARINE SAFETY UNITS

GALVESTON, TX	409-766-3655
---------------	--------------

## SEARCH AND RESCUE DETACHMENTS

DAUPHIN ISLAND, (Mobile, AL)	251-861-7239
DESTIN (Destin, FL)	850-244-7146
FREEPORT (Surfside, TX)	409-233-3801
GALVESTON (Galveston, TX)	409-766-5642
GRAND ISLE (Grand Isle, LA)	504-787-2135
GULFPORT (Gulfport, MS)	601-868-5818
NEW ORLEANS (New Orleans, LA)	504-846-6181
PADRE ISLAND (South Padre Island, TX)	956-761-2668 Ext. 202
PANAMA CITY (Panama City, FL)	850-234-2475

## STATIONS

DESTIN (Destin, FL)	850-244-2682
FREEPORT (Surfside, TX)	979-233-7551
GALVESTON (Galveston, TX)	409-766-5633
GRAND ISLE (Grand Isle, LA)	504-787-2135
GULFPORT (Gulfport, MS)	228-868-3743
MOBILE (Mobile, AL)	334-441-5015
NEW ORLEANS (New Orleans, LA)	504-589-2331
Support Center Number	504-942-3049
PANAMA CITY (Panama City, FL)	850-234-4228
PASCAGOULA (Pascagoula, MS)	228-761-2600
PENSACOLA (Pensacola, FL)	850-453-9195
PORT ARANSAS (Port Aransas, TX)	361-749-5217
PADRE ISLAND (South Padre Island, TX)	956-761-2668
PORT O'CONNOR (Port O'Connor, TX)	512-983-2616
SABINE (Sabine Pass, TX)	409-971-2519
VENICE (Venice, LA)	504-534-2332

## LORAN STATIONS

BOISE CITY, OK (Felt, OK)	580-426-2221
DANA, IN (Dana, IN)	765-665-3335/832-9266
GRANGEVILLE, LA (Grangeville, LA)	225-222-6128
GILLETTE, WY (Gillette, WY)	307-682-8920
MALONE, FL (Malone, FL)	850-569-2223
RAYMONDVILLE, TX (Raymondville, TX)	956-689-2488
LAS CRUCES, NM (Las Cruces, NM)	505-233-4645/4709

## FLOATING UNITS

USCGC:	
AMBERJACK (WPB 87315) South Padre Island, TX	956-761-2373/75
AXE (WLIC-75310) Morgan City, LA	985-385-0037
BARBARA MABRITY (WLM 559) Mobile, AL	251-441-6275/76
BONITO (WPB 87341) Corpus Christi, TX	
BRANT (WPB 87348) Corpus Christi, TX	731-642-7181
CLAMP (WLIC-75306) Galveston, TX	409-766-5681/82
COBIA (WPB87311) Mobile, AL	251-441-5417
COHO (WPB87321) Panama City, AL	850-234-2031
CYPRESS (WLB-210) Mobile, AL	251-441-6277
DECISIVE (WMEC 629) Pascagoula, MS	228-761-2500
HARRY CLAIBORNE (WLM-561) Galveston, TX	409-766-5690/91
HATCHET (WLIC-75309) Galveston, TX	409-766-5683/84
HERON (WPB-87344) Sabine, TX	409-971-2198
MALLET (WLIC-75304) Corpus Christi, TX	361-844-6500 ext. 531
MANOWAR (WPB-87330) Galveston, TX	409-766-5669
MANTA (WPB-87230) Freeport, TX	979-233-3301
PAMLICO (WLIC-800) New Orleans, LA	504-
PELICAN (WPB 87327) Abbeville, LA	337-898-8660
POMPANO (WPB 87339) Gulfport, MS	228-868-8779
RAZORBILL (WPB 87332) Gulfport, MS	228-863-2655
SAGINAW (WLIC-803) Mobile, AL	251-441-5197/99
SEAHAWK (WPB 87323) Carrabelle, FL	850-697-9797
SKIPJACK (WPB 87323) Galveston, TX	
STEELHEAD (WPB 87324) Port Aransas, TX	361-749-0062
STINGRAY (WPB 87305) Mobile, AL	251-441-5268/29
STURGEON (WPB 87336) Grand Isle, LA	504-787-2137
WEDGE (WLR 75307) Demopolis, AL	334-289-0354

## AIDS TO NAVIGATION TEAMS

CORPUS CHRISTI (Corpus Christi, TX)	985-563-4473/3128
COLFAX (Colfax, LA)	318-627-2783
DULAC (Dulac, LA)	985-563-4473
EUFULA (Eufaula, AL)	334-687-5140
GALVESTON (Galveston, TX)	409-766-5637/66
GULFPORT (Gulfport, MS)	228-864-5522
MOBILE (Mobile, AL)	251-441-6244
MORGAN CITY (Morgan City, LA)	985-384-7000/8314
NEW ORLEANS (New Orleans, LA)	504-253-6562
PANAMA CITY (Panama City, FL)	850-234-8139
PENSACOLA (NAS Pensacola, FL)	850-455-2354
PORT O'CONNOR (Port O' Connor, TX)	361-983-4313
SABINE (Sabine Pass, TX)	409-971-2519



**AIDS TO NAVIGATION TEAMS (Cont.)**

SOUTH PADRE ISLAND (South Padre Island Texas)  
VENICE (Venice, LA)

956-761-7257  
985-534-7250

# CHAPTER II

## EMERGENCY PROCEDURES

### INTERNATIONAL DISTRESS SIGNALS

All seamen should be familiar with the international distress signals and procedures, both for recognition purposes and for self reliance in the event of distress where the captain and officers may have been incapacitated.

**Short range distress signals, limited to range of visibility or audibility, are:**

- “SOS” signal made by any audio or visual means.
- International Code of Signals “NC”.
- Hoisting any square flag with a ball or anything resembling a ball, above or below it.
- Flames made visible (as a burning oil barrel).
- A rocket parachute flare or hand held flare showing a red light.
- Rockets or shells, throwing red stars one at a time at short intervals.
- Orange smoke, as emitted from a distress flare.
- A gun or other explosive signal fired at intervals of about one minute.
- A continuous sounding of any fog - signal apparatus.
- Slowly and repeatedly raising and lowering of arms outstretched to each side.
- Signals transmitted by emergency position - indicating radiobeacons (EPIRB).

#### **Radio distress signals via radiotelephone:**

Trip the radiotelephone alarm signal (if available) equipment to distress frequency 2182 kHz, (or VHF telephone set to Channel No. 16 (156.80 MHz) and transmit the spoken word “MAYDAY” repeated three times followed by “this is” and then the name of the vessel repeated three times. Do not wait for acknowledgment. Continue by stating the nature of the distress; the kind of assistance desired; the position; any other information which might facilitate the rescue. Wait a few moments for acknowledgment. Then, if none, repeat the entire distress message until acknowledged. Speak the message clearly and unhurriedly. Non-acknowledgment is not definite indication that someone did not receive the message.

#### **For radio distress signals via INMARSAT ship-earth station:**

Select either the telex or telephone mode of operation and place a distress call to the nearest rescue coordination center (RCC) in accordance with the ship-earth station manufacturer’s instructions. Note that communications over the satellite terminal may be interrupted during a ship casualty if terminal and antenna are not connected to a source of emergency power.

Section 359 (d) of the United States Communications Act provides that: “No charges shall be made by any ship or station in the mobile service of the United States for the transmission of distress messages and replied there to in connection with situations involving the safety of life and property at sea.” The FCC interprets this to apply equally to maritime mobile satellite systems.

Note that neither INMARSAT nor U.S. coast earth stations charge for any distress communications provided that the communication is initiated by a terminal user pressing the distress button (Priority 3 Distress Alert). Note that this button should be used to initiate distress relay as well as distress communications. Simple to follow instructions for the operation of auto alarms, radiotelephone and radiotelegraph equipment should be conspicuously posted in the radio rooms of all ships. Procedures outlined here are purposely brief. Complete information on emergency radio procedures is contained in Chapter 5 of Radio Navigational Aids (Pub. 117).

## **DISTRESS PROCEDURES**

IF ABOARD A VESSEL IN TROUBLE GIVE:

- WHO you are (your vessel's call sign and name).
- WHERE you are (your vessel's position in latitude/longitude or true bearing and distance in nautical miles from a widely known geographical point; local names known only in immediate vicinity are confusing). Indicate method of determining your position; give actual LORAN readings, depth of water, radiobeacon bearings, etc. Indicate which information you are certain of and which position information may be doubtful.
- WHAT is wrong (nature of distress or difficulty).
- Kind of assistance needed.
- Number of persons aboard and the condition of any injury.
- Present seaworthiness of your vessel.
- Description of your vessel; length, type, cabin, masts, power, color of hull, superstructure and trim.
- Your listening frequency and schedule.

## **IF YOU HAVE A MEDICAL CASE SEND:**

- Name of vessel and call sign.
- Position.
- Patient's name and age.
- Nature of problem (symptoms, locations of pain or injury).
- Is patient conscious? (Unconscious at any time?)
- Is patient ambulatory? (able to walk)
- Patient's temperature and pulse. Difficulty breathing? Number of respirations per minute?
- Is patient bleeding? Is the bleeding controlled?
- Duration of pain.
- Previous similar episode (if yes, treatment and diagnosis).

Medicine taken and medicine available.

Private physician's name and phone number.

Vomiting? Diarrhea?

Can you take his blood pressure?

How do his eyes react to light?

## **IF OBSERVING ANOTHER VESSEL IN DIFFICULTY GIVE:**

- Your position, and (if possible) the bearing and distance of the vessel in difficulty.
- Nature of distress or difficulty.
- Description of the vessel in distress or difficulty.
- Your intentions, course, and speed, etc.
- Your radio call sign, name of your vessel, listening frequency and schedule.

The distress call has absolute priority over all other transmissions and need not be addressed to any particular station. Any mariner hearing a distress call shall immediately cease all transmissions capable of interfering with the distress message and shall continue to listen on the frequency which the call was heard. If your vessel is in distress and abandonment is necessary, the radio transmitter should be set for continuous emission, if possible, to provide rescue vessels and aircraft with a homing signal.

## **PREPARATIONS FOR TOWING:**

- Have forecandle cleared.
- If line-throwing gun is used, keep all personnel out of the way until projectile clears board.
- Have material handy for chaffing gear.
- Secure tow line to bit or crucifix and remove heaving line.

## **PUMP DROP PROCEDURES**

If a DISTRESS situation involves the control of flooding or dewatering of your vessel, a portable pump may be flown to your location. The pump will be packed in a floating container and will have a retrieving line attached. If delivered by an airplane it will be dropped into the water near your vessel at a safe distance. If delivered by helicopter it will be lowered to the deck of your vessel unless conditions are unsafe.

Preparations for arrival of the helicopter are the same as outlined in HELICOPTER HOISTING PROCEDURE below.

If the pump is lowered from a helicopter, allow the retrieving line to touch the deck to discharge static electricity before touching it. If your vessel still has propulsion, it should be underway as indicated in the hoisting procedure. Once on deck the canister should be released and the helicopter permitted to retrieve its hoist cable as soon as possible. DO NOT attach anything to your vessel that has not been detached from the hoist cable. Follow instructions provided with the pump. When the pump has served its purpose, return it with the canister and all accompanying instructions and attachments to the nearest Coast Guard facility.

## **HELICOPTER HOISTING PROCEDURE**

### **PREPARE FOR ARRIVAL**

Stand by on 2182 kHz or VHF-FM Channel 16 or a specified alternate frequency. If possible display DISTRESS signal, which is the orange flag with a black circle and black square superimposed. Clear hoist area. The best hoist area is aft, but maximum horizontal clearance is important. If hoist area is amidships, lower antenna and secure running gear. At night, light area. DO NOT shine lights on helicopter.

### **HOISTING**

Tag patient, indicate medication given and conditions doctor should be aware of. Keep vessel underway into wind or with wind about 20 degrees on port bow at 10 to 15 knots. The pilot will give hoist instructions. Allow litter or basket to touch deck to discharge static electricity. Wear dry cotton or rubber gloves. If litter is used it will be equipped with a hoisting bridle. Conditions permitting, have patient in life jacket, strapped in, face up, and hands clear of sides. DO NOT secure hoist cable to vessel or attempt to move litter without first unhooking cable. With patient strapped in, signal pilot to lower hoist cable. Hook cable to stretcher. Signal pilot to hoist. Steady litter using trail line. Make sure line is clear of rigging.

## SHIP ABANDONMENT AND HYPOTHERMIA

If you are forced to abandon ship, your chances of rescue are increased if you have a pre-planned survival procedure and follow it. Records show that even the quickest ship sinkings usually require 15 to 30 minutes for the vessel to fully submerge. This affords valuable time for preparation. Here are some sound pointers for you to remember in a situation of this type:

- Don as much warm clothing as possible, covering head, neck, hands, and feet.
- If an immersion (exposure) suit is available, put it over warm clothing.
- If the immersion suit does not have inherent flotation, put on a life jacket.
- All persons who know that they are likely to be affected by seasickness should, before or immediately after boarding the survival craft, take the recommended dose of some recommended preventative tablets or medicine. The incapacitation caused by seasickness interferes with your survival chances; the vomiting removes precious body fluid while seasickness in general makes you more prone to hypothermia.
- Avoid entering the water if possible. Board davit-launched survival craft on the embarkation deck. If davit-launched survival craft are not available, use ladders, or, if necessary, lower yourself by means of a rope or fire hose.
- Unless it is unavoidable, do not jump from higher than 5 meters (16.4 feet) into the water. Try to minimize the shock of sudden cold immersion. Rather than jumping into the cold water, try to lower yourself gradually. A sudden plunge into the cold water can cause death or an uncontrollable rise in breathing rate may result in an intake of water into the lungs. On occasions it may be necessary to jump into the water; if so, you should keep your elbows at your sides, cover your nose and mouth with one hand holding the wrist or elbow firmly with the other hand.
- Once in the water, orient yourself and try to locate the ship, lifeboats, liferafts, other survivors or other floating objects. If you are unable to prepare yourself before entering the water, button up clothing immediately. In cold water you may experience violent shivering and great pain. These are natural body reflexes that are not dangerous. You do, however, need to take action as quickly as possible before you lose full use of your hands. Button up clothing, turn on signal lights, locate whistle, etc.
- While afloat in the water, do not attempt to swim unless it is to reach a nearby craft, a fellow survivor, or a floating object, on which you can lean or climb on to. Unnecessary swimming will “pump” out any warm water between your body and the layers of clothing, thereby increasing the rate of the body-heat loss. In addition, unnecessary movements of your arms and legs send warm blood from the inner core to the outer layer of the body. This results in a very rapid heat loss. Hence, it is most important to remain as still as possible in the water, no matter how painful it may be. Remember, pain will not kill you, but heat loss will.
- Try to conserve body heat. Float as still as possible with your legs together, elbows close to your side and arms folded across the front of your life jacket, minimizing the exposure of the body surface to the cold water. Try to keep your head and neck out of the water. Another technique is to huddle closely to one or more persons afloat, making as much body contact as possible. You must be wearing a life-vest to be able to hold these positions in the water.
- Try to board a lifeboat, raft, or other floating platform or object as soon as possible in order to shorten your immersion time. Take EPRIB when boarding life boat. Remember, you lose body heat many times faster in water than in air. Since the effectiveness of your insulation is seriously reduced by water soaking, you must try to shield yourself from wind to avoid a wind chill effect (convective cooling).
- Do not use “drownproofing” in cold water. “Drownproofing” is a technique whereby you relax in the water and allow your head to submerge between breaths. It is an energy saving procedure to use in warm water when you are not wearing a life-vest. However, the head and neck are high heat loss areas and must be kept above water. That is why it is more important to wear a life-vest in cold water. If you are not wearing a vest, tread water only as much as necessary to keep your head out of the water.
- Keep a positive attitude about your survival and rescue. This will improve your chance of extending your survival time until rescue comes. Your will to live does make a difference.

## **NON-EMERGENCY ASSISTANCE CASES**

Routinely, the Coast Guard receives calls for assistance that pose no threat to life.

These calls are classified as “NON-EMERGENCY ASSISTANCE.”

The Coast Guard is required to attempt turn non-emergency assistance cases over to “QUALIFIED OPERATORS” to provide the appropriate assistance. A qualified operator is a private firm (or individual) who has demonstrated to the satisfaction of the local Coast Guard Group Commander that it has the appropriate professional capability, equipment, and operating personnel to render assistance safely and in a reasonable time in specific non-emergency cases. Firms or individuals desiring to become “Qualified Operators” to be called for non-emergency assistance cases, may make application with their local Coast Guard Group Commander. The local Group Commander will evaluate the firm/individual’s capability and qualify or advise the applicant of the necessary steps to attain qualification. For application or more information on non-emergency assistance, contact your local Coast Guard Group Commander.

## **FALSE SAR REPORTS**

False Search and Rescue (SAR) reports save nobody, and are a violation of the law. All too often the Coast Guard responds to distress calls that are later determined to be hoaxes. Responding to hoax calls occupies critical SAR resources, and often prevents these much needed units from responding to legitimate distress cases. The end result sometimes leads to an unnecessary fatality. When the perpetrator of a SAR hoax is discovered, he will be prosecuted to the fullest extent of the law. Anyone having knowledge that a distress call was fraudulently issued should report that fact to the nearest Coast Guard unit. Maximum penalty for making a false SAR report: It is a felony. Fine of \$10,000.00, imprisonment for 5 years, or both, plus all cost associated with the SAR response.

## **URGENCY AND SAFETY SIGNALS**

The radiotelephone urgency signal, which is the group of words PAN PAN (pronounced “PAWN” as in lawn) spoken three times, is provided for use in cases in which a ship making a call has a very urgent message to transmit concerning the safety of a ship, aircraft, or other vehicle, or the safety of a person, but it does not necessarily imply that the ship is in imminent danger or requires immediate assistance. The call has priority over all other communications except distress calls and it should be used in all urgent cases in which the sending out of MAYDAY call is not fully justified. The urgency signal may be used when the Master of a ship desires to issue a warning that circumstances are such that it may become necessary for him to send out the distress signal at a later stage.

The radiotelephone SAFETY signal “SECURITE” (pronounced “SAY-CUR-TAY”) spoken three times is provided for reporting hazards to navigation or meteorological warnings including dangers regarding ice, derelicts, tropical storms, etc.

## **AUTOMATED MUTUAL - ASSISTANCE RESCUE (AMVER)**

The AMVER System, operated by the United States Coast Guard, with the cooperation of coastal radio stations and satellite carriers of many nations, provides important aid to the development and coordination of search and rescue (SAR) efforts in the offshore areas of the world. Merchant vessels of all flags and all nations are encouraged to voluntarily send projected sail plans and periodic position reports to the AMVER computer located at the Coast Guard’s Operations System Center in Martinsburg, West Virginia. Using a system of dead reckoning, the computer can project the position of a ship at any point along its voyage, so that ships in the vicinity of a vessel in distress can be identified and dispatched to assist. AMVER ships incur no greater obligation to render assistance than under usual law of the sea.

Registration information from participating ships is entered into a database providing ships characteristics, which are valuable for determining SAR capability. Information concerning the relative position and SAR capabilities of each vessel known to be in the area of a distress is made available, upon request, to recognized SAR agencies of any nation. The system is used only for search and rescue purposes, not for pollution, illegal drug or migrant interdiction, or law enforcement purposes. The voyage information is protected as “commercial proprietary” information.

Messages sent to AMVER by coastal radio station are at no cost to the ship or owner. Currently, ships using satellite communications pay the regular tariff, but system enhancements such as “compressed message” software, and Internet and E-mail links are being developed to make AMVER reporting less of a burden on reduced crews and reduce communication costs. Benefits to shipping companies include:

- Insurance and peace of mind to crews of ships in AMVER.
- Reduces response time in the case of emergencies at sea.
- AMVER complements GMDSS technology to “take the search out of search and rescue”.
- Reduces the number of calls for diversion to ships not favorably located.
- Allows ships not required for assistance to continue on their voyages uninterrupted, thus saving money.
- Compressed message software allows both AMVER and VOS weather reports to be sent in a single message.

Instructions regarding participation in the AMVER Safety Network are available in the following languages:

Danish, Dutch, English, French, German, Greek, Italian, Japanese, Korean, Polish, Norwegian, Portuguese, Russian, Spanish, and Swedish. They are available from the AMVER Maritime Relations Office, United States Coast Guard, Battery Park Building, New York, N.Y., 10004-5034; Commander Pacific Area, United States Coast Guard, Coast Guard Island, Alameda, California 94501; and at U.S. Coast Guard District Offices, Marine Safety Offices, and Captain of the Port Offices in major U.S. ports. Requests should specify the language required.

AMVER participants bound for U.S. ports enjoy the additional benefit of AMVER reports satisfying the requirements of the United States Code of Federal Regulations, Title 33 Parts 161.7 and 161.9. These regulations require, with certain exemptions, that the Master or agent of each United States registered vessel and every foreign vessel arriving at a United States port (including the Great Lakes) from an offshore passage give advance notice to the U.S. Coast Guard at least 24 hours prior to arrival. The AMVER message must include the first port of call where a harbor entrance serves more than one port. AMVER forwards pertinent information to local Coast Guard officials automatically.

## **EMERGENCY POSITION INDICATING RADIOBEACONS (EPIRB's)**

An EPIRB is a small battery-powered transmitter carried by vessels. In the event of distress, an EPIRB is activated to transmit locating and homing signals, which assist search and rescue units in finding the vessel or survivors. SRSAT or Search and Rescue Satellite Aided Tracking systems use satellites to locate positions of most EPIRBs. When a SRSAT receives an EPIRB signal, it determines the beacon's location, which is relayed to the Coast Guard.

***The following are several types of EPIRB's in use today:***

### ***CATEGORY I - 406 & 121.5 MHz VHF-FM***

This type is float free. It is required on fishing vessels operating on the high seas (beyond 3 miles). It is automatically energized and it identifies the vessel and owner. It is accurate to within 3 nautical miles with 121.5 MHz as a homing beacon for rescue craft. It is detected by COSPAS-SARSAT international satellites system.

### ***CATEGORY II - 406 MHz VHF-FM***

Float free. Manually activated. Operates the same as Category I.

## **EPIRB'S - Continued**

### ***CLASS A - 121.5 & 243.0 MHz VHF-FM***

### ***CLASS B - 121.5 & 243.0 MHz VHF-FM***

Energized manually before immersed in water. Use is voluntary. Use for vessels operating more than 20 miles from the coast.

### ***CLASS C - 156.8 MHz VHF-FM Channel 16***

After 15 seconds this EPIRB shifts to 156.75 MHz VHF-FM Channel 15 for longer periods for direction finding purposes, then it recycles. It is activated manually before immersion in water. Its use is voluntary for vessels operating within 20 miles off the coast. Use by recreational craft is encouraged. Detection by VHF-FM equipped shore and other units that routinely monitor channel 16.

### ***CLASS S - 121.5 MHz VHF-FM***

This EPIRB is generally a small craft device and is used in lifeboats and rafts.

## **HANDLING EPIRBs**

All mariners are reminded that EPIRBs should not be activated unless in an actual emergency. Most EPIRBs are manufactured with a TEST mode. Also, use extra caution when handling EPIRBs to avoid activating signal.

## **EPIRB REGISTRATION**

The importance of keeping EPIRB registration information updated when emergency contacts names and numbers change cannot be over emphasized. Update this information with the National Oceanic & Atmospheric Administration (NOAA). The office of NOAA may be reached at (301) 817-4515, to receive a registration form. Also, the completed form can be FAXED to NOAA at (301) 817-4565.



# CHAPTER III

## COMMUNICATIONS

### CHANNELS 13 AND 16

#### **CHANNEL 13 (156.65 MHz)--**

Channel 13 is the Vessel Bridge-to-Bridge Radiotelephone frequency, except for the southern section of the Lower Mississippi River (See Bridge-to-Bridge Radio Telephone Regulations below). All vessels of 300 gross tons or more, 100 gross tons and over carrying one or more passengers for hire, 26 feet or longer engaged in towing, and every dredge or floating plant working in or near a channel or fairway in operations likely to restrict or affect navigation of other vessels, are required to participate in the Bridge-to-Bridge Radiotelephone system. Channel 13 is for the exclusive use of these vessels to transmit and confirm the intentions of other vessels in passing, meeting or crossing situations, and to provide any other necessary information for navigation safety.

#### **CHANNEL 16 (156.8 MHz)--**

Channel 16 is the International VHF-FM radiotelephone distress, safety and calling frequency used for distress and urgent traffic, safety signals, marine information broadcast announcements, and general calling and reply. After the preliminary call to establish communications, mariners should shift as soon as possible to an appropriate working frequency. In order to facilitate the reception of distress traffic, all transmissions should be kept to an absolute minimum and must not exceed one minute.

#### **CHANNEL 9 VHF-FM CALLING CHANNEL**

In an effort to eliminate traffic congestion on Channel 16 VHF-FM, the Federal Communications Commission (FCC) has designated Channel 9 VHF-FM as the nationwide Recreational Calling Channel for use by noncommercial boaters. Use of this channel by recreational boaters is strictly voluntary, but is strongly encouraged by the Coast Guard and the FCC.

It is important to note however, that **THE COAST GUARD WILL NOT—REPEAT WILL NOT—MONITOR CHANNEL 9 VHF-FM FOR DISTRESS CALLS.** Vessels in distress should make their calls on Channel 16 VHF-FM. Further information can be obtained from your nearest Coast Guard facility.

### BRIDGE-TO-BRIDGE RADIO TELEPHONE REGULATIONS

The Federal Communications Commission (FCC) has designated the frequency 156.65 MHz (Channel 13) for the use of bridge-to-bridge Stations in most of the United States. However, FCC rules designate the frequency 156.375 MHz (Channel 67) to be used instead of channel 13 in the following areas, except to facilitate transition from these areas: The Mississippi River from South Pass Lighted Bell Buoy “2” and Southwest Pass Entrance (midchannel) Lighted Whistle Buoy SW to mile 242 AHP (Above Head of Passes) near Baton Rouge; and in addition, over the full length of the Mississippi River-Gulf Outlet Canal from its entrance to its junction with the Inner Harbor Navigation Canal, and over the full length of the Inner Harbor Navigation Canal from its junction with the Mississippi River to its entry to Lake Pontchartrain at the New Seabrook vehicular bridge. Additional information on Bridge-to-Bridge Radiotelephone Regulations can be found in 33 CFR 26 and Navigation Rules International-Inland COMDTINST M16672.2A. Technical information on telecommunications can be found in 47 CFR 80.

## COAST GUARD BROADCAST NOTICES TO MARINERS

The Coast Guard broadcasts marine safety information on VHF-FM Channel 22A (157.1 MHz) and on 2670 kHz single sideband (SSB). These safety broadcasts contain information such as notices to mariners, storm warnings, distress warnings, and other information that is vital to safe navigation.

Following a preliminary call on VHF-FM Channel 16 (156.8 MHz) and/or 2182 kHz (SSB), mariners are instructed to shift to VHF-FM Channel 22A simplex (157.1 MHz) or 2670 kHz (SSB), respectively. Channel 22A (157.1 MHz) used in the United States is the ship station transmit frequency portion of the international Channel 22. This simplex use of Channel 22A (157.1 MHz) is not compatible with the international duplex arrangement of the channel Coast transmit 161.7 MHz, ship transmit 157.1 MHz, described in Appendix 18 of the International Telecommunications Union (ITU) Radio Regulations. As a result, many foreign flag vessels in U.S. waters cannot receive Coast Guard maritime safety broadcasts on Channel 22A.

Operators of vessels who plan to transit U.S. waters and who do not have VHF radios tunable to the United States Channel 22A are urged to obtain the necessary equipment. As a minimum, they should continually monitor 2182 kHz (SSB) for announcements of Coast Guard marine safety broadcasts on 2670 kHz (SSB).

## EIGHTH COAST GUARD DISTRICT HF COVERAGE

The Eighth Coast Guard District HF system consists of 10 transmitter/receiver sites and 6 remote receiver sites denoted ®. These sites may provide HF coverage out to about 100 miles offshore, and have a contact frequency of 2182 kHz. The following is a list of HF sites along with the controlling station.

### TRANSMITTER/RECEIVER SITES

SECTOR MOBILE	SECTOR NEW ORLEANS	SECTOR CORPUS CHRISTI	SECTOR HOUSTON-GALVESTON
Panama City, FL Carrabelle, FL ® Mobile Point, AL ® Mobile, AL ® Santa Rosa, FL ®	New Orleans, LA Southbend, LA ® Grand Isle, LA	Port Isabel, TX Port O'Connor, TX Port Aransas, TX Port Mansfield, TX	Galveston, TX Sabine, TX Pecan Island, LA Freeport, TX ®

## SCHEDULED MARINE INFORMATION BROADCASTS

NAVTEX Broadcasts normally include only coastal navigational warnings and weather information. Medium frequency radiotelephone broadcasts can include coastal or selected coastal and local major navigational warnings. These single sideband voice broadcasts are announced on 2182 kHz and are made on 2670 kHz. Information regarding USA VHF FM marine safety broadcasts are published in the ITU List of Radio-determination and Special Service Stations and other internationally available publications. Preliminary announcements are made on 2182 kHz or 156.8 MHz as appropriate. All times are given in Greenwich Mean Time. Subtract 6 hours from Greenwich Mean Time to get Central Standard Time or subtract 5 hours from Greenwich Mean Time to get Central Daylight Time.

### Information Codes and Notes:

A - Safety Broadcasts of Notices to Mariners; Hydrographic information; Gale Advisories; Special Weather Broadcasts.

B - NTM; Hydrographic Information; Forecasts and Advisories for the Gulf of Mexico.

C - Middle Gulf, Synopsis coastal waters from Apalachicola, FL to Port Arthur, TX and coastal waters from Apalachicola, FL to Pensacola, FL and from Pensacola, FL to Gulfport, MS.

D - Northwest and Southwest Gulf; coastal area from Brownsville, TX to Port O'Connor, TX; Hydrographic Information; NTM.

**Information Codes and Notes:**

E - Northwest, Southwest and Middle Gulf; coastal areas Vermilion Bay, LA to Port Arthur, TX; from Port Arthur, TX to Port O'Connor, TX; and from Port O'Connor, TX to Brownsville, TX; Hydrographic Information; NTM.

F - Synopsis Texas coastal waters, plus forecasts from, Port Arthur, TX to Port O'Connor, TX and from Port O'Connor, TX to Brownsville, TX.

G - Synopsis coastal waters from Apalachicola, FL to Port Arthur, TX; coastal waters from Gulfport, MS to Mississippi River and from Mississippi River to Vermilion Bay, LA.

**These information codes apply to the broadcast schedule on the following pages.**

TIME (Z)	FREQUENCY/CHANNEL	INFO CODES	RANGE IN NAUTICAL MILES
----------	-------------------	------------	-------------------------

<b>COMMUNICATION SECTOR NEW ORLEANS: NAVTEX</b>			
TIME (Z)	FREQUENCY/CHANNEL	INFO CODES	RANGE IN NAUTICAL MILES
0300	518 kHz	A/B	200
0900	518 kHz	A/B	200
1500	518 kHz	A/B	200
2100	518 kHz	A/B	200

<b>SECTOR MOBILE</b>			
TIME (Z)	FREQUENCY/CHANNEL	INFO CODES	RANGE IN NAUTICAL MILES
1020	2670 kHz		70
1220	2670 kHz		70
1620	2670 kHz		70
2220	2670 kHz		70
1020	157.1 MHz/22A	A	20
1220	157.1 MHz/22A	A	20
1620	157.1 MHz/22A	A	20
2220	157.1 MHz/22A	A	20

<b>SECTOR NEW ORLEANS</b>			
TIME (Z)	FREQUENCY/CHANNEL	INFO CODES	RANGE IN NAUTICAL MILES
0550	2670 kHz	B	70
1035	2670 kHz	C	70
1235	2670 kHz	C	70
1635	2670 kHz	C	70
2235	2670 kHz	C	70
1035	157.1 MHz/22A	G/A	20
1235	157.1 MHz/22A	G/A	20
1635	157.1 MHz/22A	G/A	20
2235	157.1 MHz/22A	G/A	20

<b>SECTOR HOUSTON-GALVESTON</b>			
TIME (Z)	FREQUENCY/CHANNEL	INFO CODES	RANGE IN NAUTICAL MILES
1050	2670 kHz		70
1250	2670 kHz		70
1650	2670 kHz		70
2250	2670 kHz		70
1050	157.1 MHz/22A	A/E	20
1250	157.1 MHz/22A	A/E	20
1650	157.1 MHz/22A	A/E	20
2250	157.1 MHz/22A	A/E	20

<b>SECTOR CORPUS CHRISTI</b>			
<b>TIME (Z)</b>	<b>FREQUENCY/CHANNEL</b>	<b>INFO CODES</b>	<b>RANGE IN NAUTICAL MILES</b>
1040	2670 kHz	F/D/A	70
1240	2670 kHz	F/D/A	70
1640	2670 kHz	F/D/A	70
2240	2670 kHz	F/D/A	70
2300	157.1 MHz	F/A	20

<b>ANY STATION AS DIRECTED:</b>			
<b>TIME (Z)</b>	<b>FREQUENCY/CHANNEL</b>	<b>INFO CODES</b>	<b>RANGE IN NAUTICAL MILES</b>
0930	2670 kHz	A	70
1230	2670 kHz	A	70
1530	2670 kHz	A	70
2130	2670 kHz	A	70
0945	157.1 MHz/22A	A	20
1545	157.1 MHz/22A	A	20
2145	157.1 MHz/22A	A	20

## NAVTEX

NAVTEX is an internationally standard method of broadcasting notices to mariners and marine weather forecasts using small, low cost printing receivers designed to be installed in the pilot house of a vessel.

NAVTEX receivers screen incoming messages inhibiting those which had been previously received or are of a category of no interest to the user, and print the rest on adding machine size paper. NAVTEX not only provides marine information previously available only to those knowledgeable in Morse code, but also allows any mariner who cannot man a radio full time to receive safety information at any hour immediately.

All NAVTEX transmissions are made on 518 kHz. Mariners who do not have NAVTEX receivers but have SITOR radio equipment can also receive these broadcasts by operating it in the FCC mode and tuning to 518 kHz.

Information broadcast over NAVTEX include offshore weather forecasts, offshore marine advisory warnings, search and rescue information, and navigational information that applies to waters from the line of demarcation (separating Inland Rules from COLREG Rule waters) to 200 miles offshore. Navigational information that affects the safety of navigation of deep draft (15 feet or more) vessels within the U.S. Inland Rule waters will also be included. Gulf stream location is also included from Miami and Portsmouth. Coastal and high seas weather forecasts are not being broadcast over NAVTEX. The Safety of Life at Sea Convention, as amended in 1988, requires vessels regulations by that convention to carry NAVTEX receivers. As of August 1, 1993, the Coast Guard discontinued broadcast messages over MF Morse frequencies. NAVTEX messages are now broadcast from the following locations:

<b>LOCATION</b>	<b>IDENTIFICATION (B1)</b>	<b>SCHEDULE (UTC)</b>
BOSTON, MA (NMF)	F	0445, 0845, 1245, 1645, 2045, 0045
MIAMI, FL (NMA)	A	0000, 0400, 0800, 1200, 1600, 2000
SAN JUAN, PR (NMR)	R	0200, 0600, 1000, 1400, 1800, 2200
GUAM (NRV)	V	0100, 0500, 0900, 1300, 1700, 2100
ADAK, AK (NOJ)	X	2340, 0340, 0740, 1140, 1540, 1940
PORTSMOUTH, VA (NMN)	N	0130, 0530, 0930, 1330, 1730, 2130
NEW ORLEANS, LA (NMG)	G	0300, 0700, 1100, 1500, 1900, 2300
HONOLULU, HI (NMO)	O	0040, 0440, 0840, 1240, 1640, 2040
KODIAK, AK (NOJ)	J	0300, 0700, 1100, 1500, 1900, 2300
SAN FRANCISCO, CA (NMC)	C	0400, 0800, 1200, 1600, 2000, 0000
CAMBRIA, CA	Q	0445, 0845, 1245, 1645, 2045, 0045
ASTORIA, OR (NMC)	W	0130, 0530, 0930, 1330, 1730, 2130

## **COAST GUARD TO CHECK FOR FCC LICENSE DURING BOARDINGS**

The Coast Guard has agreed, with the Federal Communications Commission (FCC), to a joint effort designed to promote maritime safety by reducing the number of hoaxes, interference with search and rescue operations, and other problems associated with the misuse of radios on board vessels. In many instances, boaters and operators of uninspected vessels are not familiar with or disregard FCC radio rules. The Coast Guard will inspect radio equipped vessels for the required FCC license during routine boardings. In turn, the FCC has agreed to prosecute radio violations based on evidence presented by the Coast Guard. This change applies to uninspected vessels and does not affect procedures for inspected vessels. FCC rules require that operators of radio equipment, capable of maritime transmission, have a legible copy of the ship's "station license" posted at the principle control point of each radio unit. A posted copy must indicate the location of the original. If a license cannot be posted, then it must be kept where it is readily available for inspection. The license regulations apply to equipment such as VHF maritime radios, VHF hand held radios, emergency position indicating radio beacons (EPIRB), receive only radars or radio telephones. The regulations exempt CB radios and cellular telephones. Failure to obtain the proper license could result in a criminal misdemeanor with penalties up to \$10,000, one year in prison or both.

## **VHF MARINE RADIO INFORMATION**

When operating VHF-FM Radio equipment adhere to the following procedures:

Channel 16 may **ONLY** be used for Distress and Calling. Keep all calls as short as possible. Keep **ALL** calling to an **ABSOLUTE MINIMUM** on Channel 16.

It is **ILLEGAL** to use Channel 16 for radio checks with the Coast Guard. Use other working channels. Before transmitting, **LISTEN** long enough to be sure there is not a distress in progress and to also ensure you will not interfere with another station making a call.

Do **NOT** call Marine Operators on Channel 16. Use their working channel. Children should be instructed how to operate the radio in case of an emergency, but they also must be taught that it is **NOT A TOY** or a land telephone or CB circuit (some adults need to be reminded of this also.) Be sure the channel you are using is appropriate for the type of communications. Each channel has a designation.

Use **LOW POWER** or one watt whenever possible to avoid interference to other users (mandatory on Channels 13, 14, & 67). **NO** unnecessary communications of any kind are permitted on VHF. General chitchat is not permitted.

Use your FCC assigned call letters at the beginning and end of each transmission sequence. Never use a Telephone Credit Card on your VHF to the Marine Operator. Other people can hear your number.

Use only a Marine Telephone Identification Number "MIN". Your VHF **MUST** be licensed. If you cruise outside U.S. waters you must have an operators license.

# CHAPTER IV

## VESSEL TRAFFIC SAFETY

### BERWICK BAY VESSEL TRAFFIC SERVICE

U.S. COAST GUARD  
800 DAVID DRIVE  
ROOM 232  
MORGAN CITY, LA 70380-1304  
TELEPHONE: (985) 380-5370  
FAX: (985) 385-1687

Participation in Vessel Traffic Service (VTS) Berwick Bay is mandatory in accordance with 33 CFR 161.15. Vessel operators intending to transit the VTS Berwick Bay area should have a copy of VTS User's Manual for reference. A copy of this manual may be obtained from the above address. VTS Berwick Bay utilizes a VHF-FM communication network, which is guarded continuously by Coast Guard personnel, and all transmissions to and from the Vessel Traffic Center (VTC) are automatically recorded. The VTC has the capability of monitoring the VTS area with closed circuit television and radar.

Participation in VTS Berwick Bay is accomplished through the use of VHF-FM Channel 11 (156.550). During periods of high water, horsepower to length requirements are placed on transiting tows. Notification of when high water limitations are in effect is accomplished through Broadcast and Local Notice to Mariners.

#### **BERWICK BAY VESSEL TRAFFIC SERVICE (Continued)**

During periods of high water, mariners are requested to exercise extreme caution due to severe cross-currents, which set to the west toward Morgan City between the highway and railroad bridges. The effect of cross-currents may be increased due to local wind conditions. Severe currents may also be encountered at the Atchafalaya River, Intracoastal Waterway junction at Little Wax Bayou, mile 98.5 west of Harvey Lock. Mariners must give due regard to the handling characteristics and available horsepower of their vessels. In addition, tows transiting Southbound through the Berwick Bay bridge complex are recommended to use an additional crew member in the pilothouse to assist the vessel operator with communications, radar observations and lookout responsibilities through this critical approach area.

Mariners should make effective use of their assist boat (if required). These assist vessels transit Berwick Bay more frequently than almost any other vessels, thus these operators can generally provide expert advice on local conditions and can contribute significantly to a safe transit through this especially hazardous area. Mariners are also reminded that the Berwick Bay Bridge Approach Danger Range, located on the west side highway bridge abutments, marks the western boundary of the suggested downbound course for approaching the bridges. This range is not to be steered on. Downbound tows to the west or right of this range are standing into danger and must take early corrective action to avoid being set down onto the highway bridge west abutments.

The mariner is cautioned that information provided by the VTC is to a large extent based upon reports of participating vessels and can be no more accurate than the information received. The Coast Guard may not know of all hazardous circumstances within the VTS area. Unreported hazards may confront the mariner at any time. Any conflicting circumstances or hazardous conditions should be reported to the VTC immediately.

### TRAFFIC SEPARATION SCHEMES AND AREAS TO BE AVOIDED

To increase the safety of navigation, particularly in converging areas of high traffic density, routes incorporating traffic separation have been established in certain areas of the world. In the interest of safe navigation, it is recommended that through traffic use these schemes, as far as circumstances permit, by day and by night and in all weather conditions.

An area to be avoided is a routing measure comprising an area within defined limits, in which either navigation is particularly hazardous or it is exceptionally important to avoid casualties, and which should be avoided by all ships, or certain classes of ships.

The International Maritime Organization (IMO) is recognized as the only international body responsible for establishing and recommending measures on an international level concerning ships' routing. In deciding whether or not to adopt or amend a traffic separation scheme, IMO will consider whether the scheme complies with the design criteria for traffic separation schemes and with the established methods of routing. IMO also considers whether the aids to navigation proposed will enable mariners to determine their position with sufficient accuracy to navigate the scheme in accordance with Rule 10 of the International Regulations for Preventing Collisions at Sea. (72 COLREGS)

General principles for navigating in Traffic Separation Schemes are as follows:

1. A ship navigating in or near a traffic separation scheme adopted by IMO shall in particular comply with Rule 10 of the 72 COLREGS to minimize the development of risk of collision with another ship. The other rules of the 72 COLREGS apply in all respects and particularly the steering and sailing rules if risk of collision with another ship is deemed to exist.
2. Traffic separation schemes are intended for use by day and by night in all weather.
3. Traffic separation schemes are recommended for use by all ships unless stated otherwise. Bearing in mind the need for adequate under keel clearance, a decision to use a traffic separation scheme must take into account the charted depth, the possibility of changes in the seabed since the time of last survey, and the effects of meteorological and tidal conditions on water depths.
4. A deep water route is an allied routing measure primarily intended for use by ships, which require the use of such a route because of their draft in relation to the available depth of water in the area concerned. Through traffic, to which the above consideration does not apply, should avoid following deep water routes if practicable. When using a deep water route, mariners should be aware of possible changes in the indicated depth of water due to meteorological or other effects.

5. The arrows printed on charts merely indicate the general direction of traffic; ships should not set their courses strictly along the arrows.
6. Vessels should, so far as practicable, keep clear of traffic separation line or separation zone.
7. Vessels should avoid anchoring in traffic separation scheme or in the area near its termination.
8. The signal “YG” meaning “You appear not to be complying with the traffic separation scheme” is provided in the International Code of Signals for appropriate use.

NOTE: Several governments administering Traffic Separation Schemes have expressed their concern to IMO about the large number of infringements of Rule 10 of the 72 COLREGS and the dangers of such contraventions to personnel, vessels and environment. Several governments have initiated surveillance of traffic separation schemes for which they are responsible and are providing documented reports of vessel violations to flag states.

As in the past, the U. S. Coast Guard will investigate these reports and take appropriate action. Mariners are urged to comply at all times with the 72 COLREGS and, in particular, Rule 10 when operating in or near Traffic Separation Schemes.

9. Notice of temporary adjustments to traffic separation schemes for emergencies or for accommodation of activities, which would otherwise contravene Rule 10 or obstruct navigation may be made in Notices to Mariners. Temporary adjustments may be in the form of a precautionary area within a traffic lane, or a shift in the location of a lane.
10. The IMO approved routing measures, which affect shipping in Eighth District waters are:
  - a. Approaches to Galveston Bay (refer to NOS Chart 11323).
  - b. Louisiana Offshore Oil Port (LOOP) in the Gulf of Mexico (refer to NOS Chart 11359).

## REGULATED NAVIGATION AREAS

### a. Lower Mississippi River Between Miles 88 and 127 Above Head of Passes (AHP)

The Coast Guard Captain of the Port New Orleans enforces regulations that govern the mooring of barges in fleets, fleeting operations and towing operations. Special high water regulations place additional restrictions upon operators in the area. Operators of towing vessels in the above area should refer to 33 CFR 165.803 or contact the Captain of the Port New Orleans for information.

### b. Lower Mississippi River Between Miles 311.5 and 340 Above Head of Passes (AHP)

The Coast Guard Captain of the Port New Orleans enforces regulations that govern and prohibit the mooring of vessels in the area of Old River Control structure and the new Auxiliary Control Structure. See 33 CFR 162.80.

### c. Calcasieu River, Louisiana

The Calcasieu River from the Calcasieu jetties up to and including the Port of Lake Charles. Unless authorized by the Captain of the Port, Port Arthur, TX, tows on a hawser of 1,000 gross tons or greater are prohibited unless such tows have a tug of sufficient horsepower made up to the tow in such a manner as to insure that complete and effective control is maintained at all times. Inbound vessels only may shift the tow or pick up an additional tug within 100 yards inside the entrance jetties provided that such action is necessary or prudent seamanship. See CFR 165.807.

### d. Sabine Neches Waterway, Texas

The Sabine Neches Waterway includes the following waters: Sabine Pass Channel, Port Arthur Canal, Sabine Neches Canal, Neches River, Sabine River and all navigable waterways tributary to them. Unless authorized by the Captain of the Port, Port Arthur, TX, tows on a hawser of 1,000 gross tons or greater are prohibited unless such tows have a tug of sufficient horsepower made up to the tow in such a manner as to insure that complete and effective control is maintained throughout the transit. Inbound vessels only may shift the tow or pick up an additional tug within 100 yards inside the entrance jetties provided that such action is necessary or prudent seamanship. See CFR 165.806



## LIMITED ACCESS AREAS PERMANENT SAFETY ZONES

### a. Lower Mississippi River Vicinity of Old River Control Structure

The area enclosed by the following boundary is a safety zone: from Black Hawk Point Light, mile 316.1 AHP to a point opposite Ft. Adams Light, mile 311.5 AHP, along the low water reference plane above the right descending bank; thence to the levee on a line perpendicular to the channel centerline; thence along the levee to the upstream end of Old River Overbank structure; thence along a line to the Black Hawk Point Light. Any vessel desiring to enter this safety zone must first obtain permission from the Corps of Engineers, Old River Control Structure. See 33 CFR 165.802 53 FR 82 July 1, 1990.

### b. Snake Island - Texas City, Texas

The following is a safety zone: The west and northwest shores of Snake Island; the turning basin west of Snake Island; the area of Texas City Channel from the north end of the Turning Basin to a line drawn 000<sup>2</sup> true from the Northwestern most point of Snake Island. All vessels are prohibited from mooring, anchoring or stopping. Vessels shall advise Captain of the Port, Galveston of emergencies. See 33 CFR 165.804.

### c. Calcasieu Channel and Industrial Canal - Calcasieu River, Lake Charles, Louisiana

The waters within the following boundaries are a safety zone: The area extending 150 feet out into the Industrial Canal, Calcasieu River, Lake Charles, LA, along the shoreline of the Trunkline Liquid Natural Gas (LNG) Company's waterfront property, from position 30°06'31.9"N, 93°17'37.0"W to the end of the Turning Basin and to include an area 50 feet out from LNG ships while moored to the Trunkline facility. The area 2 miles ahead, 1 mile astern, and to either side of a non-gas free LNG vessel, to the width of the ship channel, while the vessel is transiting the Calcasieu River Ship Channel and between Lighted Whistle Buoy "CC" and the Trunkline LNG facility. Meeting, crossing, or overtaking are not permitted unless authorized by Captain of the Port, Port Arthur. See 33 CFR 165.805.

## LIMITED ACCESS AREAS PERMANENT SAFETY ZONES

### d. Corpus Christi Ship Channel

The following areas are safety zones:

- (1) The waters within a 500 yard radius of inbound tank vessels loaded with Liquefied Petroleum Gas (LPG) while the vessel transits the Corpus Christi Ship Channel to the LPG facility and moors.
- (2) The waters within a 500 yard radius of outbound LPG carriers while the vessels departs the LPG facility and transits the Corpus Christi Ship Channel, until the vessel passes the seaward extremity of the Aransas Pass Jetties. See 33 CFR 165.808.

## ANCHORAGE AREAS

Special Anchorage Areas - Vessels not more than 65 feet in length, when at anchor, shall not be required to carry or exhibit the white anchor lights required by the Navigation Rules. Special Anchorages are located in Corpus Christi Bay 33 CFR 110.75 and Amistad Reservoir 33 CFR 110.77.

Anchorage Grounds - Designated and specific regulations for anchorages in the Eighth Coast Guard District are listed in the Code of Federal Regulations. The areas are Mobile Bay, AL, at entrance (110.194), Mobile Bay, AL, and Mississippi Sound, MS (110.194 (a)) and Gulf of Mexico, near Petit Bois Island, MS, (110.194 (b)); Mississippi River below Baton Rouge, LA, including South and Southwest Passes (110.195), Sabine Pass Channel, Sabine Pass, TX, 110.96, Galveston Harbor, Bolivar Roads Channel, TX (110.197). See 33 CFR 110.

## **INLAND WATERWAYS NAVIGATION REGULATIONS (OVERSIZE TOWS)**

These regulations apply to all waterways from St. Marks, FL., to the Rio Grande tributary to the Gulf of Mexico and the Gulf Intracoastal Waterway (except the Mississippi River, its tributaries, South and Southwest Passes and the Atchafalaya River).

General Regulations are contained in 33 CFR 162.75 (b) (1)-(4) pertaining to channels, fairways, anchoring, mooring, and speed.

Oversize Tow Regulations 33 CFR 162.75 (b) (5):

On waterways 150 feet wide or less, tows which are longer than 1,180 feet including the towing vessel, but excluding the length of the hawser, or wider than one-half of the bottom width of the channel or 55 feet, which ever is less are not allowed. Permission for oversize tow movements must be received from the Captain of the Port on a case by case basis. In addition, the following exceptions are allowed:

Gulf Intracoastal Waterway - Between mile 6.2 East of Harvey Locks (EHL) (Inner Harbor Navigation Canal Lock) and mile 33.6 EHL tows of 75 feet in width will be allowed.

Gulf Intracoastal Waterway - Between mile 33.6 EHL and the Mobile Bay Ship Channel, tows of 110 feet in width will be allowed if under 750 feet in length including the towboat but excluding the length of the hawser.

Gulf Intracoastal Waterway - Mobile Bay Ship Channel to St. Marks, Fl., for tows made up of empty barges on the off or shallow side, a width of 75 feet will be allowed.

All tows navigating the Pass Manchac bridges in Louisiana are limited to no more than two barges, not to exceed a combined tow length of 400 feet (excluding the towboats). Vessel operators for tows exceeding these limits must request and receive permission from the COTP New Orleans prior to navigating the bridges. Requests should be made by telephoning the COTP at 504-589-6261. For all exemptions listed oversize tows shall give way in meeting and overtaking situations involving other tows, vessels, or floating plants working in channels to the extent necessary to ensure a minimum of one-half channel width to all users. This includes disassembling tows, if required, to effect a safe passage.

In addition to the exemptions listed in 33 CFR 162.75 (b) (5) the following exemptions are in effect for the Eighth Coast Guard District:

## **GULF INTRACOASTAL WATERWAY (GIWW)**

### **SPECIAL NOTICE TO NAVIGATION OVERWIDTH TOWS ON GIWW - COE LOCKING REGULATIONS**

As of June 1, 1989, tows over 55 feet in width and tows configured with offset barges transiting the Inner Harbor Navigation Canal, Harvey, Algiers, Bayou Boeuf, Leland Bowman and Calcasieu locks shall station either two deckhands or one deckhand equipped with radio communications on the bow of the tow during lockage. Tow operators utilizing radio communications with a deckhand shall notify the lock operator of their working channel for monitoring and lockage instructions. These procedures are necessary to minimize marine damages, which create safety and operational hazards at navigation structures. Tows not in compliance with the above procedures shall be denied lockage in accordance with 33 CFR, Navigation and Navigable Waters, part 207.180 paragraph (d) (2) and (d) (7).

GIWW Between mile 238.5 WHL (west side of Calcasieu Locks) and mile 352 WHL (Pelican Island Cut), for tows made up of empty barges on the off or shallow side, a width of up to 110 feet will be allowed, provided that, if the width exceeds 55 feet, the overall length, shall not exceed 750 feet including the length of the hawser.

GIWW, Main Stem - Between mile 352 WHL (Pelican Island Cut) and mile 363 WHL, tows of up to 72 feet in width will be allowed, provided that, the overall length shall not exceed 750 feet including the towboat but excluding the length of the hawser.

GIWW - Between 363 WHL and mile 670.6 WHL (Brownsville Channel), for tows made up of empty barges on the off or shallow side, a width of up to 110 feet will be allowed, provided that, if the width exceeds 55 feet, the overall length shall not exceed 750 feet including the towboat, but excluding the length of the hawser. This exemption to the regulations does not apply to the Brazos River Floodgates (Mile 400.8 WHL) or the Colorado River Locks (Mile 441.5 WHL) since these Government-owned facilities have a horizontal clearance of 75 feet.

## **APALACHICOLA, CHATTAHOOCHEE AND FLINT RIVERS (TRI-RIVERS SYSTEM)**

Tows up to 55 feet in width will be allowed. For southbound tows made up of two empty barges, a width of 72 feet will be allowed. All tows shall not exceed a combined tow length of 450 feet, excluding the towboat.

## **BILOXI EAST CHANNEL TO BACK BAY CHANNEL**

Between the GIWW and the end of Back Bay Channel (300 yards west of Big Island), tows having a width of less than 75 feet and an overall length of less than 750 feet, including the towboat but not the length of the hawser will be allowed.

## **CHOCOLATE BAYOU CHANNEL**

Between the GIWW at mile 376 WHL and mile 8.1 (Chocolate Bayou Channel), tows of up to 55 feet in width will be allowed.

## **VICTORIA CHANNEL**

Between the Gulf Intracoastal Waterway at mile 492 WHL and mile 34.6 (Victoria Channel), tows of up to 55 feet in width will be allowed.

NOTE: Revision of these GIWW tow size regulations are currently being considered by the Coast Guard. The changes will allow for tows up to 55 ft wide by 1194 ft, or 72 ft wide and 750 ft long to transit the GIWW, Port Allen Route and other waterways without a permit. It is expected that permits will rarely be granted. Present exceptions will be written into the new regulations. (Final publication date is not known at this time. Existing regulations remain in force until new regulations are promulgated).

## **HIGH WATER TOWING LIMITATIONS, MORGAN CITY, LA**

The high water limitations apply to the operation of vessels with tows intending to transit under the lift span of the Southern Pacific Railroad (SPRR) bridge or through the navigational openings of either the U.S. Highway 90 bridge or the LA Route 187 bridge, both north of the SPRR bridge. MSO MORGAN City will issue a precautionary notice for these limitations when the Morgan City River Gage reads 2.5 feet above mean sea level. The limitations are in effect when the gage reads 3 feet or more above mean sea level. Contact MSO Morgan City for information.

## **VESSEL TRAFFIC CONTROL LIGHTS ALGIERS POINT, NEW ORLEANS HARBOR**

When the Mississippi River reaches 8 feet on the Carrollton Gage on a rising stage, and until the gage reads 9 feet on a falling stage, the movement of all ships and all tugs with tows in the vicinity of Algiers Point are governed by red and green lights. They are the Governor Nicholls Light located on the left descending bank on the wharf shed at the upstream end of Esplanade Avenue Wharf, New Orleans, approximately 94.3 miles above Head of Passes, and Gretna Light located on the right descending bank on top of the levee at the foot of Ocean Avenue, and approximately 96.6 miles above Head of Passes. Communication with the Governor Nicholls and Gretna Light Operators using radiotelephone channel 67 VHF-FM (or channel 16 VHF-FM for emergency communications only) is mandatory for all vessels intending to navigate the regulated area. Contact MSO New Orleans for additional information.

## **NAVIGATION RULES**

The International Rules are applicable seaward of the COLREGS demarcation lines, and the Inland Rules apply inside these lines. The demarcation lines are printed on most navigational charts and are published in the NAVIGATION RULES International-Inland (COMDTINST M16672.2B). The vessel operator is responsible for knowing, understanding and following the applicable navigational rules. Copies of the rules may be obtained from your local chart agent or the Superintendent of Documents, U. S. Government Printing Office, Washington, D.C. 20402-9322, toll free (866) 512-1800.

## **ALPHA FLAG FOR RESTRICTED MANEUVERABILITY (Due to Diving Operations)**

There has been some confusion over the status of the traditional sports divers' flag because of a change to the U.S. Inland Navigation Rules concerning the use of a one meter rigid replica of the International Code Flag Alpha (a blue and white flag). The Alpha flag is to be flown on small vessels engaged in diving operations whenever these vessels are restricted in their ability to maneuver if divers are attached to the vessel. But in

sports diving, where divers are usually free swimming, the Alpha flag does not have to be shown and the Coast Guard encourages the continued use of the traditional sports diver flag. The distinction the Coast Guard wants to make clear is: The Alpha flag is a navigational signal intended to protect the vessel from collision. The sports diver flag is an unofficial signal that, through custom, has come to be used to protect the diver in the water. It is the responsibility of the operator of a diving vessel to determine if his craft's movements are restricted. To be most effective, the sports diver flag should be exhibited on a float in the water to mark the approximate location of the diver.

## **SPECIAL RULES WITH RESPECT TO ADDITIONAL STATION AND SIGNAL LIGHTS FOR NAVY SHIPS**

1. Man overboard lights - Naval vessels may display, as a means of indicating man overboard, two pulsating, all around red lights in a vertical line located on a mast from where they can best be seen.
2. Yard arm signaling lights - Naval vessels may display, as a means of visual signaling, white all around lights at the end of the yardarms. These lights will flash in varying sequences to convey the intended signal.
3. Aircraft warning lights - Naval vessels may display, as a means of indicating the presence of an obstruction to low flying aircraft, one or two all around red lights on each obstruction.
4. Underway replenishment contour lights - Naval vessels may display, as a means of outlining the contour of the delivery ship during nighttime underway replenishment operations, red or blue lights at deck edge extremities. These lights are being converted to blue, vice red, therefore either color may be seen until conversion is complete.
5. Mine clearance station keeping lights - Naval vessels engaged in minesweeping operations may display as an aid in maintaining a prescribed interval and bearing, two white lights in a vertical line visible from 070<sup>2</sup> through 290<sup>2</sup> relative.
6. Submarine identification light - Submarines may display, as a distinctive means of identification, an intermittent flashing amber (yellow) beacon with a sequence of operation of one flash per second for three (3) seconds followed by a three (3) second off-period.
7. Special operations lights - Naval vessels may display, as a means of coordinating certain operation, a revolving beam colored red, green or amber, located on either yardarm or mast platform from where it can be seen all around the horizon.
8. Convoy operations stern light - Naval vessels may display, during periods of convoy operations, a blue light located near the stern, with the same characteristics as, but in lieu of the normal white stern light.
9. Wake illumination light - Naval vessels may display a white light located near the stern to illuminate the wake.
10. Flight operations light - Naval vessels engaged in night flight operations may display various arrangements of light systems containing combinations of different colored lights as a means of assisting in the launch and recovery of aircraft and enhancing flight safety. These light systems will be located at various points on the vessels, depending on the vessel type and nature or the flight operations being conducted.
11. Amphibious operations lights - Naval vessels engaged in night amphibious operations may display various arrangements of light systems containing combinations of different colored lights as a means of assisting in the launch and recovery of assault craft and enhancing the safety of the amphibious operation. These light systems will be located at various points on the vessels, depending on the vessel type and the nature of the amphibious operations being conducted.
12. Replenishment-at-sea floodlights - Naval vessels engaged in replenishment-at-sea operations may display various arrangements of floodlights of different colors for general illumination of equipment, work areas and cargo being transferred between ships. These lights will be located at various points on the vessels, depending on the vessel type and location of the replenishment-at-sea.
13. Replenishment-at-sea cargo transfer signal lights - Naval vessels engaged in replenishment-at-sea operations may display one or more red light signal devices on the delivery side of the vessels. These devices display various combinations of lights to indicate type of cargo being transferred.
14. Replenishment-at-sea truck light - Naval vessels engaged in replenishment-at-sea operations may display one or more red all-round light(s) located on a mast to assist the receiving vessel in approaching the delivery vessel.
15. Replenishment-at-sea lights - Naval aircraft carriers and similar type vessels may display two all-round lights installed along the forward starboard flight deck edge to indicate the fore-and-aft axis when the aircraft carrier or similar type vessel is the delivery vessel.

## **UNITED STATES NAVAL VESSELS - NAVIGATIONAL LIGHT WAIVERS - DISTINCTIVE LIGHTS AUTHORIZED FOR NAVAL VESSELS**

All ships are warned that, when U.S. Naval vessels are met on the high seas or on navigable waters of the United States during periods when navigational lights may be displayed; certain navigational lights of some naval vessels may vary from the requirements of the regulations for Preventing Collisions at Sea, 1972, and rules applicable to the navigable waters of the United States, as to number, position, range of visibility or arc of visibility. Reasons of military function or special construction of the naval ships necessitates these differences. An example is the aircraft carrier where the two white lights are considerably displaced to starboard from the center or keel line of the vessel when viewed from ahead. Certain other naval vessels cannot comply with horizontal separation requirements of the white lights, and the two white lights on even larger naval vessels, such as some cruisers, will thus appear to be crowded together when viewed from a distance. Other naval vessels may also have unorthodox navigational light arrangements or characteristics when seen either underway or at anchor.

Naval vessels may also be expected to display certain other lights. These lights include, but are not limited to, different colored recognition light signals, and aircraft landing lights. These lights may sometimes be shown in combination with navigational lights.

During naval maneuvers, naval ships, alone or in company, may also dispense with showing any lights, though efforts will be made to display lights on the approach of shipping.

Naval vessels, except for aircraft carrier types (CV, CVN, AVT, LPH and LHA), may dispense with showing the masthead lights during operations or maneuvers in which the vessels are restricted in ability to maneuver.

## **CAUTION REGARDING APPROACH OF SINGLE VESSELS TOWARD NAVAL FORMATIONS AND CONVOYS**

A formation of warships or a convoy is more difficult to maneuver than a single ship. Therefore, the attention of masters is called to the danger to all concerned which is caused by a single vessel approaching a formation of warships or convoy so closely as to involve risk of collision, or attempting to pass ahead of, or through such a formation or convoy. All ships are therefore cautioned to employ the customary manners of good seamanship and where there is ample sea room, adopt early measures to keep out of the way of a formation of warships or convoy. The fact that, in the interests of safety, a single vessel should keep out of the way of a formation or convoy does not entitle vessels sailing in company to proceed without regard to the movements of the single vessel. Vessels sailing in formation or convoy should accordingly keep a careful watch on the movements of any single vessel approaching the squadron or convoy and should be ready, in the case the single vessel does not keep out of the way, to take such action as will best avert collision.

## **IMPROPER USE OF SEARCHLIGHTS AND FLOODLIGHTS AT SEA**

The Coast Guard has received reports that fishing vessels which use high intensity lights when setting and retrieving gear are routinely leaving them lit at all times when the vessel is underway. Although these lights may make a vessel easier to locate at great distances, improper use could interfere with the safe navigation of vessels. This may constitute a violation of the International Regulations of Preventing Collisions at Sea, 1972 (72 COLREGS) if the glare of such lights:

- (a) Interferes with the night vision of mariners operating in the vicinity and the keeping of a proper lookout - Rule 5 and 20 (proper lookout).
- (b) Obscures the navigation lights of the vessel, making it difficult to determine a vessel's heading and type of operation - Rule 20 (impair distinctive character of navigation lights).
- (c) Makes it difficult for mariners to identify aids to navigation and their geographical location in the vicinity of the vessel using these lights - Rule 36 (mistaken for any aid to navigation or embarrass another vessel).

Several reports indicated a vessel using sodium vapor floodlights was mistakenly reported as a vessel on fire, which resulted in a search and rescue response to a false alarm. The use of these high intensity lights may ultimately reduce the level of vigilance on the part of other mariners, which could result in an actual distress situation not being reported or answered. This notice does not prohibit a vessel from using any lights that cannot be mistaken for the lights specified in the 72 COLREGS. Mariners are cautioned that all types of high intensity lights when used at sea must be properly directed or adequately screened to ensure that under any conditions such lights will not embarrass another vessel, be misinterpreted, or illuminate beyond the immediate vicinity of the vessel. When these lights are not being used for a specific task they should be extinguished.

# CHAPTER V

## AIDS TO NAVIGATION

### CAUTION TO BE USED IN RELIANCE

#### UPON AIDS TO NAVIGATION

The aids to navigation depicted on charts comprise a system of fixed and floating aids with varying degrees of reliability. Therefore, prudent mariners will not rely solely on any single aid to navigation, particularly a floating aid. With respect to buoys, the buoy symbol on nautical chart is used to indicate the approximate position of the buoy and the sinker, which secured the buoy to the seabed. The approximate position is used because of practical limitations in positioning and maintaining buoys and their sinkers in precise geographical location. These limitations include, but are not limited to, inherent imprecision in position fixing methods, prevailing atmospheric and sea conditions, the slope of and the material making up the seabed, the fact that buoys are moored to sinkers by varying lengths of chain, and the fact that buoy bodies and/or sinker positions are not under continuous surveillance but are normally checked only during periodic maintenance visits which often occur more than a year apart. The position of the buoy body can be expected to shift inside and outside the charting symbol due to forces of nature. The mariner is also cautioned that buoys are liable to be carried away, shifted, capsized, or sunk. Lighted buoys may be extinguished or sound signals may not function as the result of natural causes, collisions, or other accidents.

For the foregoing reasons, a prudent mariner must not rely completely upon the position or operation of floating aids to navigation, but will also utilize bearings from fixed objects and aids to navigation on shore. Further, a vessel attempting to pass close aboard, always risk collision with a yawing buoy or with the obstruction the buoy marks.

#### REPORTING AID TO NAVIGATION DISCREPANCIES

Experienced mariners realize that the Coast Guard cannot keep the thousands of aids to navigation comprising the federal system under simultaneous and continuous observation. For this reason, it is impossible to maintain every buoy, daybeacon, light or fog signal and other aids operating properly and on its charted position at all times. Therefore, the safety of mariners and that of all persons embarked or serving in vessels will be enhanced if every person who discovers an aid to be missing, sunk, capsized, or damaged, or who observes a defect in the position or characteristic of any aid, will promptly notify the nearest Coast Guard unit of the fact.

#### COLLISION WITH OR DAMAGE TO AIDS TO NAVIGATION

It frequently occurs that aids to navigation are collided with, causing damage and displacement, or complete loss, without the knowledge of the Coast Guard. The replacement or repair of such aids is consequently often not made as promptly as desired. This situation results in diminished protection for marine traffic, and is attributable in large part to the failure of vessel operators to furnish notice of these collisions to the nearest local or district office of the U.S. Coast Guard, or to Coast Guard Headquarters, as required by law and regulation. The prompt submission of notice of any marine casualty or accident, including damage or destruction of aids to navigation, is required by the Marine Investigation Regulations, Section 4.05-20 of Title 46, Code of Federal Regulations, with penalty for noncompliance. Mariners are also required to provide owner/operator identification.

# INTERNATIONAL ASSOCIATION OF LIGHTHOUSE AUTHORITIES (IALA) MARITIME BUOYAGE SYSTEM

The IALA Maritime (combined Cardinal/Lateral) Buoyage System has been, is being, or will be implemented by nearly every maritime buoyage jurisdiction worldwide as either REGION A buoyage (red to port) or REGION B (red to starboard).

The terms “REGION A” and “REGION B” will be used to determine which type of buoyage region is in effect or undergoing conversion in a particular area. The major difference between the two buoyage regions concerns the lateral marks. When viewed from sea, the lateral marks in REGION A will be red to port; in REGION B they will be red to starboard. Shapes of lateral marks will be the same in both REGIONS, can to port; cone (nun) to starboard. Cardinal and other marks will continue to follow current guidelines and may be found in both REGIONS. A modified lateral mark, indicating the preferred channel where a channel divides, has been introduced for use in both REGIONS. It is intended that after a reasonable period of time, each chart will make reflection to REGION A or REGION B to indicate which type of lateral buoyage is in used in that particular area.

Mariners are advised that the U.S. maritime aids to navigation system have been modified to incorporate the International Association of Lighthouse Authorities (IALA) Maritime Buoyage System for REGION B.

## CHARACTERISTICS OF LIGHTS

### ***Type - Abbreviation - Description***

1. FIXED - F - A light showing continuously and steady.
2. OCCULTING - A light in which the total duration of light in a period is longer than the total duration of darkness and the intervals of darkness (eclipses) are usually of equal duration.
  - 2.1 Single-occulting - Oc - An occulting light in which an eclipse is regularly repeated.
  - 2.2 Group occulting - Oc(2) - An occulting light in which a group of eclipses, specified in numbers, is regularly repeated.
  - 2.3 Composite group-occulting - Oc(2+1) - A light similar to a group-occulting light, except that successive groups in a period have different numbers of eclipses.
3. ISOPHASE - Iso - A light in which all durations of light and darkness are equal.
4. FLASHING - A light in which the total duration of light in a period is shorter than the total duration of darkness and the appearances of light (flashes) are usually of equal duration.
  - 4.1 Single-flashing - Fl - A flashing light in which a flash is regularly repeated (not to exceed 30 flashes per minute)
  - 4.2 Group flashing – Fl (2) - A flashing light in which a group of flashes, specified in number, is regularly repeated.
  - 4.3 Composite group-flashing - Fl (2+1) - A light similar to a group flashing light except that successive groups in the period have different numbers of flashes.
5. QUICK - A light in which flashes are produced at a rate of 60 flashes per minute.
  - 5.1 Continuous quick - Q - A quick light in which a flash is regularly repeated.
  - 5.2 Interrupted quick - IQ - A quick light in which the sequence of flashes is interrupted by regularly repeated eclipses of constant and long duration.
6. MORSE CODE - Mo(A) - A light in which appearances of light of two clearly different durations (dots and dashes) are grouped to represent a character or characters in Morse code.
7. FIXED AND FLASHING - FFL - A light in which a fixed light is combined with a flashing light of higher luminous intensity.
8. ALTERNATING - Al RW - A light showing different colors alternately.



## **ISOLATED DANGER MARKS**

These aids are presently being introduced into the system. They will be used to mark hazards, which have navigable water all around them. They may be buoys or fixed structures with red and black bands (similar to the old preferred channel mark now being phased out). They can also be identified by their topmark, which consists of two black spheres, one above the other, on both lighted and unlighted aids. If lighted, they will display a Group Flashing (2) White light, Fl(2) 5s. An ISOLATED DANGER MARK should not be approached closely without special caution.

## **VANDALISM OF AIDS TO NAVIGATION**

Vandalism of aids to navigation is a serious problem in the Eighth Coast Guard District. Many of the aids, which are vandalized, require thousands of dollars to replace and may well endanger the lives and property of the mariners who depend on them for safe navigation. Vandalism ranges from destruction of lights by gunfire and malicious destruction to stealing the lanterns and batteries. Mariners are urged to report cases of vandalism to the nearest Coast Guard unit or by calling the Eighth Coast Guard District, Aids to Navigation Branch, at (504) 589-3075. Information pertaining to names, times, places and descriptions of boats or vehicles will be helpful in prosecuting malefactors.

33 CFR, Parts 70.05-1 and 70.05-5 state:

“No person shall take possession of or make use of for any purpose, or build upon, alter, deface, destroy, move, injure, obstruct by fastening vessels thereto or otherwise, or in any manner whatever impair the usefulness of any aid to navigation established and maintained by the United States.”

PENALTY: “Every person and every corporation that shall violate, or that shall knowingly aid, abet, authorize, or instigate a violation of the provisions of 70.05-1 shall be guilty of a misdemeanor, and on conviction thereof shall be punished by fine not exceeding \$2500.00 or less than \$500.00, or by imprisonment (in case of a natural person) for not less than thirty days nor more than one year, or both, one half of such fine to be paid to the person or person giving information which shall lead to conviction. (CFR 52-15, 18 CFR 12).”

## **AIDS TO NAVIGATION MAINTENANCE SIGNALS**

A Coast Guard vessel engaged in Aids to Navigation work will display the following signals (Navigation Rules, Rule 27):

Day—Three black shapes in a vertical line where they can best be seen. The highest and lowest of these shapes shall be balls and the middle one a diamond.

Night—Three all-round lights, equally spaced, at least 2 meters apart in a vertical line where they can best be seen. The highest and lowest of these lights shall be red and the middle light shall be white.

Mariners passing Coast Guard vessels displaying these signals are required to reduce their speed to insure safety of both vessels and personnel.

## **PRIVATE AIDS TO NAVIGATION**

Coast Guard Approval: No person, public body, or instrumentality not under the control of the Coast Guard, except the Armed Forces and states with designated state waters, shall establish, erect, or maintain in the navigable waters of the United States any aid to maritime navigation, without first obtaining permission to do so from the Coast Guard. No authorized private aid to navigation can be changed, moved, or discontinued without prior permission from the Coast Guard.

Application Procedures: Submit an application to establish and maintain private aids to navigation, with all appropriate parts of the form completed, to Commander, Eighth Coast Guard District (oan). Application form (CG-2554) will be provided upon request. Approval of a private aid to navigation application by the Coast Guard automatically constitutes authorization by the U.S. Army Corps of Engineers (ACOE) to establish an aid to navigation, buoy or structure in the navigable waters of the United States, since the ACOE has issued a nationwide permit covering this.

Protection of Private Aids: Private Aids to Navigation must be maintained in proper working order and entitled to the same protection against interference or obstruction provided by law as Coast Guard aids to navigation. If interference or obstruction occurs, a prompt report containing all the evidence available should be made to the Eighth Coast Guard District. Any person obstructing or interfering with an authorized Private Aid to Navigation may be fined \$500.00 for each offense (33 CFR 70.01).

Changes required to Private Aids: Private Aids to Navigation owners must comply with recent U.S. Aid to Navigation System regulation changes by December 31, 1994. These changes will make the U.S. Aid to Navigation System (including private aids) coincident with the International Association of Lighthouse Authorities (IALA) Maritime Buoyage System. This transition period allows conversion to be made in the course of routine maintenance. Some of the more noteworthy affects on private aid owners are as follows: Buoy owners must change all laterally black buoys to green. Special purpose buoys, which mark fishing reefs, cable areas, military exercise areas, etc., must be changed to yellow. Laterally significant lights must be the same color as buoys or daybeacons in that location. White lights on lateral aids will no longer be allowed. Special purpose lights must be yellow. Midchannel buoys are changing from black and white to red and white. All special purpose daybeacons must be changed to yellow. Notify the nearest Coast Guard unit with the position of any structure with aids to navigation discrepancies.

### ***RACONS Authorized for Private Aids to Navigation***

33 CFR 66.01 has been amended so that, upon application of the owner, the Coast Guard may approve voluntary use of radar beacons (RACONS) as private aids to navigation.

For further information and assistance concerning Private Aids to Navigation you may contact: Commander, (DPW), Eighth Coast Guard District, Hale Boggs Federal Building, 500 Poydras Street, Room 1211, New Orleans, LA 70130-3310. Phone: (504) 671-2328.

## **ELECTRONIC AIDS TO NAVIGATION**

### **RACONS**

Aids to navigation may be enhanced by the use of radar beacons (Racon). Racons, when triggered by pulses from a vessel's radar, will transmit a coded reply to the vessel's radar. This reply serves to identify the Racon station by exhibiting a series of dots and dashes which appear on the radar display emanating radially from the Racon. This display will represent the approximate range and bearing to the Racon. Although Racons may be used on both laterally significant and non-laterally significant aids to navigation, the Racon signal itself is for identification purposes only, and therefore carries no lateral significance. Racons are also used as bridge marks to mark the point of best passage. All Racon operate in the marine radar X-band from 9,300 to 9,500 MHz. Some frequency-agile Racon also operate in the 2,900 to 3,000 MHz marine radar S-band. Racons have a typical output of 100 to 300 milliwatts and are considered a short-range aid to navigation. Reception varies from a nominal range of 6 to 8 nautical miles when mounted on a buoy to as much as 17 nautical miles for a Racon with a directional antenna mounted at a height of 50 feet on a fixed structure. It must be understood that these are nominal ranges and are dependent upon many factors.

The beginning of the Racon presentation occurs about 50 yards beyond the Racon position and will persist for a number of revolutions of the radar antenna (depending on its rotation rate). Distance to the Racon can be measured to the point at which the Racon flash begins, but the figure obtained will be greater than the ship's distance from the Racon. This is due to the slight response delay in the Racon apparatus.

Radar operators may notice some broadening or spoking of the Racon presentation when their vessel approaches closely to the source of the Racon. This effect can be minimized by adjustment of the IF gain or sweep gain control of the radar. If desired, the Racon presentation can be virtually eliminated by operation of the FTC (fast time constant) controls of the radar.

## **LORAN-C**

LORAN, an acronym for LOnG RAnge Navigation, is an electronic aid to navigation consisting of shore-based radio transmitters. The LORAN system enables users equipped with a LORAN receiver to determine their position quickly and accurately, day or night, in practically any weather.

A user's position is determined by locating the crossing point of two lines of position on a LORAN-C chart. Many receivers have built-in coordinate converters, which will automatically display the receiver's latitude and longitude. With a coordinate converter, a position can be determined using a chart that is not overprinted with LORAN-C lines of position.

Although LORAN-C signal availability normally exceeds 99.9% and scheduled off-air periods are broadcast to the mariner, LORAN-C should not be relied upon as the only aid to navigation. A prudent navigator will use radar, radio direction finder, fathometer, and any other aid to navigation, in addition to the LORAN-C receiver.

For a more detailed explanation of the LORAN-C operating system, consult your Light List.

## **GLOBAL POSITIONING SYSTEM (GPS)**

The Global Positioning System (GPS) is a satellite-based radionavigation system providing continuous worldwide coverage. GPS provides navigation, position, and timing information to air, marine, and land users. The GPS system has reached Full Operating Capability (FOC). FOC status signifies that the system meets specific requirements of performance.

GPS consists of a constellation of 24 satellites, orbiting Earth in six planes of 4 satellites each, at an altitude of 10,900 nautical miles. The orbit period of each satellite is 12 hours. Mariners can expect 7 to 9 satellites available for use with unrestricted view of the sky. In areas where portions of the sky are blocked by mountains, buildings, or vegetation, fewer satellites can be expected. A minimum of three satellites is required for a two-dimensional solution. The DOD has reduced the accuracy available to civilian users for national security reasons; users can expect position solutions accurate to within +/- 100 meters. The GPS system does not provide integrity information and mariners should exercise extreme caution when using GPS in restricted waterways.

Although originally intended for military use only, Federal radionavigation policy has established that GPS will be available for civil use. Whenever possible, advance notice of when the GPS satellites should not be used will be provided by the DOD and made available by the U.S. Coast Guard.

## **DIFFERENTIAL GPS (DGPS)**

The Coast Guard has implemented a new system for marine navigation called Differential GPS (DGPS). As the newest electronic system of navigation, DGPS transmitters provide offshore coverage and an all weather electronic aid to navigation capability. The Coast Guard DGPS transmitting sites provide DGPS coverage to the Great Lakes, and coastal areas of the continental United States, as well as selected portions of Alaska, Hawaii, Puerto Rico, and the inland river system. For a more detailed explanation of the DGPS operating system, consult your Light List.

# CHAPTER VI

## COMMON CAUTIONARY SITUATIONS

### CAUTION - CLOSE APPROACH TO MOORED OFFSHORE AIDS TO NAVIGATION

Courses should invariably be set to pass these aids with sufficient clearance to avoid the possibility of collision from any cause. Errors of observation, current and wind effects, other vessels in the vicinity, and defects in steering gear may be, and have been, the cause of actual collisions, or the jeopardizing of navigation services provided by these important aids to navigation. Experience shows that buoys cannot be safely used as leading marks to be passed close aboard, and should always be left broad off the course, whenever sea room permits.

When approaching an offshore light structure, large navigational buoy, or station on a submarine site, on radio bearings, insuring that the radio bearing does not remain constant will lessen the risk of collision.

It should be borne in mind that most large buoys are anchored to a very long scope of chain and, as a result, the radius of their swinging circle is considerable. The charted position is the approximate location. Furthermore, under certain conditions of wind and current, they are subject to sudden and unexpected sheers, which are certain to hazard a vessel attempting to pass, close aboard.

### CAUTION-OIL WELL STRUCTURES IN THE GULF OF MEXICO

Caution should be exercised when navigating in the Gulf of Mexico in order to avoid collision with oil well structures and their associated mooring piles, anchor and mooring buoys, etc. In general, oil well structures can be identified at night by the display of one or more quick flashing white or red lights. However, ships can expect to encounter unlighted structures as well. Structures may be equipped with a fog signal consisting of a horn sounding one 2-second blast every 20 seconds. Lighted or unlighted buoys may mark submerged wells.

Shipping safety fairways have been established through the concentration of oil wells in the Gulf of Mexico. Mariners are encouraged to use these fairways and should avoid anchoring within a safety fairway. Certain areas adjacent to shipping safety fairways have been charted as fairway anchorage's.

### PIPELINE LAYBARGES AND JETBARGES

Pipeline laying operations are often being conducted in the Gulf of Mexico and other areas. Operators of all types of vessels should be aware of the dangers of passing close aboard, close ahead, or close astern of a jetbarge or pipelaying barge.

Pipelaying and jetbarges usually move at a half of a knot or less and have anchors, which extend out approximately 3500-5000 feet in all directions and may be marked by lighted anchor buoys. The exposed pipeline behind the pipelaying barge and the area in the vicinity of anchors are hazardous to navigation and should be avoided. The pipeline and anchor cables may also represent submerged hazards to navigation.

### WARNING - POSSIBLE DANGER FROM UNLABELED DRUMS

With the many exotic chemicals being transported in drums as deck cargo, increasingly more reports are received of loss overboard of these potentially dangerous containers. Even empty drums may contain residues, which are extremely hazardous to touch, or smell, and a few vapors may be explosive.

When coming upon derelict drums, whether afloat or from the sea bottom, this danger should be considered. Identifying labels will give adequate warning, but containers are more likely to be found with caution labels washed off. Avoid direct contact and notify U.S. Coast Guard of any sightings in U.S. coastal waters (24 HR TOLL FREE reporting number 1-800-424-8802), or government authorities of the nearest port if sighting is near any foreign shores.

## **SEISMIC SURVEYS**

Survey vessels may operate alone or in company with other surface vessels or submersibles. Survey vessels may be towing cables in excess of 2 miles astern. Cables may be marked by buoys and may be towed on the surface or submerged. During a survey, repeated shock waves are created by using explosive charges, compressed air, and mechanical vibrators or by electric means at any level from the bottom to the surface. Vessels surveying may be underway but sometimes are stopped for extended periods.

Seismic survey vessels which are unable to maneuver are required to carry the lights and signal described in Rule 27 of International Regulations for Preventing Collisions at Sea. These vessels should be given a wide berth.

## **DANGER FROM SUBMARINE CABLES AND PIPELINES**

Submarine cables or pipelines pass beneath various navigable waterways throughout the Eighth Coast Guard District. Installation of new submarine cables and pipelines may be reported in the Local Notice to Mariners; their locations may or may not be charted. Where feasible, warning signs are often erected to warn the mariners of their existence.

In view of the serious consequences resulting from damage to submarine cables and pipelines, vessel operators should take special care when anchoring, fishing or engaging in underwater operations near areas where these cables or pipelines may exist or have been reported to exist.

Certain cables carry high voltages; many pipelines carry petroleum products or natural gas under high pressure. Electrocutation, fire or explosion with injury or loss of life or a serious pollution incident could occur if they are penetrated.

Vessels fouling a submarine cable or pipeline should attempt to clear without undue strain.

anchors or gear that cannot be cleared should be slipped; no attempt should be made to cut a cable or pipeline.

## **UNITED STATES SUBMARINE CABLE ACT**

The provisions of the United States Submarine Cable Act (47 USC Sections 21-39) make it a federal offense to damage a submarine cable. These penalties do not bar civil suit by the cable owner for damages to the cable. This act also requires the master of a vessel to keep his gear at least one nautical mile from a vessel engaged in laying or repairing a submarine cable.

## **SUBMERGED OFFSHORE PIPELINES**

Throughout the Gulf of Mexico, numerous submerged pipelines exist in the navigable waters used by both large and small vessels. These submerged pipelines carry natural gas under high pressure and petroleum products. In inshore areas, these submerged pipelines are usually buried beneath the seabed, but in offshore areas the pipeline may lie on the ocean floor. The locations of numerous submerged pipelines are not known. A selection of submerged pipelines is shown on National Ocean Service (NOS) nautical charts from information which has been reported to NOS. However, additional uncharted submerged pipelines may exist within the area of the chart.

Several incidents have occurred where vessels have struck these submerged pipelines leading to loss of life and property due to the explosion and fire resulting from damage to the pipelines. Investigations of these incidents indicate many mariners believe that because the submerged pipelines were buried at installation, they remain buried and do not pose a danger to vessels or operators. Mariners should be aware that winter storms, hurricanes, and the placement of man-made structures such as jetties, can lead to erosion and subsidence and the removal of the sediment covering the submerged pipelines.

In view of the serious consequences resulting from damage to submerged pipelines, vessel operators operating in water depths at or near the vessel's draft or when operating bottom dragging equipment, should take special care near areas where these submerged pipelines may exist or have been reported to exist.

Operators of offshore gas or hazardous liquid pipeline facilities are now required to mark pipelines which are found to be buried less than 12 inches below the mudline with yellow lighted buoys displaying flashing yellow lights (flashing less than 30 times per minute). These buoys are to be placed on the exposed segments of pipelines at intervals of not more than 500 yards apart. However, if the exposed segment of pipeline is less than 200 yards in length, only one lighted buoy will be placed at the center of the segment.

Vessel operators fouling a submerged pipeline should attempt to clear the pipeline without excessive force. Anchors or gear that cannot be cleared should be released without damaging the pipeline. Exposed pipelines are a hazard to navigation. Mariners discovering an exposed pipeline should report the location immediately to the U.S. Coast Guard.

## **FIRING DANGER AREAS**

Firing and bombing practice exercises take place either occasionally or regularly in numerous areas established for those purposes along the coast of practically all maritime countries. In view of the difficulty in keeping these areas up to date on the charts, and since the responsibility to avoid accidents rest with the authorities using the areas for firing and/or bombing practice, these areas will not as a rule be shown on DMAHTC charts. National Ocean Service Charts show firing and bombing practice areas as defined by Code of Federal Regulations (Title 33, Part 334) in United States waters. Any permanent aid to navigation that may be established to mark a danger area, any target, fixed or floating, that may constitute a danger to navigation, will be shown on the appropriate charts. Warning signals, usually consisting of red flags or red lights, are customarily displayed before and during the practice, but the absence of such warnings cannot be accepted as evidence that a practice area does not exist. Vessels should be on the lookout for local warnings and signals, and should whenever possible, avoid passing through an area in which practice is in progress, but if compelled to do so should endeavor to clear at the earliest possible moment.

## **EXPLOSIVE ORDNANCE - WARNING**

All fisherman conducting operations on the ocean bottom are warned that the Continental Shelf of the United States contains many forms of unexploded ordnance. Types most likely to be encountered are underwater ordinances such as torpedoes, mines, depth charges, and aerial bombs. Non-explosive ordnance such as practice torpedoes will normally be painted bright yellow or orange.

Any item having fins, vanes, propellers, or horns should be regarded as dangerous. If in doubt, treat it as an explosive. Do not attempt to bring the object on board or alongside. Release it and notify the nearest Coast Guard Unit or Navy Station, giving your position and description of the object.

## **REPORTING OF HAZARDS TO NAVIGATION**

Mariners occasionally discover shoals, sunken derelict vessels or miscellaneous debris, which could endanger other navigators. Upon discovery of such potential hazards to navigation, mariners should immediately report them to the nearest Coast Guard unit, Defense Mapping Agency and the U.S. Army Corps of Engineers providing as much of the following information as possible:

- Description of the obstruction
- Location in latitude and longitude (Reference chart used)
- Depth of water over obstruction if submerged
- Reporting vessel and observer
- Time and date observation made

## **LIFE THREATENING SITUATION FOR OCCUPANTS OF SMALL BOATS IN THE MISSISSIPPI RIVER GULF OUTLET CHANNEL**

Large ships transiting the Mississippi River Gulf Outlet Channel, especially those that are loaded, can displace up to 35,000 tons of water. A ship of this size proceeding at even the most modest speed can create a very large wave of water from the ship to the shore and at times create a rolling wave of water along channel margins. When meeting large ships, small boat operators should not take their boat right up to the shoreline or place the stern of their boat toward the oncoming wave. This is extremely dangerous. Operate your boat cautiously, steer into the waves and stay away from the channel banks.

## **INLAND OBSTRUCTIONS IN CANALS AND BAYOUS**

In addition to numerous bayous and natural canals, thousands of man-made canals have been dredged in the wetlands of the Eighth Coast Guard District. While the original purpose of these canals was for private access to pipelines, well locations, or for other mineral related activities, some are being used by boaters. These canals and bayous contain numerous obstructions including barriers, pipes, piles, construction debris, etc. Some of these structures are permanently maintained and have been suitably marked or lighted by their owners. Many others appear and disappear without notice and are uncharted, unlighted, and unmarked. Even on marked structures, because of vandalism, etc. mariners cannot rely on the markings always being maintained in good condition. Therefore, all persons using canals and bayous must anticipate the hazards posed by these obstructions and navigate with extreme caution, especially at night and during periods of reduced visibility.

## **MARKING OF WRECKS**

When a vessel, or craft of any type is wrecked and/or sunk, accidentally or otherwise, in the navigable waters of the United States, the owner thereof has a non-delegable statutory requirement to mark immediately such sunken wreck with a buoy or daymark during the day and a lighted lantern at night, until the sunken craft is removed or abandonment is legally determined. Such markings shall conform to the lateral system of buoyage characteristics. Until the owner has the opportunity to establish the standard markings, he is well advised to maintain the most suitable markings available under the circumstances, which will warn the navigator of the sunken wreck. The regulations pertaining to wrecks may be found in the Title 33 Code of Federal Regulations, Part 64. The owner, agent, master, or person in charge of such vessel shall notify the nearest United States Coast Guard Marine Safety Office of the casualty as soon as possible, and in addition, shall advise what action he is taking to establish proper markings, giving the following information:

- Name and description of sunken wreck
- Accurate location of wreck
- Depth of water over wreck
- Location and type of marking established, including color of daymark, or buoy and color and characteristic of light.

## **FLOOD WARNINGS**

During flood conditions additional precautions are necessary for safe navigation. The basic rule is: If you don't have to use the waterway, don't. Flood flows can cause greatly increased currents, particularly during the ebbs. Channels sometimes shift and obstructions become covered with floodwaters. Trees and other shoreline growth and debris are carried into the streams creating additional hazards. Docks and pilings become submerged and aids to navigation may be submerged, carried off station, or rendered inoperative due to flooding. Small unlighted buoys may become completely submerged. Heavy rains often reduce visibility, further complicating safe navigation. Bridge clearances may be reduced from the charted clearances due to abnormally high water levels. Mariners should refer to bridge clearance gauges if installed.

## HURRICANE SEASON

The hurricane season is considered to extend from 1 June through 30 November and hurricanes often develop with little warning. Extensive damage to small craft attended by loss of life often results. Mariners, particularly operators of small fishing vessels, are reminded that advance planning which might prevent loss of vessel and crew should include:

- Instruction of crews.
- Presailing check of vessel, machinery and equipment for seaworthiness.
- Provision for strong ground tackle.
- Evasion of storm center.
- Seeking of shelter in nearest port.
- Constant radio watch on Coast Guard frequency for latest advisory.

Aids to navigation, particularly lighted and unlighted buoys, may be moved from charted position, damaged, destroyed, extinguished, or otherwise made inoperative as a result of storms, hurricanes, or other natural causes. Mariners should not rely completely upon the position or operation of an aid to navigation, but should also employ such other methods of determining position as may be available.

During the hurricane season, drawbridges along the coast may deviate from normal operating procedures. Some bridges may be unable to open because of high winds. Others may be authorized extended closed periods to facilitate evacuation of land traffic. Mariners should anticipate bridge closures by listening to the National Weather Service and Coast Guard broadcasts on hurricane conditions. Because of the uncertainty of hurricane movements and bridge closures, mariners are urged to seek passage through drawbridges well in advance of the arrival of gale force winds.

Locks and navigation structures are operated to pass navigation until such time that water levels and wind conditions warrant operations unsafe. The structures are then closed in accordance with hurricane preparation procedures. Mariners will be given as much notice as possible when structures are to be closed. However, these structures may be closed on short notice well in advance of the actual storm. Mariners are advised to seek safe harbor as soon as possible.

The civilian hurricane warning service for the North Atlantic is provided by the National Hurricane Center, Miami, Florida. They collate ship, aircraft, radar, and satellite data to produce and issue tropical cyclone warnings and forecasts for the North Atlantic Ocean, including the Caribbean Sea and the Gulf of Mexico. A Tropical Cyclone Advisory message is issued every six hours, with intermediate bulletins provided as needed.

For tropical storms and hurricanes threatening to cross the coast of the U.S., coastal warnings are issued to the public so that precautionary actions, including evacuation, can be initiated to minimize damage and loss of life. Two levels of warnings are employed:

- (a) **HURRICANE WATCH** - a preliminary alert that a hurricane **MAY** threaten a specified portion of the coast. It is issued 36 hours before landfall may occur; and
- (b) **HURRICANE WARNING** - which indicated that hurricane conditions are **EXPECTED** along a specified portion of the coast. It is issued 24 hours before landfall will occur. To provide additional information for maritime interests, a Marine Advisory is also issued which provides storm position forecasts for up to 72 hours in advance of a storm, and probabilities of hurricane strikes for coastal locations and offshore coordinates.



## HOW HURRICANES ARE CATEGORIZED

Forecasters use the SAFFIR-SIMPSON Scale to rate the strength and damage potential of hurricanes. A Category 1 hurricane is the weakest, and a category 5 is the strongest.

**CATEGORY 1** MINIMAL damage; winds of 74 to 95 mph; storm surge of 4 to 5 feet. Damage to shrubs, trees, and unanchored mobile homes. Low-lying roads may be inundated.

**CATEGORY 2** MODERATE damage; winds of 96 to 110 mph; storm surge of 6 to 8 feet. Some trees may be blown down, damage to roofs, windows and doors. No major damage to buildings expected other than mobile homes. Most coastal roads under water.

**CATEGORY 3** EXTENSIVE damage; winds of 111 to 130 mph; storm surge of 9 to 12 feet. Large trees blown down, mobile homes destroyed. Some structural damage to small buildings expected. Windows, roofs, and doors damaged. Serious flooding near coast, waves batter coastal structures is possible.

**CATEGORY 4** EXTREME damage; winds of 131 to 155 mph; storm surge of 13 to 18 feet. Roofs blown off many small residences, heavy damage to roofs, windows, and the doors. Flooding extends well inland. Major damage to coastal structures from storm surge.

**CATEGORY 5** CATASTROPHIC damage; winds of 156 mph and up; storm surge 18 feet and above. Massive damage to roofs, windows and doors, roofs blown off many small buildings, some complete building failures. Major damage to lower floors of all oceanfront structures from storm surge. Extensive flooding in low-lying inland areas.

## STORM SURGE

A considerable rise or fall in the level of the sea along a particular coast may result from strong winds and sharp change in barometric pressure. In cases where the water level is raised, higher waves can form with greater depth and the combination can be destructive to low-lying regions, particularly at high stages of tide. This type of wave occurs especially in coastal regions bordering on shallow waters, which are subject to tropical storms.

## MANEUVERING TO AVOID A STORM CENTER

If you find yourself caught within a storm area, the proper action to take depends in part upon your position relative to the storm center, as well as upon its direction of travel. It is customary to divide the circular area of the storm into two parts. In the northern hemisphere, that part to the RIGHT of the storm track (facing in the same direction in which the storm is moving) is called the DANGEROUS SEMICIRCLE. It is considered dangerous because:

- (a) the wind speed is intensified by the forward motion of the storm;
- (b) the direction of the wind and sea push the vessel into the path of the storm; and
- (c) the greater wind speed in this semicircle creates higher seas.

The area to the left of the storm track is called the NAVIGABLE SEMICIRCLE. In this region, the storm-generated wind is in opposition to the storm's forward motion, and blows the vessel away from the storm track if in the forward part of the semicircle.

Plotting the movement of the storm center should indicate which semicircle you are in. However, storm positions issued in weather bulletins may be unreliable because of the time lag between the observation and the broadcast. The use of radar eliminates the time lag, but may not provide a true indication of the storm center. The most reliable guide is often the wind.

In the northern hemisphere, according to BUYS BALLOT'S LAW, an observer with his back to the wind has the center of the low on his left, and somewhat in front of him (115 degrees is a good approximation). This value applies when the storm is still several hundred miles away. Closer to the center, 90 degrees is a better figure.

While the vessel can still make good headway, a course should be selected which will take it as far as possible from the center of the storm. If the vessel can move faster than the storm, it is a simple matter to outrun the danger as long as sea room permits. When the storm is faster than you are, matters are trickier. The problem is to select a course that will put as much distance between you and the storm center as possible.

- (a) Within the right or DANGEROUS SEMICIRCLE bring the wind on the starboard bow (045 relative), hold course and make as much headway as possible at a safe speed. Vessel A is being approached by the dangerous semicircle, and is struck by both the warm and cold fronts, which produce increasing, gusty, rapidly shifting winds, heavy rain, and confused seas.
- (b) In the left or NAVIGABLE SEMICIRCLE bring the wind on the starboard quarter (135 relative), hold course and make as much headway as possible at a safe speed. Vessel B avoids both fronts, most of the rain, and experiences lower seas because the wind and the movement of the storm are acting against one another.

Obviously, none of the standard rules should be followed when doing so heads a vessel into additional dangers, such as shoals, currents that could cause heavy seas, headings that result in the vessel rolling dangerously, or other vessels in the area.

# CHAPTER VII

## BOATING SAFETY

### A. Alcohol Abuse and Recreational Boating.

1. The United States Coast Guard and many state governments are conducting an aggressive campaign to combat the problem of the operation of recreational boats while under the influence of alcohol or dangerous drugs. Excessive consumption of alcoholic beverages is a major factor in the large number of fatal boating accidents that occur each year.
2. The approach taken by the Coast Guard and the states has been and will continue to be three-fold: adoption of stiff legal sanctions along the lines of intoxicated automobile operation; stepped-up on-water law enforcement efforts, and improved boater education programs to warn of the dangers of mixing boating with excessive alcohol consumption.
3. Title 33 Code of Federal Regulations, 95.020(a), states that an individual operating a recreational vessel is intoxicated when the operator has an alcohol concentration of .08 percent by weight or more in their blood.
4. This information is provided for the benefit of recreational boaters, fisherman and other users of the lakes and rivers in the area of the Eighth Coast Guard District. Adherence to the standards of safe boating should ensure many accident-free days on the water. FOR BOATING SAFETY INFORMATION CALL: 504-671-2157

### B. Non-Emergency Assistance.

1. Eighth Coast Guard District Sectors maintain lists of commercial operators desiring to provide assistance of a non-emergency nature to pleasure craft. Any operator wishing to be listed as a resource for such assistance should make a written request to the Coast Guard Sector Commander in their area of operations. Addresses for all groups, and other areas of responsibility, are listed on pages 1 thru 3 of this publication. The request must contain the following information:
  - a. Type of assistance available.
  - b. Size of vessel the operator is capable of assisting, or desires to assist.
  - c. VHF-FM radio capabilities.
  - d. Type and size of resources available.
  - e. Hours of operation.
  - f. Phone number (after hours phone number if available).
  - g. Response area/area of operations.
2. Operators submitting such a written request will be placed on the list of commercial resources available for non-emergency assistance maintained by each Sector Commander. Operators on the list will be called on a rotating basis for incidents occurring in their response area.

## CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)

### C. Law Enforcement.

1. Coast Guard vessels are identified by distinctive blue and red stripes on the bow, the words "Coast Guard" on the side, the Coast Guard ensign (flag), and are operated by a uniformed crew. Coast Guard law enforcement people occasionally use other vessels, displaying the Coast Guard ensign, when engaged in law enforcement activity.
2. A vessel underway, upon being hailed by a Coast Guard vessel, is required to stop immediately and lay to, or maneuver in a way to permit a boarding officer to board. Failure to stop may subject the operator to be arrested for violation of 18 USC 111.
3. A civil penalty of up to \$5,000 for each violation may be imposed by the Coast Guard for failure to comply with equipment, numbering and reporting requirements, or failure to observe rules of the road. Some requirements are summarized here. Contact the Coast Guard for requirements applicable to your boat.
4. Negligent and grossly negligent operation of a vessel which endangers life, limb, or property is prohibited by law. A civil penalty may be imposed by the Coast Guard for negligent operation, or the operator may be subject to a fine up to \$5,000, or imprisonment of no more than one year, or both, for the criminal offense of grossly negligent operation.
5. A Coast Guard Boarding Officer who observes an unsafe condition and determines an especially hazardous condition exists, may direct an operator to make immediate steps to correct the condition, including returning to the nearest safe mooring.
6. An operator who refuses to comply with the order to stop unsafe use of a boat can be cited for failure to comply with directions of a Coast Guard Boarding Officer, as well as for specified statutory or regulatory violations or provisions which were the basis for the termination order.

### D. The Coast Guard Auxiliary.

1. The Coast Guard Auxiliary is a volunteer organization used to supplement Coast Guard units or to provide services to the boating public. Auxiliarists may be assigned to missions that have law enforcement connotations, such as vessel traffic control during a regatta. However, Auxiliarists are not vested with any law enforcement authority.
2. Auxiliary Vessel Safety Checks - The Coast Guard Auxiliary conducts vessel safety checks to determine if a vessel meets federal and state requirements. Contact a member of the Coast Guard Auxiliary for a free vessel safety check. A decal is awarded to vessels that meet all requirements. If a boat does not have the proper equipment, no report is made to any law enforcement authority. The Auxiliarist advises the boater of the deficiencies so they can be corrected. You may contact an Auxiliary Vessel Examiner through your local Auxiliary Flotilla, or by contacting one of the Regional Director of Auxiliary Offices listed below:

Director of Auxiliary  
Eastern Region  
Room 415  
Martin Luther King Jr. Blvd.  
Louisville, KY 40202-2230  
(502) 625-7543

Director of Auxiliary  
Coastal Region  
500 Poydras St.  
New Orleans, LA 70130-3396  
(504) 671-2144

## CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)

Director of Auxiliary  
Western Region  
1222 Spruce Street  
St. Louis, MO 63103-2832  
(314) 539-3900 ext. 212

3. The Coast Guard Auxiliary also offers public courses in boating safety and seamanship. They are taught by experienced Auxiliary members and the only charge is for course materials. These courses are usually given in the fall and winter. For more information, contact (Boat/US at 1-800-336-BOAT), your local Auxiliary Flotilla, or the Regional Director of Auxiliary Offices listed in paragraph D - 2 above.

4. The courses available are:

a. "Boating Skills and Seamanship" (8 core lessons, 5 additional lessons available). The most comprehensive course for the recreational boater. The course covers boat terminology, Aids to Navigation, Boat handling and equipment required for the boat. It also covers Navigation rules, Boating emergencies.

b. "America's Boating Course" (7 lessons). This course provides basic safety information for the Recreational boater. It covers boat terminology, navigating waterways, operating a boat safely, legal requirements of boating, and boating emergencies.

c. "Basic Coastal Navigation" (6-13 lessons) - Hands -on training of the basics of Navigation techniques. This course focuses on chart work.

d. "GPS for Mariners" (Seminar Course- 4 hours) The course is designed to cover equipment typically owned by the recreational boater. This course focuses on hands on experience with the GPS Unit.

### **E. Coast Guard Approved Equipment.**

1. Life Jackets are classified by "type". The amount and type required in a recreational boat depends on its length:

a. All recreational boats less than 16 feet in length, and all canoes and kayaks, must have one serviceable Coast Guard approved type I, II, III, IV, or V device of a suitable size aboard for each person.

b. All recreational boats 16 feet in length and over must have one serviceable Coast Guard approved type I, II, III, or V device of suitable size aboard for each person and, in addition, one throwable type IV device.

c. The type I, II, and III devices must be readily accessible to all persons on board. Since the type IV device is designed for throwing to a person in the water and not for wearing, it must be immediately available for use. If a type V or inflatable Life Jacket is to be counted toward minimum carriage requirement, it must be worn.

## CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)

- d. Effective 12/23/2002, the Coast Guard is requiring all children under 13 years of age wear Coast Guard approved life jackets, while on board recreational vessels underway, except when the child is below decks or in an enclosed cabin. This rule affects only those States that have not established requirements, by statute or rule, for children to wear life jackets. For the remaining States, the rule recognizes and adopts the existing state regulation, even if less stringent.
2. Fire extinguishers - must be carried in all motorboats with inboard engines having one or more:
  - a. Closed compartments under thwarts and seats wherein portable fuel tanks may be stored, or
  - b. Double bottoms not sealed to the hull or which are not completely filled with flotation materials, or
  - c. Closed living spaces, or
  - d. Closed storage compartments in which combustible or flammable materials are stored, or
  - e. Permanently installed fuel tanks.
3. Flame arresters (backfire flame controls) - Gasoline engines installed after April 25, 1940, except outboard motors, must be equipped with an acceptable means of backfire flame control. The device must be suitably attached to the air intake with a flame tight connection and is required to be Coast Guard approved or comply with SAEJ-1928 or UL1111 standards and marked accordingly.

### F. Minimum Required Equipment by Length of Boat.

1. Less than 16 feet in length:
  - a. Backfire flame arrester -- one approved device installed on each carburetor of all gasoline engines installed after April 25, 1940, except outboard motors.
  - b. Equipment for Sound Signals -- some means of making an efficient sound signal.
  - c. Life Jackets
  - d. Fire extinguisher (portable) -- when no fixed fire extinguishing system is installed in machinery spaces:
    - (1) At least one B-I type approved hand portable fire extinguisher (Not required on outboard motorboats less than 26 feet in length if the construction of such motorboat will not permit entrapment of explosive or flammable gases or vapors).
    - (2) When a fixed system is installed in machinery spaces, one less B-I type extinguisher is required.
2. 16 feet to less than 26 feet in length:
  - a. Backfire flame arrester -- same as section one.
  - b. Bell, whistle -- no bell required. One hand, mouth, or power operated whistle or horn, audible at least one-half mile.

## CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)

- c. Life Jackets
  - d. Fire extinguisher (portable) -- same as section one.
3. 26 feet to less than 40 feet in length:
- a. Backfire flame arrester -- same as section one.
  - b. Equipment for Sound Signals -- one of the following: either a bell, a whistle, or some other means of making an efficient sound signal.
  - c. Life Jackets
  - d. Fire extinguisher (portable) -- at least two B-I type approved fire extinguishers; or at least one B-II type approved portable fire extinguisher. When an approved fixed system is installed, only one B-I type is required in addition to the fixed system.
4. 40 feet to not more than 65 feet in length:
- a. Backfire flame arrester -- same as section one.
  - b. Bell – vessel over 12M(39’ 4”); 200mm(7.9” with clapper)
  - c. Whistle – vessel under 12M; efficient means of making a sound signal. Vessel over 12M(39’ 4”) one, audible at least one-half nautical mile
  - d. Life Jackets
  - e. Fire extinguisher (portable) -- at least three B-I type approved portable fire extinguishers; or at least one B-I type plus one B-II type approved portable fire extinguisher. When an approved fixed system is installed, one B-II type or two B-I type are required in addition to the fixed system.
5. Fire extinguishing equipment requirements for motor vessels greater than 65 feet in length are in Title 46, Code of Federal Regulations, Part 25.
6. Commandant Instruction M16672.2B, Navigation Rules International-Inland, Annex V, ss88.05, states that after January 1, 1983, the operator of each self-propelled vessel of 12 meters or more in length must carry on board and maintain for ready reference a copy of the Inland Navigation Rules.

### **G. Title 33 Code of Federal Regulations - Ventilation.**

No person may operate a boat built after July 31, 1980, that has a gasoline engine for electrical generation, mechanical, power, or propulsion unless it is equipped with an operable ventilation system that meets the requirements of Title 33 Code of Federal Regulations.

1. Applicability. This subpart applies to all boats that:
- a. Have gasoline engines for electrical generation, mechanical power, or propulsion; and
  - b. Are built after July 31, 1980.

## CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)

### 2. Definitions. As used in this subpart --

- a. "Fuel" means gasoline.
- b. "Open to the atmosphere" means a compartment that has at least 15 square inches of open area directly exposed to the atmosphere for each cubic foot of net compartment volume.

### 3. Powered Ventilation System.

- a. Each compartment in a boat that has a permanently installed gasoline engine with a cranking motor must --
  - (1) Be open to the atmosphere, or
  - (2) Be ventilated by an exhaust blower system.
- b. Each exhaust blower or combination of blowers must be rated at an air flow capacity not less than that computed by the formulas given in Title 33 Code of Federal Regulations.
- c. Each exhaust blower system required by Title 33 Code of Federal Regulations must exhaust the air from the boat at a rate which meets requirements of Table 183.610, when the engine is not operating.
- d. Each intake duct for an exhaust blower must be in the lower one-third of the compartment and above the normal level of accumulated bilge water.
- e. More than one exhaust blower may be used in combination to meet the air movement requirements.
- f. Each boat that is required to have an exhaust blower must have a label that:
  - (1) Is located as close as practical to each ignition switch,
  - (2) Is in plain view of the operator, and
  - (3) Has at least the following information:

"WARNING -- GASOLINE VAPORS CAN EXPLODE. BEFORE STARTING ENGINE OPERATE BLOWER FOR 4 MINUTES AND CHECK ENGINE COMPARTMENT BILGE FOR GASOLINE VAPORS."

### 4. Natural Ventilation System.

- a. Except for compartments open to the atmosphere, a natural ventilation system which meets the requirements of Title 33 Code of Federal Regulations must be provided for each compartment in a boat that --
  - (1) Contains a permanently installed gasoline engine.



## CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)

- (2) Has openings between it and a compartment that requires ventilation, where the aggregate area of those openings exceeds 2 percent of the area between the compartments.
  - (3) Contains a permanently installed fuel tank and an electrical component that is not ignition protected in accordance with Title 33 CFR.
  - (4) Contains a fuel tank that vents into that compartment, or
  - (5) Contains a non-metallic fuel tank with an aggregate permeability rate of more than 1.2 grams of fuel loss in 24 hours.
- b. Each natural ventilation system must be constructed so that --
- (1) Each supply opening required in Title 33 CFR is forward facing and located on the exterior surface of a boat, or
- (2) Air will flow into or out of the supply or exhaust openings required in Title 33 CFR when the boat is in a wind flowing from bow to stern at a velocity of 10 miles per hour when the engine is not operating.
- b. An accommodation compartment above a compartment requiring ventilation that is separated from the compartment requiring ventilation by a deck or other structure is excepted.

### 5. Standards for Natural Ventilation.

- a. For the purpose of Title 33 Code of Federal Regulations, "Natural ventilation" means an airflow in a compartment in a boat achieved by having a --
  - (1) Supply opening or duct from the atmosphere or from a ventilated compartment or from a compartment that is open to the atmosphere, and
  - (2) An exhaust opening into another ventilated compartment or an exhaust duct to the atmosphere.
- b. Each exhaust opening or exhaust duct must originate in the lower third of the compartment.
- c. Each supply opening or supply duct and each exhaust opening or exhaust duct in a compartment must be above the normal accumulation of bilge water.
- d. Except as provided in paragraph 5. of this section, supply openings or supply ducts and exhaust openings or exhaust ducts must each have a minimum aggregate internal cross-sectional area calculated as follows:  $A = \ln(V/5)$ ; Where:
  - (1) "A" is the minimum aggregate internal cross-sectional area of openings or ducts in square inches;

## CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)

(2) "V" is the net compartment volume in cubic feet, including the net volume of other compartments connected by openings that exceed 2% of the area between the compartments.

e. The minimum internal cross-sectional area of each supply opening or duct and exhaust opening or duct must exceed 3.0 square inches. 6. Ventilation of Boats (MOTOR BOAT ACT OF 1940) TANK AND ENGINE SPACES

a. All motorboats and motor vessels, except open boats and as provided in paragraphs (d) and (e) above, the construction or decking over of which is commenced after April 25, 1940, and which use fuel (flashpoint of 110 degrees F or less), must have at least two ventilator ducts, fitted with cowls or equivalent, for the efficient removal of explosive or flammable gases from every bilge, engine and fuel tank compartment. There must be at least one exhaust duct installed so as to extend from the open atmosphere to the lower portion of the bilge and at least one intake duct installed so as to extend to a point at least midway to the bilge or at least below the level of the carburetor intake. The cowls shall be located and trimmed for maximum effectiveness and in such a manner that prevents displaced fumes from being recirculated.

b. Boats as defined in the Federal Boat Safety Act of 1971 built after July 31, 1980, or which are in compliance with Title 33 CFR are excepted from these requirements.

c. Boats, as defined in the Federal Boat Safety Act of 1971, built after July 31, 1978, are excepted from the requirements for fuel tank compartments that --

(1) Contain a permanently installed fuel tank if each electrical component is ignition protected in accordance with Title 33 CFR, and

(2) Contain fuel tanks that vent to the outside of the boat.

### H. Numbering Requirements.

1. Certificate of Number – Undocumented motor driven vessels are to be numbered (registered) by the state in which the vessel is principally used (In a few states, the Coast Guard issued number). The number issued to a vessel is shown on the certificate of number. The original Certificate of Number must be on board whenever the vessel is in use.

2. Display of Number and Validation Stickers - The vessel's number must be painted on, or permanently attached to each side of the forward half of the vessel (the bow), and no other number may be displayed there. Numbers are to read left to right, be in plain vertical block letters, be of a color contrasting with the background, be distinctly visible and legible, and be not less than three inches high, have space or hyphens that are equal to the width of a letter other than "I" or a number other than "1" between the letter and number groupings (example: DC 5673 EF or DC-5678-EF).

## **CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)**

3. Notification of Changes Required - When a vessel is lost, destroyed, or transferred, the person whose name appears as owner on the certificate of number must, within 15 days, notify the authority that issued the number. If the Certificate of Number is lost or destroyed, or the owner changes address, he must notify the issuing authority within 15 days. A person whose name appears as owner of a vessel on a Certificate of Number must surrender his certificate in the manner prescribed by the issuing authority within 15 days after it becomes invalid for any reason.

### **I. Pollution Placards.**

1. The Coast Guard has issued a final rule which revises the placard language required to be posted on ships 26 feet in length or greater stating oil discharge prohibition and the penalty for violation of that prohibition. However, vessel owners and operators will continue to be allowed to use placards meeting existing Coast Guard requirements for the lifetime of the card.

2. Placards must be at least 5 by 8 inches, made of durable material, and fixed in a conspicuous place in each machinery space or at the bilge and ballast pump control station, stating the following:

#### **DISCHARGE OF OIL PROHIBITED**

THE FEDERAL WATER POLLUTION CONTROL ACT PROHIBITS THE DISCHARGE OF OIL OR OILY WASTE INTO OR UPON THE NAVIGABLE WATERS OF THE UNITED STATES, OR THE WATERS OF THE CONTIGUOUS ZONE, OR WHICH MAY AFFECT NATURAL RESOURCES BELONGING TO, APPERTAINING TO, OR UNDER THE EXCLUSIVE MANAGEMENT AUTHORITY OF THE UNITED STATES, IF SUCH DISCHARGE CAUSES FILM OR DISCOLORATION OF THE SURFACE OF THE WATER OR CAUSES A SLUDGE OR EMULSION BENEATH THE SURFACE OF THE WATER. VIOLATORS ARE SUBJECT TO SUBSTANTIAL CIVIL PENALTIES AND/OR CRIMINAL SANCTIONS INCLUDING FINES AND IMPRISONMENT.

### **J. Notices to Sponsors of Marine Events.**

1. An individual or organization planning to hold a regatta or marine parade on the navigable waters of the Eighth Coast Guard District which by its nature, circumstances or location, will introduce extra or unusual hazards to the safety of life or property or interfere with the normal flow of commercial or recreational traffic, must submit an application to the Sector responsible for the area the event will be in. Page 2 lists Sectors and their addresses. In granting a permit, the Sector may prescribe regulations for the event. In addition, sponsors of marine events must submit applications to their state and local governments as required by law.

2. When events are held regularly in a single area, the Sector may grant a permit for a series of events over a fixed period, not to exceed one year. This permit is subject to conditions which may change if circumstances warrant.

## **CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)**

3. Applications are available from the Sector. Federal law requires permits to be submitted no later than 135 days before the start of an event. An event for which application is required must be held only after approval by the Sector. New environmental rules, applicable to regattas and marine events, were published in the Federal Register. The majority of events held in the Eighth Coast Guard District will not be affected by these new rules. However, a significant number of events will require additional coordination with other state and federal agencies which may require up to 90 days to process permit applications. Should you need further information in regard to the new environmental rules, please contact the appropriate Sector.
4. Events held on waters other than those discussed above require permits approved by cognizant state boating officials pursuant to agreements between those states and the Coast Guard.
5. Any boater interested in obtaining the special regulations or notice to mariners issued regarding a marine event may contact the Eighth Coast Guard District Legal Office, 500 Poydras St., New Orleans, LA 70130-3396.
6. Any structures which may be necessary (i.e., temporary docks or mooring devices) may require authorization from the Corps of Engineers.

### **K. Safe Boating is no Accident.**

1. It is a federal offense to operate any motorboat or any vessel in a negligent manner so as to endanger life, limb or property of any person. Fines may include \$5,000 for each violation and/or imprisonment of one year.
2. Negligent acts include, but are not limited to:
  - a. Using excessive speed during periods of reduced visibility.
  - b. Excessive speed near other vessels, or in narrow winding channels.
  - c. Operating while under the influence of alcohol or dangerous drugs.
  - d. Towing water skiers too close to other boats or obstructions.

### **L. Boating Accident Reports.**

1. When a person dies, or disappears from a vessel, as a result of an occurrence involving a vessel or its equipment, the operator must, without delay, by the quickest means possible, notify the nearest state boating authority or Coast Guard unit of the following:
  - a. Date, time and exact location of the occurrence.
  - b. Name of each person who died or disappeared.
  - c. Number and name of vessel.

## CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)

- d. Name and address of vessel owner and operator.
  - e. Note: If the operator cannot give this notice, each person on board must notify that authority, or determine that such notice has been given.
2. The operator of a vessel must submit a proper state form within 24 hours of a boating accident (Coast Guard report form CG-3865 may also be used) in which a person dies and within 48 hours of a boating accident which:
    - a. A person is injured and requires medical treatment beyond first aid.
    - b. A person disappears from the vessel under circumstances that indicate death or injury.
  3. Accidents must be reported within 10 days if damage to the vessel and other property totals more than \$2000, or there is a complete loss of vessel and an earlier report is not required as indicated above.
  4. For assistance in filing reports call the appropriate state authority.

### **M. Make a Float Plan.**

1. If trouble occurs while you're cruising on your boat, help will come faster if the Coast Guard or other rescue agency knows where to look. The Coast Guard encourages boaters to leave Float Plans with friends or relatives to whom they can report their safe arrival. Should friends or relatives fail to receive information of your safe arrival when due, or within a reasonable time thereafter, they should notify the nearest Coast Guard unit or Marine Safety activity and provide the information in the Float Plan. A sample Float Plan is shown in enclosure 1. For your safety, and your family's peace of mind, complete this form, leave it with a responsible person upon whom you can depend to notify authorities if you're overdue. Float Plans should never be sent to the Coast Guard.

### **N. Marine Sanitation Devices.**

1. In 1976, the Environmental Protection Agency issued final standards of performance for marine sanitation devices. The Coast Guard has established regulations which implement these standards. The following information is presented to advise owners of boats of their responsibilities and options in complying with these requirements.

#### "WAIVER OF CERTAIN REQUIREMENTS FOR VESSELS OF 65 FEET IN LENGTH OR LESS"

2. Vessels on which construction was started on or after January 30, 1975 (new vessels), must have a certified marine sanitation device (MSD). This requirement is not affected by the waiver.
3. The regulations would have required vessels manufactured after January 30, 1980, to have a type II or III MSD. New vessels manufactured prior to this date would have been permitted to use a type I MSD only if the MSD was installed before January 31, 1980. The Commandant is waiving these requirements.

## CHAPTER 7. RECREATIONAL BOATING SAFETY (Cont)

4. Vessels on which construction was started prior to January 30, 1975 (existing vessels), must have a certified MSD by January 31, 1980. This requirement is not affected by this waiver.
5. For existing vessels, present regulations would have required installation of either a type II or III MSD to meet the January 31, 1980, deadline. A type I MSD would have been accepted on an existing vessel only if it had been installed before January 31, 1978 (extended by a previous Coast Guard waiver, November 28, 1977, 42 FR 60619). The Commandant waives these requirements.
6. The MSD requirements for vessels of 65 feet in length or less with installed toilet facilities which remain in effect under the waiver are as follows:
  - a. All vessels of 65 feet in length or less with installed toilet facilities must install a certified type I, II, or III MSD. This requirement is effective now for new vessels. This requirement is effective on January 31, 1980, for existing vessels [vessel length is determined by 46 CFR 24.10-17(b)].
  - b. The Commandant is waiving the applicability of 33 CFR 159.5(b) and 159.7(b) to new vessels of 65 feet in length or less. The Commandant is also waiving the applicability of the dates in 159.5(c)(2) and 159.7(c)(2) to existing vessels. Finally, the applicability of 40 CFR 140.3(d) to vessels 65 feet in length or less is also waived.
7. The waiver is as follows: This waiver applies only to vessels 65 feet in length or less, that have installed toilet facilities. [Vessel length is determined by 46 CFR 24.10-17(b)]. Type I MSDs may be installed in new or existing vessels. New or replacement MSD installations after January 30, 1980, may be type I, II, or III.
8. The EPA standards state that in freshwater lakes, freshwater reservoirs or other freshwater impoundments whose inlets or outlets are such as to prevent the ingress or egress by vessel traffic subject to this regulation, or in rivers not capable of navigation by interstate vessel traffic subject to this regulation, marine sanitation devices certified by the U.S. Coast Guard installed on all vessels shall be designed and operated to prevent the overboard discharge of sewage, treated or untreated, or of any waste derived from sewage.
9. The EPA standards further state that this shall not be construed to prohibit the carriage of Coast Guard-certified flow-through treatment devices which have been secured so as to prevent such discharges. They also state that waters where a Coast Guard-certified marine sanitation device permitting discharge is allowed include coastal waters and estuaries, the Great Lakes and interconnected waterways, freshwater lakes and impoundments accessible through locks, and other flowing waters that are navigable interstate by vessels subject to this regulation (40 CFR 140.3).

# CHAPTER VIII

## WATER POLLUTION

### COMPLIANCE WITH CLEAN WATER ACT AND REFUSE ACT

The Federal Water Pollution Control Act (FWPCA) prohibits the discharge of a harmful quantity of both oil and a hazardous substance into or upon the navigable waters of the United States. This prohibition encompasses adjoining shorelines, waters of the contiguous zone, activities connected with the Outer Continental Shelf Lands Act(OSLA) and Deepwater Port Act 1974. Also, natural resources belonging to the United States or under its exclusive management authority are governed by Section 311 of the FWPCA as amended by 33 USC 1321, including those resources under the Fishery Conservation and Management Act of 1976. Furthermore, in the event a spill does occur in violation of the Act the person in charge of a vessel or onshore or offshore facility is required to notify the Coast Guard as soon as he has knowledge of the spill. Such notification is to be by the most rapid means available to the National Response Center (1-800-424-8802, nationwide 24 hour number).

### COMPLIANCE WITH THE ACT TO PREVENT POLLUTION FROM SHIPS

The Act to Prevent Pollution from ships (33 U.S.C. 1901) implements into U.S. law the International Convention for the Prevention of Pollution from Ships, as modified by the Protocol of 1978 (MARPOL 73/78). Annex I of MARPOL 73/78 deals with oil and oily waste and Annex II deals with hazardous chemicals and other substances referred to as Noxious Liquid Substances (NLS).

Annex I of MARPOL 73/78 is applicable to oceangoing tankers over 150 gross tons and all other oceangoing ships over 400 gross tons. The MARPOL 73/78 requirements include oily waste discharge limitations, oily-water separating equipment, monitoring and alarm systems for discharges from cargo areas, cargo pump rooms and machinery space bilges. Ships to which Annex I MARPOL 73/78 is applicable are also required to have an International Oil Pollution Prevention (IOPP) Certificate verifying that the vessel is in compliance with the requirements of MARPOL 73/78 and that any required equipment is on board and operational. Vessels must also maintain an Oil Record Book recording all oil transfers and discharges. The Oil Record Book is available from the Government Printing Office.

Annex II of Marpol 73/78 is applicable to oceangoing vessels and non-self propelled oceangoing ships, which carry Noxious Liquid Substances (NLS) in bulk. The Annex II requirements include discharge restrictions for various classes of cargo residues; the maintenance of a Cargo Record Book for recording all NLS cargo and residue transfers and discharges; and Procedures and Arrangements Manual describing the correct procedures for off-loading and pre-washing cargo tanks.

Annex II NLS cargoes are classified in one of four categories: A, B, C, or D. Category A is the most hazardous to the environment. Category A and other substances which tend to solidify in tanks must be pre-washed in port under the supervision of a Pre-wash Surveyor prior to departure from the off-loading terminal. Vessel discharges must be underwater when discharge at sea is allowed. Tanks which carry Category B and C NLS must be tested to ensure that after tank stripping only minimum amount of residues will remain. Reception facilities must be able to assist in cargo stripping operations by reducing back pressure during the final stages of off-loading.

Terminals and ports receiving oceangoing tankers, or any other oceangoing ships of 400 GT or more, carrying residues and mixtures containing oil, or receiving oceangoing ships carrying NLSs are required to provide adequate reception facilities for the waters generated. Coast Guard Captains of the Port issue a Certificate of Adequacy to terminals or ports to show that they are in compliance with Federal reception facility requirements. An oceangoing tanker or any other oceangoing ship of 400 GT or more required to retain oil or oily residues and mixtures on board and an oceangoing ship carrying a Category A, B or C NLS cargo or NLS residue in cargo tanks that are required to be pre-washed, may not enter any port or terminal unless the port or terminal holds a valid Certificate of Adequacy or unless the ship is entering under force majeure.

Annex V deals with the prevention of marine pollution by plastics and other garbage produced during vessel operations. These provisions apply to all recreational, fishing, un-inspected and inspected vessels, and foreign flag vessels on the navigable waters and all other waters subject to the jurisdiction of the United States, out to and including the Exclusive Economic Zone (200 miles).

Annex V prohibits the disposal of any and all plastic material from any vessel anywhere in the marine environment. Dunnage, lining and packing materials, which float, may be disposed of beyond 25 miles from the nearest land. Other garbage that will not float may be disposed beyond 12 miles of land, except that garbage, which can pass through a 25mm mesh screen (approximately 1 square inch), may be disposed of beyond 3 miles. Dishwater is not to be considered garbage within the meaning of Annex V when it is the liquid residue from the manual or automatic washing of dishes or cooking utensils. More restrictive disposal regimes apply in waters designated "Special Areas." This Annex requires terminals to provide reception facilities at ports and terminals to receive plastics and other garbage from visiting vessels.

The civil penalty for each violation of MARPOL 73/78 is not more than \$27,500. The criminal penalty for a person who knowingly violates the MARPOL Protocol, or the regulations (33 CFR 151, 155, 157, and 158) consists of a fine of not more than \$50,000 and/or imprisonment for not more than 5 years.

## **POLLUTION - OCEAN DUMPING**

The Marine Protection Research and Sanctuaries Act of 1972, as amended (33 USC 1401 et seq.) regulates the dumping of all material, except fish waste, into ocean waters. Radiological, chemical and biological warfare agents and other high level radioactive wastes are expressly banned from ocean disposal. The Army Corps of Engineers issues permits for the disposal of dredged spoils; the Environmental Protection Agency is authorized to issue permits for all other dumping activities. Surveillance and enforcement to prevent unlawful transportation of material for dumping or unlawful dumping under the Act has been assigned to the U.S. Coast Guard. The Act provides civil penalties of up to \$50,000 and criminal penalties of up to \$50,000 and/or one year imprisonment.



# CHAPTER IX

## LAW ENFORCEMENT

The Coast Guard has authority to make inquiries, examinations, inspections, searches, seizures, and arrests upon the high seas and waters over which the United States has jurisdiction, in order to enforce Federal Laws. To compel compliance, the Coast Guard may use all necessary force. A vessel underway, upon being hailed by a Coast Guard vessel or patrol boat, is required to heave to immediately, or maneuver in such a way as to permit the boarding officer to come aboard. Failure to stop to permit boarding may subject the operator or owner to a maximum penalty of \$5000. Forcibly resisting a Coast Guard boarding officer is a felony punishable up to 10 years in prison and a \$10,000 fine. A civil penalty of up to \$1000 per violation may be imposed by the Coast Guard for failure to comply with equipment requirements, numbering requirements, observing the Rules of the Road, or to report a boating accident.

## COAST GUARD BOARDING POLICY

An important Coast Guard mission is maritime law enforcement on the high seas and on waters subject to Federal laws. Some of the laws that the Coast Guard enforces include fisheries laws within the 200 nautical mile Exclusive Economic Zone, drug smuggling, illegal immigration, safety, and water pollution.

To enforce these laws on the water, the Coast Guard is empowered to board and inspect vessels. Many of the laws can only be successfully enforced by boarding a vessel while it is underway. About 70,000 boardings are conducted annually with nearly half finding some kind of noncompliance with regulations.

Random boardings can be a key to successful law enforcement in our Government's efforts to stem the flow of illegal drugs into the country. Often as a result of routine boardings, the Coast Guard discovers illegal drugs, and drug traffickers at sea are caught by surprise.

Boardings are not necessarily based on suspicion that a violation already exists aboard the vessel. Their purpose is to prevent and suppress violations. The courts have consistently upheld this authority. All Coast Guard officers and petty officers are Federal law enforcement officers, and they may board any United States vessel, virtually anywhere.

The Coast Guard boarding team is armed. Although most mariners that are boarded are engaged in legitimate recreational or commercial pursuits, a seemingly innocent pleasure boat boarding sometimes turns into a dangerous confrontation.

Drugs and criminals have been found in almost every type of vessel; from very sleek yachts to small freighters, and in fishing vessels of almost every description. The Coast Guard, as one of the five armed services, trains its personnel to understand the risks of their mission and to protect themselves. The Coast Guard follows a standard procedure before boarding. The boarding team contacts the vessel and provides an explanation of what is about to happen. Coast Guard personnel will always properly identify themselves, will always be in uniform, coveralls, or survival suits displaying Coast Guard insignia.

Once aboard the vessel, examination is usually limited to determining the vessel's status and checking for compliance with Federal civil law. If during inspection, a reasonable suspicion develops that the vessel has been engaged in criminal activity, the boarding officer may investigate further. If the vessel is subject to a customs inspection, the boarding officer may conduct a thorough search of the entire vessel.

Coast Guard boarding officers are trained to be courteous to the public. If there is full cooperation, the boarding will be over quickly, and with minimum disruption. Failure to cooperate or becoming hostile can lead to suspicion of illegal activity, and the check can become detailed and time consuming for everyone.

Coast Guard vessels will normally display the Coast Guard ensign. At night, the Coast Guard ensign will normally be illuminated. If possible, the red identification stripe on the bow of the Coast Guard cutter will also be illuminated. Even if the boarding is being done by a boat from a U.S. Navy vessel, that boat or the U.S. Navy vessel will fly the Coast Guard ensign.

Many law abiding citizens are uncomfortable in the presence of an armed boarding party, but the Coast Guard is depending on the public to be patient and cooperative during boardings, and to bear in mind that the Coast Guard is like any other armed police force. The Coast Guard also asks the public to report any suspicious activity of other boats.

The Coast Guard strives, when conducting a boarding, for minimum intrusion into the activities of law abiding individuals. Occasionally, the Coast Guard will receive a complaint that a boarding was conducted improperly. Any complaints of a boarding conducted contrary to the Coast Guard's policy will be investigated. Complaints should be directed to the Coast Guard District Commander at:

Commander (dre)  
Eighth Coast Guard District  
Hale Boggs Federal Building  
500 Poydras Street  
New Orleans, LA 70130-3396  
(504) 671-2245

## **CITIZENSHIP REQUIREMENTS FOR OPERATING ON U. S. DOCUMENTED VESSELS**

U.S. documented vessels may not be placed under the command of non-U.S. citizens. Violations render the certificate of documentation invalid and are owners are liable for fines of up to \$11,000.00 per day per violation. Operation of a vessel engaged in trade or fisheries without a valid document and trade endorsement subject the vessel to possible seizure and forfeiture.

## **FOREIGN FISHING ACTIVITIES OFF THE COAST OF THE UNITED STATES**

The area over which the United States exercises fishing management jurisdiction changed in March 1977. In accordance with the Fishery Conservation and Management Act of 1976, the United States now exercises exclusive fishery management authority over:

- 1) All species of fish, except tuna, within the fishery conservation zone. This zone extends seaward to 200 miles.
- 2) All anadromous species (salmon) which spawn in the United States throughout their migratory range beyond the fishery conservation zone, except within a foreign country's recognized fishery zone.
- 3) All United States' Continental Shelf fishery resources, even if beyond the fishery conservation zone. Such resources include American lobster, species of coral, crab, abalone, conch, clam, sponge, and others. The 200 mile fishing zone does not prohibit all foreign fishing. However, it does limit the nations and areas where foreign vessels may fish. It also limits the amount and type of fish that the foreign vessel may catch.

## **EXPANSION OF THE TERRITORIAL SEA OF THE UNITED STATES OF AMERICA**

On December 28, 1988, the President, by Presidential Proclamation, proclaimed the extension of the territorial sea of the United States of America, the Commonwealth of Puerto Rico, Guam, American Samoa, the United States Virgin Islands, the Commonwealth of the Northern Marianas, and other outlying areas over which the United States exercises sovereignty.

The territorial sea of the United States henceforth extends to twelve nautical miles from the baselines of the United States determined in accordance with international law.

In accordance with international law, as reflected in the applicable provisions of the 1982 United Nations Convention on the Law of the Sea, within the territorial sea of the United States, the ships of all countries enjoy the right of innocent passage and the ships and aircraft of all countries enjoy the right of transit passage through international straits.

Nothing in the proclamation:

(a) extends or otherwise alters existing federal or state law or any jurisdiction, rights, legal interests or obligations derived therefrom; in particular, the boundary between state waters and the Exclusive Economic Zone for the purposes of the Magnuson Fishery Conservation and Management Act does not change; or

(b) impairs the determination, in accordance with international law, of any maritime boundary of the United States with a foreign jurisdiction.

Official nautical charts for the coastal United States, which are published by the Department of Commerce, National Ocean Service, will, as revised, depict the new United States territorial sea boundary. The seaward boundary of the United States Exclusive Economic Zone does not change.

## **SMUGGLING**

Significant amounts of contraband, specifically narcotics, enter the United States via vessels. The most common drugs smuggled are marijuana, hashish, and cocaine. The Coast Guard aims to prevent drug traffic by interdicting drug-carrying vessels at sea. Mariners observing activity or having information that a vessel may be involved in narcotics trafficking are requested to contact the nearest Coast Guard unit or:

Commander (dre)  
Eighth Coast Guard District  
Hale Boggs Federal Building  
500 Poydras Street  
New Orleans, LA 70130-3396  
(504) 671-2245

Any report should include, if available: Name, homeport, flag displayed, date, time and position, estimated course and speed, description and color of vessel. An incomplete report is better than no report.

## **OPERATING A VESSEL WHILE INTOXICATED**

Federal Regulations went in effect in 1988 that provide for civil and/or criminal penalties for operating a vessel while intoxicated. The regulations pertain to both recreational and commercial vessels; however, the provisions are slightly different for the two categories.

### ***Recreational Vessels***

As applied to recreational vessels, "Operator" is defined as an individual who has an essential role in the operation of a vessel underway, including but not limited to navigation of the vessel or control of the vessels propulsion system. An individual is considered intoxicated when:

- 1) The individual is considered intoxicated with a blood alcohol concentration of .10% by weight or more in the blood.
- 2) The effect of the intoxicants consumed by the individual on the person's manner, disposition, speech, muscular movement, general appearance or behavior is apparent by observation. If the operator is intoxicated, the voyage may be terminated for unsafe condition and the operator subject to civil penalties up to \$1,000 or criminal penalties up to \$5,000 and/or one year in prison.

### ***Commercial Vessels***

The principal difference in the enforcement of these regulations for operators of commercial vessels are:

- 1) An individual is considered intoxicated with a blood alcohol concentration of .04% by weight or more in the blood.
- 2) The individual is a crew member (including a license individual), pilot, or watchstander not a regular member of the crew, of a vessel other than a recreational vessel.

## **MANDATORY DRUG TESTING IN THE MARINE WORKPLACE**

December 21, 1990, was the final phase-in date for pre-employment and periodic chemical drug testing for persons who hold licenses or Merchant Mariner's Documents. The requirement also applies to certain other persons working on commercial vessels even though they may not have a license or document. On that date, pre-employment drug screens must be passed before any offer of employment can be made. This requirement now applies to all marine employers regardless of the number of employees. Also, effective December 21, 1990, anyone applying for a license or a document, which requires a physical examination, must be tested for drugs as part of the physical or at about the same time the physical exam is performed. Alternatively, if the applicant has been subjected to a pre-employment drug screen within six months prior to the date of application, the applicant can submit proof of that drug screen and satisfy the requirement. For more information contact the Regional Exam Center in New Orleans or Houston. REC New Orleans: (504) 846-6190. REC Houston: (713) 948-3350/51.

## **HIJACKING DANGER**

The U.S. Coast Guard warns boaters of possible danger from hijacking and acts of piracy. While the incidence of known or suspected hijacking has been relatively small in the past few years, the possibility of hijacking exists. Most of the actual hijacking incidents have been carried out by persons who came aboard with the vessel operator's permission and knowledge.

Protection for vessels and crews on the high seas and in remote or out-of-the-way places is difficult to insure and is primarily dependent upon the alertness of vessel operators. However, certain preventative measures can assist in lessening hijacking possibilities. Vessel operators should know the crew, particularly the hired crew. Tagalong guests from the marina should be identified as well.

Insist on positive identification of U.S. citizens through the use of the social security card and a secondary identification, which has a picture or physical description of the person. Check the passport, entry visa, or alien registration of non- U.S. citizens. Before departure, personally deliver or mail the complete crew and passenger list to a relative or trusted friend along with a float plan and instructions to notify the U.S. Coast Guard if you fail to arrive at your destination after a reasonable time. Let all personnel aboard your vessel know about this precaution.

When departing on a foreign cruise from a U.S. Port, consider taking time to clear vessel for stowaways. When going to the assistance of anyone in apparent distress during the voyage, as any good sailor is expected to do, try to notify the nearest Coast Guard radio facility or any coastal radio station and describe the situation. While preparing to render assistance, be alert of any unusual situation and be wary when the apparently distressed person insists on boarding your vessel. In addition to providing the complete crew manifest, list on a Customs Form 4455 all firearms, high value personal property and portable vessel equipment. Retain a certified copy to save trouble in foreign ports and in clearing Customs on the return to the United States.

## **RIVER WATCH PROGRAM**

In response to the terrorist attacks within the United States there has been an increased public awareness and sense of community service. In response to this awareness the River Watch program was developed by the U.S. Coast Guard and the Louisiana Office of Emergency Preparedness. This program, in much the same manner as the Neighborhood Watch, is meant to inform, educate and enlist the assistance of all persons who may witness suspicious or illegal activities. All information reported will be handled confidentially. To report any suspicious or illegal activities call the **U. S. Coast Guard National Response Center at 1-800-424-8802** or the **Louisiana Homeland Security Office at 1-800-434-8007**. We are all responsible for the safety and security of our community.

# CHAPTER X

## CHARTS AND PUBLICATIONS AVAILABILITY PURCHASE AND ISSUE

The National Ocean Service prepares nautical charts for the waters of the United States. You may obtain nautical chart catalogs at no charge from your local chart dealer or from Distribution Division (N/ACC3), National Ocean Service, Riverdale, MD 20737-1199, telephone 1-800-638-8972. The catalogs show which charts are available by area and whether or not a particular chart includes LORAN-C lines. Symbols and abbreviations approved for use on all regular nautical charts published by the Defense Mapping Hydrographic/Topographic Center and the National Ocean Service are contained in the January 1990 edition of Chart No. 1, United States of America Nautical Chart Symbols and Abbreviations. The introduction to this publication includes a number of paragraphs on metric and fathom charts, soundings, drying heights, shorelines, landmarks, buoys, IALA Buoyage, heights, conversion scales, traffic separation schemes, and correction dates. Buoys and Beacons of the IALA Buoyage System Regions A and B are illustrated in the back of Chart No. 1, including light characteristics in full color.

Charts and related publications may be ordered from the Distribution Division (N/ACC3), National Ocean Service, Riverdale, MD 20737-1199, telephone 1-800-638-8972; counter sales: 6501 Lafayette Ave., Riverdale, MD, 20737 or from authorized sales agents. Orders mailed to Riverdale, Maryland must be accompanied with a check or money order payable to NOAA, Department of Commerce. Remittance from outside of the United States must be made in U.S. funds either with an International Money Order or with a check payable on a United States Bank.

Local telephone directories and Yellow Pages should be consulted for recently established chart agents. Maps and related publications for the Mississippi River System and the Tennessee-Tombigbee Waterway are published by the various District Engineers, U.S. Army Corps of Engineers.

## LOCAL NOTICE TO MARINERS

Local Notices to Mariners are issued by each Coast Guard District to disseminate important information affecting navigational safety within the district. They report changes to and discrepancies in aids to navigation, maintained by and under the authority of the Coast Guard, and other marine information such as new charts, channel depths, naval operations, regattas, dredging, chart corrections, drill rig movements, lock and waterway closures, wrecks, hazards to navigation, etc., which may affect the vessels and waterways within the area of each Coast Guard District.

Broadcast Notices to Mariners are used to disseminate marine information until it can be published in the Local Notice to Mariners. Broadcasts are repeated only until the information is published in the Local Notice to Mariners or until the information is no longer valid.

The Eighth Coast Guard District currently publishes (2) separate Local Notice to Mariners. The Gulf of Mexico edition covers an area extending from St. Marks, Florida, to the Texas/Mexico border, including the states of Texas, Louisiana, Mississippi, Alabama, and part of Florida, as well as the Mississippi River below mile 233.7. The Mississippi River System edition includes the Upper Mississippi River and its tributaries as well as the vast western river system. To be placed on the mailing list for either edition, write or phone:

Commander, (dpw)  
Eighth Coast Guard District  
Hale Boggs Federal Building  
500 Poydras Street, Room 1230  
New Orleans, Louisiana 70130-3310  
Phone: (504) 671-2327

## UNITED STATES COAST PILOT

The National Ocean Service Coast Pilot is a series of nine nautical books that cover a wide variety of information important to navigators of U.S. coastal and intracoastal waters and the waters of the Great Lakes. Most of this book information cannot be shown graphically on the standard nautical charts and is not readily available elsewhere. The subjects in the Coast Pilot include, but are not limited to, channel descriptions, anchorages, bridge and cable clearances, currents, tide and water levels, prominent features, pilotage, towage, weather, ice conditions, wharf descriptions, dangers, routes, traffic separation schemes, small-craft facilities, and Federal regulations applicable to navigation. The U.S. Coast Pilot may be purchased at local marine supply dealers where charts are purchased, or by contacting National Ocean Service in Riverdale, MD (301) 436-6990.

## WEEKLY NOTICE TO MARINERS

Weekly Notice to Mariners (worldwide coverage) are prepared jointly by the National Imagery and Mapping Agency, the U.S. Coast Guard, and the National Ocean Service, and are published weekly by the National Imagery and Mapping Agency. The Weekly Notice to Mariners advises mariners of important matters affecting navigational safety including new hydrographic discoveries, changes in channels and aids to navigation. Also included are corrections to Light Lists, Coast Pilots, and Sailing Directions. Foreign marine information is also included. This notice is intended for mariners and others who have a need for information related to oceangoing operations. Because it is intended for use by oceangoing vessels, many corrections that affect small craft navigation and waters are not included. Information concerning small craft is contained in the Coast Guard Local Notice to Mariners only. The Weekly Notice to Mariners may be obtained, free of charge, upon request to: National Ocean Service (NOS): phone: (800) 638-8972; FAX: (301) 436-6829; or mail: National Ocean Service/NOAA, Distribution Division N/ACC3, Riverdale, MD 20737-1199.

## LIGHT LIST

The Light List describes both federal and private aids to marine navigation maintained by or under the authority of the United States Government. It is compiled and published by the Coast Guard, in 7 volumes to provide mariners with more complete details regarding aids to navigation than can be found on charts. However, nautical charts must always be consulted as well. Additionally, the Light List elaborates on specifics pertaining to aids to navigation such as characteristics, light rhythms, types of marks and shapes, as well as information about bridge markings, RACONS, LORAN-C and the Global Positioning System (GPS).

### **The following Light List volumes are issued:**

- Atlantic Coast, Volume I, COMDTINST M16502.1, describing aids to navigation in United States waters from St. Croix River, Maine to Shrewsbury River, New Jersey.
  - Atlantic Coast, Volume II, COMDTINST M16502.2, describing aids to navigation in United States waters from Shrewsbury River, New Jersey to Little River, South Carolina.
  - Atlantic and Gulf Coasts, Volume III, COMDTINST M16502.3, describing aids to navigation in United States waters from Little River, South Carolina to Econfina River, Florida (includes Puerto Rico and U.S. Virgin Islands).
  - Gulf Coast Volume IV, COMDTINST M16502.4, describing aids to navigation in United States waters from Econfina River, Florida to Rio Grande, Texas.
  - Mississippi River System Volume V, COMDTINST M16502.5, describing aids to navigation on the Mississippi River and its navigable tributaries.
  - Pacific Coast and Pacific Islands, Volume VI, COMDTINST M16502.6, describing aids to navigation on the Pacific Coast and outlying Pacific Islands.
  - Great Lakes, Volume VII, COMDTINST M16502.7, describing aids to navigation on the Great Lakes and the St. Lawrence River above the St. Regis River.
- Coast Guard Light Lists are sold by the Superintendent of Documents, U.S. Government Printing Office (GPO) and can be ordered by phone: (202) 512-1800; FAX (202) 512-2250; or mail: Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Light Lists are also available at GPO Bookstores and from GPO Sales Agents.

# CHAPTER XI

## BRIDGE ADMINISTRATION

HALE BOGGS FEDERAL BLDG  
500 POYDRAS ST. ROOM 1313  
NEW ORLEANS, LA 70130-3310  
PHONE: (504) 671-2327

WESTERN RIVER OPERATIONS  
1222 SPRUCE ST.  
ST. LOUIS, MO 63103  
PHONE: (314) 539-3900

Coast Guard Bridge Administration oversees a program covering all bridges across navigable waters of United States.

It is responsible for the permitting of bridges, establishment of drawbridge operating regulations and alteration of unreasonably obstructive bridges, prescribing bridge navigation lighting, and authorizing temporary closures for bridge repairs.

Consistent with the National Environmental Policy Act and related laws, environmental considerations are now an integral and significant part of the permit process, along with the traditional navigational ones.

Operating regulations for drawbridges are formulated and administered in keeping with the needs of navigation while recognizing the needs of overland traffic, particularly in an urban area. A sustained activity is maintained in the determination and alteration of bridges considered unreasonably obstructive to navigation because of changes in the character of, or in the type and size of vessels using the waterway.

Vessels owners/operators are responsible for ensuring that their personnel who operate vessels are familiar with the regulations. Copies of Title 33, Code of Federal Regulations, Parts 1 to 199, in which the revised regulations appear in Part 117, may be obtained by contacting the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Your attention is invited specifically to Section 117.11 which prohibits signaling for bridge openings to pass appurtenances unessential to the operation of the vessel (antenna, outrigger, false stack, decorative mast, etc.) and to Sections 117.15 through 117.21 regarding signals for bridge openings and acknowledgment of signals by both the vessel operator and the bridgetender.

### LIST OF DRAWBRIDGES WITH SPECIAL OPERATING REGULATIONS

All drawbridges, except those authorized to operate under special regulations, are required to open promptly and fully for the passage of vessels after receipt of the prescribed signal of one prolonged blast (four to six seconds duration) followed by one short blast (one second duration) from a horn or whistle, or by radiotelephone contact. For vessels required to be passed through a draw during a scheduled closure period (such as an emergency aboard the vessel), the request for opening signal is five short blasts in rapid succession. If a draw cannot open immediately, or if the draw is open and must be closed immediately, the sound signal is five short blasts not more than 30 seconds after the requesting vessels signal. For radiotelephone contact, the working channel is 16 and the emergency channel is 18. Drawbridges are not required to monitor channel 18. However, no vessel owner or operator shall signal a drawbridge to open when the vessel can pass under the closed drawspan, nor for any nonstructural vessel appurtenance which is not essential to navigation or which is easily lowered or can be modified to be lowered. Appurtenances unessential to navigation include but are not limited to fishing outriggers, radio antennae, television antennae, false stacks, and masts purely for ornamental purposes.

Drawbridges within the Eighth Coast Guard District, which operate under special regulations, are published, by State, in Part 117 of Title 33 of the Code of Federal Regulations (CFR) which is available online at "[www.access.gpo.gov](http://www.access.gpo.gov)". Changes to the regulations are published in the Federal Register, the Eighth Coast Guard District Local Notice to Mariners, and updated annually in Part 117 of 33 CFR.

Drawbridges listed in 33 CFR Part 117 are required to have signs posted both upstream and downstream of the bridge which summarize the special regulation for the bridge. If advance notice is required for an opening, the signs must also state the name and telephone number to call. Names, addresses and telephone numbers of bridge owners or operators may be obtained by contacting the Bridge Administration Branch at (504) 589-2965 in New Orleans, LA, or (314) 539-3900 in St. Louis, MO. Bridge owners must accept collect calls for advance notice openings.



## APPROACH OF BASCULE BRIDGES

Mariners are advised to approach and transit all bascule bridges with caution. Navigation clearances for bascule bridges are measured between the inside tips of the bascule leaves when in the open position. Because bascule leaves protrude over the navigation channel when in the open position, unlimited clearances may not be available throughout the full width of the navigation span. Vessels with high freeboard should ensure adequate horizontal and vertical clearances are available.

## ALABAMA

### 117.101 Alabama River

- (a) The draw of the Burlington Northern Santa Fe railroad bridge, mile 105.3 at Coy, shall open on signal if at least 48 hours notice is given.
- (b) The draw of the Canadian National/Illinois Central railroad bridge, mile 277 near Montgomery, shall open on signal if at least 24 hours notice is given.
- (c) The draw of the US31 and 82 bridge, mile 278.2 near Montgomery, shall open on signal if at least 24 hours notice is given.
- (d) The draw of the CSX Transportation Railroad bridge, mile 293.3 near Montgomery, shall open on signal if at least 24 hours notice is given.

### 117.103 Bayou La Batre.

The draw of the S188 bridge, mile 2.3 at Bayou La Batre, shall open on signal; except that, the draw need not be opened from 8 p.m. to 4 a.m., daily and from 6:30 to 8:30 a.m. and 2:00 to 5:00 p.m. Monday through Friday except holidays.

### 117.105 Bayou Sara.

The draw of the CSX Transportation Railroad bridge, mile 0.1 near Saraland, shall open on signal; except that, from 6 p.m. to 10 a.m., the draw shall open on signal if at least eight hours notice is given. During periods of severe storms or hurricanes, from the time the National Weather Service sounds an "alert" for the area until the "all clear" is sounded, the draw shall open on signal.

### 117.107 Chattahoochee River.

The draw of the CSX Transportation Railroad bridge, mile 117.1 near Omaha, GA, shall open on signal if at least six hours notice is given.

### 117.109 Coosa River.

The draw of the CSX Transportation Railroad bridge, mile 175.0 at Gadsden, shall open on signal if at least six hours notice is given.

### 117.113 Tensaw River.

The draw of the CSX Transportation Railroad bridge, mile 15.0 at Hurricane, shall open on signal; except that, from 5 p.m. to 9 a.m., the draw shall open on signal if at least eight hours notice is given. During periods of severe storms or hurricanes, from the time the National Weather Service sounds an "alert" for the area until the "all clear" is sounded, the draw shall open on signal.

### 117.115 Three Mile Creek

- (a) The draw of the US43 bridge, mile 1.0 at Mobile need not be opened from 7 a.m. to 9 a.m. and from 4:30 p.m. to 6:30 p.m. daily. At all other times, the draw shall open on signal if at least 12 hours notice is given.
- (b) The draw of the Norfolk Southern Railway bridge, mile 1.1 at Mobile, shall open on signal if at least five days notice is given.

## FLORIDA

### 117.271 Blackwater River.

The draw of the CSX Transportation Railroad bridge, mile 2.8 at Milton, shall open on signal; except that, from 8 p.m. to 4 a.m., the draw shall open on signal if at least eight hours notice is given.

### 117.327 St. Marks River

The draw of the US98-S30 bridge, mile 9.0 at Newport, need not be opened for passage of vessels.

## GEORGIA

### 117.359 Chattahoochee River.

See 117.107, Chattahoochee River, listed under Alabama.

### 117.361 Flint River.

The draws of the CSX Transportation Railroad bridges, miles 28.0 and 28.7, both at Bainbridge, shall open on signal if at least 15 days notice is given.

## LOUISIANA

### 117.422 Amite River

- (a) The draw of the S22 bridge, mile 6.0 at Clio, shall open on signal if at least four hours notice is given.
- (b) The draws of the S16 bridge, mile 21.4 near French Settlement, and the S42 bridge, mile 32.0 at Port Vincent shall open on signal if at least 48 hours notice is given.

### 117.423 Atchafalaya River.

The draw of the KCS railroad bridge, mile 133.1 (mile 5.0 on NOS chart) above the mouth of the waterway at Simmesport, shall open on signal if at least three hours notice is given.

### 117.424 Belle River.

The draw of the S70 bridge, mile 23.8 (Landside Route) near Belle River, shall open on signal; except that, from 10 p.m. to 6 a.m., the draw shall open on signal if at least four hours notice is given. During the advance notice period, the draw shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

### 117.425 Black Bayou.

The Terrebonne Parish Policy Jury bridges, mile 7.5, 15.0, 18.7, and 22.5, between Gibson and Houma, shall open on signal if at least 24 hours notice is given. The draw of the U.S. 90 bridge, mile 7.0 at Gibson, need not be opened for passage of vessels.

### 117.427 Black River.

The draw of the US84 bridge, mile 41.0 at Jonesville, shall open on signal if at least one hour notice is given.

### 117.429 Boeuf Bayou.

The draw of the S307 bridge, mile 1.3 at Kraemer, shall open on signal; except that, from 9 p.m. to 5 a.m., the draw shall open on signal if at least 12 hours notice is given.

### 117.431 Boeuf River.

The draw of the S4 bridge, mile 32.3 near Mason, shall open on signal if at least 48 hours notice is given.

**117.431 Bonfouca Bayou.**

The draw of the S433 bridge, mile 7.0 at Slidell, shall operate as follows:

- (a) The draw need not open for passage of vessels from 7:00 a.m. to 8:00 a.m. and from 1:45 p.m. to 2:45 p.m., Monday through Friday except for Federal Holidays.
- (b) The draw need open only on the hour and half hour from 6:00 a.m. to 7:00 a.m. and from 3:00 p.m. to 6:00 p.m., Monday through Friday except for Federal Holidays.
- (c) The draw shall open on signal from 9:00 p.m. to 5:00 a.m. if at least 4 hours notice is given to the Louisiana Department of Transportation and Development Security Service at (504) 375-0100.
- (d) At all other times the draw shall open on signal.

**117.434 Caddo Lake.**

The draw of the Kansas City Southern railroad bridge, mile 26.4 near Mooringsport, shall open on signal if at least 24 hours notice is given.

**117.435 Carlin Bayou.**

The draw of the S14 bridge, mile 6.4 at Delcambre shall open on signal; except that, from 9 p.m. to 5 a.m. the draw shall open on signal if at least four hours notice is given. The draw shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

**117.436 Chef Menteur Pass.**

The draw of the U.S. Highway 90 bridge, mile 2.8, at Lake Catherine, shall open on signal except the from 5:30 a.m. to 7:30 a.m., Monday through Friday except Federal holidays, the draw need not open for the passage of vessels. The draw shall at any time for a vessel in distress.

**117.437 Colyell Bayou.**

The removable span of the Louisiana highway bridge, mile 1.0 near Port Vincent, shall be removed for the passage of vessels if at least 48 hours notice is given.

**117.438 Company Canal.**

- (a) The draw of the S1 bridge, mile 0.4 at Lockport, shall open on signal; except that, from 6 p.m. to 10 a.m., the draw shall open on signal if at least four hours notice is given. During the advance notice period, the draw shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.
- (b) The draw of the S24 bridge, mile 8.1 at Bourg, shall open on signal; except that, from 10 p.m. to 6 a.m., the draw shall open on signal if at least four hours notice is given. During the advance notice period, the draw shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

**117.439 Des Allemands Bayou.**

- (a) The draws of the S631 bridge, mile 13.9 at Des Allemands, shall open on signal if at least four hours notice is given.
- (b) The draw of the Burlington Northern Santa Fe Railroad bridge, mile 14.0, shall open on signal Monday through Friday from 7:00 a.m. to 3:00 p.m. At all other times the draw shall open on signal if at least four hours notice is given.

**117.441 D'Inde Bayou.**

The draw of the Union Pacific railroad bridge, mile 4.3, shall open on signal if at least 72 hours notice is given to the Defense Plant Corporation, Cities Service Refining Corporation Agent.

**117.443 Du Large Bayou.**

The draw of the Terrebonne Parish bridge, mile 23.2, near Theriot, shall open on signal; except that, from 9 p.m. to 5 a.m., the draw shall open on signal if at least 12 hours notice is given.

**117.444 Falgout Canal.**

The draw of the LA 315 bridge across Falgout Canal, mile 3.1, shall open on signal; except that from 15 August to 5 June, the draw need not open from 7 a.m. to 8 a.m. and from 3 p.m. to 4 p.m. Monday through Friday except holidays. The draw shall open on signal at any time for an emergency aboard a vessel.

**117.445 Franklin Canal.**

The draw of the Chatsworth bridge, mile 4.8, at Franklin, shall open on signal from 5 a.m. to 9 p.m. From October 1 through January 31 from 9 p.m. to 5 a.m., the draw shall open on signal if at least three hours notice is given. From February 1 through September 30 from 9 p.m. to 5 a.m., the draw shall open on signal if at least 12 hours notice is given.

**117.447 Grand Cabahanosse Bayou.**

The draw of the S70 bridge, mile 7.6 near Paincourtville, shall open on signal if at least 24 hours notice is given.

**117.449 Grosse Tete Bayou.**

- (a) The draw of the Union Pacific railroad bridge, mile 14.7 at Grosse Tete, need not be opened for the passage of vessels.
- (b) The removable span of the S377 bridge, mile 15.3 near Rosedale shall be removed for the passage of vessels if at least 48 hours notice is given.

**117.451 Gulf Intracoastal Waterway.**

- (a) The draw of the Lapalco Boulevard Bridge, Harvey Canal Route, mile 2.8 at Harvey, shall open on signal; except that, from 6:30 a.m. to 8:30 a.m. and from 3:45 p.m. to 5:45 p.m. Monday through Friday except holidays, the draw need not be opened for the passage of vessels.
- (b) The draw of the SR 23 bridge, Algiers Alternate Route, mile 3.8 at Belle Chasse, operates as follows:
  - (1) The draw shall open on signal; except that, from 6 a.m. until 8:30 a.m. and from 3:30 p.m. until 5:30 p.m. Monday through Friday, except Federal holidays, the draw need not be opened for the passage of vessels.
  - (2) On Saturday and Sunday of the last weekend in October, the draw need not open for the passage of vessels from 4 p.m. until 7 p.m.
- (c) The draw of the Bayou Dularge bridge, mile 59.9, at Houma, shall open on signal; except that, the draw need not be opened for the passage of vessels Monday through Friday except holidays from 6:45 a.m. to 8:30 a.m. and from 4:30 p.m. to 6:00 p.m.
- (d) The draw of the State Route 319 (Louisa) bridge across the Gulf Intracoastal Waterway, mile 134.0, near Cypremort, shall open on signal; except that from 15 August to 5 June, the draw need not be opened from 6:55 a.m. to 7:10 a.m. and from 3:50 p.m. to 4:05 p.m. Monday through Friday, except holidays.
- (e) The draw of the Louisiana highway bridge, mile 243.8 west of Harvey Canal Locks, shall open on signal when more than 50 feet vertical clearance is required, if at least four hours notice is given to the Louisiana Department of Highways, District Maintenance Engineer, at Lake Charles.

**117.453 Houma Canal.**

The draw of the S3197 bridge, mile 1.7 at Houma, shall open on signal if at least four hours notice is given.

**117.455 Houma Navigational Canal.**

The draw of the bridge across the Houma Navigational Canal at S661, mile 36.0 at Houma, shall open on signal; except that the draw need not be opened for the passage of vessels Monday through Friday except holidays from 7 a.m. to 8:30 a.m. and 4:30 p.m. to 6 p.m.

**117.457 Houston River.**

The draw of the Kansas City Southern Railroad bridge, mile 5.2 near Lake Charles shall open on signal if at least 24 hours notice is given.

**117.458 Inner Harbor Navigational Canal, New Orleans.**

- (a) The draw of the US90 (Danziger) bridge, mile 3.1, shall open on signal; except that, from 8:00 p.m. to 7:00 a.m., the draw shall open on signal if at least four hours notice is given, and the draw need not open from 7:00 a.m. to 8:30 a.m. and 5 p.m. to 6:30 p.m., Monday through Friday.
- (b) The draw of the Leon C. Simon Blvd. (Seabrook) bridge, mile 4.6, shall open on signal; except that, from 7:00 a.m. to 8:30 a.m. and 5 p.m. to 6:30 p.m., Monday through Friday, the draw need not be opened.

**117.459 Kelso Bayou.**

The draw of the S27 bridge, mile 0.7 at Hackberry, shall operate as follows:

- (a) From May 20, through October 31, the draw shall open on signal from 7 a.m. to 7 p.m. From 7 p.m. to 7 a.m., the draw shall open on signal if at least four hours notice is given.
- (b) From November 1 through December 22, the draw shall open on signal from 7 a.m. to 3 p.m. From 3 p.m. to 7 a.m., the draw shall open on signal if at least four hours notice is given.
- (c) From December 23 through May 19, the draw shall open on signal if at least 24 hours notice is given.

**117.460 La Carpe Bayou.**

The draw of the S661 bridge, mile 7.5, shall open on signal if at least four hours advance notice is given; except that, the draw need not be opened for passage of vessels Monday through Friday except holidays from 7 a.m. to 8:30 a.m. and 4:30 p.m. to 6 p.m.

**117.461 Lacassine Bayou.**

The draws of the S14 bridge, mile 17.0 and the Southern Pacific railroad bridge, mile 20.4, both near Hayes, shall open on signal if at least 24 hours notice is given.

**117.463 Lacombe Bayou.**

The draw of the US190 bridge, mile 6.8 at Lacombe shall open on signal if at least 48 hours notice is given.

**117.465 Lafourche Bayou.**

- (a) The draws of the SR1 bridge, mile 30.6 and the SR1 bridge, mile 33.9, both near Cutoff, shall open on signal; except that, from 2 p.m. to 3 p.m. and from 4:30 p.m. to 5:30 p.m. Monday through Friday except Federal holidays, the draws need not be opened for the passage of vessels.
- (b) The draws of the S3220 bridge, mile 49.2 near Lockport, and S655 bridge, mile 50.8 at Lockport, shall open on signal; except that, from 6 p.m. to 10 a.m. the draw shall open on signal if at least four hours notice is given. During the advance notice period, the draws shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.
- (c) The draw of the S364 bridge, mile 54.2 at Mathews, shall open on signal if at least four hours notice is given. During the advance notice period, the draws shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

- (d) The draws of the S3199 bridge, mile 58.2, and the Lafourche Parish bridge, mile 58.7, both at Raceland, shall open on signal if at least six hours notice is given.
- (e) The draws of the S649 bridge, mile 66.1, and the new S649 bridge, mile 66.6, shall open on signal if at least forty-eight hours notice is given.
- (f) The draws of the Burlington Northern Santa Fe Railroad bridge, mile 69.0 at Lafourche, and all bridges upstream of the Burlington Northern Santa Fe Railroad bridge need not be opened for the passage of vessels.

**117.467 Lake Pontchartrain.**

- (a) The south draw of the US11 bridge near New Orleans shall open on signal if at least 48 hours notice is given. In case of emergency, the draws shall open within 12 hours and shall be kept in condition for immediate operation until the emergency is over.
- (b) The draw of the Greater New Orleans Expressway Commission causeway, north bascule spans, shall open on signal if at least three hours notice is given.

**117.469 Liberty Bayou.**

The draw of the S433 bridge, mile 2.0 at Slidell, shall open on signal; except that, from 9 p.m. to 5 a.m., the draw shall open on signal if at least 12 hours advance notice is given.

**117.471 Little Black Bayou.**

The draw of the Southern railroad bridge, mile 1.3 at Southdown, need not be opened for the passage of vessels.

**117.473 Little River.**

The draw of the Louisiana and Arkansas railroad bridge, mile 12.1 at Archie, shall open on signal if at least 12 hours notice is given.

**117.475 Little (Petit) Caillou Bayou.**

- (a) The draws of the S58 bridge, mile 25.7 at Sarah, the Terrebonne Parish (Smithridge) bridge, mile 26.6 near Montegut, shall open on signal; except that, from 9 p.m. to 5 a.m., the draws shall open on signal if at least 12 hours notice is given.
- (b) The draws of the Terrebonne Parish (DuPlantis) bridge, mile 29.9 near Bourg, and the S24 bridge, mile 33.7 at Presquille, shall open on signal if at least four hours notice is given. The draws shall open on less than four hours notice for an emergency, and shall open on signal should a temporary surge in waterway traffic occur.

**117.477 Lower Atchafalaya River.**

The draw of the St. Mary Parish bridge, mile 26.8 at Patterson, shall open on signal from 5 a.m. to 9 p.m. From October 1 through January 31 from 9 p.m. to 5 a.m., the draw shall open on signal if at least three hours notice is given. From February 1 through September 30 from 9 p.m. to 5 a.m., the draw shall open on signal if at least 12 hours advance notice is given.

**117.478 Lower Grand River.**

- (a) The draw of the LA75 bridge, mile 38.4 (Alternate Route) at Bayou Sorrel, shall open on signal; except that, from about 15 August to about 5 June (the school year), the draw need not be opened from 6 a.m. to 7:30 a.m. and from 3 p.m. to 4:30 p.m., Monday through Friday except holidays. The draw shall open on signal at any time for an emergency aboard a vessel.
- (b) The draw of the LA77 bridge, mile 47.0 (Alternate Route) at Grosse Tete, shall open on signal; except that, from about 15 August to about 5 June (the school year), the draw need not be opened from 6 a.m. to 7:30 a.m. and from 2:30 p.m. to 4:30 p.m., Monday through Friday except holidays. The draw shall open on signal at any time for an emergency aboard a vessel.

- (c) The draw of the S997 bridge, mile 41.5 (Landside Route) at Pigeon, shall open on signal; except that, from 10 p.m. to 6 a.m., the draw shall open on signal if at least four hours notice is given. During the advance notice period, the draw shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

**117.479 Macon Bayou.**

The draw of the S4 bridge, mile 44.8 near Winnsboro, shall open on signal if at least 24 hours notice is given.

**117.480 Mermentau River.**

The draw of the S82 bridge, mile 7.1 at Grand Chenier, shall open on signal; except that, from 6 p.m. to 6 a.m., the draw shall open on signal if at least 4 hours notice is given. During the advance notice period, the draws shall open on less than 4 hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

**117.481 Milhomme Bayou.**

The draw of the St Martin Parish bridge, mile 12.0 (Landside Route) at Stephenville, shall open on signal; except that, from 10 p.m. to 6 a.m. the draw shall open on signal if at least two hours notice is given. During the advance notice period, the draw shall open on less than two hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

**117.482 Nezpique Bayou.**

The draw of the S97 bridge, mile 7.0 near Jennings, shall open on signal if at least 48 hours advance notice is given.

**117.483 Ouachita River.**

The draws of the S8 bridge, mile 57.5 at Harrisonburg, and the US165 bridge, mile 110.1 at Columbia, shall open on signal if at least one hours notice is given.

**117.484 Pass Manchac.**

The draw of the Canadian National/Illinois Central Railroad automated bridge, mile 6.7, at Manchac, operates as follows:

- (a) The draw is not constantly manned and the bridge will normally be maintained in the open position, providing 56 feet vertical clearance above mean high tide to the raised tip of the bascule span for one-half the channel, and unlimited vertical clearance for the other half.
- (b) Railroad track circuits will detect an approaching train and initiate bridge closing warning broadcasts over marine radio and over the Public Address (PA) system six (6) minutes in advance of the train's arrival. Navigation channel warning lights will be lit, and photoelectric (infrared) boat detectors will monitor the waterway beneath the bridge for the presence of vessels. The waterway approaches to the bridge will be monitored by closed circuit TV (CCTV) cameras.
- (c) Activation of the warning broadcasts also activates a marine radio monitor in the Mays Yard (New Orleans switch yard). The yardmaster will continuously monitor marine radio broadcasts on the normal and emergency marine radio channels throughout the warning period and at all times the bridge is closed. The yardmaster will communicate with waterway users via the marine radio, if necessary.
- (d) At the end of the warning period, if no vessels have been detected by the boat detectors, and no interruptions have been performed by the yardmaster based on his monitoring of the marine radio and the CCTV, the bridge lowering sequence will automatically proceed.
- (e) Upon passage of the train, the bridge will automatically open. Railroad track circuits will initiate the automatic bridge opening and closing sequences. (Estimated duration that the bridge will remain closed for passage of rail traffic is 10 to 12 minutes.) The bridge will also be manually operable from two locked trackside control locations (key releases) on the approach spans, one on each side of the movable span.

- (f) The yardmaster will be provided with a remote EMERGENCY STOP button which, if pressed, will stop the bridge operation, interrupt the lowering sequence, and immediately return the bridge to the open position. The yardmaster will utilize this control feature in the event a vessel operator issues an urgent radio call to keep the waterway open for immediate passage of the vessel.

**117.485 Patout Bayou.**

The draw of the S83 bridge, mile 0.4 near Weeks, shall open on signal if at least four hours notice is given.

**117.486 Pierre Pass.**

The draw of the S70 bridge, mile 1.0 at Pierre Part, shall open on signal; except that, from 10 p.m. to 6 a.m., the draw shall open on signal if at least four hours notice is given. During the advance notice period, the draws shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

**117.487 Plaquemine Bayou.**

- (a) The draw of the S3066 (Spur) bridge, mile 6.5 at Indian Village, shall open on signal if at least four hours advance notice is given.
- (b) The draws of the Union Pacific railroad bridge, mile 10.5 at Plaquemine, and the S1 bridge, mile 10.5 at Plaquemine need not be opened for the passage of vessels.

**117.488 Pearl River.**

- (a) The draw of the CSX Transportation railroad bridge, mile 1.0 near English Lookout, shall open on signal; except that, from 9 p.m. to 5 a.m., the draw shall open on signal if at least four hours notice is given.
- (b) The draw of the US90 highway bridge, mile 8.8 near Pearlington, shall open on signal; except that, from 7 p.m. to 7 a.m., the draw shall open on signal if at least four hours notice is given.

**117.489 Plaquemine Brule Bayou.**

- (a) The draw of the Union Pacific railroad bridge, mile 5.1 near Midland, shall open on signal if at least 24 hours advance notice is given.
- (b) The draw of the S91 bridge, mile 8.0 at Estherwood, shall open on signal from 5 a.m. to 9 p.m. if at least 4 hours advance notice is given. From 9 p.m. to 5 a.m., the draw shall open on signal if at least 12 hours notice is given.

**117.491 Red River.**

- (a) The draw of the Union Pacific Railroad bridge, mile 90.1, at Alexandria, shall open on signal if at least eight hours notice is given.
- (b) The draw of the US 165 (Jackson Sr.) bridge, mile 88.6, at Alexandria, shall open on signal if at least eight hours notice is given; except that, from 7 a.m. to 9 a.m. and from 4 p.m. to 6 p.m. the draw need not be opened Monday through Friday except holidays.
- (c) The draws of the bridges above mile 105.8 through mile 234.4 shall open on signal if at least 48 hours notice is given.
- (d) The draws of the bridges above mile 234.4 to mile 276 need not be opened for passage of vessels.
- (e) When a vessel, which has given notice, fails to arrive at the time specified in the notice, the drawtender shall remain on duty for up to two additional hours to open the draw if that vessel appears. After that time, a new notice of the appropriate length of time is required.

**117.493 Sabine River.**

- (a) The draw of the Union Pacific railroad bridge, mile 19.3 near Echo, shall open on signal if at least 24 hours advance notice is given.



- (b) The Kansas City Southern railroad bridge, mile 36.2 near Ruliff and the draw of the S12 bridge, mile 40.8 at Starks, need no be opened for passage of vessels.

**117.494 Schooner Bayou Canal.**

The draw of the S82 bridge, mile 4.0 from White Lake at Little Prairie Ridge, shall open on signal; except that, from 10 p.m. to 6 a.m., the draw shall open on signal if at least four hours notice is given. The draw shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

**117.495 Superior Oil Canal.**

The draw of the S82 bridge, mile 6.3 in Cameron Parish, shall open on signal if at least 8 hours notice is given. Public vessels of the United States and vessels in distress shall be passed as soon as possible.

**117.497 Stumpy Bayou.**

The removable span of the Louisiana highway bridge, mile 1.0 near Weeks Island, shall be removed for the passage of vessels if at least six days notice is given.

**117.499 Tante Phine Pass.**

The draw of the Tidewater Associated Oil Company bridge, mile 7.6 near Venice, shall open on 24 hours advance notice.

**117.500 Tchefuncta River.**

The draw of the State Route 22 bridge, mile 2.5 at Madisonville, shall open on signal; except that, from 5 a.m. to 8 p.m., the draw need open only on the hour and half-hour. The draw shall open on signal at any time for a vessel in distress or for an emergency aboard a vessel.

**117.501 Teche Bayou.**

- (a) The draws of the following bridges shall open on signal if at least four hours advance notice is given:
- (1) St. Mary Parish bridge, mile 3.9 at Calumet.
  - (2) St. Mary Parish bridge, mile 11.8 at Centerville.
  - (3) S3069 bridge, mile 16.3 at Franklin.
  - (4) S322 bridge, mile 17.2 at Franklin.
  - (5) S323 bridge, mile 22.3 at Oaklawn.
  - (6) St. Mary Parish bridge, mile 27.0 at Baldwin.
  - (7) S324 bridge, mile 32.5 at Charenton.
  - (8) S670 bridge, mile 37.0 at Adeline.
  - (9) St. Mary Parish bridge, mile 38.9 at Sorrel.
  - (10) S671 bridge, mile 41.8 at Jeanerette.
  - (11) S3182 bridge, mile 43.5 at Jeanerette.
  - (12) LSU Agri bridge, mile 46.5 near Jeanerette (notice required for opening from 7 a.m. to 5 p.m., Monday through Friday except holidays)
  - (13) S320 bridge, mile 48.7 at Oliver.
  - (14) S3195 bridge, mile 50.4 at New Iberia.
  - (15) S87 Spur bridge, mile 52.5 at New Iberia.
  - (16) S86 bridge, mile 53.0 at New Iberia.
  - (17) S3156 bridge, mile 53.3 at New Iberia.

- (18) S44 bridge, mile 56.7 at Morbihan.
- (19) Iberia Parish bridge, mile 58.0 at New Iberia.
- (20) Iberia Parish bridge, mile 60.7 at Vida.
- (21) S344 bridge, mile 62.5 at Loreauville.
- (22) S86 bridge, mile 69.0 at Daspit.
- (23) S92 bridge, mile 73.3 at St. Martinville.
- (b) The draws of the S96 bridge, mile 75.2 at St. Martinville, the St. John Road bridge, mile 77.7 at Levert, and the S350 bridge, mile 82.0 at Parks, shall open on signal if at least 24 hours advance notice is given.
- (c) The draws of the S31 bridge, mile 90.5 at Breaux Bridge, and the Union Pacific railroad bridge, mile 91.0 at Breaux Bridge, shall open on signal if at least 48 hours advance notice is given.
- (d) The draws of the bridges listed in ref. (a) shall open on signal if at least four hours notice for an emergency during the advance notice period, and shall open on signal should a temporary surge in waterway traffic occur.

**117.505 Tensas River.**

- (a) The draw of the Missouri Pacific railroad bridge, mile 27.2 at Clayton, shall open on signal from May 1 through December 31 during normal river stages if at least 12 hours notice is given to the Dispatcher, Missouri Pacific Railroad, Little Rock Arkansas. During High-water periods, the District Commander may require the bridge be constantly tended and the draw open on signal.
- (b) The draws of the S15 bridge, mile 27.3 at Clayton, and the S128 bridge, mile 61.0 at New Light, shall open on signal if at least 48 hours notice is given.

**117.505 Terrebonne Bayou.**

- (a) The draws of the S58 bridge, mile 22.2 at Montegut, and the S55 bridge, mile 27.3 at Klondyke, shall open on signal; except that from 9 p.m. to 5 a.m. the draw shall open on signal if at least four hours notice is given.
- (b) The draw of the S24 bridge, mile 31.3 at Presquille, need not be opened for the passage of vessels.
- (c) The draw of the S3087 bridge, mile 33.9 at Houma, shall open on signal; except that, from 5 p.m. to 9 a.m. the draw shall open signal if at least four hours advance notice is given.
- (d) The draw of the Daigleville bridge, mile 35.5 at Houma, shall open on signal; except that the draw need not open for passage of vessels Monday through Friday except holidays from 7 a.m. to 8:30 a.m. and 4:30 p.m. to 6 p.m. From 10 p.m. to 6 a.m. the draw shall open on signal if at least four hours notice is given.
- (e) During advance notice periods, the draws of the bridges listed in this section shall open on less than four hours notice for an emergency and shall open on signal should a temporary surge in waterway traffic occur.

**117.507 Tigre Bayou.**

The draw of the S330 bridge, mile 2.3 near Delcambre, shall open on signal if at least four hours notice is given. The draw shall open on less than four hours notice for an emergency and shall open on demand should a temporary surge in waterway traffic occur.

#### **117.509 Vermilion River.**

- (a) The draw of the S82 bridge, mile 22.4 at Perry, shall open on signal; except that, from 9 p.m. to 5 a.m. the draws shall open on signal if at least four days notice is given.
- (b) The draws of the following bridges shall open on signal; except that, from 6 p.m. to 10 a.m. the draws shall open on signal if at least four hours advance notice is given:
  - (1) S14 bridge, mile 25.4 at Abbeville.
  - (2) S14 By pass bridge, mile 26.0 at Abbeville.
  - (3) Vermilion Parish bridge, mile 34.2 near Milton.
  - (4) S92 bridge, mile 37.6 at Milton.
- (c) The draws of the following bridges shall open on signal if at least four hours advance notice is given:
  - (1) S733, mile 41.0 at Eloi Broussard.
  - (2) S3073 bridge, mile 44.9 at New Orleans.
  - (3) S182 bridge, mile 49.0 at Lafayette.
- (d) During the advance notice periods, the draws of the bridges listed in this section shall open on less than four hours notice for an emergency and shall open on signal should a temporary surge in waterway traffic occur.

#### **117.511 West Pearl River.**

- (a) The draw of the Norfolk Southern Railway bridge, mile 22.1 at Pearl River Station, shall open on signal if at least six hours advance notice is given.
- (b) The draw of the US90 bridge, mile 7.9 near Pearlington, shall open on signal if at least four hours advance notice is given.

## **MISSISSIPPI**

#### **117.675 Back Bay of Biloxi.**

- (a) The draw of the US 90 bridge, mile 0.4 between Biloxi and Ocean Springs shall open on signal; except that, from 6:30 a.m. to 7:05 a.m., 7:20 a.m. to 8:05 a.m., 4:00 p.m. to 4:45 p.m., and 4:45 p.m. to 5:30 p.m., Monday through Friday except holidays, the draw need not be open for the passage of vessels.
- (b) The draw of the I-110 bridge, mile 3.0 at Biloxi, shall open on signal if at least six hours notice is given.
- (c) The draw of the Popp's Ferry Road bridge, mile 8.0, at Biloxi, shall open on signal; except that, from 7:30 a.m. to 9 a.m. and from 4:30 p.m. to 6 p.m. Monday through Friday, except Federal holidays, the draw need not be opened for passage of vessels. The draw shall open at any time for a vessel in distress.

#### **117.677 Big Sunflower River.**

The draw of the Columbus and Greenville railroad bridge, mile 96.1 at Baird, shall open on signal if at least four hours notice is given.

#### **117.680 Industrial Seaway Canal.**

The draw of the Lorraine-Cowan Road Bridge across the Industrial Seaway Canal, mile 11.3, shall open on signal; except that, the draw need not be opened from 6:30 a.m. to 8:30 a.m. and from 4:30 p.m. to 6 p.m., Monday through Friday, except holidays.

**117.681 Old Fort Bayou.**

The draw of the bridge, mile 1.6 at Ocean Springs, shall open on signal; except that, from 9 p.m. to 5 a.m., the draw shall open on signal if at least eight hours notice is given to the Old Fort Bayou drawtender. During periods of storm or hurricane warnings issued by the National Weather Service, the draw shall open on signal at any time.

**117.682 Pascagoula River.**

The draw of the US90 bridge, mile 1.8 at Pascagoula, shall open on signal; except that, from 6:15 a.m. to 7:15 a.m., 7:25 a.m. to 8 a.m., and 3:30 p.m. to 4:45 p.m., Monday through Friday except Federal holidays, the draw need not be opened for the passage of vessels.

**117.683 Pearl River.**

See 117.488, Pearl River, listed under Louisiana.

**117.684 Portage Bayou.**

The draw of the Portage Bridge over Portage Bayou, mile 2.0, shall open on signal if at least two hours notice is given.

**117.685 Tchoutacabouffa River.**

The draws of the Cedar Lake Road Bridge over the Tchoutacabouffa River, mile 8.0, shall open on signal if at least twenty-four hours notice is given.

**117.686 Yazoo River.**

- (a) The draws of the Canadian National/Illinois Central railroad bridge, mile 16.7 at Redwood, and the Satartia highway (S433) bridge, mile 53.3 at Satartia, shall open on signal if at least two hours notice is given. When a vessel has given notice and fails to arrive within the two hour period specified, the drawtender shall remain on duty for two additional hours and open the draw if the requesting vessel appears. After this time, an additional two hour notice is required.
- (b) The draws of the bridges upstream from the Satartia highway (S433) bridge shall open on signal if at least four hours notice is given. When a vessel has given notice and fails to arrive within the four hour period specified, the drawtender shall remain on duty for two additional hours and open the draw if the requesting vessel appears. After this time, an additional four hour notice is required.

## **TEXAS**

**117.951 Arroyo Colorado River.**

The draw of the S106 highway bridge, mile 22.5 at Rio Hondo, shall open on signal if at least 12 hours notice is given.

**117.953 Brazos River (Diversion Channel).**

- (a) The draw of the S36 highway bridge, mile 4.4 at Freeport, shall open on signal if at least 12 hours notice is given.
- (b) The draw of the Union Pacific railroad bridge, mile 22.6 at Brazoria, need not be opened for the passage of vessels.

**117.955 Buffalo Bayou.**

- (a) The draw of the Houston Belt and Terminal bridge, mile 1.2 at Houston, and all drawbridges downstream of it shall open on signal if at least 24 hours notice is given.
- (b) The draws of the Union Pacific railroad bridge, mile 3.1 and the Houston Belt and Terminal railroad bridge, mile 4.3 need not be opened for the passage of vessels.

**117.957 Cedar Bayou.**

The draw of the Union Pacific railroad automated bridge, mile 7.0 at Baytown, operates as follows:

- (a) The draw shall be maintained at a vertical clearance of 81.4 feet above mean high water. Fixed green navigation lights shall be displayed in center of the draw.
- (b) When a train approaches the bridge, the navigation lights shall be changed from green to red, alternating flashing red lights turned on, and a horn sounded for six minutes. At the end of six minutes, the draw may be lowered and locked if the scanning equipment does not detect any object under the span. If the scanning equipment detects an obstruction, the draw shall be raised until the obstruction is cleared.
- (c) After a train has cleared the bridge, the draw shall be raised to 81.4 feet above mean high water, the flashing red lights stopped, and the navigation lights changed from red to green.

**117.959 Chocolate Bayou.**

The draw of the Union Pacific railroad bridge, mile 11.4 at Liverpool, need not be opened for the passage of vessels.

**117.963 Colorado River.**

The draw of the highway bridge, mile 10.7 at Wadsworth, need open on signal Monday through Friday only, and then only from 8 a.m. to 5 p.m. At least 48 hours notice is required.

**117.965 Cow Bayou.**

The draws of the Orange County highway bridge, mile 2.9 at West Orange, and the S87 bridge, mile 4.5 at Bay City, shall open on signal if at least six hours advance notice is given.

**117.967 Greens Bayou.**

The draw of the Port Terminal Railroad Association railroad bridge, mile 2.8 at Houston, shall open on signal if at least four hours notice is given. The draw shall open on signal for 3 hours thereafter for returning downbound vessels.

**117.968 Gulf Intracoastal Waterway.**

The draw of the Port Isabel bridge, mile 666.0, shall open on signal; except that, from 5 a.m. to 8 p.m. on weekdays only, excluding holidays, the draw need open only on the hour for pleasure craft. The draw shall open on signal at any time for commercial vessels, for a vessel in distress, or for an emergency aboard a vessel. When the draw is open for a commercial vessel, waiting pleasure craft shall be passed.

**117.969 Lavaca River.**

The draws of the Union Pacific railroad bridge, mile 11.2 and the FM616 highway bridge, mile 11.2, both at Vanderbilt, shall open on signal if at least 48 hours notice is given. In emergencies, the draws shall open as soon as possible.

**117.971 Neches River.**

The draw of the Burlington Northern Santa Fe railroad bridge, mile 53.9 at Evadale, need not be opened for the passage of vessels.

**117.975 Old Brazos River.**

The draw of the Union Pacific railroad bridge, mile 4.4 at Freeport shall be maintained in the fully open position, except for the crossing of trains or for maintenance.

**117.977 Pelican Island Causeway, Galveston Channel.**

The draw of the Pelican Island Causeway bridge, mile 356.1 across Galveston Channel at Galveston, shall open on signal; except that, from 7 a.m. to 8:30 a.m., 12 noon to 1 p.m., and 4:15 p.m. to 5:15 p.m. Monday through Friday except Federal holidays, the draw need not be opened for the passage of vessels. Public vessels of the United States and vessels in distress shall be passed at any time.

**117.979 Sabine Lake.**

The draw of the S82 bridge, mile 10.0 at Port Arthur, shall open on signal; except that, from 9 p.m. to 5 a.m., the draw shall open on signal if at least 6 hours notice is given to the Maintenance Construction Supervisor or the Maintenance Foreman at Port Arthur.

**117.981 Sabine River.**

See §117.493 Sabine River, listed under Louisiana

**117.983 Sabine River (Old Channel) behind Orange Harbor Island.**

The draw of the highway bridge, mile 9.5 at Orange, need not be opened for the passage of vessels.

**117.984 San Bernard River.**

The draw of the Union Pacific railroad bridge, mile 20.7 near Brazoria, shall open on signal; except that, from 10 a.m. to 2 p.m. and 10 p.m. to 2 a.m., the draw shall open on signal if at least three hours notice is given.

**117.987 Taylor Bayou.**

The draws of the Union Pacific railroad bridge, mile 2.0, and the S73 bridge, mile 10.2, both at West Port Arthur, need not be opened for the passage of vessels.

**117.989 Trinity River.**

The draws of the Union Pacific railroad bridges, mile 41.4 at Liberty, mile 54.8 at Kenefick, mile 117.3 at Goodrich, mile 181.8 at Riverside, and the Burlington Northern Santa Fe railroad bridge, mile 96.2 at Romayor, need not be opened for the passage of vessels.

## **APPROACH OF BASCULE BRIDGES**

Mariners are advised to approach and transit all bascule bridges with caution. Navigation clearances for bascule bridges are measured between the inside tips of the bascule leaves when in the open position. Because bascule leaves protrude over the navigation channel when in the open position, unlimited clearances may not be available throughout the full width of the navigation span. Vessels with high freeboard should ensure adequate horizontal and vertical clearances are available.

Filename: 2007SPECIAL NOTICE CORRECTED.doc  
Directory: C:\TEMP\IE4Cache\OLK34  
Template: U:\Templates\Normal.dot  
Title: EIGHTH COAST GUARD DISTRICT  
Subject:  
Author: SCaskey  
Keywords:  
Comments:  
Creation Date: 1/8/1999 1:14:00 PM  
Change Number: 182  
Last Saved On: 1/9/2007 1:52:00 PM  
Last Saved By: SRBrooks  
Total Editing Time: 1,763 Minutes  
Last Printed On: 1/10/2007 6:54:00 AM  
As of Last Complete Printing  
Number of Pages: 78  
Number of Words: 36,824 (approx.)  
Number of Characters: 188,176 (approx.)