

Table of Contents

1. Summary
2. Longitudinal acceptance
3. Transverse emittance dilution during injection
4. Painting study
5. AC chromaticity
6. DC chromaticity
7. Acceptance decrease due to orbit bumps and doglegs

1. Summary

- Longitudinal acceptance of the Booster:
 - Two different measurements (one by varying the linac beam energy, another by varying RPOS) give similar result: $\Delta p/p = \pm 0.15-0.2\%$
- Transverse emittance dilution during injection:
 - The first 50-turn IPM data shows a fast dilution during the 10-turn injection. After that the dilution slows down.
 - This dilution is intensity dependent.
 - The results agree with space charge simulation using the code ORBIT.
 - Lower linac current and longer pulse (while keeping the total injected beam intensity a constant) seem to reduce the dilution in the first 50 turns. (But this gain could be washed away in 200 turns according to simulation.)
- Injection painting:
 - Painting by using the falling side of the orbit bump pulse seems to reduce the dilution. But this result is inconclusive.
- AC chromaticity:
 - Chromaticity throughout the cycle was measured with the normal sextupole setting.
 - The vertical chromaticity in the early stage of the cycle is measured positive. This causes concerns


about possible head-tail instability. (It will be adjusted in the follow-up study.)

- DC chromaticity:
 - It was measured at 400 MeV for nine different sextupole settings.
 - The data were used to find the unknown body sextupoles of the main magnets. The results:
 $sd = -0.0454, sf = -0.003$
 - These two parameters are now included in the MAD lattice model.


- Acceptance decrease due to orbit bumps and doglegs:
 - There is a good pattern match between the MAD prediction and measurement on the changes of tune and dispersion due to edge focusing of the orbit bumps and doglegs at 400 MeV.
 - This effect leads to about a factor of two reduction in the machine acceptance at injection.
 - Investigations of possible corrections are under way.

2. Longitudinal Acceptance Measurement


Linac beam energy calibration (1 cm = 1 MeV)



Linac beam pulse (green trace)



Measured momentum acceptance




Notes:


1. The 400 MeV line was not retuned when the linac beam energy was varied. So the result is a combination of the acceptance of the 400 MeV line and that of the Booster.
2. A separate measurement by varying RPOS gives the Booster acceptance in the range of ± 0.15 - 0.2% , consistent with this result. (see the dc chromaticity measurement)

3. Transverse Emittance Dilution during First 50 Turns


ORBIT simulation:
different bunch intensity, same number of injection turns (11)




ORBIT simulation:
emittance histogram at 12th turn, with and without space charge




Measurement at 43 mA, 10 turns




Measurement at 20 mA, 10 turns




ORBIT simulation:
same bunch intensity, different number of injection turns
(tracking 50 turns)




Measurement at 43 mA, 6 turns



Measurement at 20 mA, 12 turns




ORBIT simulation:
same bunch intensity, different number of injection turns
(tracking 200 turns)




4. Painting Study:

Painting study: injection timing




Measurement at 43 mA, 12 turns, with painting




5. AC Chromaticity Measurement

Chromaticity sextupole setting (normal operation)




Beam (2-turn), pinger and Roff setting




Note: The measurement was done at four different Roff values: 0, +2 mm, -2 mm, -4 mm. In this plot, Roff = 0.


Dp/p for Roff = 0 mm




Dp/p for Roff = +2 mm





Dp/p for Roff = -2 mm




Dp/p for Roff = -4 mm





6. DC Chromaticity Measurement





Booster Chromaticity Measurement

Jan 30 2003



R. Tomlin, W. Chou, F. Ostiguy

Note: VGOOD and HGOOD are correlation coefficients for the linear regression



RPOS	SEXTL	SEXTSDP/P	NUH	NUV	HCHROMA	HGOOD	VCHROMA	VGOOD	
[mm]	[A]	[A]							
0	0	0	0.0022	0.6657	0.83				
1	0	0	0.0015	0.681	0.824				
2	0	0	0.0008	0.697	0.817				
3	0	0	0	0.715	0.809				
4	0	0	-0.0008	0.736	0.797				
						-23.302202	0.99878	10.834517	0.98793





RPOS	SEXTL	SEXTSDP/P	NUH	NUV	HCHROMA	HGOOD	VCHROMA	VGOOD	
[mm]	[A]	[A]							
0	10	10	0.0022	0.68	0.828				
1	10	10	0.0015	0.689	0.824				
2	10	10	0.0008	0.7	0.819				
3	10	10	0.0001	0.707	0.812				
4	10	10	-0.0006	0.717	0.807				
						-13.142857	0.9967	7.7142857	0.99184





RPOS	SEXTL	SEXTSDP/P	NUH	NUV	HCHROMA	HGOOD	VCHROMA	VGOOD	
[mm]	[A]	[A]							
0	-10	-10	0.0021	0.644	0.836				
1	-10	-10	0.0015	0.676	0.827				
2	-10	-10	0.0008	0.7	0.817				
3	-10	-10	-0.0001	0.727	0.805				
4	-10	-10	-0.0013	0.768	0.791				
						-35.236111	0.99106	13.236111	0.99731





RPOS	SEXTL	SEXTSDP/P	NUH	NUV	HCHROMA	HGOOD	VCHROMA	VGOOD	
[mm]	[A]	[A]							
0	0	-10	0.0022	0.651	0.834				
1	0	-10	0.00155	0.672	0.827				
2	0	-10	0.0008	0.7	0.819				
3	0	-10	-0.00005	0.725	0.809				
4	0	-10	-0.0015	0.762	0.791				
						-30.167966	0.99368	11.625675	0.99869





RPOS	SEXTL	SEXTSDP/P	NUH	NUV	HCHROMA	HGOOD	VCHROMA	VGOOD	
[mm]	[A]	[A]							
0	0	10	0.00215	0.682	0.83				
1	0	10	0.00145	0.69	0.824				
2	0	10	0.001	0.7	0.817				
3	0	10	0.00007	0.709	0.811				
4	0	10							
						-13.341456	0.97749	9.367008	0.97485





RPOS	SEXTL	SEXTSDP/P	NUH	NUV	HCHROMA	HGOOD	VCHROMA	VGOOD	
[mm]	[A]	[A]							
0	-10	0	0.0021	0.666	0.834				
1	-10	0	0.00145	0.684	0.824				
2	-10	0	0.00077	0.7	0.817				
3	-10	0	-0.00002	0.717	0.807				
4	-10	0	-0.0009	0.738	0.795				
						-23.651808	0.99835	12.721725	0.99751





RPOS	SEXTL	SEXTSDP/P	NUH	NUV	HCHROMA	HGOOD	VCHROMA	VGOOD	
[mm]	[A]	[A]							
0	10	0	0.0022	0.664	0.832				
1	10	0	0.00155	0.68	0.827				
3	10	0	0.00015	0.713	0.812				
4	10	0	-0.00075	0.733	0.8				
2	10	0		0.697	0.819				
						-23.40152	0.9997	10.873174	0.99276



RPOS	SEXTL	SEXTSDP/P	NUH	NUV	HCHROMA	HGOOD	VCHROMA	VGOOD
[mm]	[A]	[A]						
0	10	-10	0.0023	0.651	0.834			
1	10	-10	0.0016	0.67	0.828			
2	10	-10	0.00087	0.695	0.818			
3	10	-10	0.0001	0.72	0.811			
4	10	-10	-0.0001	0.76	0.803			
Improved by removing last point ----->					-40.53509	0.91465	12.212976	0.97002
					-31.674217	0.99794	10.777903	0.99193



RPOS	SEXTL	SEXTSDP/P	NUH	NUV	HCHROMA	HGOOD	VCHROMA	VGOOD
[mm]	[A]	[A]						
0	-10	10	0.0021	0.682	0.83			
1	-10	10	0.0014	0.692	0.823			
2	-10	10	0.0007	0.702	0.814			
3	-10	10	-0.00005	0.711	0.807			
4	-10	10	-0.0008	0.72	0.8			
					-13.092431	0.99788	10.473564	0.99651



7. Acceptance Decrease due to Orbit Bumps and Doglegs

$$A = \{\beta_{\max} \times \varepsilon_N / \beta\gamma\}^{-1/2} + D_{\max} \times \Delta p/p + \text{C.O.D.}$$

Good field region (horizontal): ± 1 inch (TM-405)

At injection (400 MeV):

$$\beta\gamma = 1.0$$

$$\Delta p/p = \pm 0.13\% \text{ (measured)}$$

$$\text{C.O.D.} = 2 \text{ mm (optimal)}$$

Without orbit bumps and doglegs:

$$\beta(x)_{\max} = 33.7 \text{ m}, D_{\max} = 3.19 \text{ m}, \beta(y)_{\max} = 20.5 \text{ m}$$

Max allowable beam emittance: $\varepsilon_N(x) = 11 \pi$ mm-mrad

With orbit bumps and doglegs:

$$\beta(x)_{\max} = 46.1 \text{ m}, D_{\max} = 6.13 \text{ m}, \beta(y)_{\max} = 27.0 \text{ m}$$

Max allowable beam emittance: $\varepsilon_N(x) = 5.2 \pi$ mm-mrad

→ a factor of 2 reduction in acceptance due to large β and D!