University of California

Los Angeles

Phi Meson Production in Au+Au Collisions at the Relativistic Heavy Ion Collider

A dissertation submitted in partial satisfaction

of the requirements for the degree

Doctor of Philosophy in Physics

by

Eugene Toyonari Yamamoto

2001

The dissertation of Eugene Toyonari Yamamoto is approved.

Nu Xu

An Yin

Huan Z. Huang, Committee Co-chair

Charles A. Whitten Jr., Committee Co-chair

University of California, Los Angeles

2001

To my family…

who—along with the love and support they provided—

made sure I finished what I started.

Table of Contents

List of Figures

List of Tables

Vita

24 July, 1975	Born, Honolulu, Hawaii, USA.
1997	B.S. Applied Physics Columbia University New York, NY
1997 – 1998	Teaching Assistant Department of Physics University of California - Los Angeles
1998	M.S. Physics University of California - Los Angeles Los Angeles, CA
1998 – 2001	Graduate Research Assistant Intermediate Energy Group University of California - Los Angeles

Publications and Presentations

K.H. Ackermann *et al.*
Hardware Controls for the STAR Experiment at RHIC.
IEEE Trans. Nucl. Sci. **47**:210, 2000.

K.H. Ackermann *et al.*
The STAR Time Projection Chamber.
Nucl. Phys. **A661**:681, 2000.

K.H. Ackermann *et al.*
Elliptic Flow in Au+Au Collisions at $\sqrt{s_{_{NN}}} = 130$ GeV.
Phys. Rev. Lett., **86**:402, 2001.

C. Adler *et al.*
Multiplicity distribution of negatively charged hadrons in Au+Au collisions at $\sqrt{s_{NN}} = 130$ GeV .
Accepted by *Phys. Rev. Lett.* 16 July, 2001.

C. Adler *et al.*
Pion Interferometry of $\sqrt{s_{NN}} = 130$ GeV Au+Au Collisions at RHIC.
Accepted by *Phys. Rev. Lett.* 11 July, 2001.

C. Adler *et al.*
Midrapidity Antiproton-to-Proton Ratio in Au+Au Collisions at $\sqrt{s_{NN}} = 130$ GeV.
Phys. Rev. Lett. **86**:4778, 2001.

E. Yamamoto
Measuring Strangeness Production in Heavy Ion Collisions using the STAR TPC.
Proceedings of the Lake Louise Winter Institute, 2000.

E. Yamamoto
Performance of the STAR TPC using Au+Au Collisions at RHIC.
Proceedings of the American Physical Society, 2000.

Abstract of the Dissertation

Phi Meson Production in Au+Au Collisions at the Relativistic Heavy Ion Collider

by

Eugene Toyonari Yamamoto

Doctor of Philosophy in Physics

University of California, Los Angeles, 2001

Professor Charles A. Whitten Jr., Co-chair

Professor Huan Z. Huang, Co-chair

Results from the first measurement of mid-rapidity ϕ vector meson production in $Au + Au$ collisions at RHIC ($\sqrt{s_{NN}} = 130$ GeV) are described. Using the STAR detector, ϕ mesons were measured from the $\phi \rightarrow K^+K^-$ decay channel. For the 11% most central collisions, the slope parameter from an exponential fit to the transverse mass distribution is $T = 379 \pm 51$ (stat) $\pm$ 45 (syst) MeV, the yield $dN/dy = 5.73 \pm 0.37$ (stat) $\pm$ 0.57 (syst) per event and the ratios N_ϕ/N_{h^-} and N_ϕ/N_{K^-} are found to be 0.021 ± 0.001 (stat) $\pm$ 0.004 (syst) and 0.14 ± 0.01 (stat) $\pm$ 0.03 (syst). Within the statistics available, the mid-rapidity ratios, N_ϕ/N_{h^-} and N_ϕ/N_{K^-}, and the slope parameter for the ϕ meson do not change for the selected centrality bins. The slope parameter increases in heavy ion collisions as a function of $\sqrt{s_{NN}}$ from the BNL AGS to CERN SPS to RHIC. Comparisons of the ϕ meson slope parameter to the slope parameters for the π, K, and $\bar{p}$ measured at STAR indicate that the ϕ meson deviates from a systematic trend of a mass dependence of the slope parameter, suggesting that the ϕ meson may not interact as strongly as anti-protons during a collective expansion of the collision system.

The production of ϕ mesons relative to negatively charged hadrons (N_ϕ/N_{h^-}) in nucleus-nucleus collisions indicates an overall increase in strange and anti-strange quark production from $\sqrt{s_{NN}} = 4.9$ GeV to $\sqrt{s_{NN}} = 130$ GeV. When comparing the N_ϕ/N_{K^-} ratio in $p+p$, $p+\bar{p}$, $Pb+Pb$ and $Au+Au$ collisions, we find that the ratio is independent of both system size and energy from the AGS to the Tevatron. This result suggests some universal relationship between the mechanisms responsible for ϕ and K^- meson production.

CHAPTER 1

Introduction

The motivation for studying relativistic heavy ion collisions is to understand the *Equation of State* of nuclear matter. The goal of relativistic heavy ion physics is to understand Quantum Chromodynamics (QCD) at extreme temperatures and energy over large volumes and to create a Quark-Gluon Plasma (QGP) [BGS98, Wil00a, Wil00b] (Figure 1.1). Under such extraordinary conditions, it is believed that the symmetries of QCD will reveal themselves: color will be deconfined and chiral symmetry will be restored. The environment created by heavy ion collisions is currently the only means in the laboratory to study QCD in the macroscopic limit and to observe a possible phase transition.

As with all non-Abelian gauge theories [PS95], QCD exhibits asymptotic freedom: the strong coupling constant, α_s, becomes small at large momentum transfers and short distances. According to Lattice QCD, when the vacuum temperature exceeds ~150 MeV, the structured QCD vacuum melts, hadrons dissociate and fuse, and a macroscopic space-time region is formed, filled with quarks and gluons which cannot be associated with individual hadrons. This region of dissociated quarks and gluons is commonly referred to as the Quark-Gluon Plasma. A QGP is believed to have existed in the early universe about one micro-second after the Big Bang. After that, the couplings between quarks and gluons favored the formation of color neutral bound states, and the universe transitioned to hadronic matter.



Figure 1.1: QCD phase diagram. The major features of the QCD phases possibly accessible in nature and heavy ion collisions are shown.

Since the mid 1980's, scientists have studied heavy ion collisions with the hope of observing deconfinement and chiral symmetry restoration. Results from the Alternating Gradient Synchrotron (AGS) at Brookhaven and the CERN SPS proved that a direct observation of the predicted QCD transition through the haze created by hadronic interactions is difficult. The final products at AGS energies proved to be dominated by final state hadronic interactions, with similar dynamics at the SPS.

Scientists working at Brookhaven National Laboratories are currently studying heavy ion collisions using the Relativistic Heavy Ion Collider (RHIC). With center of mass collision energies that are 10 times greater than the previous energies studied in heavy ion collisions, we may finally observe the predicted QCD phase transition. RHIC, and its associated experiments, including the Solenoidal Tracker at RHIC (STAR), offer the opportunity to study QCD in a controlled environment. With RHIC we can systematically measure the macroscopic properties of strongly interacting matter and the predicted transition back to normal matter. RHIC, with its nucleus-nucleus collisions at unprecedented high energy density and temperature, will provide a unique opportunity to better understand non-perturbative QCD and the conditions prevalent in the early universe.

CHAPTER 2

Physics

2.1 QCD



Figure 2.1: Differential cross sections for the observation of a single jet of pseudo-rapidity $\eta = 0$ as a function of the transverse momentum of the jet. The lines through the data are next-to-leading order (NLO) QCD curves for 630 GeV and 1800 GeV $p + \bar{p}$ collisions. Figure taken from the Particle Data Book [GG00].

In some ways, QCD is a mature, well established subject. Its principles are precisely defined and have been extensively confirmed by experiment (Figure 2.1). QCD specifies unambiguous algorithms that supply answers to any physically meaningful question within its realm, namely the strong interaction. The foundations of QCD are rooted in concepts of symmetry and local quantum field theory, which lead uniquely to its equations. One cannot revise the equations without undermining these concepts.

QCD is enigmatic: while the equations of QCD are relatively simple and mathematically sound, they seem at first to have nothing to do with reality. QCD refers exclusively to particles (quarks and gluons) that are not directly observed. More profoundly, the equations of QCD exhibit a host of symmetries that are not apparent in our world. It has been found that these various symmetries are hidden: color is confined, scale invariance and axial baryon number are anomalous, and chiral symmetry is broken. It is bewitching how a theory that superficially appears too good for this world actually describes it accurately. *Vis-a-vis*, it is aesthetically pleasing to realize that the world is simpler and more beautiful than it first appears.

To say that QCD describes reality well is a gross understatement. QCD describes processes extremely well, so much so that people have calculated QCD corrections to other processes. Mature, however, does not necessarily mean dead. The peculiarities of QCD, namely that its fundamental entities and symmetries are well hidden in ordinary matter, lends itself to the discussion of its behavior in extreme conditions. Quarks, gluons, and the various symmetries of QCD will, in the right circumstances, reveal themselves.

The behavior of QCD at high temperatures is intrinsically interesting. The fundamental theoretical result of the asymptotically high temperature QCD phase is that it becomes quasi-free: one can now describe the major features of this phase by modeling it as a plasma of weakly interacting quarks and gluons. By answering the question, "What happens to empty space if we add more and more heat?", we will have an understanding of the earliest moments after the Big

Bang, when the matter content of the universe was most likely dominated by a quark-gluon plasma.

2.2 Strangeness Production

The production of strange (s) and anti-strange ($\bar{s}$) quarks was proposed by Rafelski [Raf82] as a probe to study the QCD phase transition.

$$\pi + N \rightarrow \Lambda + K \qquad E_{threshold} \simeq 530 \text{ MeV} \tag{2.1}$$

Hadronic scenarios for strangeness production involve relatively high energy thresholds (Equation 2.1). A significant enhancement of strangeness production is predicted if a phase transition to a QGP occurs. Since the temperature at which the QCD transition occurs is very close to the strange quark current mass of 150 MeV, $s\bar{s}$ pairs could form copiously through gluon fusion (Equation 2.2) [BGS98] in a gluon rich QGP state.

$$g + g \rightarrow s + \bar{s} \qquad E_{threshold} \simeq 2m_s \simeq 300 \text{ MeV} \tag{2.2}$$

If we compare the threshold energy for strangeness production in a QGP via gluon fusion (Equation 2.2) to the threshold energy in a hadronic scenario (Equation 2.1), we would expect to see more $s\bar{s}$ pairs produced in a QGP. Quantitative theoretical calculations by Koch, Müller and Rafelski [Raf82, KMR86] support the conclusion of strangeness enhancement in a QGP when compared to a hadronic scenario.

Experimental evidence from both the BNL AGS and CERN SPS accelerators have reported large increases in relative strange particle yields when compared to non-strange hadrons in central light (Si, S) [Abb90, Ahl99, Alb94, Ant99], and heavy ion (Au, Pb) [Ahl98, Ahm96, And99, Bor97, Mar99] collisions when compared to $p+p$ collisions. We nevertheless cannot claim a true understanding of the physics of strangeness enhancement due to the complexity of hadronic interactions in $A+A$ collisions. The difficulty of interpreting the enhancement in $A+A$ data has prompted the use of $p+A$ collisions to study this problem further.

The simpler final state in $p+A$ collisions allows the production rate for strange particles to be directly connected with the scattering dynamics of the incoming proton. Recent results from $p+A$ collisions at the AGS have shown that strange baryon production is enhanced when compared to $p+p$ collisions. The E910 experiment [Che00] has studied strangeness enhancement in $p+A$ collisions as a function of centrality, where centrality in $p+A$ collisions is correlated to the number of "grey" tracks from a collision. Their results suggest that an increase in strangeness production is present over a simple number of participants (N_{part}) scaling of $p+p$ data. The qualitative implications for using a simple N_{part} scaling are clear: to establish an anomalous strangeness enhancement in $A+A$ collisions that may be attributed to the formation of a deconfined state of quarks and gluons, one must include the effects of multiple collisions of the projectile traversing the target nucleus. Furthermore, a simple N_{part} scaling to the $A+A$ data is insufficient to firmly establish the formation of a new state of matter. A detailed study of both $p+p$ and $p+A$ collisions at RHIC energies will be necessary.

2.3 The ϕ Meson

The ϕ meson is the lightest vector meson with hidden strangeness ($s\bar{s}$). The major properties of the ϕ meson are listed in Table 2.1. In e^+e^- and nucleon-nucleon collisions, ϕ meson production is believed to proceed mainly via a color singlet gluon configuration. The production of ϕ mesons through light quark pair annihilation is suppressed by the OZI rule [Oku63, Iiz66]. The origin of the suppression is believed to lie in the non-abelian nature of QCD. Since the ϕ is produced by gluons, the gluons must carry enough energy to create the ϕ resonance state. The gluons therefore have higher momenta and the coupling constant, α_s, is smaller.

ϕ Meson	
Mass	1019.417 MeV/c^2
Γ (FWHM)	4.458 MeV/c^2
Branching Ratios	
K^+K^-	49.1%
e^+e^-	0.0291%
$\mu^+\mu^-$	0.037%

Table 2.1: Properties of the ϕ vector meson.

2.3.1 ϕ Meson Production in Heavy Ion Collisions

It has been postulated that in heavy ion collisions, several mechanisms for ϕ meson production are available. The canonical ϕ meson production mechanisms are $ggg \to \phi$ and $q\bar{q} \to \phi$. There is also the possibility of producing ϕ mesons via the reverse reaction of the phi decay, namely $K + \bar{K} \to \phi$.

Baltz and Dover [BD96] proposed that in heavy ion collisions where the final state phase space density of K and $\bar{K}$ is much higher than in simple colliding systems ($p + p$ and $p + \bar{p}$), ϕ meson production may proceed by the coalescence of hadronic state kaons (Equation 2.3) to form an $s\bar{s}$ bound state. Although their analysis of ϕ meson production was specific to $Si + Au$ collisions at the

AGS (E802 and E859), the concepts are based on general phase space density arguments and are applicable to all heavy ion systems. This mechanism seems viable because it proceeds by the exchange of soft gluons.

$$K + \bar{K} \rightarrow \phi \tag{2.3}$$

If, however, one considers that kaons are spin zero particles while the ϕ has spin one, it now becomes apparent that the kaon coalescence model, although favorable when considering the magnitude of α_s, suffers a penalty due to the constraints imposed by the spin quantum number.

There is also the tantalizing mechanism mentioned in Section 2.2, namely $gg \rightarrow s\bar{s}$. Shor [Sho85] and Sorge [BSG94] proposed an enhancement of ϕ meson production as a direct measurement of QGP formation. Their proposals make two assumptions: the production of ϕ mesons from a hadronic gas is OZI suppressed, whereas the sheer abundance of $s\bar{s}$ pairs in a QGP will enhance the ϕ yield during the hadronization of a QGP. In his paper, Shor claims the variation of the ratio $\phi/(\rho+\omega)$ with baryon density or energy density as a measurement of QGP formation that is experimentally feasible. Unfortunately, the measurements of the ρ and ω are extremely difficult and will not be available from the year one data.

Extracted slope parameters (T) from an exponential fit to the invariant multiplicity distribution may yield information on the dynamical evolution of the heavy ion collision. A deviation of T from the mass systematics attributed to radial flow could elucidate the production mechanism for the ϕ meson as well as the dynamical properties of the ϕ meson's interaction with other particles.

Sorge, *et al.* made a striking prediction using RQMD [Sor92, BSG94]. By implementing a string fusion mechanism, they predicted that the production of ϕ's would be enhanced while the kaon production would remain unaffected.

While the K/π ratio gives an overall indication of the strangeness content in the final state of the collision, the ϕ/π ratio, because of the $s\bar{s}$ content of the ϕ meson, may provide a more sensitive measure of the strangeness production in heavy ion collisions. One would naïvely expect that while kaon production is proportional to the phase space density of strange quarks, γ_s, the dependence of the ϕ meson should scale with γ_s^2. There is currently no clear description of s and $\bar{s}$ hadronization.

Experimentally, the ϕ to K^- ratio is the most promising: K^-'s are produced only via pair production, very few resonances decay into kaons when compared to pions, and the analysis is possible with the data in hand. A comparison of the ϕ/K^- ratio as a function of $\sqrt{s_{NN}}$ and collision system ($p+p$, $p+\bar{p}$, $A+A$) could provide an insight to the production mechanisms for the ϕ meson in heavy ion collisions. If the ϕ/K^- ratio differs as a function of $\sqrt{s_{NN}}$ and/or system size, this may indicate that dynamical processes such as kaon coalescence play a significant role in ϕ meson production. On the other hand, if the ratio is independent of both collision energy and system size, this will put a severe constraint on the production mechanisms responsible for ϕ meson production. At the very least, a similar ϕ/K^- ratio for all energies and system sizes would indicate that the probability for strange quark hadronization into a ϕ meson or K^- meson is a universal property. One may then study the possible production mechanisms for the ϕ meson in simpler systems and possibly make a statement on the actual production process: whether this be $ggg \to \phi$, $s + \bar{s} \to \phi$ or $K + \bar{K} \to \phi$.

2.3.2 Understanding the Production Properties of the ϕ Meson



Figure 2.2: Anti-baryon to baryon ratio vs. $\sqrt{s_{NN}}$. Heavy ion data for $\bar{\Lambda}/\Lambda$ and $\bar{p}/p$ are shown as well as the $\bar{p}/p$ ratio from $p+p$ collisions. There is considerable stopping in heavy ion collisions at the AGS and SPS ($\sqrt{s_{NN}} = 4.9$ and 17.2 GeV, respectively). Year 2000 RHIC data at $\sqrt{s_{NN}} = 130$ GeV indicates that $B - \bar{B}$ pair production accounts for over half of the baryon number in the central rapidity region.

Recent results from STAR [Adl01a] show that unlike the AGS and SPS where the stopping of projectile nucleons contributed significantly to the initial conditions of the heavy ion collision, anti-baryon and baryon pair production becomes more important. Results of the mid-rapidity anti-baryon to baryon ($\bar{B}/B$) ratio show that as a function of $\sqrt{s_{NN}}$ (Figure 2.2), this ratio is approaching unity in the central rapidity region for the most central heavy ion collisions through the year 2000 RHIC energy ($\sqrt{s_{NN}} = 130$ GeV).

The production properties of the ϕ meson in this environment, when compared to different colliding systems and system energies from $Au + Au$ collisions at the AGS to $p + \bar{p}$ collisions at the Tevatron will be addressed. Of interest is the central rapidity region at RHIC which is most likely dominated by the dynamics of gluons. A comparison of the production properties of the ϕ meson in different collision environments may elucidate the dominant production mechanism for the ϕ meson and its interaction with other particles. In particular, if one observes significant differences in the particle ratio ϕ/K^- between the AGS where the net baryon number is high and RHIC where the net baryon number is low and pair production is the dominant mechanism (at least for baryons and anti-baryons, presumably for quarks and anti-quarks), one may deduce from this difference that mesons carrying strange quarks are sensitive to the initial conditions of the colliding system. Comparisons of the heavy ion data to $p + p$ collisions will also shed light on this matter. On the other hand, the lack of a significant dependence of the ϕ/K^- ratio on collision energy and system size would indicate that the probability of anti-strange quark hadronization into either a ϕ or K^- meson is universal.

2.3.3 Dynamical Properties of the ϕ Meson

Equation 2.4 shows the expected relation between the measured slope parameter from an exponential fit to the invariant transverse mass (m_t) distribution, T, the thermal freeze out temperature, T_0, and the common expansion velocity, β [Bea97]. This equation is approximately valid under the assumption that all particles approach the hydrodynamical limit because of large cross-sections. Section 8.2 contains a brief discussion on the origins of Equation 2.4. Any deviation from this linear trend with mass may be indicative of a quantitative difference in the dynamical evolution of these particles.

$$\langle T \rangle = T_0 + m\beta^2 \tag{2.4}$$



Figure 2.3: Slope parameters from an exponential fit to the transverse mass distribution vs. the mass of the particle from the most central $Pb+Pb$ collisions at the CERN SPS. Pions, kaons and protons seem to follow an increasing linear trend with their mass. For baryons with strange quarks, there is a deviation from this straight line. Note that there are two measurements for the ϕ meson ($\phi \rightarrow K^+K^-$ from NA49 and $\phi \rightarrow \mu^+\mu^-$ from NA50). Error bars shown are statistical errors only.

In central Pb+Pb collisions at the SPS (nucleon-nucleon center of mass energy $\sqrt{s_{NN}} = 17.2$ GeV), the slope parameter (T) in an exponential fit to the transverse mass (m_t) distribution at mid-rapidity ($\propto e^{-m_t/T}$) follows a systematic trend as a function of hadron mass for pions, kaons and protons [Bea97] (Figure 2.3). This observation is interpreted as resulting from a common expansion velocity developed in the final state for pions, kaons, and protons [Hei96]. The slope parameters measured for the multi-strange hyperons Ξ and Ω [Lie99], however, show deviations from a linear mass dependence, suggesting that these particles do not interact as strongly in the final state at SPS energies [HSX98]. Measurements of ϕ meson production at the SPS were inconclusive [Afa00, Wil99].

NA49 measurements of the ϕ meson slope parameter from the K^+K^- decay channel seemed to indicate that in central $Pb+Pb$ collisions, the ϕ meson fits into the model of collective radial expansion of the system. However, NA50 results from the $\mu^+\mu^-$ decay channel showed the ϕ meson slope parameter is significantly lower, a result which in the radial expansion model suggests the ϕ meson does not interact strongly in the final state radial expansion. The difference between the NA49 and NA50 measurements disappears for peripheral collisions. It has been hypothesized that in central heavy ion collisions, rescatterings of the kaons from ϕ decays in the fireball may change the measured ϕ slope parameter [JJD01, Sof01]. This effect, however, can only account for 10 to 20% of the difference in the two measurements. If there is a significant modification of the spectral shape due to radial expansion, there will be a strong p_t dependence of the measured slope parameter (see Section 8.2).

CHAPTER 3

Facilities

3.1 RHIC Accelerator Complex



Figure 3.1: Cross section of an arc dipole. The outer diameter of the vacuum vessel is 610 millimeters.

The RHIC facility consists of two rings of superconducting magnets, each with a circumference of 2.4 miles. The main components of the magnet system are 288 arc dipoles (Figure 3.1), 108 insertion dipoles, and 276 arc and 216 insertion quadrupoles. In addition to the dipoles and quadrupoles, an inventory of 72 trim quadrupoles, 288 sextupoles, and 492 corrector magnets exists. The arc dipoles have a physical length of 9.728 m (9.45 m effective), are bent with a 4.85 cm sagitta and have a coil aperture of 8 cm in order to accommodate intra-beam scattering. The beam tubes in the magnets are at liquid helium temperatures, with the beams in the arcs separated by 90 cm. The magnets are cooled to a temperature of < 4.6 K by circulating super-critical helium supplied by 24.8 kW refrigerators. Extremely good vacuums of $< 10^{-11}$ mbar in the cold bore and $\sim 7 \times 10^{-10}$ mbar in the warm beam tube sections is achieved at RHIC to minimize beam losses and radiation background.

Physical Parameters		
No. Intersection Regions	6	
No. Bunches/ring	60	
Bunch Spacing (nsec)	213	
Collision Angle	0	
Free Space at Crossing Point (m)	± 9	
Performance Specifications	Au	p
No. Particles/Bunch	1×10^9	1×10^{11}
Top Energy (Gev/u)	100	250
Luminosity, average ($cm^{-2}sec^{-1}$)	$\sim 2 \times 10^{26}$	$\sim 1 \times 10^{31}$

Table 3.1: Physical parameters and performance specifications for the Relativistic Heavy Ion Collider (RHIC).

RHIC is the first collider to accelerate heavy ion beams and is capable of accelerating any combination of species from $p+p$ @ $\sqrt{s} = 500$ GeV up to $Au+Au$ @ $\sqrt{s} = 40$ TeV. This unprecedented flexibility allows the study of colliding systems as a function of both energy and system size, a capability unique to this facility. RHIC is designed for a $Au + Au$ luminosity of about $2 \times 10^{26} cm^{-2} sec^{-1}$ at top energy, while maintaining the potential for future upgrades by an order of magnitude. The luminosity for lighter ions will be higher, with $p + p$ collisions at

$\mathcal{L} = 1 \times 10^{31} cm^{-2} sec^{-1}$. Table 3.1 lists the performance specifications for RHIC.

The collider's performance is achieved in different ways. An important choice in the RHIC design was the utilization of short bunches colliding head-on to enhance the luminosity while keeping the average current and stored beam energy low. Formation of the bunches occurs prior to injection, using the previously existing accelerator complex at BNL.

The complex required to produce, accelerate and store the heavy ion beam consists of the Tandem Van de Graaff accelerators, the Booster Synchrotron and the Alternating Gradient Synchrotron (AGS), which combine to serve as the injector for RHIC (Figure 3.2). Gold (Au) atoms with a charge -1 are generated in the Pulsed Sputter Ion Source in the Tandem Van de Graaff facility, accelerated and passed through two Au foils, leaving the Au atoms with a net +32 charge. The 1 MeV/nucleon Au beam is transferred to the booster where it is accelerated to 95 MeV/nucleon and then stripped further to a net +77 charge. In the AGS, the Au beam is bunched and further accelerated to 10.8 GeV/nucleon and is extracted using fast extraction. Fast Extracted Beam (FEB) attempts to extract a significant portion of many AGS Au bunches into one RHIC bunch. The FEB bunches are then delivered to RHIC through the AGS To RHIC (ATR) transfer line. In this final stage before injection into the RHIC ring, the Au nuclei are completely stripped of orbital electrons and have a charge of +79. Once injected into RHIC, the bunches are accelerated to collision energy and stored for data taking.

To accelerate, capture and store the beam, RHIC employs a radio frequency (rf) system [Pro94]. The varying requirements imposed on the rf are satisfied by three systems.

- An acceleration system (26 MHz) for capture of the injected beam, acceleration to top energy, and bunch shortening at top energy.

- A storage system (196 MHz) for sufficient longitudinal focusing to keep bunches short during the 10 hour storage time.
- A longitudinal kicker to damp longitudinal injection errors of individual bunches and for damping longitudinally coupled bunch instabilities.

Table 3.2 lists the major characteristics of these systems.

Systems	Accelerating	Storage	Kicker
Harmonic	342	2508	
Radio frequency (MHz)	26.743	196.12	wide band
Stations	4	10	2
Stations/ring	2	$3+4$	1
Voltage/station (kV)	300	1000	1
Voltage/ring (kV)	2×300	7×1000	1×1

Table 3.2: RHIC *rf* cavity systems and longitudinal kicker.

3.1.1 RHIC 2000 Commissioning

RHIC has six interaction regions, with 4 regions currently occupied. Two small experiments, BRAHMS and PHOBOS, and two large experimental programs, PHENIX and STAR, have successfully taken data during the summer 2000 RHIC run.

Progress at RHIC was made in fits and starts, with RHIC operations beginning slowly. The operators were just beginning to understand the characteristics of the accelerator and very little progress was initially made. But on the night of 11 June 2000, STAR recorded the first beam-beam collision at the injection energy of $\sqrt{s_{NN}} = 20$ GeV. At 9 PM on 12 June 2000, STAR recorded the first ever beam-beam collision event at RHIC at a collision energy of $\sqrt{s_{NN}} = 60$ GeV



Figure 3.2: Diagram of the AGS - RHIC facility. The heavy ion beam is produced at the Pulsed Sputter Ion Source, accelerated through the Tandem Van de Graaff, booster and AGS, fast extracted at 10.8 GeV/nucleon and injected into RHIC where the beam is accelerated to a top energy of 100 GeV/nucleon and stored. Protons do not proceed through the Tandem Van de Graaff but are accelerated through the LINAC and then to the booster, AGS, and injected into RHIC.

(Figure 3.3). The collisions at $\sqrt{s_{NN}} = 60$ GeV were a major milestone for RHIC because they proved that RHIC could accelerate and collide beams of heavy ions. Just a few short weeks after that, collisions at $\sqrt{s_{NN}} = 130$ GeV (Figure 3.4), our nominal beam energy for the summer, were recorded by STAR.



Figure 3.3: First collision at $\sqrt{s_{NN}} = 60$ GeV.

3.1.2 Summer 2000 Operations

Overall, RHIC performed well during the first year of running. Sufficient luminosity was delivered in the last month of operations, with the luminosity achieved being about 10% of the design luminosity. The first year's dataset showed that there are issues remaining that need to be addressed.

Since the storage *rf* cavities were not in use, the bunches in the ring were relatively long, resulting in a wide distribution for the primary vertex position along the beam axis. The design goal is for an interaction region with a width of



Figure 3.4: First collision at $\sqrt{s_{NN}} = 130$ GeV.

20 cm. During the summer run, we measured a gaussian sigma for the primary vertex position in Z between 70 and 100 cm. This is cause for some concern since our detector acceptance depends on the location of the collision. Another complication is with the material in the beam pipe. There is a 150 cm section of beryllium (Be) beam pipe centered about the midpoint of each interaction region. Be is used instead of steel or aluminum because the radiation length is an order of magnitude less then these more commonly used pipe materials, resulting in fewer multiple scatterings and secondary particle production at the beam pipe. Unfortunately, with a sigma of 70 cm for the primary vertex position, at least 30 percent of our events will have particles traversing the high interaction length material. The storage rf system will also help with beam losses into adjacent rf buckets. This type of loss not only reduces our luminosity, but also increases the rate of beam-gas interactions.

STAR measured significant background rates from beam interactions with residual gas molecules within the beam pipe. As previously mentioned in Section 3.1, there is an order of magnitude difference in vacuum pressure between the cold bore sections of the beam pipe and the warm beam pipe sections. Near each interaction region in RHIC, there are straight sections of beam pipe which are not actively cooled. Within these warm bore sections, beam gas events are more likely to occur than in the cold bore sections. Since these straight sections are in the line of sight of the detector, we tend to see a high rate of these background events. Compounding this situation was the decision by RHIC operators to forego baking of the straight sections of the beam line, which resulted in out-gassing of the beam pipe over the course of the RHIC run. This is expected to be resolved for the year 2001 running when the full RHIC design luminosity will be achieved.

3.2 The STAR Detector

STAR (Figure 3.5) is a large acceptance cylindrical geometry detector system with complete azimuthal coverage over the central rapidity region. The entire detector system is located within a 0.5 Tesla solenoidal analyzing magnet. STAR consists of several detectors centered around the main tracking chamber, the Time Projection Chamber (TPC) [Ack99], which covers the pseudo-rapidity (η) region -2 $< \eta <$ 2. The TPC allows both momentum and particle identification information to be gathered, the latter accomplished by measuring the energy loss of a particle through the TPC's gas volume. Along with the TPC there is the Forward TPC, which extends the coverage in η, and the Silicon Vertex Tracker (SVT) [Pan99], which helps in reconstructing secondary vertices of neutral particles decaying to charged particles away from the primary vertex. There is also a full barrel electromagnetic calorimeter and end-cap calorimeter which provide



Figure 3.5: The STAR experiment.

complete coverage for photons and electrons. The lowest level trigger system is composed of a plastic scintillator trigger barrel (CTB), and two Zero Degree Calorimeters (ZDC). The CTB array is configured as a cylindrical barrel and surrounds the TPC. The ZDC's are located 18 meters up and downstream along the beam direction and measure beam-like neutrons from the fragmentation of colliding nuclei. The design of the ZDC's is the same for all RHIC experiments, allowing for a meaningful comparison of event centrality among the RHIC experiments.

For the year 2000 data taking, the experimental setup consisted of the TPC, CTB, and ZDC. There was also one ladder of prototype silicon detector from the SVT and a small acceptance ring imaging Cherenkov detector in place.

STAR offers excellent capabilities to study hadronic observables using the TPC, FTPC, and the silicon detectors, and good photon and electron coverage

Hadronic Observables	
a) Charged hadrons:	p, $\bar{p}$, π's, K's, Ξ^-, $\overline{\Xi}^-$, Ω^-, $\overline{\Omega}^-$, d, $\bar{d}$
b) Neutral hadrons:	Λ, $\bar{\Lambda}$, K_s^0, ϕ, ρ, K^*, $\bar{K}^*$
c) Spectra:	p_t, particle ratios, slope parameters
d) Collision Geometry:	Flow, HBT, E-by-E correlations, Event Multiplicity
Electromagnetic Observables	
e) π_0, η distributions	
f) High p_t particles and jets	

Table 3.3: Quantities measurable on an Event-By-Event basis.

using the TPC and the EM calorimeter. Because of STAR's large acceptance, it is possible to measure the quantities listed in Table 3.3 on an Event-by-Event basis with reasonable statistics. For the first year, STAR has detected all quantities listed in Table 3.3 a), b), c) and d), as well as the π_0. With such a large sample of measurable particles, STAR has the unique opportunity to describe the global features of the heavy ion collisions recorded during the summer of 2000.

CHAPTER 4

The Time Projection Chamber



Figure 4.1: Sectioned view of STAR TPC. The major features of the STAR TPC are shown, including the inner and outer field cages, the high voltage central membrane and the MWPC sectors.

The TPC (Figure 4.1) is a fully pixelized drift chamber with a Multi-Wire Proportional Chamber (MWPC) [BR94] at both ends of the TPC for readout.

The TPC has 144,000 pads which give xy coordinate information and up to 512 time buckets which provide z-position information for each hit, a total of over 70 million pixels.

Charged particles can be detected in drift chambers because they ionize the gas along their flight path. The energy required for them to do this is taken from their kinetic energy and is very small, typically a few keV per cm of gas under normal conditions. When a charged particle traverses the TPC volume, it ionizes on average gas atoms and molecules every few tenths of a millimeter along its path and leaves behind a cluster of electrons. Under the influence of an externally applied electric field, the electron clusters then drift at a constant average velocity to the readout electronics where their time of arrival and location are recorded.

In the STAR TPC, the electric field is provided by the outer field cage (OFC), the inner field cage (IFC), and the high voltage central membrane (CM) (Figure 4.1). The purpose of the OFC and IFC is to provide a nearly uniform electric field along the axis of the cylinder in which to drift the electrons to the anode plane, since any distortions in the field will result in a distortion of the recorded tracks. The OFC and the IFC also serve to define the active gas volume and were designed to contain the TPC gas and prevent it from being contaminated by outside air. The central membrane is located in the middle of the TPC and is held at a high voltage (-31 kV for the year 2000). The anode and pad planes are organized into sectors on each end of the TPC and the pads are held at virtual ground.

The OFC and IFC include a series of gradient rings (see Section 4.1) that divide the space between the central membrane and the anode planes. The total distance from the CM to either inner or outer sector anode planes is slightly



Figure 4.2: Outer Field Cage and outer sector dimensions. Dimensional units are in millimeters.

greater than 2 meters (Figures 4.2 and 4.3).

4.1 Field Cages

The field cages are designed to be low mass and "thin" for particles passing through them yet they must also be gas tight and strong enough to be self supporting. The field cages were built using two sheets of metal coated Kapton separated by a honeycomb of Nomex. The whole assembly was rolled into a tube and the sheets of Kapton were epoxied to the honeycomb to form a strong



Figure 4.3: Inner Field Cage and inner sector dimensions. Dimensional units are in millimeters.

sandwich of material.

The Kapton in the outer field cage (OFC) (Figure 4.4) is laminated with a 35 micron layer of copper and the metal layer is etched into stripes so that, after rolling the tube, the stripes become rings around the tube. The inner field cage (IFC) (Figure 4.5) is similar to the outer field cage but the Kapton is laminated with a thinner layer of Aluminum (9 micron) and the Nomex layer is thicker (1.27 cm). The two sides of the tube are connected by metal pins. The stripes on one side of the tube are not aligned with the stripes on the other side; instead they overlap, with the stripes on one side centered over the gap on the opposite side. This allows the metal layers to become part of the mechanical structure of the tube which increases its strength. This also puts metal opposite the gap in the



Figure 4.4: Outer Field Cage structure. Dimensional units are in millimeters.



Figure 4.5: Inner Field Cage structure. Dimensional units are in millimeters.

rings facing the TPC volume. The image charges developed on the opposite side of the gap are supposed to reduce the field distortions that might be caused by charge build up on the exposed Kapton in the gap facing the TPC.

There is approximately one ring per centimeter and the rings are biased by a chain of resistors that connect to the central membrane, the anode plane ground, and each of the gradient rings in-between. The rings are separated by two mega-ohm resistors and there are 182 rings and 183 resistors in each chain (Figures 4.2 and 4.3).

The last two resistors are adjustable and are housed in a rack which is external to the TPC. Note that the outer field cage has a ground shield attached to ring 182. It marks the end of the TPC drift volume and is used to better define the shape of the field at the terminus. The inner field cage does not have a ground shield. The spark gaps are safety devices for the protection of personnel and equipment in case the external resistors are disconnected while the field cages are biased.



Figure 4.6: Aluminum gas containment vessel. Dimensional units are in millimeters.

The outer field cage is nested inside an aluminum gas containment vessel (Figure 4.6) which presents additional radiation lengths of material to particles passing out of the TPC in the radial direction. It is separated from the OFC by 5.7 cm of nitrogen gas. The gas vessel also has aluminum brackets glued onto its outer circumference to support the CTB trays and to temperature stabilize the TPC.

4.2 Multi-Wire Proportional Chamber



Figure 4.7: Inner sector wire geometry.

The MWPC's are located on the ends of the TPC. The MWPC's consist of three planes of wires and a pad plane (Figures 4.7 and 4.8) connected to the front end readout electronics. The three wire planes are the gating grid, the ground grid, and the anode grid. The ground grid and gating grid help to define the drift field of the TPC. The anode wires are biased to a high voltage to provide the necessary electric field to avalanche the electrons from the track ionization.



Figure 4.8: Outer sector wire geometry.

The TPC is divided into 24 super sectors, each subsequently divided into an inner and outer sector (Figure 4.9). Although the inner and outer sector dimensions are slightly different, the ground grid and the gating grid are aligned to provide a uniform drift field.

Along with defining the drift field of the TPC, the ground grid and the gating grid perform other important tasks.

The gating grid separates the drift volume of the TPC from the amplification region. The gating grid controls the passage of electrons from the drift region into the amplification region, and prevents ions originating from the amplification process to enter the drift region. By biasing alternating wires on the gating grid



Figure 4.9: Super-sector pad plane layout.



Figure 4.10: Drift field lines in a typical MWPC. The three wire planes, the gating grid, the ground grid, and the anode grids are shown as well as the pad plane. (a) Drifting electrons are collected on the gating grid until gated open by a triggering event. A shielding grid at ground potential is used to terminate the drift region. Electrons drift through an open gating grid (b) pass through to the amplification region around the anode wires. The motion of positive ions generated in the avalanche induces a signal on the segmented pad plane to provide precise measurements of ionization along the wire. The slow positive ions are blocked from entering the drift region by closing the gating grid after the electrons have drifted through. Figure was taken from the Particle Data Book [GG00].

positive and negative with respect to a reference voltage, the passage of ionization electrons is prohibited (Figure 4.10 (a)). When all wires are at the reference voltage, the nearby equi-pontential lines are nearly flat, allowing the passage of ionization electrons (Figure 4.10 (b)). The reference voltage on the gating grid is set such that when the grid is open, the grid is electrostatically transparent to drifting electrons. The gating grid is closed by shifting the voltages on alternate wires up or down symmetrically, leaving the average potential unchanged. Therefore, to first order, opening and closing the gating grid should only affect fields nearby.

Without the gating grid, ions from the amplification process would enter the drift region of the TPC, producing distortions in the drift field which would degrade the position resolution of the TPC. As MWPC's age, their performance tends to degrade. An increase of the dark current, a lowering of the gain, and a loss of pulse height resolution typically occur over time. At RHIC, where the charged track multiplicity per event is measured in the thousands, the MWPC would quickly deteriorate unless selection criteria are applied when recording events. By selectively reading out events, the life of the MWPC can be extended, simply because fewer electrons are being avalanched. Previous experiments employing MWPC's have reported performance losses with wire lifetimes of 10^{-4} Coulomb per cm of wire [BR94].

The ground grid lies between the anode wires and the gating grid. When switching, there is a large instantaneous current on the gating grid wires, which introduces noise into the MWPC. By positioning the ground grid with the gating grid on one side and the anode grid and pad plane on the other side, the ground grid helps to shield the pad plane and anode grid from feeling the full impact of the gating grid noise. The ground grid also helps to define the anode wire avalanche cells.

4.3 Anode High Voltage System

The anode wire high voltage system is powered using LeCroy 1471 high voltage power supplies. Two full systems are used, one controlling the inner sector high voltage and the other controlling the outer sector high voltage. There are a total of 192 channels for the anode high voltage system. Nominal operating voltages for the anode wires were +1390 volts DC for the outer sector and +1170 volts DC for the inner sector (Table 4.1) during the summer 2000 run. The LeCroy system can be controlled via both serial and ARCNet connections, the latter connection interfacing directly to the slow controls system. There are serious limitations to communicating via the ARCNet connection, the greatest being the lack of block data transfers, which results in high levels of network traffic. Without block data transfers, the data refresh rate in the user interface is extremely slow, and the system crashes the vxWorks kernel when there is too much data being transferred simultaneously. The crashes of the kernel are due to a lack of scalability in the vxWorks interrupt buffer. One could argue that the problem is a vxWorks issue and not a LeCroy ARCNet. The problem was partially overcome by splitting the control of the two LeCroy power supplies to two independent cpus, thus reducing the amount of data being handled by the cpu at any given moment.

4.4 Gating Grid Driver System

The gated high voltage for the gating grid is supplied by custom modules designed and built at UCLA [Gha98]. The system consists of 12 pairs of modules,

TPC Anode Wire Voltages	
Inner Sector (Volts)	1170
Outer Sector (Volts)	1390
TPC Gating Grid Wire Voltages	
Reference (Volts)	-127
Wire Bias w.r.t. reference (Volts)	± 75

Table 4.1: MWPC high voltage settings during the summer 2000 heavy ion physics run.

with each pair of modules controlling 4 sub-sectors. There are a total of 144 high voltage channels for the TPC gating grid. A complete set of functioning modules includes one VME control module and one high voltage module. Two modules are required because the control modules are VMEbus standard cards, while the high voltage modules reside in a crate with a special bus to supply the modules with power. The control modules communicate with a Motorola VME162 processor board, which handles the interface to the STAR slow controls. The nominal operating voltages for all gating grid channels are -127 VDC for the reference voltage and ± 75 VDC on alternating wires (Table 4.1).

4.4.1 Gating Grid Operations

During the summer of 1999 cosmic ray testing, several problems with the gating grid drivers arose. Each high voltage stage in the gating grid consists of a switching power supply which pulses a transformer, rectifies and generates the voltage, which is then passed through a secondary linear regulator. Between the original prototyping and final production of the gating grid drivers, a component in the original design was phased out of production by the manufacturer. This component, a pass transistor (P-channel MOSFET) in the linear voltage regulation stage, was replaced by another component. It is controlled by an op-amp which compares the output of that transistor with the set-point voltage and varies the transistor's conductivity to match the output voltage to that of the reference voltage supplied by the control board. Unfortunately, we encountered problems because the replacement device did not have the capacity to deliver the required current when the voltage set-point on the gating grid was low. Although the occurrence is rare, this situation could occur during power up. For instance, in the case when the voltage drop across the MOSFET, $(V_{setpoint} - V_{output})$, is maximum, we would need at least 0.5 - 1 mA just to measure it. This condition exceeded the safe operating parameters of the replacement MOSFET. We had failures in 10 percent (7 out of 72, including backup modules) of the high voltage channels, all traced to a failure in this single component. As a result, all 72 channels were repaired and upgraded to overcome this problem. This was done on site at the experimental hall and took two weeks to complete. Each module was then burned in for 5 days to ensure that the modification did resolve the problem and that other components were not compromised during the modification. Three more modules in production will include this design change.

4.4.2 Mismatches in the Gating Grid Voltages

As part of the summer 2000 detector commissioning, I studied the transmission of electrons as a function of gating grid voltage and distortions to the drift field as a function of mismatched gating grid voltages. Both studies were conducted using the TPC laser system and with the magnetic field at 0.25 Tesla (half the nominal field strength). Electron transmission is a typical study conducted in TPC's and results from other TPC's have been published [BR94]. There are also solutions for the transmission function available which ignore the effects of gas diffusion [BR94]. Measuring the distortions caused by mismatched voltages allows us to set reasonable alarm limits on the high voltages.

The transmission study was done by keeping the gating grid in a closed state, with wires at their bias voltages. Laser triggers were sent, and we looked for traces of a laser signal in our data. This was repeated for different bias voltage settings. The study revealed two things. First, the gating grid completely attenuated the laser signal for all voltages that we were capable of setting. The gating grid drivers had difficulty with low bias voltage settings so we were unable to study this region of the transmission curve. The second result, which was more important, was the discovery that one of the sectors was always transmitting electrons. This was a cause for some concern since there were several possible failure points. There could have been anything from a cable problem up to a sector problem, the latter requiring the replacement of a sector. Fortunately, it was found that the high voltage gating grid cable for that sector was disconnected at the TPC sector connection. As a result, the voltage on that sector floated to an unknown value, allowing that sector to transmit electrons continuously. When we looked at the history of anode wire trips on the entire sector due to excess DC or peak currents, this sector showed a pattern of trips when beam was in the accelerator, which were most likely due to severe beam losses. After the sector cable was connected, no trips have been recorded to date on that sector.

The distortion study was done by varying the gating grid voltages on the 12 o'clock and 6 o'clock outer sectors. The residual of the hits in pad row 12 to 15 were then averaged over many laser events. From previous numerical calculations and discussions with the detector designers [Wie00, Wie00], we expected to see a systematic pull of the drift electrons in one direction if there was a voltage mismatch of at least 10 volts on the gating grid. Figure 4.11 shows the final result of this study. As expected, we see measurable effects when the voltages are mismatched by 10 volts, followed by a linear increase in the mean x residual.



Figure 4.11: Mean x residual (along pad row) vs. gating grid voltage excursion.

4.5 TPC Gas

There are many factors that must be considered in choosing the best gas for the TPC. Gas purity, multiple scattering, drift velocity, cost, and safety are just a few of the more important issues.

The STAR TPC is very large and ionization electrons from a track may drift as much as two meters before reaching the anode plane. The gas must have sufficiently small attenuation for drifting electrons. Since the electron attenuation is a strong function of the oxygen and water content, the gas must be kept relatively pure. Typically, the oxygen and water concentrations should be kept below 40 parts per million. As a safety precaution, the entire detector will shut down if either the oxygen or water content exceeds 80 parts per million in the

TPC gas. Oxygen poses an extra hazard when mixed with flammable gas. Due to the presence of high voltages on the wires of the MWPC, there is a potential for sparking which could result in ignition if the oxygen content is high. The experimental and safety requirements demand that the gas must be easy to recirculate and clean in order to achieve these stringent standards. Noble gases are good candidates because they are easily cleaned with simple technologies and many pure organic gases are also easily handled. Examples of these gases are helium, argon, methane, ethane, and iso-butane.

STAR has considered two gas mixtures: Argon(90%)-Methane(10%), also known as P-10, and Helium(50%)-Ethane(50%). The noble gas component has a very low affinity for free electrons while the organic gases quench the propagation of UV photons throughout the TPC volume. This property of organic gases is critical for stable electron amplification. The avalanches near the anode wires produce many UV photons which could produce photo-electrons if they propagate to metal surfaces such as the pad plane or the other wire planes. If the UV photons were not quenched in the gas, the photo-electric effect would lead to a catastrophic feedback effect where UV photons from an avalanche would produce more electrons which would lead to more avalanches. The argon-methane mixture will be used in the TPC because it is the least hazardous of the two. The argon component, however, increases the multiple scattering of the primary particle relative to helium so the best performance of the TPC would be achieved with the helium mixture. The dangers, however, posed by the helium-ethane mixture outweigh the benefits of better TPC resolution. The helium-ethane mixture requires a higher electric field to obtain an acceptable drift velocity, and the diffusion of helium may damage other detector systems in STAR. The STAR TPC will most likely continue to use P-10 throughout its lifetime.

4.6 TPC Gain Variations

The gas gain in the TPC is affected by the gas density and is measurable in the TPC. Since the TPC is operated at atmospheric pressure, the pressure is recorded by the gas system. According to the ideal gas law, the gas density (ρ) is proportional to the pressure of the gas (Equation 4.1).

$$P/T = \rho R \tag{4.1}$$

$$R = \text{ideal gas constant}$$

From Diethorn's formula for gain [Die56], we obtain Equation 4.2 [BR94]. In Equation 4.2, ΔV is the average potential difference an electron must traverse to obtain the required energy to produce one free electron from the TPC gas. The mean charge per unit length on the anode wire is denoted as λ, and ϵ_0 is the permittivity of free space. The constant (S) is negative because as the density of the gas rises, the mean free path of the electrons decreases. As a result, the mean of the electron kinetic energy distribution decreases, resulting in fewer electrons which exceed the threshold energy for multiplication.

$$\frac{dG}{G} = S\frac{d\rho}{\rho} \tag{4.2}$$

$$S \equiv \frac{\lambda ln2}{\Delta V 2\pi\epsilon_0}$$

With STAR, the TPC temperature was well regulated so one can reduce Equation 4.2, using the ideal gas law (Equation 4.1) to relation 4.3.

$$\frac{dG}{G} = S\frac{dP}{P} \tag{4.3}$$

Since the gas pressure was monitored, the variations can be accounted for. The TPC gas system parameters were stored in the conditions database, which is briefly described in Section 4.9. Figure 4.12 is a plot showing the result of a



Figure 4.12: Change in gain vs. change in pressure in the STAR TPC.

study done in October 2000 of the relationship between gain and pressure in the STAR TPC. The results were obtained by calculating the mean position of the pion band in the momentum range $0.25 < p < 0.30$ GeV/c for several runs. This number was then compared to the pressure during the run. The pressure was corrected for a calibration offset in the barometric pressure readings from the TPC gas system. With this data, the slope, S, in Equation 4.3 was extracted and found to be -3.7.

4.7 TPC Drift Field

The STAR TPC uses the field cages to establish a longitudinal electric field to drift the electrons from any point in the TPC to the multi-wire proportional chambers. The drift rate is a function of the applied field, but the relation is non-linear and depends on the gas composition (Figure 4.13).

4.7.1 Drift Velocity

For accurate track reconstruction, it is reasonable to choose an electric field near the peak in the drift velocity curve. This ensures that the drift velocity is saturated and the drift velocity is least sensitive to minor changes in the gas pressure or temperature caused by the local environment. The STAR TPC, however, has an automatic drift velocity stabilization feedback loop which works by monitoring the drift of laser tracks in the TPC. Since the origin of these tracks is well known in time and space, it is easy to calculate the actual drift velocity and to apply corrections to the drift field to compensate for any time dependent variations in the gas properties. The operating point for the drift velocity must therefore be slightly off peak in order to provide some slope to the observed changes in parameters and to avoid the problem of a double valued solution when the drift velocity is observed to drop. A review of Figure 4.13 reveals that any reduced field greater than 0.16 V/cm/mm-Hg satisfies these conditions. Transforming to standard temperature and pressure, this means the drift field should be slightly greater than 120 V/cm, which is why the TPC is operated at an average gradient of about 145 V/cm.

We tested the drift velocity stabilization feedback loop during the summer 2000 run but did not use it for data taking. In retrospect, I believe this was the



Figure 4.13: Drift curves: velocity vs. E/P.

correct choice. While a feedback loop to stabilize the drift velocity is appealing, there are many pitfalls to this. The most obvious is the need to track not only field cage voltage but also the gating grid voltage accordingly. If the gating grid voltage is not adjusted, there will be a field mismatch at the gating grid, which will distort the drift field. Another concern is the stability of the feedback loop. It is conceivable to have a runaway feedback mechanism, either in the form of oscillations or a complete divergence from a reasonable voltage setting.

4.7.2 Imperfections in the Drift Field

There are many ways the the TPC drift field may be distorted. These include:

- Misalignment of the TPC in the magnet. If the center-line of the magnet does not correspond to the center-line of the TPC, there will be an ExB effect.

- Misalignment, bulging or other deformation of the central membrane will cause distortions near the center of the TPC.

- Misalignment of the TPC sectors in z.

- Mismatches in sector and field cage voltages

- Distortions due to defective wire connections, or lack of MWPC wires at sector boundaries

- ExB effect due to a component of the magnetic field in the $r - \phi$ direction. This is the major ExB effect we correct for, and is present in all solenoidal magnets.

It was shown [LWT00] in November 2000 that there is a constant distortion at the inner-outer sector boundary. This distortion has been attributed to a gap in the wiring of the MWPC. There is at least a 1 cm region near the inner-outer sector boundary (pad rows 13–14) which has no wiring. The field in that region is no longer uniform, and causes the distortion seen in Figure 4.14. Other distortions away from the boundary have been attributed to the $r - \phi$ magnetic field component.



Figure 4.14: Mean residual (cm) in xy plane vs. pad row for tracks with $0.4 < p_t < 1.2$ GeV/c. No electric or magnetic field distortion corrections applied. Note the discontinuity at pad row 13 and 14, which is the inner/outer sector boundary.

This effect was not apparent during the distortion study (Section 4.4.2) most likely because of two reasons. The first reason is that the distortion is bipolar across the sector boundary, which effectively canceled out when I averaged over both inner and outer sector pad rows. Secondly, the laser tracks are very wide, which reduces our sensitivity to distortions.

4.8 STAR TPC Slow Controls

The Gating Grid Drivers (GGD) for the TPC and FTPC as well as all other TPC subsystems are controlled using EPICS, the Experimental Physics and Industrial Control System. EPICS is a set of software tools and applications originally developed by Los Alamos National Laboratory and Argonne National Laboratory for the purpose of building distributed control systems to operate devices such as particle accelerators, large experiments, and telescopes. EPICS is built on a software communication bus. The functional subsystems, which provide data acquisition, supervisory control, closed loop control, archiving, and alarm management greatly reduce the need for low level programming.

Using EPICS, a substantial set of software has been developed to control the STAR TPC. This software includes distributed databases to provide local control of the TPC subsystems. The databases are loaded and executed in I/O Controllers (IOCs). The databases provide data acquisition, data conversion, alarm detection, interlocks, and closed loop control. The STAR IOCs consist of a VME back-plane, a 68020 CPU running the vxWorks real-time kernel, an ethernet connection, and a serial port. At UCLA, a database was developed to control the GGD. Control of the gating grid's analog input and output, along with digital output has been achieved.

At the heart of EPICS is Channel Access (CA), which is the software bus provided to communicate between various EPICS subsystems. CA allows the system components and user extended components to perform channel connections, gets, puts, and monitors on any field of the database using TCP and UDP protocols. Channel connections are performed by connecting a unique channel name to the IOC containing the channel. CA provides notification to its clients



Figure 4.15: Top level user interface for the STAR TPC slow controls. All TPC controls are accessible from this point of entry.

when a connection is broken and another notification when it re-connects. This connection management is used to keep all subsystems informed of the status of other IOCs, on which it may depend for parameter information. This is essential in STAR since all TPC subsystems are interconnected.

Although the software structure is quite complicated, the end user interacts with the TPC subsystems through easy to use Graphical User Interfaces (GUI's). The GUI's were built using the Motif-Based Editor and Display Manager (MEDM). MEDM allows the experimenter to easily control the relevant parameters for the TPC by taking care of CA. Figure 4.15 shows the top level user interface for the STAR TPC. From this point, an operator can control any of the TPC subsystems. Figure 4.16 shows the Gating Grid main control interface. From here, sectors may be controlled independently or together.

Figure 4.17 is the gating grid sector control interface. With this, the var-



Figure 4.16: User interface for the gating grid driver controls. From this GUI, the user can monitor the operating state all 48 sub-sectors.



Figure 4.17: User interface for the gating grid sector control. This GUI controls the power supply and high voltages for one sub-sector, sector 1-outer.