History Objects

ATLAS Software Workshop
Architecture Session

Dec 1 2003

Charles Leggett <charles.leggett@cern.ch>

Purpose

- Provide provenance of data objects to be able to fully recreate conditions under which they were produced.
- This entails recording all aspects of the job, such as initial run time configurations, default initializations, software release information, random number seeds, hardware specific options, OS, etc.
- Since there will be a lot of History Objects, want to minimize redundant and derivable data as much as possible.

History Objects

- Job History
  - date/time
  - os, cpu, hardware environment
  - ATLAS release
  - Algorithms created/used
  - Services created/used
  - jobOptions
  - created by the HistorySvc during initialization

- Service History
  - properties
  - identifier / version
  - pointer to Job History
  - created by ServiceManager when a new service is created, registered with HistorySvc via abstract interface

History Objects

- (sub)Algorithm History
  - properties
  - identifier / version
  - list of subAlgorithms it creates
  - pointer to Job History
  - created by Algorithm base class via abstract interface to HistorySvc
- AlgTools History
  - similar to Algorithms
- Data History
  - pointer to parent Algorithm History object
  - ClassID/key
  - store identifier
  - created by StoreGate during a record via abstract interface to HistorySvc

History Service

- Management of History Objects is performed by a History Service, accessed via the IHistorySvc abstract interface, located in GaudiKernel.
- Permits decoupling of HistorySvc from Gaudi and Athena.
- Provides access to History Objects, and associated properties, allowing users to trace provenance of an object to its parent Algorithm, Job, etc.

Implementation

- Implementation is transparent to users. Base classes of Algorithm, Service Locater, StoreGate, etc, are instrumented to create and update History Objects when appropriate.
- Will require a new StoreGate method: `update(...)` to replace `record(...)` when updating objects.
- Job/Service/Algorithm history objects are kept in their own store.
- Data History objects are kept in the main store.
- This makes persistification easier, as converters are triggered at the appropriate instant.