VIII. REFERENCES

- 1. Connolly EM: Fluoropolymers, in Chemical Economics Handbook. Menlo Park, Calif, SRI International, 1976, pp 580.0721A to 580.0721Q
- 2. Sherratt S: Polytetrafluoroethylene, in Kirk-Othmer Encyclopedia of Chemical Technology, ed 2 rev. New York, Interscience Publishers, 1966, vol 9, pp 805-31
- 3. Capodaglio E, Monarca G, Di Vito G: [Respiratory syndromes resulting from the inhalation of aliphatic fluoridated compounds during the preparation of polytetrafluoroethylene.] Rass Med Ind 30:124-39, 1961 (Ita)
- 4. "Teflon" Fluorocarbon Resins--Safety in Handling and Use. Wilmington, Del, EI du Pont de Nemours and Co, Plastics Dept, Fluorocarbons Division, 1970, 10 pp
- 5. Health and Safety Aspects of 'Fluon' Polytetrafluoroethylene, technical service note No. FIO, ed 2. Welwyn Garden City, Herts, England, Imperial Chemical Industries Ltd, Plastics Design, Moulding Powders Group, 1975, 17 pp
- 6. Carter VL Jr, Bafus DA, Warrington HP, Harris ES: The acute inhalation toxicity in rats from the pyrolysis products of four fluoropolymers. Toxicol Appl Pharmacol 30:369-76, 1974
- 7. Waritz RS, Kwon BK: The inhalation toxicity of pyrolysis products of polytetrafluoroethylene heated below 500 degrees centigrade. Am Ind Hyg Assoc J 29:19-26, 1968
- 8. Coleman WE, Scheel LD, Kupel RE, Larkin RL: The identification of toxic compounds in the pyrolysis products of polytetrafluoroethylene (PTFE). Am Ind Hyg Assoc J 29:33-40, 1968
- 9. Treon JF, Cappel JW, Cleveland FP, Larson EE, Aichley RW, Denham RT: The toxicity of the products formed by the thermal decomposition of certain organic substances. Ind Hyg Q 16:187-95, 1955
- 10. Harris DK: Polymer-fume fever. Lancet 7814:1008-11, 1951
- 11. Kakabadse GJ, Manohiu B, Bather JM, Weller EC, Woodbridge P: Decomposition and the determination of fluorine in biological materials. Nature 229:626-27, 1971
- 12. Kupel RE, Scheel LD: Experimental method for evaluating the decomposition of fluorocarbon plastics by heat. Am Ind Hyg Assoc J 29:27-32, 1968

- 13. Coleman WE, Scheel LD, Gorski CH: The particles resulting from polytetrafluoroethylene (PTFE) pyrolysis in air. Am Ind Hyg Assoc J 29:54-60, 1968
- 14. Birnbaum HA, Scheel LD, Coleman WE: The toxicology of the pyrolysis products of polychlorotrifluoroethylene. Am Ind Hyg Assoc J 29:61-64, 1968
- 15. Atkinson B, Atkinson VA: The thermal decomposition of tetra-fluoroethylene. J Chem Soc 108:2086-94, 1957
- 16. Lewis EE, Naylor MA: Pyrolysis of polytetrafluoroethylene. J Am Chem Soc 69:1968-70, 1947
- 17. Siegle JC, Muus LT, Lin T, Larsen HA: The molecular structure of perfluorocarbon polymers--II. Pyrolysis of polytetra-fluoroethylene. J Polym Sci Part A 2:391-404, 1964
- 18. Hygienic Guide Series--"Teflon" fluorocarbon resins and their decomposition products. Am Ind Hyg Assoc J 24:198-200, 1963
- 19. Zapp JA Jr, Limperos G, Brinker KC: Toxicity of pyrolysis products of "Teflon" tetrafluoroethylene resin, in Proceedings of the American Industrial Hygiene Association Annual Meeting, Cincinnati, April 26, 1955, 10 pp
- 20. Light TS, Fitzpatrick LF, Phaneuf JP: Thermogravimetric analysis of silica-filled polytetrafluoroethylene. Anal Chem 37:79-82, 1965
- 21. Errede LA: The application of simple equations for calculating bond dissociation energies to thermal degradation of fluorocarbons. J Org Chem 27:3425-30, 1962
- 22. Adams WGF: Polymer fume fever due to inhalation of fumes from polytetrafluoethylene. Trans Assoc Ind Med Off 13:20-21, 1963
- 23. Clayton JW Jr: Fluorocarbon toxicity and biological action. Fluorine Chem Rev 1:197-252, 1967
- 24. Zapp JA Jr: Polyfluorines, in Encyclopedia of Occupational Safety and Health. Geneva, International Labour Office, 1972, pp 1095-96
- 25. Duus HC: Thermochemical studies on fluorocarbons--Heat of formation of CF4, C2F4, C3F6, C2F4 dimer, and C2F4 polymer. Ind Eng Chem 47:1445-49, 1955
- 26. Madorsky SL, Hart VE, Straus S, Sedlak VA: Thermal degradation of tetrafluoroethylene and hydrofluoroethylene polymers in a vacuum. J Res Natl Bur Stand 51:327-33, 1953

- 27. Michaelsen JD, Wall LA: Further studies on the pyrolysis of polytetrafluoroethylene in the presence of various gases. J Res Nat Bur Stand 58:327-33, 1957
- 28. Atkinson B, Trenwith AB: The thermal decomposition of tetra-fluoroethylene. J Chem Soc 104:2082-87, 1953
- 29. Hygienic Guide Series--Teflon TFE-fluorocarbon resins and their decomposition products. Am Ind Hyg Assoc J 20:436-40, 1959
- 30. Thermal stability of Teflon. Nat Bur Stand Tech News Bull 38:43-45, 1954
- 31. Gloria HR, Stewart WJ, Savin RC: Initial Weight Loss of Plastics in a Vacuum, technical note No. D-1329. Langley, Va, National Aeronautics and Space Administration, 1962, 19 pp
- 32. Madorsky SL, Straus S: Thermal degradation of polychlorotrifluoroethylene, poly-alpha, beta, beta-trifluorostyrene, and polypara-xylylene in a vacuum. J Res Natl Bur Stand 55:223-30, 1955
- 33. Waritz RS: An industrial approach to evaluation of pyrolysis and combustion hazards. Environ Health Perspect 11:197-202, 1975
- 34. Bruton DM: Polymer fume fever. Br Med J 5876:757, 1967
- 35. Touey GP, Mumpower RC II: Measurement of the combustion zone temperature of cigarettes. Tobacco 144:18-22, 1957
- 36. Nuttall JB, Kelly RJ, Smith BS, Whiteside CK Jr: Inflight toxic reactions resulting from fluorocarbon resin pyrolysis. Aerosp Med 35:676-83, 1964
- 37. Barnes R, Jones AT: Polymer-fume fever. Med J Aust 2:60-61, 1967
- 38. Wegman DH, Peters JM: Polymer fume fever and cigarette smoking. Ann Intern Med 81:55-57, 1974
- 39. Evans EA: Pulmonary edema after inhalation of fumes from polytetrafluoroethylene (PTFE). J Occup Med 15:599-601, 1973
- 40. Robbins JJ, Ware RL: Pulmonary edema from Teflon fumes. N Engl J Med 271:360-61, 1964
- 41. Blandford TB, Seamon PJ, Hughes R, Pattison M, Wilderspin MP: A case of polytetrafluoroethylene poisoning in cockatiels accompanied by polymer fume fever in the owner. Vet Rec 96:175-76, 1975
- 42. Makulova ID: [The clinical picture in acute perfluoro-isobutylene poisoning.] Gig Tr Prof Zabol 9:20-23, 1965 (Rus)

- 43. Burns WA, Kanhouwa S, Tillman L, Saini N, Herrmann JB: Fibrosarcoma occurring at the site of a plastic vascular graft. Cancer 29:66-72, 1972
- 44. Harris HE Jr, Hawk WA: Laryngeal injection of Teflon paste--Report of a case with postmortem study of the larynx. Arch Otolaryngol 90:194-97, 1969
- 45. Russell FE, Simmers MH, Hirst AE, Pudenz RH: Tumors associated with embedded polymers. J Natl Cancer Inst 23:305-15, 1959
- 46. Polakoff PL, Busch KA, Okawa MT: Urinary fluoride levels in polytetrafluoroethylene fabricators. Am Ind Hyg Assoc J 35:99-106, 1974
- 47. Sherwood RJ: The hazards of Fluon (polytetrafluoroethylene). Trans Assoc Ind Med Off 5:10-12, 1955
- 48. Willard HH, Winter OB: Volumetric method for determination of fluorine. Ind Eng Chem, Anal Ed 5:7-10, 1933
- 49. Cavagna G, Finulli M, Vigliani EC: [Experimental study on the pathogenesis of the fever from inhaling Teflon fumes (polytetrafluoroethylene).] Med Lav 52:251-61, 1961 (Ita)
- 50. Machle W, Kitzmiller K: The effects of the inhalation of hydrogen fluoride--II. The response following exposure to low concentration. J Ind Hyg Toxicol 17:223-29, 1935
- 51. Machle W, Scott EW: The effects of the inhalation of hydrogen fluoride--III. Fluorine storage following exposure to sub-lethal concentrations. J Ind Hyg Toxicol 17:230-40, 1935
- 52. Machle W, Thamann F, Kitzmiller K, Cholak J: The effects of the inhalation of hydrogen fluoride--I. The response following exposure to high concentrations. J Ind Hyg Toxicol 16:129-45, 1934
- 53. Darmer KI Jr, Haun CC, MacEwen JD: The acute inhalation toxicology of chlorine pentafluoride. Am Ind Hyg Assoc J 33:661-68, 1972
- 54. Clayton JW Jr: The mammalian toxicology of organic compounds containing fluorine, in Handbook of Experimental Pharmacology, New Series. New York, Springer Verlag, 1966, vol 21, chap 9
- 55. Scheel LD, Lane WC, Coleman WE: The toxicity of polytetrafluoroethylene pyrolysis products—Including carbonyl fluoride and a reaction product, silicon tetrafluoride. Am Ind Hyg Assoc J 29:41-48, 1968
- 56. Zhemerdey AI: [Toxicity of tetrafluoroethylene.] Tr Leningr Sanit Gig Med Inst 44:164-76, 1958 (Rus)

- 57. Clayton JW Jr: The toxicity of fluorocarbons with special reference to chemical constitution. J Occup Med 4:262-73, 1962
- 58. Kochanov MM: [Data on the toxicology of chlorotrifluoroethylene]. Gig Tr Prof Zabol 2:25-31, 1958 (Rus)
- 59. Hood DB, Harrington ME, Barnes JR, Ranta KE, Gay DM: The toxicity of chlorotrifluoroethylene, in Proceedings of the American Industrial Hygiene Association Annual Meeting, Philadelphia, April 1956, 9 pp
- 60. Paulet G, Desbrousses S: [The toxicity of hexafluoropropylene (1).]
 Arch Mal Prof Med Trav Secur Soc 27:509-10, 1973 (Fre)
- 61. Clayton JW Jr, Delaplane MA, Hood DB: Toxicity studies with octafluorocyclobutane. Am Ind Hyg Assoc J 21:382-88, 1960
- 62. Lester D, Greenberg LA: Acute and chronic toxicity of some halogenated derivatives of methane and ethane. Arch Ind Hyg Occup Med 2:335-44, 1950
- 63. Vinyl Fluoride--Vinylidene Fluoride, technical report No. DP-6. Wilmington, Del, EI du Pont de Nemours and Co, Development Products, Freon Products Division, 1969, 14 pp
- 64. Clayton JW Jr, Hood DB, Raynsford GE: The toxicity of the pyrolysis products of "Teflon" TFE-fluorocarbon resins, in Proceedings of the American Industrial Hygiene Association Annual Meeting, Cincinnati, May 1959, 14 pp
- 65. Blagodarnaya OA: [Teflon fever caused by inhalation of products of the thermal-oxidative destruction of polytetrafluoroethylene.] Gig Tr Prof Zabol 17:25-29, 1973 (Rus)
- 66. Atkins E, Freedman LR: Studies in staphylococcal fever--I. Response to bacterial cells. Yale J Biol Med 35:451-71, 1963
- 67. Treon JF, Cleveland FP, Cappel J, Larson EE: The Toxicity of Certain Polymers With Particular Reference to the Products of Their Thermal Decomposition. Springfield, Va, US Dept of Commerce, National Technical Information Service, 1954, 60 pp (NTIS PB 115 873)
- 68. Zapp JA Jr: Toxic and health effects of plastics and resins: Arch Environ Health 4:335-46, 1962
- 69. Scheel LD, Robertson AB, Kupel RE, Richards DE, Cooper CV, Tolos WP, Vignati L: Toxicity of Pyrolysis Products from a Chlorotrifluoroethylene-Ethylene Copolymer (Halar Resin). Springfield, Va, US Dept of Commerce, National Technical Information Service, 1971, 25 pp (NTIS AD 751 436)

- 70. Ehrsam H: [Intoxications with lethal outcome in small pet birds after accidental overheating of cooking pans with polytetrafluoroethylene coating.] Schweiz Arch Tierheilkde 111:181-86, 1969 (Ger)
- 71. Griffith FD, Stephens SS, Tayfun FO: Exposure of Japanese quail and parakeets to the pyrolysis products of fry pans coated with Teflon and common cooking oils. Am Ind Hyg Assoc J 34:176-78, 1973
- 72. Tomatis L: Subcutaneous carcinogenesis by implants and by 7,12-dimethylbenz(a)anthracene. Tumori 52:1-16, 1966
- 73. Oppenheimer BS, Oppenheimer ET, Danishefsky I, Stout AP, Eirich FR: Further studies of polymers as carcinogenic agents in animals. Cancer Res 15:333-40, 1955
- 74. Bryson G, Bischoff F: The limitations of safety testing. Prog Exp Tumor Res 11:100-33, 1969
- 75. National Institute for Occupational Safety and Health: Criteria for a Recommended Standard...Occupational Exposure to Inorganic Fluorides, HEW Publication No. (NIOSH) 76-103. Rockville, Md, US Dept of Health, Education, and Welfare, Public Health Service, Center for Disease Control, NIOSH, 1975, 191 pp
- 76. National Institute for Occupational Safety and Health: Criteria for a Recommended Standard....Occupational Exposure to Hydrogen Fluoride, HEW Publication No. (NIOSH) 76-143. Rockville, Md, US Dept of Health, Education, and Welfare, Public Health Service, Center for Disease Control, NIOSH, 1976, 181 pp
- 77. Marchenko EM: [Fundamental problems of industrial hygiene in the processing of polyfluoroethylene resins.] Gig Tr Prof Zabol 10:12-18, 1968 (Rus)
- 78. American Conference of Governmental Industrial Hygienists Committee on Industrial Ventilation: Industrial Ventilation--A Manual of Recommended Practice, ed 14. Lansing, Mich, ACGIH, 1976, pp 1-1 to 14-8
- 79. American National Standards Institute Inc: Fundamentals Governing the Design and Operation of Local Exhaust Systems, ANSI Z9.2-1971. New York, ANSI, 1971, 63 pp
- 80. Okawa MT, Polakoff PL: Modern Industrial Plastics Division, Duriron Co-Dayton, Ohio, Health Hazard Evaluation/Toxicity Determination, report No. 72-29-28. Springfield, Va, US Department of Commerce, National Technical Information Service, 1973, 30 pp (NTIS PB 229 167)

- 81. Heyworth FF: Hydrogen fluoride, HF, in Patty FA: Industrial Hygiene and Toxicology, ed 2 rev; Toxicology (Fassett DW, Irish DD, eds). New York, Interscience Publishers, 1962, vol 2, pp 841-43
- 82. Dilley JV, Carter VL Jr, Harris ES: Fluoride ion excretion by male rats after inhalation of one of several fluoroethylenes or hexafluoropropene. Toxicol Appl Pharmacol 27:582-90, 1974
- 83. Scheel LD, McMillan L, Phipps FC: Biochemical changes associated with toxic exposures to polytetrafluoroethylene pyrolysis products. Am Ind Hyg Assoc J 29:49-53, 1968
- 84. American Conference of Governmental Industrial Hygienists: Threshold Limit Values for 1960. Arch Environ Health 1:140-44, 1960
- 85. American Conference of Governmental Industrial Hygienists: Threshold Limit Values for 1961. Cincinnati, ACGIH, 1961, p 12
- 86. American Conference of Governmental Industrial Hygienists: Threshold Limit Values for 1962. Cincinnati, ACGIH, 1962, p 12
- 87. American Conference of Governmental Industrial Hygienists: Threshold Limit Values for 1963. Cincinnati, ACGIH, 1963, p 9
- 88. American Conference of Governmental Industrial Hygienists:
 Documentation of the Threshold Limit Values for Substances in
 Workroom Air, ed 3, 1971. Cincinnati, ACGIH, 2nd printing, 1974, pp
 36-37
- 89. American Conference of Governmental Industrial Hygienists: TLV's-Threshold Limit Values for Substances in Workroom Air Adopted by ACGIH for 1972. Cincinnati, ACGIH, 1972, p 26
- 90. American Conference of Governmental Industrial Hygienists: TLV's-Threshold Limit Values for Chemical Substances and Physical Agents in the Workroom Environment with Intended Changes for 1974. Cincinnati, ACGIH, 1974, p 29
- 91. American Conference of Governmental Industrial Hygienists: TLVs-Threshold Limit Values for Chemical Substances and Physical Agents in the Workroom Environment with Intended Changes for 1976. Cincinnati, ACGIH, 1976, p 28
- 92. Permissible Levels of Toxic Substances in the Working Environment—Sixth Session of the Joint ILO/WHO Committee on Occupational Health, Geneva, 4-10 June 1968. Geneva, International Labour Office, 1968, p 336

IX. APPENDIX I

MATERIAL SAFETY DATA SHEET

The following items of information which are applicable to a specific product or material shall be provided in the appropriate block of the Material Safety Data Sheet (MSDS).

The product designation is inserted in the block in the upper left corner of the first page to facilitate filing and retrieval. Print in upper case letters as large as possible. It should be printed to read upright with the sheet turned sideways. The product designation is that name or code designation which appears on the label, or by which the product is sold or known by employees. The relative numerical hazard ratings and key statements are those determined by the rules in Chapter V, Part B, of the NIOSH publication, An Identification System for Occupationally Hazardous Materials. The company identification may be printed in the upper right corner if desired.

(a) Section I. Product Identification

The manufacturer's name, address, and regular and emergency telephone numbers (including area code) are inserted in the appropriate blocks of Section I. The company listed should be a source of detailed backup information on the hazards of the material(s) covered by the MSDS. The listing of suppliers or wholesale distributors is discouraged. The trade name should be the product designation or common name associated with the material. The synonyms are those commonly used for the product, especially formal chemical nomenclature. Every known chemical designation or

competitor's trade name need not be listed.

(b) Section II. Hazardous Ingredients

The "materials" listed in Section II shall be those substances which are part of the hazardous product covered by the MSDS and individually meet any of the criteria defining a hazardous material. Thus, one component of a multicomponent product might be listed because of its toxicity, another component because of its flammability, while a third component could be included both for its toxicity and its reactivity. Note that a MSDS for a single component product must have the name of the material repeated in this section to avoid giving the impression that there are no hazardous ingredients.

Chemical substances should be listed according to their complete name derived from a recognized system of nomenclature. Where possible, avoid using common names and general class names such as "aromatic amine," "safety solvent," or "aliphatic hydrocarbon" when the specific name is known.

The "%" may be the approximate percentage by weight or volume (indicate basis) which each hazardous ingredient of the mixture bears to the whole mixture. This may be indicated as a range or maximum amount, ie, "10-40% vol" or "10% max wt" to avoid disclosure of trade secrets.

Toxic hazard data shall be stated in terms of concentration, mode of exposure or test, and animal used, eg, "100 ppm LC50-rat," "25 mg/kg LD50-skin-rabbit," "75 ppm LC man," or "permissible exposure from 29 CFR 1910.1000," or, if not available, from other sources of publications such as the American Conference of Governmental Industrial Hygienists or the American National Standards Institute Inc. Flashpoint, shock sensitivity

or similar descriptive data may be used to indicate flammability, reactivity, or similar hazardous properties of the material.

(c) Section III. Physical Data

The data in Section III should be for the total mixture and should include the boiling point and melting point in degrees Fahrenheit (Celsius in parentheses); vapor pressure, in conventional millimeters of mercury (mmHg); vapor density of gas or vapor (air = 1); solubility in water, in parts/hundred parts of water by weight; specific gravity (water = 1); percent volatiles (indicated if by weight or volume) at 70 degrees Fahrenheit (21.1 degrees Celsius); evaporation rate for liquids or sublimable solids, relative to butyl acetate; and appearance and odor. These data are useful for the control of toxic substances. Boiling point, vapor density, percent volatiles, vapor pressure, and evaporation are useful for designing proper ventilation equipment. This information is also useful for design and deployment of adequate fire and The containment equipment. appearance and odor may facilitate identification of substances stored in improperly marked containers, or when spilled.

(d) Section IV. Fire and Explosion Data

Section IV should contain complete fire and explosion data for the product, including flashpoint and autoignition temperature in degrees Fahrenheit (Celsius in parentheses); flammable limits, in percent by volume in air; suitable extinguishing media or materials; special firefighting procedures; and unusual fire and explosion hazard information. If the product presents no fire hazard, insert "NO FIRE HAZARD" on the line labeled "Extinguishing Media."

(e) Section V. Health Hazard Information

The "Health Hazard Data" should be a combined estimate of the hazard of the total product. This can be expressed as a TWA concentration, as a permissible exposure, or by some other indication of an acceptable standard. Other data are acceptable, such as lowest LD50 if multiple components are involved.

Under "Routes of Exposure," comments in each category should reflect the potential hazard from absorption by the route in question. Comments should indicate the severity of the effect and the basis for the statement if possible. The basis might be animal studies, analogy with similar products, or human experiences. Comments such as "yes" or "possible" are not helpful. Typical comments might be:

Skin Contact--single short contact, no adverse effects likely; prolonged or repeated contact, possibly mild irritation.

Eye Contact--some pain and mild transient irritation; no corneal scarring.

"Emergency and First Aid Procedures" should be written in lay language and should primarily represent first-aid treatment that could be provided by paramedical personnel or individuals trained in first aid.

Information in the "Notes to Physician" section should include any special medical information which would be of assistance to an attending physician including required or recommended preplacement and periodic medical examinations, diagnostic procedures, and medical management of overexposed employees.

(f) Section VI. Reactivity Data

The comments in Section VI relate to safe storage and handling of hazardous, unstable substances. It is particularly important to highlight instability or incompatibility to common substances or circumstances, such as water, direct sunlight, steel or copper piping, acids, alkalies, etc. "Hazardous Decomposition Products" shall include those products released under fire conditions. It must also include dangerous products produced by aging, such as peroxides in the case of some ethers. Where applicable, shelf life should also be indicated.

(g) Section VII. Spill or Leak Procedures

Detailed procedures for cleanup and disposal should be listed with emphasis on precautions to be taken to protect employees assigned to cleanup detail. Specific neutralizing chemicals or procedures should be described in detail. Disposal methods should be explicit including proper labeling of containers holding residues and ultimate disposal methods such as "sanitary landfill," or "incineration." Warnings such as "comply with local, state, and federal antipollution ordinances" are proper but not sufficient. Specific procedures shall be identified.

(h) Section VIII. Special Protection Information

Section VIII requires specific information. Statements such as "Yes," "No," or "If necessary" are not informative. Ventilation requirements should be specific as to type and preferred methods. Respirators shall be specified as to type and NIOSH or US Bureau of Mines approval class, ie, "Supplied air," "Organic vapor canister," etc. Protective equipment must be specified as to type and materials of construction.

(i) Section IX. Special Precautions

"Precautionary Statements" shall consist of the label statements selected for use on the container or placard. Additional information on any aspect of safety or health not covered in other sections should be inserted in Section IX. The lower block can contain references to published guides or in-house procedures for handling and storage. Department of Transportation markings and classifications and other freight, handling, or storage requirements and environmental controls can be noted.

(j) Signature and Filing

Finally, the name and address of the responsible person who completed the MSDS and the date of completion are entered. This will facilitate correction of errors and identify a source of additional information.

The MSDS shall be filed in a location readily accessible to employees exposed to the hazardous substance. The MSDS can be used as a training aid and basis for discussion during safety meetings and training of new employees. It should assist management by directing attention to the need for specific control engineering, work practices, and protective measures to ensure safe handling and use of the material. It will aid the safety and health staff in planning a safe and healthful work environment and in suggesting appropriate emergency procedures and sources of help in the event of harmful exposure of employees.

MATERIAL	SAFETY	DATA	SHEET	
I PROD	UCT IDENTIFICA	ATION		
MANUFACTURER'S NAME	REGULAR TELEPHONE NO EMERGENCY TELEPHONE NO			
ADDRESS				
TRADE NAME				
SYNONYMS				
II HAZA	RDOUS INGRED	IENTS		
MATERIAL OR COMPON	MATERIAL OR COMPONENT		HAZARD DATA	
111	PHYSICAL DATA	A		
BOILING POINT, 760 MM HG	MEL-	MELTING POINT		
SPECIFIC GRAVITY (H2O=1)	VAPO	VAPOR PRESSURE		
VAPOR DENSITY (AIR=1)	SOLI	SOLUBILITY IN H ₂ O. % BY WT		
% VOLATILES BY VOL	EVA	EVAPORATION RATE (BUTYL ACETATE 1)		
APPEARANCE AND ODOR				

IV FIRE	AND EXPLO	SION DATA	
FLASH POINT (TEST METHOD)		AUTOIGNITION TEMPERATURE	
FLAMMABLE LIMITS IN AIR, % BY VOL.	LOWER		UPPER
EXTINGUISHING MEDIA		4	1
SPECIAL FIRE FIGHTING PROCEDURES			
UNUSUAL FIRE AND EXPLOSION HAZARD			
V HEALTI	H HAZARD I	NFORMATION	ĺ
HEALTH HAZARD DATA			
ROUTES OF EXPOSURE			
INHALATION			
SKIN CONTACT			
SKIN ABSORPTION			
EYE CONTACT			
INGESTION			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
EFFECTS OF OVEREXPOSURE ACUTE OVEREXPOSURE			WW. 144.5.
CHRONIC OVEREXPOSURE			
EMERGENCY AND FIRST AID PROCEDURES			
EYES			
SKIN			
INHALATION			
INGESTION			
NOTES TO PHYSICIAN	•		

VI REACTIVITY DATA
CONDITIONS CONTRIBUTING TO INSTABILITY
INCOMPATIBILITY
HAZARDOUS DECOMPORITION PRODUCTS
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION
VII SPILL OR LEAK PROCEDURES
STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED
NEUTRALIZING CHEMICALS
WASTE DISPOSAL METHOD
VIII SPECIAL PROTECTION INFORMATION
VENTILATION REQUIREMENTS
SPECIFIC PERSONAL PROTECTIVE EQUIPMENT
RESPIRATORY (SPECIFY IN DETAIL)
EYE
GLOVES
OTHER CLOTHING AND EQUIPMENT .

IX SPECIAL PRECAUTIONS
PRECAUTIONARY STATEMENTS
OTHER HANDLING AND STORAGE REQUIREMENTS
PREPARED BY
ADDRESS
DATE

Х. **TABLES**

TABLE X-1

USES OF FLUOROCARBON POLYMERS

Bearing pads Microwave components

Bearings Packings

Bellows Pipe lining

Chemical transfer tubing Piston rings

Conveyor belting Printed circuits

Prostheses

Seals

Electrical insulation Pyrotechnics

Spaghetti tubing

Filters Thread seal tapes

Fuel and hydraulic hose Tool coatings

Gaskets Vessel linings

Laboratory ware

Adapted from reference 4

Films

Cookware coatings

Feedthrough and standoff terminals

TABLE X-2
PTFE DECOMPOSITION PRODUCTS

Compound	Pyrolysis Temperature (C)	Reference
Particulate	140–325	10
material	200	19
	350	64
	400–450	7
HF	300	22
HFE	300-360	19
OFCB	300-360	19
SiF4	300-360	19
	700	8
PFIB	380-400	19
	475–480	7
	500-550	19
Hydrolyzable	400-450	7
fluoride	625	6
	800	6
HFP	450-480	7
	500-550	19
TFE	450-480	7
	500-550	19
COF 2	490-900	8
CF4	550	8
CO	800	6
CO2	800	6

TABLE X-3

TYPICAL MASS SPECTRUM OF GASES
OBTAINED FROM PTFE PYROLYSIS AT 550 C IN AIR

Mass-Charge		Scale	Relative
Ratio	Ion	Divisions	Abundance
m/e	(+)		(N2 = 100)
12	С	11.0	0.10
14	N	608.0	5.26
16	0	201.0	1.74
19	F	2.0	0.02
20	HF	19.0	0.16
23.5	COF	1.2	0.01
28	N2	11,540.0	100.00
31	CF	20.0	0.17
32	02	3,116.0	27.18
40	A	276.0	2.40
44	CO 2	199.0	1.72
47	COF	218.0	1.90
50	CF2	13.0	0.11
66	COF 2	134.0	1.16
69	CF3	72.0	0.62
81	C2F3	0.4	0.003
85	SiF3	0.0	0.00
100	C2F4	14.0	0.12
119	C2F5	7.0	0.06
131	C3F5	12.0	0.10

From reference 8

TABLE X-4

TYPICAL MASS SPECTRUM OF PARTICULATE
OBTAINED FROM PTFE PYROLYSIS AT 550 C IN AIR

ive ance
10
28
64
00
73
73
00
73
80
00
55
73
83
50
34
70
40
30
47
02
64
58
73
83
55
28
40
10
30
55
, ,
20
-0
15
IJ

From reference 13

DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE

PUBLIC HEALTH SERVICE

CENTER FOR DISEASE CONTROL

NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH

ROBERT A TAFT LABORATORIES

4676 COLUMBIA PARKWAY CINCINNATI. OHIO 45226

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300



POSTAGE AND FEES PAID

U.S. DEPARTMENT OF H.E.W.

HEW 399