

STOCK ITEMS

5180-01-368-3526 Computer Repair Kit Price - \$24.74 KT

Eleven demagnetized tools for nonelectric tasks. Contains IC inserter with pin straightener, three-way ratchet driver – 1/4", three



Phillips screwdrivers - sizes 0, 1 and 2, and five straight edge screwdrivers.

5180-01-378-4517 Computer Repair Kit Price - \$57.20 KT

This 12-piece computer repair kit comes in a durable rollup pouch with individual compartments for each item.

Consists of 4 to 6 screwdriver and nut-driver blades that are interchangeable with the provided handle. Several of the tools are antistatic in nature to protect computer chips from



ESD damage. Kit includes: One 3/16" flat-tip screwdriver blade; one No. 0 point and one No. 1 point Phillips screwdriver blade; one 3/16" hex and one 1/4" hex nutdriver blade; one T-10 Torx and one T-15 Torx screwdriver blade; one screwdriver/nutdriver handle; one chip retriever; one chip tweezers; one chip extractor and one chip inserter.

5180-01-424-9185 Computer Repair Kit Price - \$74.90 KT

The Jensen PC Mini Kit has everything you need for minor PC service and repair. Comes with 15 tools, including an IC

extractor; an IC inserter; a 3/16" nutdriver; a 1/4" nutdriver; a 3-prong parts holder; a penlight; a 4-1/4" diagonal-cutting pliers; 4-1/4" diagonal-cutting pli-



ers; a 4-3/4" long-nose pliers; a No.0 point Phillips screwdriver; a no.1 point Phillips screwdriver; a 1/8" slotted screwdriver; a 3/16" slotted screwdriver; a TT10 Tamperproof Torx Driver; a TT15 Tamper Torx Driver; and a Trimpot tool. Comes in a lightweight zipper case.

5180-01-432-3144 Computer Repair Kit Price - \$98.93 KT

Kit contains: Two swivel-head Phillips screwdrivers sizes 00 (6-1/4" lg.), 0 (7-1/8" lg.); two swivel-head slotted

screwdrivers sizes 3/32" (6-1/8) and 1/8" (7-5/8); a Phillips screwdriver size 2; a regular slotted screwdriver size 3/16"; two hollow shaft nutdrivers size



3/16" and 1/4"; screwstarter with pocket clip for Torx size T-10, T-15, T-20, T-25, T-27 & T-30 as well as most Allen hex and Phillips; 1" x 2" oval inspection mirror with pocket clip; syringe style mechanical finger; crosslock tweezers; needle-nose pliers; PC chip remover and inspection light with 6" flex and focus beam. Comes in compartmented, foam-padded, zippered vinyl canvas tool pouch.

5110-01-414-4918 E-Z OUT™ Pocket Knife

Price - \$24.84 EA Lock-Back folding knife; includes a belt clip. High carbon stainless steel 3.5" blade with non-glare satin finish. Fiscars Inc. E-Z OUT



(P/N 06701). Knife is 8" open, 4-3/4" closed.

5110-00-288-8722 Circle Cutter Price - \$171.76 EA

Adjustable cutter with hardened tool steel blades cuts washers and gaskets from sheet asbestos, rubber, leather, canvas, cork, felt and



similar materials. Movable pivoting block style consists of a plastic block with 1/32" graduations, pivot post with nut and washers, cutter blades, pivot pins and cutting board with centering ferrule. Also includes a single cutter blade holder and six blades. Cutter without extensions cuts irregular lines and circles, odd shapes and strips. Cuts materials from 0.001 to 3/8" thick and has a 1/4 to 6" cutting diameter. Includes six pivot pins. Square cutting board measures 6. Comes with a plastic or metal case.

STOCK ITEMS

5110-01-385-7393 Ergonomic Scissors Price - \$13.12 EA

OLO brand rolling scissors operate by rolling instead of squeezing. This comfort cut eliminates hand cramps and fatigue, and also makes cutting painless for people with arthritis or carpal tunnel syndrome. The nonpoint blades provide safety, precision, flexibility and durability.



*110.01.412.0010

5110-01-412-8019 Utility Knife Price - \$5.11 EA

Heavy duty shop utility knife, with self-retracting blade. Die cast zinc alloy construction. Blade is exposed only when thumb is pressed for-



ward on button, blade retracts automatically into handle when thumb is released from button. Used for right or left hand operation. Overall length 5-1/2".

5120-00-243-1689 Socket Extension (Solid Shank) Price - \$4.03 EA

Extend the reach of the socket for use in tight and confined areas. Chromium-plated steel extension bar has female/male square drive ends and a solid shank. Has a 3/8" drive, 3" length.

5120-00-757-7653 Insertion and Removal Tool Price - \$1.37 EA

Remove and install size 22 contacts, Deutsch P/Ns 2841-5-9000 (pin) and 2803-4-000 (socket) from Deutsch type RE, RSM and RTK connectors with this combination tool. Color-coded with a yellow installing tip and a white removal tip. Deutsch P/N M 15570-22-1 or equal.

5130-00-063-2923 Abrasive Wheel (Cutting Off) Price - \$3.42 EA

Aluminum oxide grinding wheel is for slicing or parting metal material. ANSI B74.2. Wheel is grade R, with a grain



size of 30 and a resinoid-reinforced bond type. Has a 4" diameter, 3/16" thickness and 3/8" arbor hole diameter.

5110-00-142-5010 Keyhole Saw (Wood-Cutting) Price - \$6.15 EA

Keyhole saw features a hardened and tempered blade and a hardwood or plastic handle that allows for blade replacement. The blade is 10" long and is



tapered in width from 1/2 to 13/16" with 10 points per".

5110-00-293-0090 Nested Saw Set Price - \$11.87 SE

Nested saw set consists of an enclosed-grip, rugged, plastic handle for comfort and safety and three blades. The handle has a simple bolt and wingnut for fast and easy blade changing. First blade is a 12-long compass blade with eight points per" for small and intricate shape cutting in wood. Disston Part#102

5180-01-441-6698 Highway Safety Tool Kit Price - \$66.83 KT

This Highway Safety Tool Kit contains essential highway safety items in a slim plastic storage box. The tool kit is designed to fit in car trunks, under van and utility vehicle seats, and behind the seat of most pickup trucks. Highway safety tool kit consists of the following components: 1 Thermal reflective blanket;1 12 ft. Battery booster cable; 1 Utility cutter; 1 D-cell size flashlight; 1 pair cotton gloves; 2 Yellow chemical light stick; 1 Inflatable pillow; 1 8 Slip joint pliers; 2 Highway warning reflector; 1 Cross and Flat tip screwdriver.

STOCK ITEMS

5120-00-169-2986 Torque Multiplier (Electronic Display) 5-1/16" x 6-5/8" x 9-1/4" PRICE - \$2695.66 (EA)

Digital readout accuracy within +/- 2% of actual output torque from 20% of rated maximum torque to the rated maximum torque. Clockwise/counter-clockwise operation. Protractor is graduated 180° in 1° increments. Has zero backlash. Operates from minus -25 to +120°F. Powered by 9v battery. Easy zero adjustment. Requires torque wrench bar NSN 5120-01-008-3632.

Has a 1200-ft-lb rated maximum output torque (1.0 ft-lb. increment) and a 6"-long x 3/4" square male output shaft. Furnished in a carrying case with a 3/8" male input crank, a 3/4" square female output shaft and a set of instructions. Weighs approximately 20 lb.

Consolidated Devices Model No. DPT-1200

5120-00-482-2543 Torque Multiplier (Electronic Display) 8" x 11" x 6-1/4" PRICE - \$5163.68 (EA)

Digital readout accuracy within +/- 2% of actual output torque from 20% of rated maximum torque to the rated maximum torque. Clockwise/counter-clockwise operation. Protractor is graduated 180° in 1° increments. Has zero backlash. Operates from minus -25 to +120°F. Powered by 9v battery. Easy zero adjustment. Requires torque wrench bar NSN 5120-01-008-3632.

Has a 2500-ft-lb rated maximum output torque (in 1.0 ft-lb increments) and a 8"-long x 1" square male output shaft. Furnished in a carrying case with a 3/8" male input crank, a 1" square female output shaft and a set of instructions. Weighs approximately 38 lb.

Consolidated Devices Model No. DPT-2500

5120-00-337-9652 Torque Multiplier 18.71" L x 12.90" W x 7.52" D PRICE - \$3939.66 (EA)

A multiplier, torque wrench is used to facilitate the loosening and tightening of propeller shaft retaining nuts, aircraft engine thrust bearing nuts, helicopter rotor clutch, fan and transmission nuts, turbo-jet engine turbine couplings and bearing retaining nuts. When used with a torque wrench or socket, torque multiplier increases the available output torque.

Torque multiplier has a maximum rated output torque of 12,000 ft-lb. in both the clockwise and counterclockwise direction. Multiplier consists of a metal housing containing a precision planetary gear multiplier having a torque gear ratio of 10.7 to 1. Multiplier has a 3/4" female square drive input in accordance with ANSI B107.4 on both sides of the multiplier. Output consists of sleeve splines with a slide fit for a male spline of 8/16" pitch, 43 teeth, 30° pressure angle and 5.375" pitch diameter, with a diameter of 5.651 to 5.669" over 0.226-pins and an outside diameter of 5.475" plus 0 and minus 0.0005". Weighs approximately 46 lb.

Consolidated Devices Model No. 12000STM

5120-00-574-9318 Torque Multiplier 25" long PRICE - \$404.28 (EA)

A multiplier, torque wrench is used to facilitate the loosening and tightening of propeller shaft retaining nuts, aircraft engine thrust bearing nuts, helicopter rotor clutch, fan and transmission nuts, turbo-jet engine turbine couplings and bearing retaining nuts. When used with a torque wrench or socket, torque multiplier increases the available output torque.

Torque multiplier has a maximum rated output torque of 2000 ft-lb. in both the clockwise and counterclockwise directions. Multiplier consists of a detachable reaction bar and a metal housing containing a precision planetary gear multiplier having a torque gear ratio of 4 to 1. Multiplier has a 3/4" female square drive input and a 1" male square drive output in accordance with ANSI B107.4. Weighs approximately 17 lb.

If you have any questions you may contact:

