

AFNI Jazzercise Answers

Below are the solutions to the AFNI Jazzercise questions.

1. `3dbucket -prefix some_stats func_slim+orig'[0,3-']'`
2. `3dMean -prefix anat_mean anat1+orig anat2+orig anat3+orig`
3. `3dAutomask -prefix anat_auto anat+orig`
`3dSkullStrip -input anat+orig -prefix anat_3dSkull &`
4. Making and Playing with ROI Masks:
 - a. `3dcalc -a 'func_slim+orig[2]' -b 'func_slim+orig[4]' \`
`-expr 'ispositive(a-4.2) * ispositive(b-4.2)' \`
`-prefix PN_mask`
 - b. `3dcalc -a 'func_slim+orig[2]' -b 'func_slim+orig[4]' \`
`-expr 'ispositive(a-4.2) + 2 * ispositive(b-4.2)' \`
`-prefix PN_mask_4`
 - c. Use the “**Pos?**” toggle button (in the AFNI GUI→Define OverLay) for positive-only intensities, and set the “**#****” (number of colors) to 4. Red, orange and yellow are values 1, 2, and 3, respectively. Alternatively, use one of the ROI color scales (right click on the overlay color bar) for the overlay named (ROI_32) and use a corresponding maximum, i.e. 32 with positive only intensities.
 - d. `3dROIstats -mask PN_mask+orig -quiet epi_r1+orig > PN_mean.1D`
5. Fun with 1D files:
 - a. `count -column 1 10 > col1.1D`
`count -column 11 20 > col2.1D`
`count -column 21 30 > col3.1D`

`or`

`count 1 10 > row1.1D`
`count 11 20 > row2.1D`
`count 21 30 > row3.1D`

`1dtranspose row1.1D > col1.1D`
`1dtranspose row2.1D > col2.1D`
`1dtranspose row3.1D > col3.1D`
 - b. `1dcat col1.1D col2.1D col3.1D > 3cols.1D`

`or`

`1dcat col?.1D > 3cols.1D`

`or`

`1dcat row1.1D\' row2.1D\' row3.1D\' > 3cols.1D`
 - c. `1dcat col1.1D col2.1D col3.1D \`
`col3.1D col2.1D col1.1D > 6cols.1D`

`or`

`1dcat 3cols.1D'[0..$,$.0]' > 6cols.1D`

```
d. 1daval -a '6cols.1D[0]' -b '6cols.1D[1] \
      -c '6cols.1D[2]' -d '6cols.1D[3] \
      -e '6cols.1D[4]' -f '6cols.1D[5] \
      -expr '(a+b+c+d+e+f)/6' > ex_mean.1D
```

or

```
3dTstat -mean -prefix ex_mean.1D 6cols.1D
```

6. Fun with the afni GUI:

- Right-click the gray-scale bar of any viewing plane (e.g., sagittal) and select the **Choose Display Mode Range**. Type in the numbers **500 1500**.
- Go to Define OverLay in the afni GUI. For both OLay and Thr select sub-brick #0 (Full F-stat). To display only positive overlay values, click on the “**Pos?**” button. To show only 8 panels in the color bar, select the “**#8**” button. Now place your cursor on the color panel that is colored pink. If you leave your cursor there for a moment, the numbers 14.2-28.4 will appear. This means that F-values that fall within this range will appear in the OverLay dataset as pink. To change the color from pink to lime green, left-click on the pink panel and a hidden pop-up menu will appear that allows you to change the color.
- The easiest way to save a jpeg file is to right-click on the **Sav1.ppm** button in the sagittal viewer. This will open a hidden menu that allows you to save the image as a ppm, jpg, gif, tif, etc. Select the **jpg** button. This will change the Sav1.ppm to a **Sav1.jpg** button. Click on that and type in the prefix name **cool_slide** and save it.
- Right click in one of the viewing planes (e.g., sagittal), which will open a hidden menu. Select the **Talairach To** button and select the right fusiform gyrus from the menu.
- Go to the sagittal viewer and click on the **Mont** (Montage) button at the bottom of the viewer. This will open the Montage controller. Select **3** slices Across, **2** slice Down and **Set**.
- The Mission Statement is hidden in the empty space in the bottom left-hand corner of the afni GUI (just to the right of the **Done** button). Right-click in this empty space to gain access to the Mission Statement and other AFNI tidbits.

7. Doing calculations in AFNI:

- 3dinfo func_slim+orig

In the output, look for lines starting with ‘--At sub-brick’. The datum type is given following ‘datum type is’.

- ccalc ‘22.3 * 44.5’

8. Image Filtering:

- 3dmerge -lblur_fwhm 8 -doall -prefix ex_blur8 epi_r1+orig
- 3dLocalstat -nbhd ‘RECT(-3,0,0)’ -stat min \
 -prefix ex_minx3 anat+orig
- 3danisosmooth -viewer -prefix ex_anisotest ex_minz3+orig
 3danisosmooth -prefix ex_aniso -iters 3 ex_minz3+orig

9. Random Exercises with AFNI Datasets:

- a. `3dinfo anat+orig` (and look for `-orient`)
`3daxialize -prefix exLPI -orient LPI anat+orig`
`3dresample -prefix exLPI -orient lpi -inset anat+orig`
- b. `3dbucket -prefix ex_fneg_coef func_slim+orig'[3]'`
`3dbucket -prefix ex_fneg_tstat func_slim+orig'[4]'`
- c. `3dbucket -prefix ex_fneg \`
`ex_fneg_coef+orig ex_fneg_tstat+orig`
- d. `adwarp -apar anat+tlrc -dpar func_slim+orig \`
`-prefix func_slim4mm -dxyz 4`
- e. `3dmaxima -input func_slim+orig'[0]' | head`
`whereami -38.9 28.72 -1.93 -rai`
- f. `3dZcutup -keep 40 90 -prefix anat_40_90 anat+orig`