


IONIZATION COOLING (BUDKER, SKRINSKY) *

- Schematic of basic principle
(see figure)
- $\frac{dE}{dz}$ in Li, Be, LiH reduces both longitudinal and transverse momentum a subsequent *rf* cavity restore p_{\parallel}
- Combined effect is: beam divergence is reduced. Transverse $\epsilon_n \rightarrow$ decreases.
- MULTIPLE SCATTERING is source of heat $\epsilon_n \rightarrow$ increases

*



$\mu^+ \mu^-$ COLLIDER

†

- Emittance rate of change

$$\frac{d\epsilon_n}{dz} = -\frac{\epsilon_n}{E\beta^2} \left\| \frac{dE}{dz} \right\| + 0.5\beta\gamma \frac{d\langle\theta^2\rangle}{dz}$$

- MINIMUM EMITTANCE

$$\epsilon_n \approx \frac{0.5E_s^2\beta_\perp}{m_\mu c^2\beta} (L_R \|dE/dz\|)^{-1}$$

- Best material for cooling, Li, LiH, Be



Material	ρ [g/cm ³]	dE/dx [MeV/cm]	L _R [cm]	cof.of β_{\perp} [mm mr/cm]
liq.H ₂	0.071	0.286	890.	42
liq.He	0.125	0.242	756.	59
LiH	0.82	1.34	102.	78
Li	0.534	0.875	155.	79
Be	1.848	2.95	35.3	103

‡

