
FIPS 140-2 Validation Certificate



The National Institute of Standards and Technology of the United States of America





Certificate No. 427

The National Institute of Standards and Technology, as the United States FIPS 140-2 Cryptographic Module Validation Authority; and the Communications Security Establishment, as the Canadian FIPS 140-2 Cryptographic Module Validation Authority; hereby validate the FIPS 140-2 testing results of the Cryptographic Module identified as:

2691 and 3725 Modular Access Routers with AIM-VPN/EPII and 3745 Modular Access Router with AIM-VPN/HPII by Cisco Systems, Inc.

(When operated in FIPS mode)

In accordance with the Derived Test Requirements for FIPS 140-2, Security Requirements for Cryptographic Modules. FIPS 140-2 specifies the security requirements that are to be satisfied by a cryptographic module utilized within a security system protecting Sensitive Information (United States) or Designated Information (Canada) within computer and telecommunications systems (including voice systems).

Products which use the above identified cryptographic module may be labeled as complying with the requirements of FIPS 140-2 so long as the product, throughout its life cycle, continues to use the validated version of the cryptographic module as specified in this certificate. The validation report contains additional details concerning test results. No reliability test has been performed and no warranty of the products by both agencies is either expressed or implied.

This certificate includes details on the scope of conformance and validation authority signatures on the reverse.

FIPS 140-2 provides four increasing, qualitative levels of security: Level 1, Level 3, and Level 4. These levels are Intended to cover the wide range and potential applications and environments in which cryptographic modules may be employed. The security requirements cover eleven areas related to the secure design and implementation of a cryptographic module. The scope of conformance achieved by the cryptographic modules as tested in the product identified as:

2691 and 3725 Modular Access Routers with AlM-VPN/EPII and 3745 Modular Access Router with AlM-VPN/HPII by Cisco Systems, Inc. (Hardware Versions: 2691, 3725 and 3745 with AlM-VPN/EPII Version 1.0, Board Version AO and AlM-VPN/HPII Verson 1.0

Board Version AO, and Firmware Version: IOS 12.3(3d); Hardware)

	Atlan Laboratories, NVLAP LAB GOUE 200492-0,
and tested by the Cryptographic Module Testing accredited laboratory:	CRYPTIK Version 4.5

as		

Cryptographic Module Specification: Level 2 Cryptographic Module Ports and Interfaces: Level 2

Roles, Services, and Authentication: Level 2 Finite State Model: Level 2

Physical Security: Level 2 Cryptographic Key Management: Level 2

(Multi-Chip Standalone)

EMI/EMC: Level 2 Self Tests: Level 2

Design Assurance: Level 2 Mitigation of Other Attacks: Level N/A

Operational Environment: Level N/A tested in the following configuration(s): N/A

The following FIPS approved Cryptographic Algorithms are used: DES (Certs. #202 and #206); Triple-DES (Certs. #156 and #160); DES-MAC (Cert. #202, vendor affirmed); Triple-DES MAC (Cert. #156, vendor affirmed); AES (Certs. #46 and #51); SHA-1 (Certs. #26 and #144); HMAC-SHA-1 (Cert. #26, vendor affirmed); RSA (PKCS#1, vendor affirmed)

The Cryptographic module also contains the following non-FIPS approved algorithms: MD4; MD5; HMAC-MD5; Diffie-Hellman (key agreement)

Overall Level Achieved: 2

Signed on behalf of the Government of the United States

Signature:

Dated: 4 M ~ Jooy

Chief, Computer Security Division
National Institute of Standards and Technology

Signed on behalf of the Government of Canada

Signature: A Condord

Dated: 4 Hay 04.

Director, Information Protection Group
The Communications Security Establishment