## §430.00

by the application of best practicable control technology currently available (BPT).

- 430.93 Effluent limitations representing the degree of effluent reduction attainable by the best conventional pollutant control technology (BCT).
- 430.94 Effluent limitations representing the degree of effluent reduction attainable by the application of best available technology economically achievable (BAT).
- 430.95 New source performance standards (NSPS).
- 430.96 Pretreatment standards for existing sources (PSES).
- 430.97 Pretreatment standards for new sources (PSNS).

### Subpart J—Secondary Fiber Non-Deink Subcategory

- 430.100 Applicability; description of the secondary fiber non-deink subcategory.
- 430.101 Specialized definitions.
- 430.102 Effluent limitations representing the degree of effluent reduction attainable by the application of best practicable control technology currently available (BPT).
- 430.103 Effluent limitations representing the degree of effluent reduction attainable by the best conventional pollutant control technology (BCT).
- 430.104 Effluent limitations representing the degree of effluent reduction attainable by the application of best available technology economically achievable (BAT).
- 430.105 New source performance standards (NSPS).
- 430.106 Pretreatment standards for existing sources (PSES).
- 430.107 Pretreatment standards for new sources (PSNS).

#### Subpart K—Fine and Lightweight Papers From Purchased Pulp Subcategory

- 430.110 Applicability; description of the fine and lightweight papers from purchased pulp subcategory.
- 430.111 Specialized definitions.
- 430.112 Effluent limitations representing the degree of effluent reduction attainable by the application of best practicable control technology currently available (BPT).
- 430.113 Effluent limitations representing the degree of effluent reduction attainable by the best conventional pollutant control technology (BCT).
- 430.114 Effluent limitations representing the degree of effluent reduction attainable by the application of best available technology economically achievable (BAT).

# 40 CFR Ch. I (7–1–03 Edition)

- 430.115 New source performance standards (NSPS).
- 430.116 Pretreatment standards for existing sources (PSES).
- 430.117 Pretreatment standards for new sources (PSNS).

### Subpart L—Tissue, Filter, Non-Woven, and Paperboard From Purchased Pulp Subcategory

- 430.120 Applicability; description of the tissue, filter, non-woven, and paperboard from purchased pulp subcategory.
- 430.121 Specialized definitions.
- 430.122 Effluent limitations representing the degree of effluent reduction attainable by the application of best practicable control technology currently available (BPT).
- 430.123 Effluent limitations representing the degree of effluent reduction attainable by the best conventional pollutant control technology (BCT).
- 430.124 Effluent limitations representing the degree of effluent reduction attainable by the application of best available technology economically achievable (BAT).
- 430.125 New source performance standards (NSPS).
- 430.126 Pretreatment standards for existing sources (PSES).
- 430.127 Pretreatment standards for new sources (PSNS).
- APPENDIX A TO PART 430—METHODS 1650 AND 1653

AUTHORITY: Sections 301, 304, 306, 307, 308, 402, and 501 of the Clean Water Act, as amended, (33 U.S.C. 1311, 1314, 1316, 1317, 1318, 1342, and 1361), and Section 112 of the Clean Air Act, as amended (42 U.S.C. 7412).

SOURCE: 63 FR 18635, Apr. 15, 1998, unless otherwise noted.

#### GENERAL PROVISIONS

#### §430.00 Applicability.

(a) This part applies to any pulp, paper, or paperboard mill that discharges or may discharge process wastewater pollutants to the waters of the United States, or that introduces or may introduce process wastewater pollutants into a publicly owned treatment works.

(b) The following table presents the subcategorization scheme codified in this part, with references to former subpart designations contained in the 1997 edition of 40 CFR parts 425 through 699:

## **Environmental Protection Agency**

## §430.01

SUBCATEGORIZATION SCHEME WITH REFERENCES TO FORMER SUBPARTS CONTAINED IN THE JULY 1,
1997 Edition of 40 CFR Parts 425 Through 699

Final subcategorization scheme	Types of products covered in the subpart
Dissolving Kraft Bleached Papergrade Kraft and Soda.	Dissolving pulp at kraft mills (F <sup>a</sup> ) Market pulp at bleached kraft mills (G <sup>a</sup> ); paperboard, coarse paper, and tissue paper at bleached kraft mills (H <sup>a</sup> ); pulp and fine papers at bleached kraft mills (I <sup>a</sup> ); and pulp and paper at soda mills (P <sup>a</sup> ).
Unbleached Kraft	Pulp and paper at unbleached kraft mills including linerboard or bag paper and other mixed products (A <sup>a</sup> ); pulp and paper using the unbleached kraft-neu- tral sulfite semi-chemical (cross recovery) process (D <sup>a</sup> ); and pulp and paper at combined unbleached kraft and semi-chemical mills, wherein the spent semi-chemical cooking liquor is burned within the unbleached kraft chemical recovery system (V <sup>a</sup> ).
Dissolving Sulfite	Pulp at dissolving sulfite mills for the following grades: nitration, viscose, cello- phane, and acetate (K <sup>a</sup> ).
Papergrade Sulfite —Calcium-, Magnesium-, or Sodium-based pulps. —Ammonium-based pulps. —Specialty grade pulps.	Pulp and paper at papergrade sulfite mills where blow pit pulp washing tech- niques are used (J <sup>a</sup> ) and pulp and paper at papergrade sulfite mills where vacuum or pressure drums are used to wash pulp (U <sup>a</sup> ).
	Pulp and paper at semi-chemical mills using an ammonia base or a sodium base (B <sup>a</sup> ).
	Pulp and paper at groundwood chemi-mechanical mills (L <sup>a</sup> ); pulp and paper at groundwood mills through the application of the thermo-mechanical process (M <sup>a</sup> ); pulp and coarse paper, molded pulp products, and newsprint at groundwood mills (N <sup>a</sup> ); and pulp and fine paper at groundwood mills (O <sup>a</sup> ).
	Pulp and paper at non-wood chemical pulp mills.
	Pulp and paper at deink mills including fine papers, tissue papers, or news-print ( $\mathbf{Q}^{a}$ ).
	Paperboard from wastepaper from noncorrugating medium furnish or from corrugating medium furnish (E <sup>a</sup> ); tissue paper from wastepaper without deinking at secondary fiber mills (T <sup>a</sup> ); molded products from wastepaper without deinking (W <sup>a</sup> ); and builders' paper and roofing felt from wastepaper (40 CFR Part 431, Subpart A <sup>a</sup> ).
Fine and Lightweight Papers from Purchased Pulp.	Fine Papers at nonintegrated mills using wood fiber furnish or cotton fiber fur- nish (R <sup>a</sup> ); and lightweight papers at nonintegrated mills or lightweight elec- trical papers at nonintegrated mills (X <sup>a</sup> ).
Tissue, Filter, Non-woven, and Paperboard from Pur- chased Pulp.	Tissue papers at nonintegrated mills (S <sup>a</sup> ); filter and non-woven papers at non- integrated mills (Y <sup>a</sup> ); and paperboard at nonintegrated mills (Z <sup>a</sup> ).
	scheme Dissolving Kraft Bleached Papergrade Kraft and Soda. Unbleached Kraft Dissolving Sulfite — Calcium-, Magnesium-, or Sodium-based pulps. — Calcium-, Magnesium-, or Sodium-based pulps. Semi-Chemical Pulp Mechanical Pulp Non-Wood Chemical Pulp Secondary Fiber Deink Secondary Fiber Non-Deink Fine and Lightweight Papers from Purchased Pulp. Tissue, Filter, Non-woven, and Paperboard from Pur-

<sup>a</sup> This subpart is contained in the 40 CFR parts 425 through 699, edition revised as of July 1, 1997.

#### §430.01 General definitions.

In addition to the definitions set forth in 40 CFR part 401 and 40 CFR 403.3, the following definitions apply to this part:

(a) Adsorbable organic halides (AOX). A bulk parameter that measures the total mass of chlorinated organic matter in water and wastewater.

(b) Annual average. The mean concentration, mass loading or production-normalized mass loading of a pollutant over a period of 365 consecutive days (or such other period of time determined by the permitting authority to be sufficiently long to encompass expected variability of the concentration, mass loading, or production-normalized mass loading at the relevant point of measurement).

(c) Bleach plant. All process equipment used for bleaching beginning with the first application of bleaching agents (e.g., chlorine, chlorine dioxide, ozone, sodium or calcium hypochlorite, or peroxide), each subsequent extraction stage, and each subsequent stage where bleaching agents are applied to the pulp. For mills in subpart E of this part producing specialty grades of pulp, the bleach plant includes process equipment used for the hydrolysis or extraction stages prior to the first application of bleaching agents. Process equipment used for oxvgen delignification prior to the application of bleaching agents is not part of the bleach plant.

(d) *Bleach plant effluent.* The total discharge of process wastewaters from the bleach plant from each physical