

The Role of Elevated Ducting for Radio Service and Interference Fields

H.T. Dougherty

E.J. Dutton



U.S. DEPARTMENT OF COMMERCE
Malcolm Baldrige, Secretary

Dale N. Hatfield, Acting Assistant Secretary
for Communications and Information

March 1981

TABLE OF CONTENTS

	Page
ABSTRACT	
1. INTRODUCTION	1
1.1 Degradation of Service Fields	2
1.2 Enhancement of Interference Fields	2
2. DUCTING STRUCTURES	8
2.1 Ducting	9
2.2 Duct Width	11
2.3 Duct Definition	11
2.4 Duct Frequency Dependence	13
2.5 Propagation Losses For Ducts	13
3. LAYER AND DUCT CHARACTERISTICS	15
3.1 Occurrence of Surface Ducts	15
3.2 Occurrence of Elevated Ducts	16
3.3 Elevated Duct Statistics	19
4. ILLUSTRATIVE EXAMPLES	23
4.1 Application To Broadcasting	27
5. RECOMMENDATIONS	30
6. REFERENCES	32
7. APPENDICES	
A: Ducting Expressions	35
B: Contour Maps For 10 and 90 Percentile Values	38
C: Schematic Representations of Some Meteorological Conditions Favorable For Anomalous Radio Propagation	47
D: List of Symbols	52

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1.	An atmospheric fading mechanism, Multipath.	3
2.	An atmospheric fading mechanism, Isolation.	4
3.	An atmospheric fading mechanism, Diffraction.	5
4.	Service and interference propagation paths for two systems.	6
5.	Elevated layer with a ducting gradient, its refractivity profile, and two trapped radio wave trajectories.	10
6.	Elevated layer with a ducting gradient, its modified refractivity profile, and two trapped radio wave trajectories.	10
7.	Elevated and surface duct parameters.	12
8.	The occurrence of elevated ducts in percent of all hours of the year.	17
9.	The occurrence of elevated ducts in percent of all hours of the worst month.	18
10.	The locations of the 107 historical radiosonde data stations.	20
11.	The median minimum trapping frequency, $f_t(50\%)$ in megahertz.	21
12.	The optimum coupling elevation, $h_o(50\%)$ in meters above the surface, expected for 50% of all elevated ducts.	22
13.	The median M-unit lapse across the observed elevated ducts, $ \Delta M(50\%) $ in M-units.	24
14.	The median base height of elevated ducts, $h_b(50\%)$ in meters above the surface.	25
15.	The median elevation of the top of elevated ducts, $h_a(50\%)$ in meters above the surface.	26
B-1.	An upper bound for the minimum trapping frequency, $f_t(10\%)$ in megahertz.	39
B-2.	A lower bound for the minimum trapping frequency, $f_t(90\%)$ in megahertz.	40
B-3.	An upper bound on the base height of the elevated ducts, $h_b(10\%)$ in meters above the surface.	41

<u>Figure</u>		<u>Page</u>
B-4.	A lower bound on the base height of elevated ducts, $h_b(90\%)$ in meters above the surface.	42
B-5.	An upper bound on the optimum coupling elevation, $h_o(10\%)$ in meters above the surface.	43
B-6.	A lower bound on the optimum coupling elevation, $h_o(90\%)$ in meters above the surface.	44
B-7.	An upper bound on the elevation at the top of the ducts, $h_a(10\%)$ in meters above the surface.	45
B-8.	A lower bound on the elevation at the top of the ducts, $h_a(90\%)$ in meters above the surface.	46

LIST OF TABLES

<u>Table</u>		
1.	Comparison of Broadcast Fields in Decibels Below the Free-Space Level at Flint, Mich., for 50% of Receiver Locations 450 to 1000 MHz.	29

LIST OF CHARTS

<u>Chart</u>		
1.	Surface Superrefractive Layers.	48
2.	Surface Subrefractive Layers.	49
3.	Elevated Superrefractive Layers.	50
4.	Elevated Subrefractive Layers.	51