Instrumentation and Control Cable

Unshielded
20 AWG, 4 Conductors

1-800-BELDEN-1

Trade Number Industry Stds.	Std. Lgth. (ft.)	Std. Units (lbs.)	AWG (strand) Type (Nom. D.C.R.)		Insul Thick (Jkt Thick)	Nom. O.D.	Nom. Imp. (ohms)	Vel. of Prop.	Nom. Cap.
			Conductors	Shields					
9444 UL AWM: 2464 NEC: CMG CEC: CMG	100 U-500 500 U-1000 1000	3.3 15.5 16.2 30.1 29.9	20 (7x28) TC		0.013 in. 0.032 in.	0.217 in.			
Metric	(Meters) 30.5 U-152.4 152.4 U-304.9 304.9	(Kg) 1.50 7.0 7.4 13.7 13.6			.330 mm .813 mm	5.512 mm			

Description:		
Insulation:	PVC	Tinned copper, PVC insulated, conductors cabled. Chrome PVC jacket.
Jacket:	PVC	
Plenum Version(s):	n/a	

Color Codes	
#	Color
1	Black
2	White
3	Red
4	Green
5	Brown
6	Blue

Color Codes	
#	Color
7	Orange
8	Yellow
9	Purple
10	Gray
11	Pink
12	Tan

▲ Top

(Select other related products with BACK or PREVIOUS.)

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors or omissions may exist. This listing of information is presented as a courtesy and does not ensure that a product with these specifications is available. Specifications and availablility should be confirmed with a call to our sales representatives or to customer service. Have a question? Call us at 1-800-BELDEN-1 or send us a comment. Page displayed 1/25/2000 for category Multi-Conductor non-Paired.

Home Page

Return to Belden's Home Page

Copyright © 2000 Belden Inc.