

# HF Ground Wave Propagation over Forested and Built-up Terrain

D.A. Hill



**U.S. DEPARTMENT OF COMMERCE**  
**Malcolm Baldrige, Secretary**

Bernard J. Wunder, Jr., Assistant Secretary  
for Communications and Information

December 1982



## TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES. . . . .	iv
LIST OF TABLES . . . . .	vi
ABSTRACT . . . . .	1
1. INTRODUCTION. . . . .	1
2. UNIFORM SLAB MODEL. . . . .	2
2.1 Integral Representation. . . . .	3
2.2 The Lateral Wave . . . . .	6
2.3 Normalized Surface Impedance . . . . .	6
2.4 Height-Gain Functions. . . . .	8
2.5 Limit of Vanishing Slab. . . . .	9
3. INTEGRAL EQUATION APPROACH. . . . .	10
3.1 Formulation. . . . .	10
3.2 Integral Equation Solution . . . . .	13
4. TWO-SECTION PATH. . . . .	15
4.1 Kirchhoff Theory . . . . .	15
4.2 Comparison with Integral Equation. . . . .	20
5. EQUIVALENT SLAB PARAMETERS. . . . .	22
5.1 Forest Cover . . . . .	24
5.2 Built-up Areas . . . . .	24
5.3 Snow Cover . . . . .	26
6. SPECIFIC PATH CALCULATIONS. . . . .	30
6.1 Smooth Paths in the Netherlands. . . . .	30
6.2 Irregular, Forested Terrain in West Germany. . . . .	35
7. CONCLUSIONS AND RECOMMENDATIONS . . . . .	50
8. ACKNOWLEDGMENTS . . . . .	53
9. REFERENCES. . . . .	53
APPENDIX A: ANTENNA WITHIN THE SLAB . . . . .	57
REFERENCES. . . . .	62
APPENDIX B: KIRCHHOFF INTEGRATION . . . . .	64
REFERENCE . . . . .	66
APPENDIX C: USER'S GUIDE, LISTING, AND SAMPLE OUTPUT FOR PROGRAM WAGSLAB. . . . .	67

LIST OF FIGURES

	<u>Page</u>
Figure 1.	Vertical electric dipole over a uniaxial anisotropic slab. . . . . 4
Figure 2.	Equivalent geometry for the limit of a free-space slab ( $\epsilon_{hc} = \epsilon_{vc} = 1$ ) . . . . . 11
Figure 3.	Geometry for integral equation. The slab and ground parameters can vary as a function of $x$ , but are constant in $y$ . . . 12
Figure 4.	Geometry for a two-section path with an elevation change $D$ . The section, $x < 0$ , has a normalized surface impedance $\Delta_a$ , and the section, $x > 0$ , has a normalized surface impedance $\Delta_b$ . . . . . 16
Figure 5.	Propagation from a forest to a clearing for a frequency of 10 MHz. . . . . 21
Figure 6.	Propagation from a clearing to a forest for a frequency of 10 MHz. . . . . 23
Figure 7.	Relative permittivity $\epsilon_v$ versus building density $B$ . . . . . 27
Figure 8.	Magnitude of the spherical earth attenuation function as a function of frequency and snow depth $D$ . Parameters: $\epsilon_v = \epsilon_h = 1.55$ , $\sigma_v = \sigma_h = 2.5 \times 10^{-5}$ S/m, $\epsilon_g = 10$ , $\sigma_g = 10^{-2}$ S/m . . . . . 29
Figure 9.	Smooth path in the Netherlands with receiving sites at 60 km and 80 km. The first 70 km has good ground ( $\epsilon_g = 15$ and $\sigma_g = 10^{-2}$ S/m), and the last 10 km has poor ground ( $\epsilon_g = 3$ and $\sigma_g = 10^{-4}$ S/m). . . . . 31
Figure 10.	Comparison of measurement with three theories at 2 MHz for a smooth path in the Netherlands. Only the integral equation solution takes into account the poor ground section shown in Figure 9. . . . . 32
Figure 11.	Comparison of measurement with three theories at 10 MHz for a smooth path in the Netherlands. Only the integral equation solution takes into account the poor ground section shown in Figure 9 . . . . . 33
Figure 12.	Comparison of measurement with three theories at 30 MHz for a smooth path in the Netherlands. Only the integral equation solution takes into account the poor ground section shown in Figure 9. . . . . 34
Figure 13.	Terrain profile for the path from Inneringen to Boblingen . . 37

LIST OF FIGURES (continued)

	<u>Page</u>	
Figure 14.	Propagation from Inneringen to Boblingen at 2 MHz. The solid curve is for bare ground, and the dotted curve includes the forest and urban slabs. . . . .	38
Figure 15.	Propagation from Inneringen to Boblingen at 5 MHz. The solid curve is for bare ground, and the dotted curve includes the forest and urban slabs. The circles are obtained from multiple knife-edge diffraction theory. . . . .	39
Figure 16.	Propagation from Inneringen to Boblingen at 10 MHz. The solid curve is for bare ground, and the dotted curve includes the forest and urban slabs. . . . .	40
Figure 17.	Propagation from Inneringen to Boblingen at 20 MHz. The solid curve is for bare ground, and the dotted curve includes the forest and urban slabs. . . . .	41
Figure 18.	Propagation from Inneringen to Boblingen at 30 MHz. The solid curve is for bare ground, and the dotted curve includes the forest and urban slabs. The circles are obtained from multiple knife-edge diffraction theory. . . . .	42
Figure 19.	Magnitude of height-gain function in forest slab and in air. Parameters: $D = 20$ m, $\epsilon_v = \epsilon_h = 1.1$ , $\sigma_v = \sigma_h = 10^{-4}$ S/m, $\epsilon_g = 10$ , and $\sigma_g = 10^{-2}$ S/m. . . . .	43
Figure 20.	Spherical earth attenuation function for bare ground and with forest cover. Parameters: $D = 20$ m, $\epsilon_v = \epsilon_h = 1.1$ , $\sigma_v = \sigma_h = 10^{-4}$ S/m, $\epsilon_g = 10$ , and $\sigma_g = 10^{-2}$ S/m . . . . .	44
Figure 21.	Propagation from Inneringen to Boblingen (solid curve) and in the reverse direction (dotted curve). Both cases are for bare ground, and the frequency is 2 MHz . . . . .	46
Figure 22.	Propagation from Boblingen to Inneringen (solid curve) and in the reverse direction (dotted curve). Both cases are for bare ground, and the frequency is 5 MHz . . . . .	47
Figure 23.	Propagation from Inneringen to Boblingen (solid curve) and in the reverse direction (dotted curve). Both cases are for bare ground, and the frequency is 20 MHz. . . . .	48
Figure 24.	Terrain profile for the path from Inneringen to Lechfeld. . .	49
Figure 25.	Propagation from Inneringen to Lechfeld (solid) and in the reverse direction (dotted). Both curves are for bare ground, and the frequency is 2 MHz. . . . .	51

LIST OF FIGURES (continued)

	<u>Page</u>
Figure 26. Propagation from Inneringen to Lechfeld (solid) and in the reverse direction (dotted). Both curves are for bare ground, and the frequency is 5 MHz. . . . .	52
Figure A.1. Integration contours in the complex $\lambda$ plane . . . . .	60

LIST OF TABLES

Table 1. Characteristic Parameters of Typical Forests (Dence and Tamir, 1969). . . . .	25
Table 2. Magnitude and Phase of Surface Impedance $\Delta$ as a Function of Snow Depth D. Parameters: $\epsilon_v = \epsilon_h = 1.55$ , $\sigma_v = \sigma_h = 2.5 \times 10^{-5}$ S/m, $\epsilon_g = 10$ , $\sigma_g = 10^{-2}$ S/m. . . . .	28